
Scaling Towards the Information Boundary of Instruction Sets: The Infinity Instruct Subject

Technical Report

Li Du^{1,2}, Hanyu Zhao^{1,2}, Yiming Ju^{1,2}, Tengfei Pan

BAAI

{ldu, hyzhao, ymju, tfpan}@baai.ac.cn

1 Abstract

Instruction tuning has become a foundation for unlocking the capabilities of large-scale pretrained models and improving their performance on complex tasks. Thus, the construction of high-quality instruction datasets is crucial for enhancing model performance and generalizability. Although current instruction datasets have reached tens of millions of samples, models finetuned on them may still struggle with complex instruction following and tasks in rare domains. This is primarily due to limited expansion in both “coverage” (coverage of task types and knowledge areas) and “depth” (instruction complexity) of the instruction set. To address this issue, we propose a systematic instruction data construction framework, which integrates a hierarchical tagging system, an informative seed selection algorithm, an evolutionary data synthesis process, and a model deficiency diagnosis with targeted data generation. These components form an iterative closed-loop to continuously enhance the coverage and depth of instruction data. Based on this framework, we construct Infinity Instruct Subject, a high-quality dataset containing ~ 1.5 million instructions. Experiments on multiple foundation models and benchmark tasks demonstrate its effectiveness in improving instruction-following capabilities. Further analyses suggest that Infinity Instruct Subject shows enlarged coverage and depth compared to comparable synthesized instruction datasets. Our work lays a theoretical and practical foundation for the efficient, continuous evolution of instruction datasets, moving from data quantity expansion to qualitative improvement.

2 Introduction

Instruction tuning serves as a cornerstone for unleashing the vast knowledge and reasoning capabilities of large pretrained models [Longpre et al., 2023, Ouyang et al., 2022]. Consequently, the construction of high-quality instruction datasets has become essential for improving model performance and generalization ability. Several efforts have constructed instruction datasets through manual annotation or automatic synthesis, with the total size of these datasets having reached tens of millions [Ahmad et al., 2025, Nayak et al., 2024]. However, current large models still struggle with complex instruction-following tasks and show limitation in “rare” tasks with low frequency [Qin et al., 2025].

A main reason would be that existing works overlooked the distribution of existing data, and thus failed to efficiently enhance the “coverage and “depth of synthesized instructions, and thus limit the model performance in solving rare tasks and difficult tasks [Wang et al., 2024, Liu et al., 2024, Long et al., 2024]. The “coverage of an instruction dataset refers to the coverage of task types and knowledge categories it covers, while the ‘depth reflects the complexity of instructions within

¹These authors contributed equally.

²Corresponding author.

individual tasks. Both two dimensions are essential to enlarge the capability boundaries of large models [Shengyu et al., 2023]. Expanding the coverage improves the model’s ability to generalize across domains, while increasing depth helps enhance complex reasoning ability and compositional generalizability [Sinha et al., 2024, Zhong et al., 2025]. However, a key challenge remains: how to design **effective, controllable and interpretable** instruction generation strategies that continuously expand the instruction space along both dimensions, guiding models to acquire higher-level capabilities [Zhang et al., 2023, Qian et al., 2022, Qin et al., 2022]. Currently, there is a lack of unified methodology and empirical research in this area.

To address this challenge, we propose a comprehensive instruction data construction framework, which goal is to measure the current data distribution and synthesize instructions that target under-covered and high-complexity regions, thereby expanding both the coverage and depth of the dataset. This framework consists of four core components: (1) a hierarchical and multilingual tagging system to understand the content and ability distribution of existing instruction content; (2) informative seed data selection to identify valuable instructions with low coverage or high difficulty; (3) evolutionary data synthesis to synthesize more complex instructions by evolving from seed data; (4) a model deficiency diagnosis based targeted synthesis module to identify potential flaws in the model’s knowledge or capabilities and synthesize data to address those weaknesses. As illustrated in Figure 1, these four modules form a closed-loop system that can iteratively expand the coverage and depth of the instruction dataset.

Based on this framework, we construct the Infinity Instruct Subject (InfInstruct-Sub) dataset, which contains ~ 1.5 million high-quality instructions. The code and dataset are available at <https://github.com/BAAI-DIPL/InfinityInstruct-Sub> and <https://huggingface.co/datasets/BAAI/Infinity-Instruct/tree/main/Gen>. Evaluations on multiple benchmarks demonstrate its effectiveness in improving instruction-following ability. Across foundation models, our tuned models outperform their official instruction-tuned counterparts. Data analysis further reveals that, compared with comparable synthetic datasets such as Magpie [Wei et al., 2023] and UltraChat [Ding et al., 2023], our framework could obtain an instruction set with higher coverage and complexity. Moreover, interestingly, we observe a scaling law in the co-occurrence structure of tags of instructions: the co-occurrence frequency of a tag with others follows a negative logarithmic relationship with its own frequency. This indicates a scale-free connection structure between instructions, similar to the topology of the Internet. Such a pattern may offer new insights into the scaling laws of model performance and suggest ways to better understand the internal knowledge structure of datasets, potentially improving training efficiency and effectiveness. This further highlights the importance of understanding the content structure of instruction data, and underscores the value of the high-quality tagging system proposed in this work.




Figure 1: Construction pipeline of the InfInstruct-Sub dataset.

3 Construction of Infinity Instruct Subject

The construction process of Infinity Instruct Subject (InfInstruct-Sub) is illustrated in Figure 1. The process starts by collecting high-quality seed instructions. We systematically gathered all




Figure 2: Tagging system of the InfInstruct-Sub dataset for elucidating content distribution of instruction pools. (a) Fine-grained tags and normalization of fine-grained tags. (b) Construction of categorical tags and the process of mapping fine-grained tags to categorical tags.

general-domain instruction datasets both manually created and automatically generated using GPT-4[Achiam et al., 2023] or ChatGPT available up to March 2024, resulting in a data pool of approximately 7 million samples. The included datasets are listed in Table 1 of the Appendix. Next, we developed an automatic tagging system based on large language models (LLMs) to analyze the distribution of the data pool. From the perspectives of coverage and depth, we selected a set of high-information seed instructions. Then, we applied an evolutionary algorithm to generate over one million new instruction samples by evolving towards greater complexity and difficulty. Building on both the seed and synthesized data, we constructed a model deficiency diagnosis system. This system identifies gaps in model capabilities and guides the targeted synthesis of new data to efficiently address those weaknesses. Finally, we implemented a strict semantic similarity-based data leakage prevention framework to detect and mitigate potential risks of data leakage throughout the construction process.

3.1 Hierarchical Multilingual Tagging System for Characterizing Instruction Content Distribution

A prerequisite for synthesizing instructions that target under-covered areas or exhibit high complexity is understanding the content distribution of existing instruction data. To this end, we design a hierarchical, multilingual tagging system powered by LLMs as illustrated in Figure 2. This system assigns each instruction both Chinese and English tags at two levels: domain-level tags and fine-grained tags. These tags indicate the domain of each instruction, as well as the types of abilities and knowledge required to complete it, facilitating interpretation and selection for downstream tasks.

Specifically, the tagging process is implemented in a bottom-up manner. We first generate fine-grained tags for each instruction. These are then normalized (Figure 2(a)) to remove noise and merge semantically equivalent tags expressed in different forms. Finally, LLMs are used to automatically cluster and abstract fine-grained tags into broader domain-level categories, and to map each fine-grained tag to its corresponding domain tag (Figure 2(b)).

Fine-grained Tagging System Specifically, given an instance from the instruction dataset consisting of one or more Query-Response pairs, we concatenate them into a single string. We then use a carefully designed prompt to avoid generating over-detailed or over-coarse tags, as illustrated

Prompt

"Given a dialogue between a user and a conversational assistant, and a classification standard that describes different abilities, determine which one or more major categories from this standard the assistant would need to utilize in order to complete the given dialogue. Note: only list the names of the abilities, and separate each different ability with angle brackets < >."

"Classification Standard: {standard}\n"

"Note: You must select the most relevant one or more categories from the above list. Do not output any categories or content outside the given list of major categories."

"Note: Only output the names of the major categories. For example:"

"Dialogue: ### User asks: I walked 8 meters, which is three-eighths of the whole journey. How much distance is left?\nAssistant replies: 8 meters is three-eighths of the whole journey, so the total distance is 21½ meters. Since 8 meters have been walked, 13½ meters remain.\n### What abilities does the assistant need to complete this dialogue? Answer: <Mathematical Ability><Logical Reasoning>"

"Dialogue: ### User asks: Please translate 'to paint the lily' into Chinese.\nAssistant replies: 'To paint the lily' means '画蛇添足' (to overdo something unnecessarily).\n### What abilities does the assistant need? Answer:"

"<Linguistic Knowledge, Multilingual and Cross-Cultural Understanding>"

"Dialogue: {prompt}\nAnswer:"

Figure 3: Prompt used for guiding the LLM to generate tags for given instruction.

in Figure 3, to instruct LLMs to generate tags that describe the knowledge and skills required to complete the dialogue¹.

Tag Normalization Since LLMs may describe the same knowledge or skill using different expressions (e.g., “math calculation” vs. “mathematical calculation”), we normalize tags based on semantic similarity. Specifically, we obtain embeddings for all tags using BGE [Chen et al., 2024], and identify semantically similar tags whose cosine similarity exceeds an empirical threshold of $\lambda = 0.91$. Within each group of similar tags, we retain the one with the highest frequency as the representative. To further refine the tag set, we apply DBSCAN [Ester et al., 1996] clustering with parameters $eps = 0.47$ and $min_samples = 2$ to merge closely related tags. These thresholds are chosen based on empirical observations. After normalization and clustering, tags with frequency less than 100 are considered noisy and removed, following prior work [Lu et al.]. As a result, a total of 21,378 fine-grained tags are retained.

Domain Tagging System Given the set of fine-grained tags, we select the top 1,000 most frequent ones, then use GPT-4 to automatically summarize them into a set of domain-level categories, so that we employ each induced category as a domain-level tag. To establish a mapping between fine-grained tags and domain-level tags, we use the prompt shown in Figure 4 along with the categorization criteria illustrated in Figure 1 of the Appendix. Based on this setup, we employ Qwen2.5-72B-Instruct [Yang et al., 2024] to generate the mappings between fine-grained and domain tags.

Prompt

"There is now a capability-related tag and a classification standard for these capability tags. Based on this classification standard, please determine which broad category the tag belongs to."

Tag: {tag}

Standard: {standard}

Note: Only output the name of the broad category. For example, if the tag is 'Java Programming', the output should be: 'Programming and Software Development.'"

Figure 4: Prompt for categorizing a fine-grained tag into a domain-tag.

3.2 Informative Seed Instructions Selection

The initial data distribution largely determines the effectiveness of subsequent data synthesis, thus selecting a set of informative seed instructions is crucial for synthesizing high-quality instruction data. Given the abundance of existing instruction datasets, aimlessly synthesizing existing data is of limited value. In contrast, it is more meaningful to focus on instructions that are currently underrepresented in existing datasets (expanding coverage), or those that are relatively difficult and expose model limitations in reasoning or knowledge (enhancing depth)[????]. As shown in Figure 5, we design four criteria to select informative instructions:

¹We use Qwen-2.5-72B-Instruct as the tagging model to ensure high-quality annotations.




Figure 5: Standards for selecting informative seed instructions to enhance the depth and coverage of seed set.

1. Hard-to-Follow Instructions: Inspired by [??], we select the 50k instructions with the smallest reduction in token-level average cross-entropy loss after fine-tuning, ensuring the retained instructions are challenging to follow.

2. Long-Tail Instructions: To guarantee coverage, we include instructions that contain at least one fine-grained tag with a frequency below 200 in the seed set. Additionally, we randomly sample 30% of the instructions that contain tags with frequencies in the range [200, 500].

3. Multi-Skill Required Complex Instructions: Instructions associated with more than four fine-grained tags are included, as such instructions require more comprehensive reasoning or knowledge.

4. Undertrained Instructions:

These are instructions for which the base model performs poorly with a high loss value. This may either be due to either a lack of exposure or inherent difficulty. We include 200k instructions with loss greater than $\text{mean}(\text{loss}) + 1.96 \times \text{std}(\text{loss})$.

In particular, we use Llama-2-7B-base [Touvron et al., 2023] to compute the loss values for instructions. To estimate the reduction ratio in token-level average cross-entropy loss, we fine-tune Llama-2-7B-base on a balanced instruction subset with 1,000 instructions per domain category. Table 1 presents the sources of the seed data and the number of instructions retained after filtering. By applying the above criteria sequentially, we select approximately 1.2 million informative instructions from the overall data pool.

3.3 Evolutionary Algorithm for In-Distribution Generalization

Based on the previously selected informative instructions as seeds, we employ an evolutionary algorithm to synthesize new instructions, so as to ensure the performance on instruction sets similar to the seed instruction distribution, meanwhile enlarge the coverage and increasing the depth of seed instructions. Specifically, we design a three-step evolution process:

1. Metadata-Guided Evolution: In this step, we adopt the widely-adopted Evol-Instruct [Xu et al., 2023] method. By randomly choose one of four dimensions—diversity, i.e., more reasoning steps, concretizing, deepening, and more diversified, to guide each instruction’s evolution using State-of-the-Art advanced large model as synthesizer.

2. Validation and Filtering: Following [?], evolved instructions are evaluated by an advanced large model to judge the quality, as well as the similarity between the original seed instruction.

3. Multi-Turn Dialogue Generation: Following [Ding et al., 2023], each valid instruction is used to generate 1–4 rounds of dialogue, with the AI assistant simulating different roles.




Figure 6: Process of the evolution-based data synthesizing.

3.4 Deficiency Diagnosis and Defect-Driven Instruction Synthesis




Figure 7: Illustration of the deficiency diagnosis process.

Despite comprehensive data collection efforts, many topics remain underrepresented, and the model may still fail to capture key knowledge and skills within the instruction set, leading to capability and knowledge deficiency. While expanding the seed set or synthesizing more data via evolutionary methods can help, these approaches often produce redundant and inefficient results. To address this issue, we adopt a more targeted strategy: directly diagnosing model deficiencies and synthesizing instructions specifically to fill those gaps.

As illustrated in Figure 7, we first construct a diagnosis dataset $\mathcal{D} = \mathcal{D}_{i=1}^N$ drawn from the same distribution as the seed dataset, where each $\mathcal{D}_i = \{x_i, y_i\}$ represents an input query and its corresponding reference response. We then use the fine-tuned model M_{FT} to generate a response \hat{y}_i for each x_i . Next, we compare \hat{y}_i with y_i using a State-of-the-Art advanced large Oracle model, identifying knowledge or deficiencies in \hat{y}_i with the prompt shown in Figure 3.4. Given the diagnosed issues, we then prompt the Oracle model to generate new instructions that specifically address these deficiencies using the prompt in Figure 3.4, to target generate instructions that remedy deficiencies within the model.




Figure 8: Prompt for driving the oracle model for diagnosing deficiencies of finetuned model.

Prompt

"Now, suppose you are a teacher, and one of your students has a deficiency in the following ability or area of knowledge: **##{kind_of_ability}##**. Your task is to quickly help the student overcome this weakness. Can you create **{num_sample_per_prompt}** questions to train the student, aiming to improve their performance in this area precisely, efficiently, and rapidly?"

"Note: The types of questions and knowledge areas should be diverse. Only output the questions—do not include any additional text. Number the questions as 1., 2., 3., etc."

"Note: The difficulty level of the questions should be moderately to highly difficult. Include only a few simple ones; most should be more challenging. 'Moderately difficult' means requiring complex reasoning and integrating multiple knowledge points."

"Note: Each question you create should aim to address all of the student's identified deficiencies as thoroughly as possible."

"Note: Do not vaguely refer to 'an article' or 'a passage'—you must provide the specific text in the question so that it becomes answerable."

"Note: You must write the questions in English."

"Note: Do not include questions related to video (TV, movies), audio (radio), or images."

"Note: The formats of the questions should be varied and diverse."

Figure 9: Prompt for driving the oracle model for target generating instructions to remedy deficiencies of the finetuned model.

3.5 Data Leakage Prevention

Overlap between training and evaluation data can cause models to achieve inflated scores on familiar samples, leading to overestimated performance. We observe that many public instruction datasets include questions from common benchmarks like MT-Bench [Zheng et al., 2023a] and AlpacaEval [Li et al., 2023], which risks misleading evaluation. To address this issue, we use the BGE model to compute semantic similarity between evaluation queries and instructions in the training data. This process involves multi-dimensional comparisons, including semantic understanding and structural features, to ensure accurate and comprehensive matching. Based on the similarity scores, we filter out overlapping entries, effectively preventing data leakage and preserving the reliability of model evaluation.

After the above procedures, we obtain 146,9391 new instruction samples.

4 Performance Analysis

4.1 Experimental Setup

We finetune open-source pretrained models Qwen2-7B-base and LLaMA3-8B-base on the InfInstruct-Sub dataset, and compare their performance against their respective official instruction-tuned and alignment-tuned versions. Evaluations are conducted on widely adopted LLM-judging-based benchmarks AlpacaEval 2.0 [Li et al., 2023] and Arena-Hard-V0.1 [Li et al., 2024]. The reference model for AlpacaEval 2.0 is GPT-4-1106; on Arena-Hard-V0.1 is GPT-4-0314.

4.2 Experimental Results

Table 1 shows the performance of the base model Llama3-8B and Qwen-2-7B fine-tuned with InfInstruct-Sub on AlpacaEval 2.0 and Arena-Hard-V0.1. Compared to earlier and concurrent instruction datasets, models fine-tuned with InfInstruct-Sub show improved performance, especially on ArenaHard, which focuses on more complex tasks. Moreover, comparison with performance using instruction collection OpenHermes 2.5 and GenQA, which have similar or larger sizes, shows that simply enlarging the size of the instruction set would not necessarily lead to performance improvement, particularly for harder instructions. This highlights the necessity of enhancing the depth of the instruction set. Moreover, on both Llama and Qwen, the performance outperforms official instruction-tuned counterparts. Notably, InfInstruct-Sub applies strict data leakage prevention and offers high coverage and difficulty, enabling improved generalization across diverse tasks. These results demonstrate the effectiveness of our proposed data construction framework to enhance model performance and its general applicability in enhancing instruction-following performance across different base models.

Table 1: Performance comparison of various models across different benchmarks.

Model	Datasize	AlpacaEval2.0	Arena-hard
GPT-4-1106	–	50.0	–
GPT-4-0314	–	35.3	50.0
GPT-4-0613	–	30.2	37.9
Llama-3-8B			
+Self-Instruct [Wang et al., 2023]	100k	7.21	4.0
+ShareGPT [Zheng et al., 2023a]	112k	9.73	6.5
+Evol Instruct [Xu et al., 2023]	143k	8.52	5.1
+OpenHermes 1 [Teknium, 2023a]	243K	9.94	4.4
+Tulu V2 Mix [Iverson et al., 2023]	326K	9.91	5.4
+WildChat [Zhao et al.]	652k	14.62	8.7
+OpenHermes 2.5 [Teknium, 2023b]	1M	12.89	8.2
+GenQA [University of Maryland, 2024]	6.47M	9.05	3.0
+UltraChat [Ding et al., 2023]	208k	8.29	3.6
+Magpie [Xu et al., 2024]	300k	22.66	14.9
Llama-3-8B-Instruct	>10M	22.92	20.6
Llama-3-8B+InfInstruct-Sub	1.46M	36.22	35.3
Qwen-2-7B-Instruct	-	20.92	19.6
Qwen-2-7B+InfInstruct-Sub	1.46M	28.13	27.7

5 Dataset Analysis

5.1 Dataset Distribution




Figure 10: Illustration of the domain category distribution of the InfInstruct-Sub dataset.

Figure 10 shows the distribution of InfInstruct-Sub instructions across different domain labels. Figure 11 visualizes the instruction data projected into semantic space using BGE as the text encoder, followed by t-SNE for dimensionality reduction. Overall, instructions with different domain labels are distributed in clearly separated regions, suggesting that instructions associated with different semantic tags carry distinct meanings. This supports the effectiveness of our tagging system.

We further compare the semantic coverage of InfInstruct-Sub with similar instruction datasets, including Alpaca[Taori et al., 2023], llm-sys[Zheng et al., 2023b], and Magpie [Xu et al., 2024]. We sample 20,000 instructions from each dataset and apply the embedding and projection method same to abovementioned. As shown in Figure 12, InfInstruct-Sub exhibits a broader semantic spread,




Figure 11: Illustration of the distribution within the semantic space of the synthesized instructions.




Figure 12: Distribution of the different instruction sets within the semantic space.

demonstrating that our strategy of selecting more low-frequency instructions as seeds effectively increases coverage in the synthesized data.

To further quantify the spatial distribution diversity of instruction sets, we use spatial entropy to evaluate the distribution uniformity of each dataset in semantic space. Spatial entropy is an extension of information entropy that quantifies the dispersion of points in space. Higher spatial entropy indicates a more uniform and diverse distribution. Formally, we uniformly divide the 2D semantic space into n discrete grids and compute the probability p_i of a sample falling into the i -th grid. The spatial entropy is defined as:

$$H_{sp} = - \sum p_i \log p_i \quad (1)$$

In practice, p_i is estimated as the proportion of samples falling into each grid cell. We divide the 2D space into a 200×200 grid and compute spatial entropy for each dataset accordingly. As shown in Table 2, Infinity Instruct Subject achieves higher spatial entropy, indicating a more uniform and diverse distribution. This results from our targeted seed selection strategy, which emphasizes low-

Table 2: Spatial entropy of instructions within the 2D-semantic space.

Dataset	AlpacaGPT	llm-sys	Magpie	InfInstruct-Sub
Spatial Entropy	4.366	4.649	4.978	5.023

frequency and high-difficulty instructions, as well as instructions where the model underperforms, thus avoiding redundancy and enhancing the coverage and diversity of dataset.




Figure 13: Distribution of difficulty scores of different instruction sets.

To evaluate the difficulty of synthesized data, we follow the approach proposed in Magpie [Xu et al., 2024], using a large language model to assign difficulty scores to instruction samples. The difficulty is rated on a five-point scale: 'very easy': 0, 'easy': 1, 'medium': 2, 'hard': 3, 'very hard': 4. This evaluation process is independent of the method we use for selecting high-difficulty seed instructions. Specifically, we employ Qwen-2.5-32B-Instruct as the scorer and randomly sample 1,500 instructions from each of the following datasets: Alpaca-GPT, LLM-Sys, Magpie, and InfInstruct-Sub.

Figure 13 shows the distribution of difficulty scores and the average score for each dataset. Compared to others, Infinity Instruct Subject contains more high-difficulty instructions and achieves a higher average difficulty score. This helps explain the superior performance of models fine-tuned InfInstruct-Sub on challenging benchmarks such as Arena-Hard (Table 1). It also validates the effectiveness of our seed selection strategy in enhancing dataset difficulty through targeted depth-oriented instruction synthesis.

5.2 Performance Scaling with Depth and Coverage

To further validate the effectiveness of our proposed method, we construct a series of instruction subsets from the synthesized data, each containing the same number of samples (20,000) but differing in depth and coverage. We define depth as the product of the logarithm of the instruction’s label count and its token-level log loss of the base model. Coverage is measured by the logarithm of the number of non-empty grid cells occupied in the 2D semantic space described earlier.

Then, We fine-tune Llama3-8B on each subset and evaluate the aligned models on AlpacaEval and Arena-Hard. As shown in Figure 14, model performance increases consistently with instruction




Figure 14: Performance of model finetuned with different coverage and depth.

depth and coverage, even when dataset size is fixed. Intuitively, deeper instructions carry more informative signals, enabling the model to generalize better—including to simpler tasks. Previous studies have shown that instructions from different domains are difficult to substitute for each other. Therefore, it is necessary to enhance the coverage of instruction datasets to ensure model performance across various tasks. The correlation coefficient R^2 indicates that when the scale of the instruction dataset is around the tens of thousands, the model’s performance may be more sensitive to the coverage of instruction coverage than to the depth of information. These findings highlight the importance of expanding both depth and coverage of the instruction set, and further support the effectiveness of our strategy in achieving this goal during instruction synthesis, to continuously enhance the performance of models.

5.3 Scaling Phenomenon in Label Connectivity Distribution

During the data construction process, we observed an intriguing scaling law in the distribution of fine-grained tag connectivity. As shown in Figure 15, the frequency of tags with connectivity degree d exhibits a clear negative log-log linear relationship:

$$\log[\text{Freq}(\text{Degree} = d)] \sim -\gamma \log(d). \quad (2)$$

or equivalently,

$$P(\text{Degree} = d) \sim d^{-\gamma}. \quad (3)$$

Here, the connectivity degree d_i of tag i is defined as:

$$d_i = \sum_j \mathbb{I}_{ij} \quad (4)$$

where $\mathbb{I}_{ij} = 1$ if tag i and j co-occur in the same instruction. Intuitively, d_i measures the degree of association between a given fine-grained tag (i.e., a type of knowledge or skill) and others in the dataset.

This pattern suggests that the underlying knowledge structure of instruction data may follow a scale-free topology similar to that found in complex networks such as the Internet. Prior studies have




Figure 15: The connection degree of fine-grained tags with other tags exhibits a Power-Law distribution: $\text{Freq}(\text{degree}=d) \sim d^{-\gamma}$.

shown that in such networks, the probability of a node having degree k follows:

$$P(k) \sim k^{-\gamma} \quad (5)$$

where k denotes the degree of a node, and $P(k)$ represents the probability that a node with degree k appears in the network.

In our case, this implies the existence of certain “core” knowledge or skills that frequently co-occur with a wide range of other rarer or more difficult skills. For instance, tasks involving [data analysis] often require both [mathematical reasoning] and [coding skills]. Similarly, [creative writing] tasks may simultaneously involve [commonsense knowledge] and [emotion analysis] to generate coherent and context-sensitive outputs.

The presence of this topology highlights the interdependent structure of knowledge in instruction data, which should be considered within the data construction, instruction selection, and model training process. This also highlights the necessity of understanding the distribution and interrelation of instruction contents [Zhao et al., 2025], and the necessity of a high-quality tagging system, which is the foundation of understanding such knowledge structure.

Moreover, prior work (e.g., [Tan et al., 2024]) hypothesizes that the scaling law between model performance and dataset size is originated from the distribution of “latent skills” within the data, if such “latent skills” follow a power-law distribution. Our findings provide empirical support for this hypothesis, offering new insights into the origin of scaling laws between data distribution and model performance. We leave further exploration of this direction to future work, which further emphasizes the importance of the tagging system introduced in this paper.

6 Related Work

6.1 Instruction Data Synthesis

Instruction tuning is a fundamental approach to adapting base models to downstream tasks, and its effectiveness largely depends on the distribution of the instruction dataset.

Manually constructed datasets rely on experts to write instructions and responses, such as LIMA [Zhou et al., 2023] and Dolly [Ding et al., 2023]. While these datasets are high in quality, they are expensive to scale due to the high cost of human annotation.

Semi-automatic approaches, like Self-Instruct[Wang et al., 2023], Alpaca[Taori et al., 2023], and Evol-Instruct[Muennighoff et al., 2023], expand a small set of human-labeled data using prompt

engineering. While they improve scalability, the reliance on handcrafted prompts limits diversity and complexity. Fully automatic methods (e.g., WebInstruct[Yue et al., 2024], backtranslation) extract instruction-like data from web documents with minimal human input, but often lack precise control over coverage and difficulty. Recent studies explore improvements from three angles:

- **Seed Selection and High-Information Filtering:** The choice of seed data largely determines the downstream diversity and quality. Traditional methods often use a few high-frequency, simple instructions, leading to limited coverage[Wang et al., 2023]. Recent work addresses this by leveraging hierarchical tag systems and multi-dimensional metrics to select high-information seeds—i.e., rare, diverse, and complex instructions that better represent under-covered regions of the task space[Tu et al., 2024, He et al., 2025, Xie et al., 2023]. This ensures that synthesized data can expand both the coverage (domain/task diversity) and depth (instruction complexity) of the dataset.
- **Evolution-Based Instruction Generation:** To address the need for more challenging instructions, evolution-based methods iteratively expand seed data using strategies like genetic algorithms [Xu et al., 2023] or model feedback loops[Gu et al., 2025]. These approaches increase instruction complexity and reasoning depth, while dynamically adjusting generation based on model performance. They also help avoid redundancy by diversifying synthesis paths.
- **Instruction Synthesis Strategies:** Most existing synthesis methods rely on prompting large language models with handcrafted or auto-generated templates[Wang et al., 2023, Xu et al., 2023]. While effective, this can lead to templated and repetitive outputs. Magpie[Xu et al., 2024] proposes prompt-free instruction synthesis via autoregressive alignment, which improves fluency and semantic richness. Similarly, Web Reconstruction [Jiang et al., 2025] leverages real-world text to generate instruction-style data with higher realism and contextual diversity.

Despite these advances, many datasets still underrepresent complex, multi-step, or domain-specific instructions. Few existing works explicitly address the coverage and depth of instruction distribution in a unified manner. This limits model generalization in scenarios requiring deep reasoning, long-range context, or adaptation to unfamiliar domains [Yu et al., 2024, Zhang et al., 2025]. Moreover, while some studies explore feedback-driven data augmentation or generative instruction synthesis [Le et al., 2022], most lack a closed-loop framework that jointly optimizes coverage, difficulty, and model adaptation. The interplay between seed selection, model feedback, and evolution remains underexplored.

To address these gaps, we propose a unified instruction data construction framework that systematically expands both coverage and complexity. By integrating hierarchical tagging, high-information seed filtering, evolution-based synthesis, and deficiency-driven augmentation, our approach enables structured, scalable, and adaptive instruction data generation, laying the foundation for robust and generalizable instruction-tuned models.

6.2 Model Self-Improvement

Model self-improvement aims to iteratively enhance model capabilities through self-generated data or feedback signals. Representative approaches include self-refinement [Madaan et al., 2023, Zhou et al., 2024], multi-round generation and evaluation loops, and performance-driven data augmentation [Yang et al., 2025]. These methods enable models to identify and address their own weaknesses by generating more challenging training samples, thereby facilitating continual improvement.

To ensure data quality, recent studies introduce deficiency diagnosis mechanisms [Lighterness et al., 2024], which analyze model performance on downstream tasks to detect knowledge gaps or skill deficiencies. These insights guide the targeted synthesis of training data[Miller et al., 2025]. By incorporating such feedback into the training loop, models and datasets can co-evolve—improving both model performance and data coverage over time[Bauer et al., 2024].

Beyond simply increasing instruction quantity, recent research emphasizes instruction coverage (task/domain diversity) and depth (reasoning complexity). Several works have explored combining hierarchical tagging with complexity control to synthesize increasingly challenging and diverse instructions via evolutionary algorithms [Lu et al., Zhao et al., 2025]. These strategies enhance the

cognitive depth of training data and promote models’ abilities in complex reasoning and compositional generalization.

7 Conclusion

In this paper, we propose a novel framework, for constructing high-quality instruction datasets that continuously expand both the coverage and complexity of instruction data. By combining a hierarchical multilingual tagging system, informative seed instruction selection, evolutionary data synthesis, and model deficiency diagnosis, our framework enables generating instructions that effectively address gaps in coverage and complexity within existing instruction datasets. We demonstrate the utility of this framework through the construction of the Infinity Instruct Subject dataset, which contains over 1.5 million high-quality instructions, and show that it improves the instruction-following capabilities of foundation models across benchmarks. Further analyses show that our methodology can obtain instructions with enhanced coverage and depth. Moreover, the data distribution analysis uncovers interesting scaling laws in instruction data, suggesting a scale-free relationship between the co-occurrence of instruction tags and their frequency. These findings open up new avenues for understanding the internal knowledge structure of instruction datasets and offer insights into the scaling behavior of large models, which can be leveraged to improve training efficiency and model performance.

References

- Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V Le, Barret Zoph, Jason Wei, et al. The flan collection: designing data and methods for effective instruction tuning. In *Proceedings of the 40th International Conference on Machine Learning*, pages 22631–22648, 2023.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.
- Wasi Uddin Ahmad, Aleksander Ficek, Mehrzad Samadi, Jocelyn Huang, Vahid Noroozi, Somshubra Majumdar, and Boris Ginsburg. Opencodeinstruct: A large-scale instruction tuning dataset for code llms. *arXiv preprint arXiv:2504.04030*, 2025.
- Nihal Nayak, Yiyang Nan, Avi Trost, and Stephen Bach. Learning to generate instruction tuning datasets for zero-shot task adaptation. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 12585–12611, 2024.
- Yulei Qin, Gang Li, Zongyi Li, Zihan Xu, Yuchen Shi, Zhekai Lin, Xiao Cui, Ke Li, and Xing Sun. Incentivizing reasoning for advanced instruction-following of large language models. *arXiv preprint arXiv:2506.01413*, 2025.
- Ke Wang, Jiahui Zhu, Minjie Ren, Zeming Liu, Shiwei Li, Zongye Zhang, Chenkai Zhang, Xiaoyu Wu, Qiqi Zhan, Qingjie Liu, et al. A survey on data synthesis and augmentation for large language models. *arXiv preprint arXiv:2410.12896*, 2024.
- Ruibo Liu, Jerry Wei, Fangyu Liu, Chenglei Si, Yanzhe Zhang, Jinmeng Rao, Steven Zheng, Daiyi Peng, Diyi Yang, Denny Zhou, et al. Best practices and lessons learned on synthetic data. *arXiv preprint arXiv:2404.07503*, 2024.
- Lin Long, Rui Wang, Ruixuan Xiao, Junbo Zhao, Xiao Ding, Gang Chen, and Haobo Wang. On llms-driven synthetic data generation, curation, and evaluation: A survey. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 11065–11082, 2024.
- Zhang Shengyu, Dong Linfeng, Li Xiaoya, Zhang Sen, Sun Xiaofei, Wang Shuhe, Li Jiwei, Runyi Hu, Zhang Tianwei, Fei Wu, et al. Instruction tuning for large language models: A survey. *arXiv preprint arXiv:2308.10792*, 2023.

- Sania Sinha, Tanawan Premisri, and Parisa Kordjamshidi. A survey on compositional learning of ai models: Theoretical and experimental practices. *arXiv preprint arXiv:2406.08787*, 2024.
- Yingyi Zhong, Wen'an Zhou, and Zhixian Wang. A survey of data augmentation in domain generalization. *Neural Processing Letters*, 57(2):34, 2025.
- Hanqing Zhang, Haolin Song, Shaoyu Li, Ming Zhou, and Dawei Song. A survey of controllable text generation using transformer-based pre-trained language models. *ACM Computing Surveys*, 56(3):1–37, 2023.
- Jing Qian, Li Dong, Yelong Shen, Furu Wei, and Weizhu Chen. Controllable natural language generation with contrastive prefixes. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 2912–2924, 2022.
- Lianhui Qin, Sean Welleck, Daniel Khashabi, and Yejin Choi. Cold decoding: Energy-based constrained text generation with langevin dynamics. *Advances in Neural Information Processing Systems*, 35:9538–9551, 2022.
- Yuxiang Wei, Zhe Wang, Jiawei Liu, Yifeng Ding, and Lingming Zhang. Magicoder: Source code is all you need, 2023.
- Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. Enhancing chat language models by scaling high-quality instructional conversations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 3029–3051, 2023.
- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. Bge m3-embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. *arXiv preprint arXiv:2402.03216*, 2024.
- Martin Ester, Hans-Peter Kriegel, Jörg Sander, and Xiaowei Xu. A density-based algorithm for discovering clusters in large spatial databases with noise. In *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*, pages 226–231. AAAI Press, 1996.
- Keming Lu, Hongyi Yuan, Zheng Yuan, Runji Lin, Junyang Lin, Chuanqi Tan, Chang Zhou, and Jingren Zhou. # instag: Instruction tagging for analyzing supervised fine-tuning of large language models. In *NeurIPS 2023 Workshop on Instruction Tuning and Instruction Following*.
- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiayi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. Wizardlm: Empowering large language models to follow complex instructions. *arXiv e-prints*, pages arXiv–2304, 2023.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36:46595–46623, 2023a.

- Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. AlpacaEval: An automatic evaluator of instruction-following models, 2023.
- Tianle Li, Wei-Lin Chiang, Evan Frick, Lisa Dunlap, Banghua Zhu, Joseph E Gonzalez, and Ion Stoica. From live data to high-quality benchmarks: The arena-hard pipeline. *lmsys Blog* (Apr. 19, 2024), [Online]. Available: <https://lmsys.org/blog/2024-04-19-arena-hard/> (visited on 08/04/2024), 2024.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *ACL*, 2023.
- Teknium. Openhermes 1, 2023a. URL <https://huggingface.co/datasets/teknium/OpenHermes-1>.
- Hamish Ivison, Yizhong Wang, Valentina Pyatkin, Nathan Lambert, Matthew E Peters, Pradeep Dasigi, Joel Jang, David Wadden, Noah A Smith, Iz Beltagy, et al. Camels in a changing climate: Enhancing lm adaptation with tulu 2. *CoRR*, 2023.
- Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. Wildchat: 1m chatgpt interaction logs in the wild. In *The Twelfth International Conference on Learning Representations*.
- Teknium. Openhermes 2.5: An open dataset of synthetic data for generalist llm assistants, 2023b. URL <https://huggingface.co/datasets/teknium/OpenHermes-2.5>.
- College Park University of Maryland. GenQA dataset, 2024. URL <https://huggingface.co/datasets/tomg-group-umd/GenQA>.
- Zhangchen Xu, Fengqing Jiang, Luyao Niu, Yuntian Deng, Radha Poovendran, Yejin Choi, and Bill Yuchen Lin. Magpie: Alignment data synthesis from scratch by prompting aligned llms with nothing. *CoRR*, 2024.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Stanford alpaca: An instruction-following llama model, 2023.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric P Xing, et al. Lmsys-chat-1m: A large-scale real-world llm conversation dataset. *arXiv preprint arXiv:2309.11998*, 2023b.
- Hanyu Zhao, Li Du, Yiming Ju, Chengwei Wu, and Tengfei Pan. Beyond iid: Optimizing instruction finetuning from the perspective of instruction interaction and dependency. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 26031–26038, 2025.
- Zhiqian Tan, Chenghai Li, and Weiran Huang. The information of large language model geometry. *arXiv preprint arXiv:2402.03471*, 2024.
- Chunting Zhou, Pengfei Liu, Puxin Xu, Srini Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, Susan Zhang, Gargi Ghosh, Mike Lewis, Luke Zettlemoyer, and Omer Levy. Lima: Less is more for alignment. *arXiv preprint arXiv:2305.11206*, 2023.
- Niklas Muennighoff, Qian Liu, Armel Zebaze, Qinkai Zheng, Binyuan Hui, Terry Yue Zhuo, Swayam Singh, Xiangru Tang, Leandro Von Werra, and Shayne Longpre. Octopack: Instruction tuning code large language models. In *NeurIPS 2023 Workshop on Instruction Tuning and Instruction Following*, 2023.
- Xiang Yue, Tuney Zheng, Ge Zhang, and Wenhui Chen. Mammoth2: Scaling instructions from the web. *Advances in Neural Information Processing Systems*, 2024.
- Zeao Tu, Xiangdi Meng, Yu He, Zihan Yao, Tianyu Qi, Jun Liu, and Ming Li. Resofilter: Refined synthetic data filtering for large language models through data-parameter resonance analysis. *arXiv e-prints*, pages arXiv–2412, 2024.

- Junliang He, Ziyue Fan, Shaohui Kuang, Li Xiaoqing, Kai Song, Yaqian Zhou, and Xipeng Qiu. Fine: Filtering and improving noisy data elaborately with large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8686–8707, 2025.
- Sang Michael Xie, Shibani Santurkar, Tengyu Ma, and Percy S Liang. Data selection for language models via importance resampling. *Advances in Neural Information Processing Systems*, 36: 34201–34227, 2023.
- Shengkang Gu, Jiahao Liu, Dongsheng Li, Guangping Zhang, Mingzhe Han, Hansu Gu, Peng Zhang, Ning Gu, Li Shang, and Tun Lu. Llm-based user simulation for low-knowledge shilling attacks on recommender systems. *arXiv preprint arXiv:2505.13528*, 2025.
- Yuxin Jiang, Yufei Wang, Chuhan Wu, Xinyi Dai, Yan Xu, Weinan Gan, Yasheng Wang, Xin Jiang, Lifeng Shang, Ruiming Tang, et al. Instruction-tuning data synthesis from scratch via web reconstruction. *arXiv preprint arXiv:2504.15573*, 2025.
- Han Yu, Jiashuo Liu, Xingxuan Zhang, Jiayun Wu, and Peng Cui. A survey on evaluation of out-of-distribution generalization. *CoRR*, 2024.
- Xingxuan Zhang, Jiansheng Li, Wenjing Chu, Renzhe Xu, Yuqing Yang, Shikai Guan, Jiazheng Xu, Liping Jing, Peng Cui, et al. On the out-of-distribution generalization of large multimodal models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 10315–10326, 2025.
- Hung Le, Yue Wang, Akhilesh Deepak Gotmare, Silvio Savarese, and Steven Chu Hong Hoi. Coderl: Mastering code generation through pretrained models and deep reinforcement learning. *Advances in Neural Information Processing Systems*, 35:21314–21328, 2022.
- Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegrefe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *Advances in Neural Information Processing Systems*, 36:46534–46594, 2023.
- Chen Zhou, Zhe Wang, Bo Du, and Yilun Luo. Cycle self-refinement for multi-source domain adaptation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17096–17104, 2024. URL <https://ojs.aaai.org/index.php/AAAI/article/view/29654>.
- Diji Yang, Linda Zeng, Jinmeng Rao, and Yi Zhang. Knowing you don’t know: Learning when to continue search in multi-round rag through self-practicing. *arXiv e-prints*, pages arXiv–2505, 2025.
- Anthony Lighterness, Michael Adcock, Lauren Abigail Scanlon, and Gareth Price. Data quality-driven improvement in health care: Systematic literature review. *Journal of Medical Internet Research*, 26:e57615, 2024.
- Russell Miller, Sai Hin Matthew Chan, Harvey Whelan, and João Gregório. A comparison of data quality frameworks: A review. *Big Data and Cognitive Computing*, 9(4):93, 2025.
- Kevin Bauer, Rebecca Heigl, Oliver Hinz, and Michael Kosfeld. Feedback loops in machine learning: A study on the interplay of continuous updating and human discrimination. *Journal of the Association for Information Systems*, 25(4):804–866, 2024.

A Appendix

Given a dialogue between a user and a conversational assistant, and a classification standard that describes different abilities, determine which one or more major categories from this standard the assistant would need to utilize in order to complete the given dialogue. Note: only list the names of the abilities, and separate each different ability with angle brackets <>. Classification Standard: standard

1. **Programming and Software Development**
This category focuses on practical skills in programming languages, frameworks, tools, and software development. It includes mastery of various programming languages such as Python, Java, JavaScript, etc., as well as advanced skills like code comprehension, algorithm design, software architecture, and API integration.
2. **Data Science and Analysis**
Covers abilities related to using statistics, machine learning, and data processing techniques to extract knowledge and insights. These skills enable individuals to process, analyze, and interpret large datasets, make predictions or decisions, and present data via text analysis, visualization, and more.
3. **Mathematical Ability**
Includes various skills for solving mathematical problems such as computation, equation solving, and mathematical reasoning. This is not limited to basic arithmetic but also covers advanced fields such as algebra, geometry, and calculus.
4. **Natural Language Processing and Understanding**
Focuses on technologies for understanding and processing natural language. This includes everything from understanding word meanings to grasping the context of conversations or documents, interpreting instructions, and modifying text accordingly. It encompasses lexical and syntactic analysis, reading comprehension, language generation, sentiment analysis, summarization, irony detection, error correction, etc.
5. **Task Generation**
Involves generating common forms of text based on instructions, such as emails, news reports, leave requests, and other everyday document types.
6. **Education and Counseling**
Focuses on providing educational support, career guidance, personal development, and other forms of advisory services. This includes helping others learn new skills, make career decisions, and improve personal growth.
7. **Logic and Reasoning**
Centers on the ability to solve problems, perform reasoning, and understand complex concepts using logical thinking. This includes causal reasoning, common sense understanding, and problem-solving through logical inference.
8. **Creativity and Design**
Emphasizes creative thinking and design capabilities to produce outcomes, including artistic creation, storytelling, advertising, game design, poetry writing, etc. It involves original thinking and the ability to turn ideas into tangible creations.
9. **Problem Solving and Support**
Specializes in the ability to provide detailed explanations and assistance with problems. This includes direct answers to specific questions as well as explanatory guidance, suggestions, and coaching.
10. **Information Processing and Integration**
Involves skills for organizing, integrating, and managing information. This includes understanding, structuring, and articulating complex information, as well as formatting data for better usability, such as information extraction or transformation.
11. **Communication and Social Media**
Emphasizes effective communication in various contexts, especially on social media. This includes written and oral communication, conversational skills, and the ability to effectively convey information on news platforms, magazines, and social media.
12. **Project and Task Management**
Covers skills for planning, executing, and monitoring projects. This includes setting goals, allocating resources, time management, and coordinating teamwork.
13. **Analysis and Research**
Involves the ability to conduct in-depth analysis and scientific research. This includes research methodologies, problem analysis, data collection and evaluation, and the ability to write research reports, cite references, or create presentation materials like slides.
14. **Linguistic Knowledge, Multilingual and Cross-Cultural Understanding**
Focuses on the understanding and application of linguistic knowledge, including multilingual proficiency, translation ability, cultural understanding, recognition of diverse values, and effective communication in multicultural environments.
15. **STEM Knowledge**
Covers the use of science and engineering knowledge—such as physics, chemistry, electronics, biology, mechanics, computer science, geology, astronomy, artificial intelligence, etc.—to answer questions or solve problems.
16. **Humanities, History, Philosophy, and Sociology Knowledge**
Involves using knowledge from the humanities, history, and social sciences—such as history, geography, philosophy, religion, and cultural studies—to answer questions or solve problems.
17. **Finance, Economics, and Business Knowledge**
Involves understanding and applying principles of finance, economics, and business. This includes market analysis, investment and financial planning, and understanding business operations and marketing.
18. **Life Knowledge and Skills**
Includes everyday practical knowledge and skills such as cooking, sports, fashion, weather, travel, and entertainment. This category addresses solving daily life problems and improving personal quality of life and enjoyment.
19. **Legal Knowledge**
Refers to understanding and applying legal knowledge to answer questions, including knowledge about protecting personal and organizational security.
20. **Literary Creation and Arts Knowledge**
Includes using relevant knowledge to express opinions, analyze works, or answer questions related to all forms of creative and artistic expression—such as music, literature, and visual arts. This category emphasizes originality and personal expression.
21. **Medical, Pharmaceutical, and Health Knowledge**
Focuses on medical, pharmaceutical, and environmental science knowledge. This includes understanding healthcare, disease diagnosis, medication, pharmacology, wellness, and public health issues such as epidemics.
22. **Politics, Military Strategy, and Security Knowledge**
Refers to using knowledge of political science, political systems, military affairs, international relations, and strategic thinking to analyze and answer related questions.
23. **Psychology Knowledge**
Refers to using psychological knowledge to analyze and answer related questions.
24. **Open Task Completion**
Completing various customized, non-standard tasks based on the requirements or examples in the instructions, such as solving "24-point" puzzles, Sudoku, and other tasks that do not fit into the above categories, including generating custom or non-standard text.
25. **Open-Domain Knowledge Q&A**
Utilizes domain-specific or general knowledge to answer questions. Note that this ability applies specifically to areas not covered by any of the previously listed categories.

Figure 1: Classification standard for categorizing a fine-grained tag into a domain-tag.

Raw Dataset	Numbers of Rows
Alpaca GPT4 data	13,490
Alpaca GPT4 data zh	32,589
Baize	14,906
BELLE Generated Chat	43,775
BELLE Multiturn Chat	210,685
BELLE 3.5M CN	312,598
databricks-dolly-15K	10,307
LIMA-sft	712
CodeContest	523
LongForm	3,290
ShareGPT-Chinese-English-90k	8,919
UltraChat	237,199
Wizard evol instruct zh	44,738
Wizard evol instruct 196K	88,681
BELLE School Math	38,329
Code Alpaca 20K	13,296
WildChat	61,873
COIG-CQIA	45,793
BAGEL	55,193
DEITA	10,000
Summary	1,342,427

Table 1: Dataset Summary