

Collaborative Face Experts Fusion in Video Generation: Boosting Identity Consistency Across Large Face Poses

Yuji Wang^{1,*†}, Moran Li^{2,*}, Xiaobin Hu^{3,*}, Ran Yi¹, Jiangning Zhang², Chengming Xu²,
Weijian Cao², Yabiao Wang², Chengjie Wang², Lizhuang Ma^{1 ‡}

¹Shanghai Jiao Tong University, ²Tencent Youtu Lab, ³National University of Singapore

{moranli, vtzhang, chengmingxu, weijiancao, caseywang, jasoncjwang}@tencent.com,
{yujiwang, ranyi}@sjtu.edu.cn, xiaobin.hu@tum.de, ma-lz@cs.sjtu.edu.cn

Abstract

Current video generation models struggle with identity preservation under large face poses, primarily facing two challenges: the difficulty in exploring an effective mechanism to integrate identity features into DiT architectures, and the lack of targeted coverage of large face poses in existing open-source video datasets. To address these, we present two key innovations. First, we propose Collaborative Face Experts Fusion (CoFE), which dynamically fuses complementary signals from three specialized experts within the DiT backbone: an identity expert that captures cross-pose invariant features, a semantic expert that encodes high-level visual context, and a detail expert that preserves pixel-level attributes such as skin texture and color gradients. Second, we introduce a data curation pipeline comprising three key components: *Face Constraints* to ensure diverse large-pose coverage, *Identity Consistency* to maintain stable identity across frames, and *Speech Disambiguation* to align textual captions with actual speaking behavior. This pipeline yields *LaFID-180K*, a large-scale dataset of pose-annotated video clips designed for identity-preserving video generation. Experimental results on several benchmarks demonstrate that our approach significantly outperforms state-of-the-art methods in face similarity, FID, and CLIP semantic alignment.

[Project page.](#)

1. Introduction

Video generation has emerged as a critical technology for applications ranging from virtual avatars and interactive storytelling to realistic video editing. A critical yet unresolved




Figure 1. Top: Identity preservation under large face poses is challenging in current methods, while our approach shows clear gains in face similarity metrics. Bottom: With dynamic multi-feature injection, our proposed method achieves the best or competitive performance across all metrics.

challenge is maintaining the identity consistency of human characters, as *human visual perception is inherently more sensitive to identity inconsistencies in human portraits than in other subjects, particularly when face poses undergo large variations*. Such consistency is essential for narrative coherence in storybook generation, visual realism, and reliable character representation in multi-scene animations, as even subtle identity drift can severely undermine user immersion.

Recent Diffusion Transformer (DiT)-based image-to-video models such as CogVideoX [41] and Wan Model [33]

*Equal contribution.

†This work was done during internship at Tencent Youtu Lab.

‡Corresponding author.

achieve content consistency by injecting first-frame VAE features into the DiT backbone. To better preserve character identity, human-centric approaches like ConsisID [42] further inject a frequency-aware facial representation into DiT. However, both paradigms share critical limitations: they rely on a single face feature extracted from the reference frame and inject the same static face feature uniformly across all timesteps and DiT layers, thereby limiting the model’s ability to capture discriminative facial details. This leads to unstable identity preservation under large face poses, often resulting in distorted character appearances. Furthermore, existing human-centric datasets [21, 35] are ill-suited for learning pose-robust identity preservation. They often feature faces of inconsistent quality, lack sufficient dynamic large-angle examples, and seldom ensure cross-frame identity consistency or sufficient facial visibility, hindering the learning of pose-invariant identity representations.

To address these gaps, we propose Collaborative Face Experts Fusion (CoFE), a hierarchical feature integration framework that overcomes the limitations of static, single-feature identity injection. Since fixed features from the first frame often fail to provide reliable identity cues under large face poses, CoFE instead dynamically fuses complementary signals from three specialized experts via a learnable gating mechanism: *i) Identity Expert* extracts pose-robust identity features for cross-view consistency; *ii) Semantic Expert* captures high-level visual concepts (*e.g.*, hairstyle, expression); and *iii) Detail Expert* preserves pixel-level fidelity (*e.g.*, skin texture, color gradients). By aligning expert contributions with the functional role of each DiT layer, CoFE enables robust feature learning under large face poses.

Complementing our architectural innovation, we introduce LaFID-180K (**L**arge **F**ace Pose for **I**dentit**y** Preservation Dataset), a curated large-scale collection of video clips annotated with 3D face poses. This dataset specifically targets the scarcity of high-quality, identity-consistent videos under large face poses. LaFID-180K is built through a three-stage pipeline that directly addresses key data limitations: *Face Constraints* ensure clear facial visibility and diverse large-pose coverage; *Identity Consistency* enforces temporal identity coherence via feature clustering; and *Speech Disambiguation* aligns video captions with lip movements by verifying speaking status, ensuring accurate annotations under pose-induced ambiguity. We evaluate our method on two distinct benchmarks: the existing VIP-Test [23] for general full-body motion, and our newly introduced LaFID-Bench, which addresses the underexplored setting of large face poses.

Our contribution can be summarized as follows:

- We propose Collaborative Face Experts Fusion (CoFE), a dynamic, multi-source identity injection module that adaptively fuses three specialized experts across DiT layers for robust identity preservation under large face poses.

- We introduce LaFID-180K, a dataset of 180K video clips with 3D face pose annotations, curated specifically for large-pose identity preservation via Face Constraints, Identity Consistency, and Speech Disambiguation to ensure diverse large face poses, stable identity across frames, and accurate alignment between lip movements and captions.
- We establish LaFID-Bench for large face pose evaluation and show that CoFE achieves state-of-the-art results on both LaFID-Bench and VIP-Test, with strong gains under large face poses.

2. Related Work

2.1. Identity-Preserving Text-to-Video Generation

In the identity-preserving text-to-video (IPT2V) task, early methods used time-consuming fine-tuning for facial identity preservation [4, 20, 22, 36, 37, 46], driving tuning-free approaches to dominance. Pioneering works like ID-Animator [14] relied on static image-model features, harming dynamic identity consistency. ConsisID [42] injected facial frequency signals but suffered from 2D pose mismatches; FantasyID [45] added 3D priors but lacked adaptive feature selection. Recent methods like VACE [19] and SkyReels-A2 [10] used reference branches but failed to dynamically prioritize cues during large motions. These show I2V needs adaptive fusion of face features aligned with motion, especially large face motions. Thus, we introduce Collaborative Face Experts Fusion (CoFE), a DiT layer-adaptive gating mechanism that dynamically fuses multiple features to overcome static fusion and enhance large-pose robustness.

2.2. Human-Centric Image-to-Video Generation

Image-to-video (I2V) generation [3, 12, 40] struggles to control content reliably with text alone, so recent methods use first-frame conditioning for better controllability. AnimateAnything [6] and PixelDance [43] modify U-Nets by concatenating first-frame latent features with input noise to anchor spatial features for temporal consistency. Dynamicrafter [39] and Moonshot [44] enhance conditioning with image cross-attention layers, injecting stronger visual cues into diffusion. Recent methods like Wan2.1, Wan2.2 [33], and VACE [19] support I2V with strong performance but struggle to preserve identity across large face poses. Moreover, IPRO [30] introduces reinforcement learning to enhance training for facial details. Generally, identity robustness under large face pose variations remains largely undressed in current I2V frameworks.

2.3. Human-Centric Video Datasets

Large-scale human-centric video datasets [2, 5, 28] are foundational for human video generation, yet most prioritize body motion or general scenes over facial identity under large poses. For example, TikTok [18] focuses on social dance;




Figure 2. Overview of our pipeline. Our CoFE module comprises globally shared projection layers to align different face features into the feature space of DiT and per-DiT-block expert fusion layers for dynamic feature fusion. Specifically, we employ ArcFace, CLIP, and DINOv2 as our identity, semantic, and detail encoders, respectively.

UCF101 [31] and NTU RGB+D [29] on action recognition; HumanVid [35] on synthetic-real blends; and OpenHumanVid [21] provides high-resolution videos but lacks large face pose diversity, facial quality filtering, and fine-grained 3D face pose annotations, limiting its suitability for pose-robust identity learning. To address it, we introduce LaFID-180K, a dataset constructed by combining OpenHumanVid [21] with carefully selected in-house videos, and curated through a unified pipeline to emphasize diverse large face poses with 3D face pose annotations.

3. Methodology: CoFE

Current image-to-video models [13, 19, 33, 41] inject identity using a single-source feature extracted from the first frame, which is then applied statically across all timesteps and network layers, typically via uniform cross-attention. This design suffers from two fundamental limitations. First, the single feature conflates identity, semantics, and details into one representation, lacking specialization. Second, its static injection cannot adapt to pose-induced appearance changes or layer-specific attention demands, leading to severe identity drift under large pose variations. To overcome this, we propose *Collaborative Face Experts Fusion* (CoFE), a layer-adaptive fusion module that dynamically integrates three specialized facial representations into cross-attention: pose-robust identity features, semantic attributes (e.g., hairstyle, expression), and pixel-level details (e.g., color gradients). An overview of our pipeline is shown in Fig. 2.

Motivation from Cross-Attention Patterns. To under-




Figure 3. Cross-attention visualizations of different experts. Warmer colors denote higher attention strength. CoFE integrates complementary attention from Identity Expert (ArcFace), Semantic Expert (CLIP), and Detail Expert (DINOv2) to jointly enhance facial detail fidelity and identity consistency.

stand how different facial representations influence identity preservation, we analyze cross-attention patterns in the generator. As shown in Figure 3, each representation induces a distinct attention pattern: the Identity Expert (ArcFace [7]) focuses on pose-invariant landmarks such as the eyes, nose, and mouth to capture structural identity; the Semantic Expert (CLIP [26]) attends to high-level attributes including hairstyle and expression; and the Detail Expert (DINOv2 [24]) highlights fine-grained textures and structural edges. These complementary roles indicate that robust identity preservation under large pose variations requires dynamic fusion of all three signals rather than reliance on a single static feature.

Collaborative Face Experts Fusion. Our goal is to fuse hierarchical face features adaptive to distinct DiT blocks, thereby achieving complementary synergies that enhance identity persistence, semantic coherence, and pixel-level fidelity. To achieve this, we first employ a face preprocessor comprising a face detector [8] and a face parsing model [11] to obtain the cropped and aligned face image from the input

Table 1. Comparison with existing video datasets. Our LaFID-180K dataset uniquely provides **identity-consistent and clustered** human videos with skeleton and face pose annotations, supporting high-fidelity identity preservation in video generation.

Dataset name	Domain	# Videos	Annotations	Resolution	ID-Consistent?	ID-Clustered?
Koala-36M [34]	Open	36M	-	720P	✗	✗
OpenHumanVid [21]	Human	13.2M	Skeleton pose	720P	✗	✗
LaFID-180K(Ours)	Human	180K	Skeleton pose, face pose	720P, 1080P	✓	✓

image, removing background to focus on the face region. These preprocessed faces are then processed by identity, semantic, and detail encoders to generate identity-sensitive features, pixel-level detail features, and high-level semantic features, denoted as \mathbf{f}_{id} , \mathbf{f}_{sem} , \mathbf{f}_{det} , respectively.

The proposed CoFE module comprises two core components: *i)* Three globally shared projection layers, *i.e.*, P_{id} , P_{sem} , P_{det} , which project \mathbf{f}_{id} , \mathbf{f}_{sem} , \mathbf{f}_{det} into a unified feature space compatible with pre-trained DiT blocks, ensuring cross-modality alignment; *ii)* Per-DiT-block expert layers, each equipped with three dedicated experts, *i.e.*, \mathcal{E}_{id} , \mathcal{E}_{sem} , \mathcal{E}_{det} , and a lightweight gating mechanism that dynamically fuses the projected features. Each expert layer is tailored to the semantic depth of its DiT block, using adaptive gating (via a learnable MLP) to prioritize experts based on the block’s role in denoising processing. This design ensures global feature consistency through shared projection layers and local adaptivity through block-specific expert weighting, enabling end-to-end optimization of cross-dimensional facial representations. Formally, each expert refines its input feature for the i -th DiT block as:

$$\mathbf{e}_{attr}^i = \mathcal{E}_{attr}^i(P_{attr}(\mathbf{f}_{attr})), \text{attr} \in \{\text{id}, \text{sem}, \text{det}\}$$

Then a learnable gate mechanism computes adaptive weights for these experts based on the concatenated input features $\mathbf{e}_c^i = [\mathbf{e}_{id}^i, \mathbf{e}_{sem}^i, \mathbf{e}_{det}^i]$:

$$\mathbf{w}^i = \text{Softmax}(\mathcal{G}(\mathbf{e}_c^i)),$$

where \mathcal{G} is a linear projection mapping \mathbf{e}_c to weight vector $\mathbf{w}^i = [w_{id}^i, w_{sem}^i, w_{det}^i]$ with elements summing to 1. The final fused face feature, *i.e.*, \mathbf{f}_{fused}^i , can be obtained via:

$$\mathbf{f}_{fused}^i = \mathbf{w}^i \cdot \mathbf{e}_c^i$$

DiT Feature Injection To integrate the fused face features with the DiT architecture, the output of the CoFE module, \mathbf{f}_{fused}^i , is injected into the cross-attention layers of the i -th DiT block, enabling video latents to learn face-specific features throughout the denoising process. This injection introduces a dedicated facial cross-attention stream that operates in parallel with DiT’s existing context and image cross-attention streams. Each stream contributes key and value vectors: \mathbf{k}_{ctx}^i , \mathbf{v}_{ctx}^i are derived from context, \mathbf{k}_{img}^i , \mathbf{v}_{img}^i are extracted




Figure 4. The statistical analysis of the LaFID-180K dataset.

from the first frame to preserve initial visual consistency, and \mathbf{k}_{fused}^i , \mathbf{v}_{fused}^i are projected from \mathbf{f}_{fused}^i via learnable matrices to emphasize refined face features. Notably, the gate mechanism in CoFE dynamically adjusts the influence of the facial stream, adapting to various demands of different DiT blocks to achieve flexible face feature injection. The aggregated cross-attention output updates video latents as:

$$\mathbf{o}^i = \text{attn}^i(\mathbf{q}^i, \mathbf{k}_{ctx}^i, \mathbf{v}_{ctx}^i) + \text{attn}^i(\mathbf{q}^i, \mathbf{k}_{img}^i, \mathbf{v}_{img}^i) + \text{attn}^i(\mathbf{q}^i, \mathbf{k}_{fused}^i, \mathbf{v}_{fused}^i),$$

where $\text{attn}(\cdot)$ denotes the attention function.

4. LaFID Benchmark

4.1. Overview

To advance the study and evaluation of identity-preserving video generation under large face poses, we introduce **LaFID-180K**, a benchmark derived from OpenHumanVid [21] and supplemented with self-collected high-quality videos. As illustrated in Fig. 4, the dataset comprises 180K short clips (2~6 seconds, 720P~1080P) featuring diverse

identities, poses, and motions. Each clip is paired with a refined caption (45~75 words) that explicitly annotates spoken content and appearance attributes, supporting both semantic grounding and lip-sync disambiguation. This design ensures LaFID serves not only as a scalable training resource but, more critically, as a challenging benchmark for identity-preserving video generation.

A key design goal is to ensure both consistent identity representation and rich dynamic pose variation. To this end, our processing pipeline employs objective facial quality filtering that naturally yields videos with high aesthetic appeal, strong imaging quality, and stable subject identity (Fig. 5). We quantify pose variation by estimating 3D face angles (pitch, yaw, roll) per frame and computing the maximum angular range within each clip. As Fig. 5a demonstrates, LaFID exhibits significantly broader pose coverage than existing datasets, especially in extreme yaw and pitch, making it uniquely suited for identity preservation under challenging face motions.

Existing benchmarks such as VIP-Test [23] focus on full-body motion but lack sufficient variation in large face poses, limiting their ability to evaluate identity preservation under challenging pose conditions. To address this gap, we introduce **LaFID-Bench**, a standardized evaluation protocol derived from LaFID-180K, comprising fifty held-out identities (disjoint from training) with four diverse prompts per identity, all featuring large face poses that span extreme yaw and pitch ranges. For generalization assessment, we additionally construct a VIP-Test subset using SDXL-generated [25] reference images (fifty identities, four prompts each). Together, these two test sets enable the first holistic evaluation of image-to-video models across both standard full-body animation and the challenging regime of identity preservation under large face poses.

4.2. Data Processing Pipeline

Our overall data processing pipeline is illustrated in Fig. 6. To collect videos with substantial face pose variations, we apply a multi-stage procedure. The first step, **Face Constraints Filtering**, retains clips exhibiting large face pose variations (*e.g.*, extreme pitch, yaw or roll rotations). The second step, **Identity Consistency Analysis**, ensures facial identity remains coherent during pronounced face motion by discarding clips with inconsistent identity across frames. The third step, **Speech Disambiguation**, aligns lip motion or speech activity with caption by annotating whether the on-screen subject is speaking. Together, these steps ensure high-quality data for downstream identity-preserving tasks. **Face Constraints Filtering.** To support identity preservation under diverse face poses, especially large face motions, we curate high-quality samples for LaFID via multi-dimensional face constraints filtering, enforcing strict criteria on face continuity, visibility, and pose diversity. For




Figure 5. Comparison of video quality metrics between LaFID-180K and OpenHumanVid. LaFID-180K exhibits better quality.




Figure 6. The overview of the data processing pipeline for constructing dataset with large face poses.

efficiency, we sample one frame every three and detect face bounding boxes and poses using ArcFace [8]. The core constraints are: **i) Face count.** Focused on single person generation, we filter videos where any selected frame contains no faces or multiple faces. This ensures a single, continuous face throughout the video clip, foundational for consistent identity learning. **ii) Face proportion.** Video clips with

Table 2. Comparison with SOTA methods on LaFID-Bench benchmark dataset. The best results are highlighted in **Bold** (\uparrow/\downarrow represents the higher/lower the better). CoFE (Ours) has achieved the best performance across most metrics, demonstrating its superiority.

Method	Identity Preservation		Text Relevance	Video Quality				
	FaceSim-Arc \uparrow	FaceSim-Cur \uparrow		FID \downarrow	AQ \uparrow	IQ \uparrow	TF \uparrow	MS \uparrow
CogVideoX-5B [41]	0.629	0.636	29.331	104.214	0.499	0.598	0.976	0.986
LTX-2B [13]	0.438	0.440	28.800	151.773	0.513	0.581	0.980	0.992
ConsisID [42]	0.567	0.573	31.184	123.967	0.560	0.670	0.979	0.990
Wan2.1-I2V-1.3B [33]	0.654	0.656	29.200	72.322	0.553	0.660	0.989	0.993
Wan2.1 w/ CoFE	0.770	0.775	29.125	63.799	0.570	0.673	0.990	0.994
Wan2.2-TI2V-5B [33]	0.776	0.786	28.761	76.728	0.588	0.666	0.995	0.996
Wan2.2 w/ CoFE	0.814	0.827	28.729	70.727	0.591	0.669	0.996	0.996

Table 3. Comparison with SOTA methods on the VIP-Test benchmark. Our CoFE markedly improves these metrics, achieving the best identity consistency while maintaining strong text and video quality.

Method	Identity Preservation		Text Relevance	Video Quality				
	FaceSim-Arc \uparrow	FaceSim-Cur \uparrow		FID \downarrow	AQ \uparrow	IQ \uparrow	TF \uparrow	MS \uparrow
CogVideoX-5B [41]	0.462	0.474	28.947	163.001	0.512	0.585	0.926	0.948
LTX-2B [13]	0.301	0.323	28.403	203.516	0.510	0.586	0.944	0.975
ConsisID [42]	0.269	0.289	29.601	206.924	0.566	0.638	0.946	0.976
Wan2.1-I2V-1.3B [33]	0.471	0.480	29.825	129.116	0.554	0.659	0.940	0.967
Wan2.1 w/ CoFE	0.502	0.510	30.167	126.676	0.558	0.679	0.947	0.971
Wan2.2-TI2V-5B [33]	0.541	0.552	29.819	125.893	0.574	0.667	0.934	0.964
Wan2.2 w/ CoFE	0.605	0.615	29.834	113.850	0.583	0.668	0.948	0.979

low face bounding box proportion (*i.e.*, less than 10%) are filtered out to emphasize the preservation of facial details.

iii) Face pose diversity. To ensure preservation of identity across all face poses, we retain videos with diverse poses. We analyze the face poses of selected frames for each video clip, selecting videos with large face pose variations.

Identity Consistency Analysis Identity consistency is essential for human-centric videos, reflecting the stability of facial representations across frames. To ensure high-quality data curation, we analyze identity coherence using ArcFace features [7]. **i) Identity Similarity.** We compute pairwise cosine similarities between frame embeddings $\{\mathbf{d}_i\}_{i=1}^N$:

$$\text{sim}(\mathbf{d}_i, \mathbf{d}_j) = \frac{\mathbf{d}_i \cdot \mathbf{d}_j}{\|\mathbf{d}_i\| \|\mathbf{d}_j\|} \quad (i \neq j), \quad (1)$$

and use the average off-diagonal similarity \bar{s} as a measure of intra-clip identity coherence. Clips with $\bar{s} \leq 0.6$ are discarded. **ii) Identity Clustering.** To ensure disjoint identity splits for fair train/test evaluation, we cluster videos by identity using FAISS [9]. An IVF-PQ index [38] enables efficient similarity search in the ArcFace embedding space via product quantization. A two-stage hierarchical strategy is applied: a high threshold first forms tight identity clusters from strongly correlated samples; a lower threshold then assigns ambiguous samples to recover weakly correlated but same-identity instances.

Speech Disambiguation. LaFID is mainly curated from

OpenHumanVid [21], where most videos show people speaking with continuous lip movements but captions rarely indicate actual speech or lip motion. Without explicit speech semantics, identity-preserving generators often wrongly link lip motion to text, producing videos with incessant lip movement even when no speech motion is contained in the input caption. To align lip motion with caption, we disentangle speaking status in two steps: whisper [27] detects audible speech and its alignment with the primary subject’s lip movements; if the caption lacks explicit description of speaking, an LLM [1, 32] appends a context-aware sentence (*e.g.*, “The man is talking.”) to signal active speech. This ensures genuine speaking behavior is reflected in text-video alignment, enabling controllable and identity-consistent generation.

5. Experiments

5.1. Implementation Details

5.1.1. Training strategies

We integrate the proposed CoFE into the Wan2.1-I2V-1.3B and Wan2.2-TI2V-5B models [33]. To balance performance and efficiency, we inject CoFE into each even-numbered DiT block, in line with VACE [19]. This design enhances model capabilities while incurring a modest parameter increase of merely 18.5%. We employ aspect ratio bucketing for multi-resolution and multi-frame training, with a minimum video resolution of 480p and a frame count ranging



Figure 7. Qualitative comparison of identity preservation and pose handling. For each sequence, we report face similarity (sim) to the reference (first-frame) identity and face pose deviation (Δ , in degrees), defined as the angular distance between the current frame’s and the first frame’s 3D face orientations. CoFE achieves superior identity preservation and visual quality over existing methods.

from 49 to 129. To address the “copy-paste” shortcut, we incorporate face features from non-training frames into the input for video clips with additional frames. We use the Adam optimizer with a learning rate of $1e-5$ while keeping other modules frozen, and train on the LaFID-180K dataset for 4,000 iterations with a batch size of 256.

5.1.2. Evaluation Protocols

We evaluate our method on LaFID-Bench and VIP-Test [23], adopting the evaluation protocol of ConsisID [42] for metric selection. Specifically, we assess identity preservation using FaceSim-Arc [7] and FaceSim-Cur [16], text relevance via CLIP-Score [15], facial fidelity through FID, and overall video quality with VBench [17]. The latter includes four key sub-metrics: Aesthetic Quality (AQ), Imaging Quality (IQ), Temporal Flickering (TF), and Motion Smoothness (MS).

5.2. Benchmark Results

We compare our method with open-source state-of-the-art approaches [13, 33, 41, 42] on LaFID-Bench and VIP-Test [23] to demonstrate the superiority of our CoFE module in preserving identity under large face poses.

5.2.1. Quantitative Evaluation

As shown in Tables 2 and 3, our CoFE delivers substantial improvements on both Wan2.1 and Wan2.2, with larger gains for Wan2.1 on LaFID-Bench and for Wan2.2 on VIP-Test. This consistent enhancement across model generations and

generation scenarios reveals a key insight: identity preservation relies not on global video modeling alone but on the explicit injection of pose-robust, disentangled facial representations. Notably, our approach remains effective even in full-body settings where faces are small or temporally unstable, demonstrating that high-fidelity identity control can be achieved through localized facial priors decoupled from full-body motion synthesis.

On general video quality metrics (AQ, IQ, TF, and MS), CoFE outperforms all baselines, including Wan2.2, yielding higher visual appeal, fewer artifacts, and smoother motion. Existing methods exhibit distinct limitations: LTX-2B suffers from identity drift; ConsisID achieves high CLIP-Score but often generates blurry or distorted faces due to its narrow focus on facial alignment; and CogVideoX-5B delivers only moderate performance despite its large scale. Even the improved Wan2.2 falls short of CoFE in both identity fidelity and overall quality. These results demonstrate that explicitly modeling disentangled facial attributes such as identity, semantics, and detail as structured priors enables more robust and coherent video generation under complex dynamics.

5.2.2. Qualitative Evaluation

Fig. 7 presents qualitative comparison between our method and other SOTA methods. In scenarios with significant face movements, our model exhibits more stable generation and superior identity preservation: multi-source feature injection

Table 4. Comparison of face feature injection methods on LaFID-Bench. CoFE achieves the best identity preservation while maintaining strong text relevance and fidelity.

Method	FaceSim-Arc \uparrow	FaceSim-Cur \uparrow	CLIP-Score \uparrow	FID \downarrow
Wan-I2V [33]	0.654	0.656	29.200	72.322
w/ Identity Expert	0.661	0.665	29.402	80.305
w/ Semantic Expert	0.681	0.684	29.181	73.702
w/ Detail Expert	0.672	0.675	29.079	75.467
w/ Concat	0.732	0.735	29.143	63.418
w/ CoFE	0.770	0.775	29.125	63.799




Figure 8. Qualitative comparison between CoFE module and other face feature injection methods. Our proposed CoFE demonstrates superior identity preservation under large face angle variations in video sequences.

tion enhances facial details, ensuring consistent identity throughout the video clip. Specifically, ConsisID poorly renders front-facing details when given only a profile as input. CogVideoX and Wan2.2 fail to preserve identity during large face movements, causing obvious distortions and identity shifting. LTX-Video generates unstable, often blurry frames with lost identity details. Supplementary videos further validate our approach’s robustness.

5.3. Ablation Analysis

Feature Fusion Strategy Comparison. To validate the advantages of our adaptive face feature fusion, we compare CoFE with two common baselines: single-expert injection using the identity, semantic, or detail expert alone, and naive concatenation of all three experts. We evaluate these strategies on LaFID-Bench using Wan2.1-I2V-1.3B as the base model. As shown in Table 4 and Fig. 8, single-expert variants

Table 5. Ablation study on training datasets. Improvements from Pose Filtering and Speech Disambiguation (SD) are evident: LaFID w/o SD outperforms OpenHumanVid, and full LaFID further boosts identity fidelity and semantic alignment.

Dataset	FaceSim-Arc \uparrow	FaceSim-Cur \uparrow	CLIP-Score \uparrow	FID \downarrow
OpenHumanVid	0.801	0.813	28.659	75.578
LaFID w/o SD	0.807	0.816	28.634	73.128
LaFID	0.814	0.827	28.729	70.727

improve over the baseline but exhibit distinct weaknesses: the identity expert lacks fine details such as eye shape, the semantic expert shows inconsistent skin tones, and the detail expert yields blurry contours under large poses. Naive concatenation aggregates cues but treats them uniformly, introducing redundancy and misalignment that harm identity consistency. In contrast, CoFE achieves the highest FaceSim-Arc and FaceSim-Cur scores and the lowest FID, confirming that adaptive fusion of complementary facial representations is key to robust identity preservation.

Ablation of Training Data Processing. In our data processing pipeline, we introduce Face Constraints Filtering and Speech Disambiguation to enhance identity stability and semantic alignment. As shown in Table 5, models trained on our filtered data consistently outperform those using the raw OpenHumanVid subset, validating the effectiveness of our proposed data processing pipeline. Furthermore, incorporating Speech Disambiguation yields additional gains across all metrics, demonstrating that explicitly aligning captions with speaking status helps mitigate spurious lip-motion cues and improves identity preservation. More qualitative results are provided in our supplementary material.

6. Conclusion

In this paper, we address facial identity preservation under large pose variations in image-to-video generation through two key contributions. First, we introduce the Collaborative Face Experts Fusion (CoFE) module, which dynamically fuses identity-sensitive, semantic, and detail-oriented face features through a layer-adaptive cross-attention gating mechanism. Second, we curate LaFID-180K through a three-stage pipeline: facial constraints filtering for large-pose diversity, identity consistency analysis for cross-frame identity stability, and speech disambiguation to align captions with speaking status, effectively reducing lip motion and text ambiguity. To support rigorous evaluation in the challenging regime of large face poses, we introduce LaFID-Bench, a new benchmark specifically designed for this scenario. Experiments show that CoFE achieves state-of-the-art performance on both the general-purpose VIP-Test [23] and our specialized LaFID-Bench, demonstrating consistent improvements in identity preservation and overall video quality across diverse generation settings.

References

- [1] Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. Qwen technical report. *arXiv preprint arXiv:2309.16609*, 2023. 6
- [2] Max Bain, Arsha Nagrani, Gül Varol, and Andrew Zisserman. Frozen in time: A joint video and image encoder for end-to-end retrieval. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1728–1738, 2021. 2
- [3] Homanga Bharadhwaj, Debidatta Dwibedi, Abhinav Gupta, Shubham Tulsiani, Carl Doersch, Ted Xiao, Dhruv Shah, Fei Xia, Dorsa Sadigh, and Sean Kirmani. Gen2act: Human video generation in novel scenarios enables generalizable robot manipulation. *arXiv preprint arXiv:2409.16283*, 2024. 2
- [4] Hila Chefer, Shiran Zada, Roni Paiss, Ariel Ephrat, Omer Tov, Michael Rubinstein, Lior Wolf, Tali Dekel, Tomer Michaeli, and Inbar Mosseri. Still-moving: Customized video generation without customized video data. *ACM Transactions on Graphics (TOG)*, 43(6):1–11, 2024. 2
- [5] Tsai-Shien Chen, Aliaksandr Siarohin, Willi Menapace, Ekaterina Deyneka, Hsiang-wei Chao, Byung Eun Jeon, Yuwei Fang, Hsin-Ying Lee, Jian Ren, Ming-Hsuan Yang, et al. Panda-70m: Captioning 70m videos with multiple cross-modality teachers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13320–13331, 2024. 2
- [6] Zuozhuo Dai, Zhenghao Zhang, Yao Yao, Bingxue Qiu, Siyu Zhu, Long Qin, and Weizhi Wang. Animateanything: Fine-grained open domain image animation with motion guidance. *arXiv preprint arXiv:2311.12886*, 2023. 2
- [7] Jiankang Deng, Jia Guo, Niannan Xue, and Stefanos Zafeiriou. Arcface: Additive angular margin loss for deep face recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4690–4699, 2019. 3, 6, 7
- [8] Jiankang Deng, Jia Guo, Evangelos Ververas, Irene Kotsia, and Stefanos Zafeiriou. Retinaface: Single-shot multi-level face localisation in the wild. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5203–5212, 2020. 3, 5
- [9] Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvassy, Pierre-Emmanuel Mazaré, Maria Lomeli, Lucas Hosseini, and Hervé Jégou. The faiss library. *arXiv preprint arXiv:2401.08281*, 2024. 6
- [10] Zhengcong Fei, Debang Li, Di Qiu, Jiahua Wang, Yikun Dou, Rui Wang, Jingtao Xu, Mingyuan Fan, Guibin Chen, Yang Li, et al. Skyreels-a2: Compose anything in video diffusion transformers. *arXiv preprint arXiv:2504.02436*, 2025. 2
- [11] Adam Geitgey. Face recognition documentation. *Release*, 1(3):3–37, 2019. 3
- [12] Xun Guo, Mingwu Zheng, Liang Hou, Yuan Gao, Yufan Deng, Pengfei Wan, Di Zhang, Yufan Liu, Weiming Hu, Zhengjun Zha, et al. I2v-adapter: A general image-to-video adapter for diffusion models. In *ACM SIGGRAPH 2024 Conference Papers*, pages 1–12, 2024. 2
- [13] Yoav HaCohen, Nisan Chiprut, Benny Brazowski, Daniel Shalem, Dudu Moshe, Eitan Richardson, Eran Levin, Guy Shiran, Nir Zabari, Ori Gordon, et al. Ltx-video: Realtime video latent diffusion. *arXiv preprint arXiv:2501.00103*, 2024. 3, 6, 7
- [14] Xuanhua He, Quande Liu, Shengju Qian, Xin Wang, Tao Hu, Ke Cao, Keyu Yan, and Jie Zhang. Id-animator: Zero-shot identity-preserving human video generation. *arXiv preprint arXiv:2404.15275*, 2024. 2
- [15] Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. Clipscore: A reference-free evaluation metric for image captioning. *arXiv preprint arXiv:2104.08718*, 2021. 7
- [16] Yuge Huang, Yuhan Wang, Ying Tai, Xiaoming Liu, Pengcheng Shen, Shaoxin Li, Jilin Li, and Feiyue Huang. Curricularface: adaptive curriculum learning loss for deep face recognition. In *proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5901–5910, 2020. 7
- [17] Ziqi Huang, Yinan He, Jiashuo Yu, Fan Zhang, Chenyang Si, Yuming Jiang, Yuanhan Zhang, Tianxing Wu, Qingyang Jin, Nattapol Chanpaisit, et al. Vbench: Comprehensive benchmark suite for video generative models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 21807–21818, 2024. 7
- [18] Yasamin Jafarian and Hyun Soo Park. Learning high fidelity depths of dressed humans by watching social media dance videos. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12753–12762, 2021. 2
- [19] Zeyinzi Jiang, Zhen Han, Chaojie Mao, Jingfeng Zhang, Yulin Pan, and Yu Liu. Vace: All-in-one video creation and editing. *arXiv preprint arXiv:2503.07598*, 2025. 2, 3, 6
- [20] Wentao Lei, Jinting Wang, Fengji Ma, Guanjie Huang, and Li Liu. A comprehensive survey on human video generation: Challenges, methods, and insights. *arXiv preprint arXiv:2407.08428*, 2024. 2
- [21] Hui Li, Mingwang Xu, Yun Zhan, Shan Mu, Jiaye Li, Kaihui Cheng, Yuxuan Chen, Tan Chen, Mao Ye, Jingdong Wang, et al. Openhumanvid: A large-scale high-quality dataset for enhancing human-centric video generation. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 7752–7762, 2025. 2, 3, 4, 6
- [22] Yue Ma, Kunyu Feng, Zhongyuan Hu, Xinyu Wang, Yucheng Wang, Mingzhe Zheng, Xuanhua He, Chenyang Zhu, Hongyu Liu, Yingqing He, et al. Controllable video generation: A survey. *arXiv preprint arXiv:2507.16869*, 2025. 2
- [23] ACM Multimedia. Ipv challenge. <https://hidream-ai.github.io/ipv-g-challenge.github.io>, 2025. Accessed: June 5, 2025. 2, 5, 7, 8
- [24] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023. 3
- [25] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach.

- Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023. 5
- [26] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021. 3
- [27] Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR, 2023. 6
- [28] Najmeh Sadoughi, Yang Liu, and Carlos Busso. Msp-avatar corpus: Motion capture recordings to study the role of discourse functions in the design of intelligent virtual agents. In *2015 11th IEEE International Conference and Workshops on Automatic Face and Gesture Recognition (FG)*, pages 1–6. IEEE, 2015. 2
- [29] Amir Shahrudiy, Jun Liu, Tian-Tsong Ng, and Gang Wang. Ntu rgb+ d: A large scale dataset for 3d human activity analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1010–1019, 2016. 3
- [30] Liao Shen, Wentao Jiang, Yiran Zhu, Tiezheng Ge, Zhiguo Cao, and Bo Zheng. Identity-preserving image-to-video generation via reward-guided optimization. *arXiv preprint arXiv:2510.14255*, 2025. 2
- [31] Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012. 3
- [32] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023. 6
- [33] Team Wan, Ang Wang, Baole Ai, Bin Wen, Chaojie Mao, Chen-Wei Xie, Di Chen, Feiwei Yu, Haiming Zhao, Jianxiao Yang, et al. Wan: Open and advanced large-scale video generative models. *arXiv preprint arXiv:2503.20314*, 2025. 1, 2, 3, 6, 7, 8
- [34] Qiuheng Wang, Yukai Shi, Jiarong Ou, Rui Chen, Ke Lin, Jiahao Wang, Boyuan Jiang, Haotian Yang, Mingwu Zheng, Xin Tao, et al. Koala-36m: A large-scale video dataset improving consistency between fine-grained conditions and video content. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 8428–8437, 2025. 4
- [35] Zhenzhi Wang, Yixuan Li, Yanhong Zeng, Youqing Fang, Yuwei Guo, Wenran Liu, Jing Tan, Kai Chen, Tianfan Xue, Bo Dai, et al. Humanvid: Demystifying training data for camera-controllable human image animation. *Advances in Neural Information Processing Systems*, 37:20111–20131, 2024. 2, 3
- [36] Yujie Wei, Shiwei Zhang, Zhiwu Qing, Hangjie Yuan, Zhiheng Liu, Yu Liu, Yingya Zhang, Jingren Zhou, and Hongming Shan. Dreamvideo: Composing your dream videos with customized subject and motion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6537–6549, 2024. 2
- [37] Jianzong Wu, Xiangtai Li, Yanhong Zeng, Jiangning Zhang, Qianyu Zhou, Yining Li, Yunhai Tong, and Kai Chen. Motionbooth: Motion-aware customized text-to-video generation. *arXiv preprint arXiv:2406.17758*, 2024. 2
- [38] Shitao Xiao, Zheng Liu, Weihao Han, Jianjin Zhang, Defu Lian, Yeyun Gong, Qi Chen, Fan Yang, Hao Sun, Yingxia Shao, et al. Distill-vq: Learning retrieval oriented vector quantization by distilling knowledge from dense embeddings. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1513–1523, 2022. 6
- [39] Jinbo Xing, Menghan Xia, Yong Zhang, Haoxin Chen, Wangbo Yu, Hanyuan Liu, Gongye Liu, Xintao Wang, Ying Shan, and Tien-Tsin Wong. Dynamicrafter: Animating open-domain images with video diffusion priors. In *European Conference on Computer Vision*, pages 399–417. Springer, 2024. 2
- [40] Jiacong Xu, Yiqun Mei, Ke Zhang, and Vishal M Patel. Freevis: Training-free video stylization with inconsistent references. *arXiv preprint arXiv:2510.01686*, 2025. 2
- [41] Zhuoyi Yang, Jiayan Teng, Wendi Zheng, Ming Ding, Shiyu Huang, Jiazheng Xu, Yuanming Yang, Wenyi Hong, Xiaohan Zhang, Guanyu Feng, et al. Cogvideox: Text-to-video diffusion models with an expert transformer. *arXiv preprint arXiv:2408.06072*, 2024. 1, 3, 6, 7
- [42] Shenghai Yuan, Jinfa Huang, Xianyi He, Yunyang Ge, Yujun Shi, Liuhan Chen, Jiebo Luo, and Li Yuan. Identity-preserving text-to-video generation by frequency decomposition. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 12978–12988, 2025. 2, 6, 7
- [43] Yan Zeng, Guoqiang Wei, Jiani Zheng, Jiaxin Zou, Yang Wei, Yuchen Zhang, and Hang Li. Make pixels dance: High-dynamic video generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8850–8860, 2024. 2
- [44] David Junhao Zhang, Dongxu Li, Hung Le, Mike Zheng Shou, Caiming Xiong, and Doyen Sahoo. Moonshot: Towards controllable video generation and editing with multimodal conditions. *arXiv preprint arXiv:2401.01827*, 2024. 2
- [45] Yunpeng Zhang, Qiang Wang, Fan Jiang, Yaqi Fan, Mu Xu, and Yonggang Qi. Fantasyid: Face knowledge enhanced id-preserving video generation. *arXiv preprint arXiv:2502.13995*, 2025. 2
- [46] Yong Zhong, Zhuoyi Yang, Jiayan Teng, Xiaotao Gu, and Chongxuan Li. Concat-id: Towards universal identity-preserving video synthesis. *arXiv preprint arXiv:2503.14151*, 2025. 2