

Graded Distributed Belief

Emiliano Lorini

IRIT, CNRS, Toulouse University
Toulouse, France

Emiliano.Lorini@irit.fr

Dmitry Rozplokhas

TU Wien
Vienna, Austria

dmitry@logic.at

We introduce a new logic of graded distributed belief that allows us to express the fact that a group of agents distributively believe that a certain fact φ holds with at least strength k . We interpret our logic by means of computationally grounded semantics relying on the concept of belief base. The strength of the group's distributed belief is directly computed from the group's belief base after having merged its members' individual belief bases. We illustrate our logic with an intuitive example, formalizing the notion of epistemic disagreement. We also provide a sound and complete Hilbert-style axiomatization, decidability result obtained via filtration, and a tableaux-based decision procedure that allows us to state PSPACE-completeness for our logic.

1 Introduction

The idea of using belief bases as formal semantics for multi-agent epistemic logic was first introduced in [26] and further developed in [27, 28]. This approach aligns with the sentential (or syntactic) perspective on knowledge representation [21, 13, 33, 20], which holds that an agent's body of knowledge should be represented as a set of sentences in a formal language. The key novelty of belief base semantics, compared to traditional epistemic logic semantics based on multi-relational Kripke models [31, 12], lies in two main aspects. First, a possible world (or state) in a model is not treated as a primitive entity but is instead composed of the agents' belief bases and a valuation of propositional atoms. Second, the agents' accessibility relations are not explicitly part of the model but are determined *a posteriori* from their belief bases. Specifically, in this semantics, an agent at state S considers state S' possible (or epistemically accessible) if and only if S' satisfies all the formulas in the agent's belief base at S . This decomposition of a state into more fundamental elements is shared by various approaches in symbolic model checking and computationally grounded semantics for epistemic logic. These include frameworks based on interpreted systems, where a global state is decomposed into individual agents' local states [10, 25], as well as those that rely on the primitive notion of observability or visibility [17, 6, 14, 4]. At the language level, the belief base approach distinguishes explicit (or actual) belief from implicit (or potential) belief. The distinction between explicit and implicit belief has been widely discussed in the literature [23, 9]. In the belief base approach, this distinction is based on the concept of *deducibility*: explicit beliefs are those directly stored in an agent's belief base, while implicit beliefs consist of any information that can be logically inferred from those explicit beliefs.

In two subsequent works, the belief base approach has been shown to successfully represent notions of distributed and common belief [15, 29], as well as graded belief [30]. On the one hand, belief base semantics allows for a natural distinction between explicit and implicit distributed belief. While the explicit distributed belief of a group is given by the merging of the belief bases of its members, the implicit distributed belief corresponds to what can be deduced from the (collective) belief base resulting from this merging. On the other hand, the approach allows us to define a natural notion of the degree (or strength) of an agent's implicit belief that φ , understood as the maximum number of pieces of information

that can be removed from the agent's belief base without preventing the agent from deducing φ from their explicit beliefs.

In this paper, we present a generalization of the belief base semantics for epistemic logic we introduced in [26, 28]. In the original semantics, agents' belief bases were simply sets of formulas built from a language including propositional facts and explicit beliefs: an agent's belief base could include both information about the world and information about other agents' belief bases. Our generalization moves from plain (ungraded) belief bases to graded belief bases by using a multiset representation. In a graded belief base, each piece of information is associated with a natural number representing the strength of the agent's explicit belief, with 0 associated to a formula α meaning that the agent has no explicit belief that α . We use this more general semantics to define a novel notion of *graded distributed belief*, as a piece of information φ that a group can deduce from their collective belief base with a given strength k . Given a graded belief base for each agent in a group, we compute the group's graded distributed belief in two steps. First, we merge the graded belief bases of the group's members to obtain a collective graded belief base. The degree that the group assigns to a formula α corresponds to the sum of the degrees that each member assigns to α . Second, we compute the group's degree of distributed belief in a certain fact φ as the amount of information that can be removed from the group's belief base without preventing it from deducing φ . We also show how our framework can be used to define a quantitative notion of epistemic disagreement within a group, based on the amount of information that must be removed from the group's collective belief base to restore consistency. This notion of disagreement bears similarities to the measure of inconsistency defined in [19], namely, the minimal number of formulas that need to be removed from a belief base to restore consistency.

The paper is organized as follows. In Section 2, we first present the general framework: the graded belief base semantics, the modal language for representing implicit graded distributed belief, its semantic interpretation and an example illustrating our framework as well as the notion of epistemic disagreement within a group that can be defined in our framework. Following [28], in Section 3, we introduce an alternative Kripke-style semantics for our modal language, which serves as a technical tool for investigating the proof-theoretic aspects of our framework. Section 4 presents a Hilbert-style axiomatics for our logic of graded distributed belief. Then, in Section 5 we present a decision procedure based on tableaux, which allows us to establish PSPACE-completeness for our logic.

Before turning to the core of the paper, we briefly discuss some related work. Although the notion of graded distributed belief and the graded belief base semantics used to interpret it, as introduced in this paper, are new, the notion of plain distributed belief has been widely investigated in epistemic logic [12, 36, 1, 32, 7, 24, 2, 11]. Moreover, the idea of having graded belief modalities for individual agents was explored in previous work [22], in line with work in ranking theory [34]. Other approaches employ graded modalities for individual agents, where the degree of belief is determined either by the number of worlds in which the believed formula holds true [18, 16, 5], or by the amount of evidence supporting it [3]. The notion of graded belief base is also used in possibility theory [8]. In the present paper, we generalize it to the multi-agent setting and to nested beliefs.

2 Framework

In this section, we present our graded belief base semantics and show how to use it to compute graded doxastic accessibility relations for agents and groups. Then, we introduce a modal language of graded distributed belief and interpret it using the semantics. We illustrate our language and semantics with the help of a concrete example.

2.1 Notation

In this paper we will work with graded sets (or multisets), where grade (or cardinality) of each element is either a natural number (including zero) or infinity (denoted ω). To avoid confusion we use notation \mathbb{N}_0 and \mathbb{N}_1 for natural numbers with and without zero respectively, and \mathbb{N}_0^ω and \mathbb{N}_1^ω for their extensions with element ω . We represent a graded set over set X by a function $f: X \rightarrow \mathbb{N}_0^\omega$, and define the *support* of this graded set as $Supp(f) = \{x \in X \mid f(x) > 0\}$. We denote the set of all multisets over X by $\mathcal{M}(X)$.

For $X \subseteq \mathbb{N}_0^\omega$ we will use notation $\min^* X = \min(X \cup \{0\})$ and $\max^* X = \max(X \cup \{\omega\})$ to avoid dealing with the case of empty set. We will also consider potentially infinite sums of grades. Since grades are natural numbers (or infinity) such sums have natural well-behaved definition: we define it as sum of non-zero summands if there are finitely many such summands and none of them is ω , and as ω otherwise. Finally, we will use the notion of *partitions*, i.e. functions dividing the given grade $k \in \mathbb{N}_0$ among agents in group J : $\mathcal{P}art(J, k) = \{\delta: J \rightarrow \mathbb{N}_0 \mid \sum_{i \in J} \delta(i) = k\}$.

2.2 Semantics

We are going to present a belief base semantics for epistemic attitudes of agents that generalizes the belief base semantics introduced in [26, 28] to multisets. Multisets are used to represent agents' explicit beliefs with their strengths, weight or epistemic importance. Unlike the standard Kripke semantics for epistemic logic in which the notions of epistemic alternative and plausibility of a world (or state) are given as primitive, in this semantics they are defined from the primitive concept of graded belief base.

Assume a countably infinite set of atomic propositions Atm and a finite set of agents $Agt = \{1, \dots, n\}$. The set of non-empty groups is denoted by $2^{Agt*} = 2^{Agt} \setminus \{\emptyset\}$. We define the language $\mathcal{L}_0(Atm, Agt)$ for representing agents' graded explicit beliefs by the following grammar:

$$\alpha ::= p \mid \neg\alpha \mid \alpha \wedge \alpha \mid \Delta_i^k \alpha,$$

where p ranges over Atm , i ranges over Agt and k ranges over \mathbb{N}_1^ω . The formula $\Delta_i^k \alpha$ is read “agent i explicitly believes that α with at least degree k ”. For notational convenience, we abbreviate $\Delta_i \alpha \stackrel{def}{=} \Delta_i^1 \alpha$. The formula $\Delta_i \alpha$ is simply read “agent i explicitly believes that α ”.

For notational convenience we write \mathcal{L}_0 instead of $\mathcal{L}_0(Atm, Agt)$, when the context is unambiguous.

Definition 1. A state is a tuple $S = (\mathcal{B}_1, \dots, \mathcal{B}_n, V)$ where for every $i \in Agt$, $\mathcal{B}_i \in \mathcal{M}(\mathcal{L}_0)$ is agent i 's graded belief base, and $V \subseteq Atm$ is the actual environment. The set of all states is denoted by \mathbf{S} .

\mathcal{B}_i assigns a weight $\mathcal{B}_i(\alpha)$ to each formula from $\alpha \in \mathcal{L}_0$, capturing the strength of agent i 's explicit belief that α .

The language \mathcal{L}_0 is interpreted with respect to states, as follows.

Definition 2. Let $S = (\mathcal{B}_1, \dots, \mathcal{B}_n, V) \in \mathbf{S}$. Then:

$$\begin{aligned} S \models p &\iff p \in V, \\ S \models \neg\alpha &\iff S \not\models \alpha, \\ S \models \alpha_1 \wedge \alpha_2 &\iff S \models \alpha_1 \text{ and } S \models \alpha_2, \\ S \models \Delta_i^k \alpha &\iff \mathcal{B}_i(\alpha) \geq k. \end{aligned}$$

Observe in particular the following interpretation of the graded explicit belief operator: agent i explicitly believes that α with at least degree k if and only if the information α has an importance for the agent at least equal to k .

From the agents' graded belief bases $\mathcal{B}_1, \dots, \mathcal{B}_n$ it is natural to compute the collective graded belief base $\mathcal{B}_J \in \mathcal{M}(\mathcal{L}_0)$ of a group J : the degree of explicit belief of the group is equal to the sum of the degrees of beliefs of the group's members.

Definition 3. Let $S = (\mathcal{B}_1, \dots, \mathcal{B}_n, V) \in \mathbf{S}$ and $J \in 2^{Agt^*}$. Then, $\mathcal{B}_J(\alpha) = \sum_{i \in J} \mathcal{B}_i(\alpha)$ for every $\alpha \in \mathcal{L}_0$.

This definition extends the notion of “pooling” belief bases from [15] to the weighted case, assuming agent independence and epistemic egalitarianism. Note that we do not rely on more involved forms of belief base aggregation aimed at preserving consistency, since in our framework individual belief bases may already be inconsistent.

The following definition introduces the notion of graded doxastic alternative for a group.

Definition 4. Let $J \in 2^{Agt^*}$ and let $k \in \mathbb{N}_0$. Then, \mathcal{R}_J^k is the binary relation on the set \mathbf{S} such that, for all $S = (\mathcal{B}_1, \dots, \mathcal{B}_n, V), S' = (\mathcal{B}'_1, \dots, \mathcal{B}'_n, V') \in \mathbf{S}$:

$$S \mathcal{R}_J^k S' \text{ if and only if } \sum_{\substack{\alpha \in \mathcal{L}_0 \\ S' \not\models \alpha}} \mathcal{B}_J(\alpha) \leq k.$$

$S \mathcal{R}_J^k S'$ means that, from the point of view of the group J at state S , state S' is at most k -implausible, where the degree of implausibility of a state for a group is equal to the weighted sum of the group's explicit beliefs that are not satisfied at the state. This means that the degree of implausibility of a state for a group depends on i) how much information that the group has in its belief base is not satisfied at the state, and ii) how important is that information for the group.

Notice that $S \mathcal{R}_J^k S'$ can also be interpreted as the fact that state S' is considered possible for the group J after removing from its collective belief base a body of information of importance at most equal to k . Indeed, $\sum_{\substack{\alpha \in \mathcal{L}_0 \\ S' \not\models \alpha}} \mathcal{B}_J(\alpha)$ can also be conceived as the total amount of importance for the group J at state S of the information that is not satisfied at state S' .

A graded doxastic accessibility relation \mathcal{R}_J^k induces a plausibility ordering over states, as in [34, 22]. For notational convenience, we write \mathcal{R}_J instead of \mathcal{R}_J^0 . Clearly, $S \mathcal{R}_J S'$ if and only iff $\forall \alpha \in \mathcal{L}_0$, if $\mathcal{B}_J(\alpha) > 0$ then $S' \models \alpha$. In words, a state is 0-implausible from the point of view of a group if it satisfies all information in the group's belief base.

Before concluding this section, we define the concept of a model as a state supplemented with a set of states, called *context*. The latter includes all states compatible with the the agents' common ground [35], i.e., the body of information that the agents commonly believe to be the case.

Definition 5. A multi-agent graded belief model (MAGBM) is a pair (S, U) , where $S \in \mathbf{S}$ and $U \subseteq \mathbf{S}$. The class of models is denoted by \mathbf{M} .

2.3 Language

We consider a modal language $\mathcal{L}(Atm, Agt)$ that extends the language $\mathcal{L}_0(Atm, Agt)$ given above with graded distributed belief modalities. It is defined by the following grammar:

$$\varphi ::= \alpha \mid \neg \varphi \mid \varphi \wedge \varphi \mid \Box_J^k \varphi,$$

where α ranges over $\mathcal{L}_0(Atm, Agt)$, J ranges over 2^{Agt^*} and k ranges over \mathbb{N}_0 . For notational convenience we write \mathcal{L} instead of $\mathcal{L}(Atm, Agt)$, when the context is unambiguous. The other Boolean constructions \top , \perp , \rightarrow and \leftrightarrow are defined in the standard way.

We interpret the modal language \mathcal{L} relative to a model by means of the graded accessibility relations \mathcal{R}_J^k .

Definition 6. Let $(S, U) \in \mathbf{M}$. Then:

$$\begin{aligned} (S, U) \models \alpha &\iff S \models \alpha, \\ (S, U) \models \neg\varphi &\iff S \not\models \varphi, \\ (S, U) \models \varphi_1 \wedge \varphi_2 &\iff S \models \varphi_1 \text{ and } S \models \varphi_2, \\ (S, U) \models \Box_J^k \varphi &\iff \forall S' \in U, \text{ if } S \mathcal{R}_J^k S' \text{ then } (S', U) \models \varphi. \end{aligned}$$

The modal formula $\Box_J^k \varphi$ is read “group J would implicitly believe that φ , for every removal from its belief base of a body of information of importance at most equal to k ”. The value k can also be conceived as the extent to which group J distributively believes that φ . Indeed, the higher the importance of the information that can be removed from the group’s belief base without affecting what the group can infer, the stronger the inference and so the group’s resulting distributed belief. Thus, $\Box_J^k \varphi$ can also be read “group J has an implicit distributed belief that φ of degree (or strength) at least k ”. The abbreviation $\Diamond_J^k \varphi \stackrel{\text{def}}{=} \neg \Box_J^k \neg \varphi$ defines the concept of distributed belief compatibility. The formula $\Diamond_J^k \varphi$ has to be read “ φ would be compatible with group J ’s explicit beliefs, for some removal from its collective belief base of a body of information of importance at most equal to k ”.

2.4 Conceptual Analysis

We are going to show how our language and semantics can be leveraged to formally represent graded distributed belief as well as degree of epistemic disagreement within a group of agents. The latter notion is formally defined by the following abbreviation: $\text{Disagree}(J, k) \stackrel{\text{def}}{=} \Box_J^{k-1} \perp$ for $k \geq 1$. $\text{Disagree}(J, k)$ means that within the group J there is an epistemic disagreement of at least strength k .

Example 1. *Ann, Bob, Cath and John are the four members of a research project evaluation committee. Their task is to decide whether a submitted project for funding can be included in the list of “fundable” projects or not. They are all convinced with at least strength $k_0 > 0$ that a project should be included in the list (in) if and only if its idea is innovative (id) and, at the same time, the project’s consortium is of high scientific standard (hi). This hypothesis is captured by the following abbreviation:*

$$\alpha_1 \stackrel{\text{def}}{=} \bigwedge_{i \in \{\text{Ann}, \text{Bob}, \text{Cath}, \text{John}\}} \Delta_i^{k_0} (\text{in} \leftrightarrow (\text{id} \wedge \text{hi})).$$

However, they have diverging opinions and, in some cases, have not yet formed an opinion regarding these qualities of the project. In particular, Ann explicitly believes with degree $k_1 > 0$ that the project’s idea is innovative, and Cath believes the opposite with degree $k_3 > 0$, Bob explicitly believes with degree $k_2 > 0$ that the project’s consortium is of high scientific standard, and John explicitly believes the opposite with degree $k_4 > 0$. This hypothesis is captured by the following abbreviation:

$$\alpha_2 \stackrel{\text{def}}{=} \Delta_{\text{Ann}}^{k_1} \text{id} \wedge \Delta_{\text{Bob}}^{k_2} \text{hi} \wedge \Delta_{\text{Cath}}^{k_3} \neg \text{id} \wedge \Delta_{\text{John}}^{k_4} \neg \text{hi}.$$

It is routine to verify that group $\{\text{Ann}, \text{Bob}\}$ implicitly believes with degree $(\min\{2k_0, k_1, k_2\} - 1)$ that the project should be included in the list, while group $\{\text{Cath}, \text{John}\}$ believes the opposite with degree $(\min\{2k_0, k_3 + k_4\} - 1)$:

$$\models (\alpha_1 \wedge \alpha_2) \rightarrow (\Box_{\{\text{Ann}, \text{Bob}\}}^{\min\{2k_0, k_1, k_2\}-1} \text{in} \wedge \Box_{\{\text{Cath}, \text{John}\}}^{\min\{2k_0, k_3 + k_4\}-1} \neg \text{in}).$$

Moreover, when the explicit information is restricted to $\alpha_1 \wedge \alpha_2$ there is no disagreement within these groups (i.e. there exist models where $\alpha_1 \wedge \alpha_2$ is true and $\text{Disagree}(J, 1)$ is false), while all four agents together have an epistemic disagreement of at least strength $(\min\{k_1, k_3\} + \min\{k_2, k_4\})$:

$$\begin{aligned} \not\models (\alpha_1 \wedge \alpha_2) &\rightarrow (\text{Disagree}(\{Ann, Bob\}, 1) \vee \text{Disagree}(\{Cath, John\}, 1)) \\ \models (\alpha_1 \wedge \alpha_2) &\rightarrow \text{Disagree}(\{Ann, Bob, Cath, John\}, \min\{k_1, k_3\} + \min\{k_2, k_4\}). \end{aligned}$$

3 Alternative semantics

To explore the proposed logic we will follow the general approach of [26] and introduce two alternative equivalent semantical characterizations: *notional* and *quasi-notional graded doxastic models*.

First, we redefine models in terms closer to Kripke semantics for modal logics by introducing the notion of distance between states for a given group of agents as the sum of degrees in the first world of all beliefs not satisfied in the second world for all agents in the group. Note that this notion of distance is not (in general) symmetric.

Definition 7. A notional graded doxastic model (NGDM) is a tuple $M = (W, \mathcal{D}, \rho, \mathcal{V})$ where W is a set of worlds, $\mathcal{D}: \text{Agt} \times W \rightarrow \mathcal{M}(\mathcal{L}_0)$ is a doxastic function, $\rho: 2^{\text{Agt}^*} \times W \times W \rightarrow \mathbb{N}_0^\omega$ is a distance function, and $\mathcal{V}: \mathbb{P} \rightarrow 2^W$ is a valuation, such that:

$$\rho(J, w, u) = \sum_{\substack{\alpha \in \mathcal{L}_0 \\ (M, u) \not\models \alpha}} \sum_{i \in J} \mathcal{D}(i, w)(\alpha) \quad (\text{NGDM-DOX})$$

with satisfaction relation defined as follows:

$$\begin{aligned} (M, w) \models p &\Leftrightarrow w \in \mathcal{V}(p) \\ (M, w) \models \neg \phi &\Leftrightarrow (M, w) \not\models \phi \\ (M, w) \models \phi_1 \wedge \phi_2 &\Leftrightarrow (M, w) \models \phi_1 \text{ and } (M, w) \models \phi_2 \\ (M, w) \models \Delta_i^k \alpha &\Leftrightarrow \mathcal{D}(i, w)(\alpha) \geq k \\ (M, w) \models \Box_J^k \phi &\Leftrightarrow \forall u \in W : \rho(J, w, u) \leq k \Rightarrow (M, u) \models \phi \end{aligned}$$

M is called *finite* when W is finite and $\text{Supp}(\mathcal{D}(i, w))$ is finite for every i and w .

Notice that condition (NGDM-DOX) fully defines distance function ρ via doxastic function \mathcal{D} and the resulting distance function is *additive on groups*:

$$\rho(J, w, u) = \sum_{i \in J} \rho(\{i\}, w, u) \quad (\text{NGDM-}\rho\text{-ADD})$$

However, condition (NGDM-DOX) itself is not axiomatizable (see Remark 1 below), therefore we also introduce the notion of *quasi-notional graded doxastic models* (QNGDMs) where this condition is weakened to become axiomatizable. First, instead of equality, we require that the distance is no smaller than the sum of degrees of the unsatisfied beliefs (condition (QNGDM-DOX)). Additionally, we require a weakened version of (NGDM- ρ -ADD) (condition (QNGDM- ρ -ADD)): the finite distance for every group J can be partitioned into summands $\delta(i)$ for every agent $i \in J$ such that $\delta(i)$ is at least the distance for any agent $i \in J$, and moreover the distance for any sub-group does not exceed the sum of $\delta(i)$ for the agents involved.

Definition 8. A quasi-notional graded doxastic model (QNGDM) is a tuple $M = (W, \mathcal{D}, \rho, \mathcal{V})$ where W , ρ , \mathcal{D} , \mathcal{V} are as in Def. 7 except that (NGDM-DOX) is replaced by the two following weaker conditions

for every $J \in 2^{Agt^*}$ and $w, u \in W$ if $\rho(J, w, u) \neq \omega$:

$$\rho(J, w, u) \geq \sum_{\substack{\alpha \in \mathcal{L}_0 \\ (M, u) \models \alpha}} \sum_{i \in J} \mathcal{D}(i, w)(\alpha) \quad (\text{QNGDM-DOX})$$

$$\exists \delta \in \mathcal{P}art(\rho(J, w, u), J) \text{ such that for any non-empty } J' \subset J, \sum_{i \in J'} \delta(i) \geq \rho(J', w, u) \quad (\text{QNGDM-}\rho\text{-ADD})$$

We will now show equivalence of the three semantics following the strategy of [28]: we will first show that semantics of QNGDMs satisfies the finite model property (Lem. 1), then we will show how every satisfying *finite* QNGDM can be transformed into a satisfying NGDM (Lem. 2), satisfying NGDM — into a satisfying MAGBM (Lem. 3), and a satisfying MAGBM into a satisfying QNGDM (Lem. 4), closing the circle.

To establish Finite Model Property for QNGDMs we adapt the standard filtration technique.

Lemma 1. *If M is QNGDM satisfying $\varphi \in \mathcal{L}$ then there exists a finite QNGDM M' satisfying φ .*

Proof. (Sketch) We consider an equivalence relation \equiv_φ on worlds of M , relating worlds with the same evaluation on all subformulas of φ . Then we transform $M = (W, \rho, \mathcal{D}, \mathcal{V})$ into finite a QNGDM $(W', \rho', \mathcal{D}', \mathcal{V}')$ as follows: $W' = W / \equiv_\varphi$; $\rho'(J, U, V) \stackrel{\text{def}}{=} \min\{\rho(J, u, v) \mid u \in U, v \in V\}$; $\mathcal{D}'(i, U)(\alpha) \stackrel{\text{def}}{=} \max^*\{k \mid \triangle_i^k \alpha \text{ is a subformula of } \varphi \text{ and } \mathcal{D}(i, u)(\alpha) \geq k \text{ for all } u \in U\}$; $\mathcal{V}'(p) \stackrel{\text{def}}{=} \{U \mid U \subseteq \mathcal{V}(p)\}$. We check that M' preserves evaluation on subformulas of φ and satisfies both conditions of QNGDMs. \square

Now we show how to transform a finite QNGDM into a (finite) NGDM. We will adapt the idea of two-stage model transformation for distributed belief bases from [15] to our graded setting. At the first stage we achieve (NGDM- ρ -ADD) in a QNDM by creating copies of each world for every possible group and redefining distances for them on the basis of partitions given by condition (QNGDM- ρ -ADD). At the second stage we achieve (NGDM-DOX) by adapting the transformation from [30] to our case: introducing a fresh characterizing atom for each world and add such atoms as beliefs with the required degree to satisfy the equality in (NGDM-DOX).

Lemma 2. *If M is a finite QNGDM satisfying $\varphi \in \mathcal{L}$ then there exists a finite NGDM M'' satisfying φ .*

Proof. (Sketch) We first change the set of worlds W in M to $W' = W \times 2^{Agt^*}$, keep \mathcal{V} and \mathcal{D} the same for each copy, and redefine distances for copies using δ from condition (QNGDM- ρ -ADD) for J , w and u : $\rho'(J', (w, J''), (u, J)) = \sum_{i \in J'} \delta(i)$ for $J' \subseteq J$ and $\rho'(J', (w, J''), (u, J)) = \omega$ otherwise. With such definition of distances, the transformed model M' preserves the satisfaction relation for each copy, trivially satisfies (NGDM- ρ -ADD), and still satisfies (QNGDM-DOX), since distances between copies did not decrease w.r.t. original distances (by condition (QNGDM- ρ -ADD)). At the second stage, for each $w' \in W'$ we select a distinctive atom $\chi(w')$ not appearing in φ and in any $\alpha \in \text{Supp}(\mathcal{D}'(i, w'))$ in M' (which we can do since M' is finite), and change \mathcal{V}' to \mathcal{V}'' such that $\mathcal{V}''(\chi(w')) = W' \setminus \{w'\}$ (not changing the valuation on other atoms). Then we change the degrees of these atoms: $\mathcal{D}'(i, w)(\chi(u)) = \rho(i, w, u) - \sum_{\substack{\alpha \in \mathcal{L}_0 \\ (M', u) \models \alpha}} \mathcal{D}(i, w)(\alpha)$, turning inequality in (QNGDM-DOX) into equality for $M'' = (W', \rho', \mathcal{D}'', \mathcal{V}'')$. \square

Remark 1. *Contrapositive reading of Lemma 2 implies that any formula from \mathcal{L} satisfied in all NGDMs is also satisfied in all QNGDMs, which is a proper superclass of NDMs. Therefore there can be no characterizing axiom $\xi \in \mathcal{L}$ that is true exactly in the QNGDMs satisfying (NGDM-DOX). On the other hand, as we will see in the next section, there is a characterizing axioms in this sense for properties (QNGDM-DOX) and (QNGDM- ρ -ADD).*

We can also easily transform a satisfying NGDM into a satisfying MAGBM.

Lemma 3. *If ϕ is satisfied by some NGDM then ϕ is satisfied by some MAGBM.*

Proof. (Sketch) Each world can be mapped into a state (by reconstructing belief bases from the doxastic function) and the evaluation will be preserved thanks to the condition (NGDM-DOX). \square

And, finally, we can move from MAGBMs back to QNGDMs, closing the cycle.

Lemma 4. *If ϕ is satisfied by some MAGBM then ϕ is satisfied by some QNGDM.*

Proof. (Sketch) The doxastic function is defined by belief bases, and the distances can be defined via condition (NGDM-DOX), apart from the distances to the initial state S defined as ω (to reflect that, in general, S does not belong to the context U). \square

Thus, we have established the equivalence of all three introduced semantics (MAGBMs, NGDMs, and QNGDMs), which will be crucial for axiomatization of the proposed logic. Moreover, the described transformations turn an arbitrary QNGDM into an NGDM of exponential size, which implies decidability of the proposed logic (since all NGDMs of bounded size can be checked for satisfaction in finite time).

4 Axiomatics

In this section, we present an axiomatization for the proposed logic **LGDDA** (Logic of Graded Distributed Doxastic Attitudes) based on the semantics of QNGDMs introduced in the previous section.

Definition 9. *Logic **LGDDA** extends the classical propositional logic by the following axioms and rules:*

$$\begin{array}{ll}
 \frac{\phi}{\Box_J^k \phi} & (\text{Nec}_{\Box_J^k}) \\
 \Box_J^k(\phi \rightarrow \psi) \rightarrow (\Box_J^k \phi \rightarrow \Box_J^k \psi) & (\text{K}_{\Box_J^k}) \\
 \Delta_i^k \alpha \rightarrow \Delta_i^{k'} \alpha & \text{if } k \geq k' \quad (\text{Mon}_{\Delta_i^k}) \\
 \left(\bigwedge_{\Delta_i^{k'} \alpha \in \Omega} \Delta_i^{k'} \alpha \rightarrow \Box_J^k \bigvee_{\substack{\Omega' \subseteq \Omega \\ \text{Sum}(\Omega') \leq k}} \bigwedge_{\Delta_i^{k'} \alpha \in \Omega'} \alpha \right) & \begin{array}{l} \text{if } \Omega \subseteq \{\Delta_i^{k'} \alpha \mid i \in J\} \\ \text{and } \Delta_i^{k'} \alpha, \Delta_i^{k''} \alpha \in \Omega \Rightarrow k' = k'' \\ \text{where } \text{Sum}(\Omega') = \sum_{\Delta_i^{k'} \alpha \in \Omega'} k' \end{array} \quad (\text{Int}_{\Delta_i^{k'}, \Box_J^k}) \\
 \left(\bigwedge_{\Box_{J'}^{k'} \psi \in \Psi} \Box_{J'}^{k'} \psi \rightarrow \Box_J^k \bigvee_{\substack{\delta \in \mathcal{P}art(k, J) \\ \sum_{i \in J'} \delta(i) \leq k}} \bigwedge_{\Box_{J'}^{k'} \psi \in \Psi} \psi \right) & \text{if } \Psi \subseteq \{\Box_{J'}^{k'} \psi \mid J' \subseteq J\} \quad (\text{Int}_{\Box_{J'}^{k'}, \Box_J^k})
 \end{array}$$

$\phi \in \mathcal{L}$ is said to be derivable from $\Gamma \subseteq \mathcal{L}$ in **LGDDA** (denoted $\Gamma \vdash_{\text{LGDDA}} \phi$) when there is finite $\Gamma_f \subseteq \Gamma$ such that formula $(\bigwedge_{\psi \in \Gamma_f} \psi) \rightarrow \phi$ can be derived using axioms and rules of **LGDDA**.

Rule **(Nec) $_{\Box_J^k}$** and axiom **(K) $_{\Box_J^k}$** reflect the fact that \Box_J^k is a normal modality. Monotonicity axiom **(Mon) $_{\Delta_i^k}$** reflects the fact that k in modality Δ_i^k gives a lower bound on the weight of the belief. Two final axioms determine the interaction between triangles and boxes, and between boxes with different groups and degrees respectively. Informally, axiom **(Int) $_{\Delta_i^{k'}, \Box_J^k}$** states that group J believes with level k that their pulled beliefs are correct apart from some subset with the cumulative importance not exceeding k . Axiom **(Int) $_{\Box_{J'}^{k'}, \Box_J^k}$** captures the fact that the distance d between states (as defined by (NGDM-DOX)) for

group J can be partitioned into distances $\delta(i)$ for $i \in J$ such that any graded belief for a subgroup J' with degree k' is preserved for group J with degree $k \geq d$, as long as k' is greater than the sum of distances $\delta(i)$ for $i \in J'$. Notice that the following two validities, defining monotonicity of boxes w.r.t. group and degrees, are instances of $(\mathbf{Int}_{\square_{J'}, \square_J}^{k', k})$ for the case when there is only one box on the left:

$$\begin{aligned} \square_J^k \varphi &\rightarrow \square_{J'}^{k'} \varphi && \text{if } k \geq k' && (\mathbf{Mon}_{\square_J}^k) \\ \square_J^k \varphi &\rightarrow \square_{J'}^k \varphi && \text{if } J \subseteq J' && (\mathbf{Mon}_{\square_J}^J) \end{aligned}$$

Remark 2. Note that the axiomatization in Def. 9 does not simply adjust and merge axioms for graded beliefs and distributed beliefs. While $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ is a natural adjustment of axiom $(\mathbf{Int}_{\Delta_i, \square_i})$ from [30] for the case of graded belief bases, the logic of distributed belief from [15] requires only axiom $(\mathbf{Mon}_{\square_j}^J)$, and our logic for distributed graded belief requires significantly more sophisticated (and perhaps less intuitive) axiom $(\mathbf{Int}_{\square_{J'}, \square_J}^{k', k})$ that reflects the combinatorics of partition of distances for groups and subgroups captured in condition (QNGDM- ρ -ADD).

The proposed axiomatization is sound and complete w.r.t. QNGDM model semantics. To prove completeness we construct a canonical QNGDM, using rule $(\mathbf{Nec}_{\square_j}^k)$ and axioms $(\mathbf{K}_{\square_j}^k)$ and $(\mathbf{Mon}_{\Delta_i}^l)$ to establish the truth lemma, and axioms $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ and $(\mathbf{Int}_{\square_{J'}, \square_J}^{k', k})$ characterizing conditions (QNGDM-DOX) and (QNGDM- ρ -ADD) of QNGDMs respectively.

Theorem 1. $\Gamma \vdash_{\mathbf{LGDDA}} \varphi$ iff $\Gamma \models_{\mathbf{QNGDM}} \varphi$ (i.e. any pointed QDNM satisfying all formulas from Γ also satisfies φ).

Proof. (Sketch) Soundness: Validity of axiom $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ in any QNGDM follows from the condition (QNGDM-DOX) (if $\rho(J, w, u) \leq k$ then the disjunct for $\Omega' = \{\Delta_i^{k'} \alpha \in \Omega \mid M, u \not\models \alpha\}$ will be satisfied in u) and validity of axiom $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ — from condition (QNGDM- ρ -ADD) (it ensures existence of partition δ that corresponds to a satisfied disjunct), validity of other axioms and preservation of validity by the rules is trivial.

Completeness: We construct a canonical model $M^C = (W^C, \mathcal{D}^C, \rho^C, \mathcal{V}^C)$, where W^C is the set of all **LGDDA**-maxiconsistent sets of formulas (i.e. maximal sets not deriving \perp), $\mathcal{D}^C(i, \Phi)(\alpha) = \max^* \{l : \Delta_i^l \alpha \in \Phi\}$; $\rho^C(J, \Phi, \Phi') = \min^* \{k : \square_J^k \varphi \in \Phi \Rightarrow \varphi \in \Phi'\}$; $\mathcal{V}^C(p) = \{\Phi \in W^C : p \in \Phi\}$. The truth lemma stating $M^C, \Phi \models \psi \Leftrightarrow \psi \in \Phi$ is proved by structural induction on ψ , axiom $(\mathbf{Mon}_{\Delta_i}^l)$ is used for the case of triangles, and the case of box follows from presence of $(\mathbf{K}_{\square_j}^k)$ and $(\mathbf{Nec}_{\square_j}^k)$ as usual. Then conditions (QNGDM-DOX) and (QNGDM- ρ -ADD) can be proved contrapositively using axioms $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ and $(\mathbf{Int}_{\square_{J'}, \square_J}^{k', k})$ respectively. Failure of (QNGDM-DOX) for some w, u , and J would allow us to select some finite set Ω of beliefs false in u with aggregated weight in w greater than $\rho(J, w, u)$, and applying axiom $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ we would conclude that some beliefs in Ω are true in u . Failure of (QNGDM- ρ -ADD) for some w, u , and J would imply existence of subgroup $J_\delta \subset J$ for every $\delta \in \mathcal{Part}(\rho^C(J, w, u), J)$ such that $d_\delta = \sum_{i \in J_\delta} \delta(i) < \rho^C(J_\delta, \Phi, \Phi')$, which also implies existence of $\psi_\delta \in \mathcal{L}$ such that $\square_{J_\delta}^{d_\delta} \psi_\delta$ is satisfied in w but ψ_δ is not satisfied in u . Taking $\Omega = \{\square_{J_\delta}^{d_\delta} \psi_\delta \mid \delta \in \mathcal{Part}(\rho^C(J, w, u), J)\}$ and applying axiom $(\mathbf{Int}_{\Delta_i, \square_j}^{k', k})$ to it, we can derive that some ψ_δ is satisfied in u , reaching contradiction. \square

5 Tableau calculus and satisfiability checking

In this section, we present a tableau-based decision procedure for our logic and establish PSPACE-completeness of satisfiability checking (the same complexity as the basic logic of belief bases in [28]).

Definition 10. *The tableau calculus $\mathbf{Tab}_{\mathbf{LGDDA}}$ extends the standard tableau calculus \mathbf{LK} for the classical logic with the following two rules:*

$$\frac{\{\Delta_i^k \alpha, \neg \Delta_i^{k+i} \alpha\} \cup X}{\{\perp\}} (\Delta\text{-Mon}) \quad \frac{\{\neg \Box_j^k \phi\} \cup X}{\{\neg \phi\} \cup Y_1^{\Box\downarrow} \cup Y_1^{\Delta_j\downarrow} \mid \dots \mid \{\neg \phi\} \cup Y_N^{\Box\downarrow} \cup Y_N^{\Delta_j\downarrow}} (\Box\text{-Elim})$$

where $\{Y_1, \dots, Y_N\} = \{Y \subseteq X \mid \exists \delta \in \mathcal{P}art(k, J) : \Box_j^{k'} \psi \in Y \Rightarrow \sum_{i \in J'} \delta(i) \leq k' \text{ and } \mathcal{D}_{agg}(i, X \setminus Y) \leq \delta(i) \forall i \in J\}$

$$\begin{aligned} \mathcal{D}_{agg}(i, X \setminus Y) &= \sum_{\alpha \in \mathcal{L}_0} \max^* \{k' : \Delta_i^{k'} \alpha \in X \setminus Y\} \\ Y^{\Box\downarrow} \cup Y^{\Delta_j\downarrow} &= \{\psi \mid \Box_j^{k'} \psi \in Y\} \cup \{\alpha \mid \Delta_i^{k'} \alpha \in Y, i \in J\} \end{aligned}$$

Each tableau rule states that the satisfiability of a set of formulas above the line (called *numerator*) implies satisfiability of at least one of the sets of formulas below the line separated by the symbol ‘—’ (called *denominators*). We can use it to derive the non-satisfiability of some formula by applying the rules sequentially, with each branch ending with a set containing \perp (thus unsatisfiable). Such tree-like derivations are called *closed tableaux*. For our logic, it is sufficient to add just one rule for each modality (in addition to standard rules for the classical connectives). The rule ($\Delta\text{-Mon}$) captures the monotonicity of triangles w.r.t. grades, and the rule ($\Box\text{-Elim}$) adapts the rule eliminating negative boxes to our logic: if $\{\neg \Box_j^k \phi\} \cup X$ is satisfied in some world w of some model M then there should exist a world u with $\rho(J, w, u) \leq k$ and a partition $\delta \in \mathcal{P}art(k, J)$, such that u satisfies $\neg \phi$, all boxed formulas for subgroups with smaller distance, and some selection of triangled formulas in X , such that the cumulative degree of the rest of triangled formulas does not exceed k . Note that the rule ($\Box\text{-Elim}$) has potentially exponentially many denominators. At the same time, in all rules (apart from the closing ones) the denominators contain only subformulas of formulas in the numerator, and the total number of connectives and modalities in each denominator decreases w.r.t. the numerator, so the length of each branch is linear w.r.t. size of the initial formula. The resulting calculus is sound and complete w.r.t. logic \mathbf{LGDDA} .

Theorem 2. *A closed tableau in $\mathbf{Tab}_{\mathbf{LGDDA}}$ starting from $\{\phi\}$ exists iff ϕ is not satisfiable in \mathbf{LGDDA} .*

Proof. (Sketch) The soundness of all rules w.r.t. QNGDM semantics is straightforward. To prove completeness we show that for each set Γ underivable in $\mathbf{Tab}_{\mathbf{LGDDA}}$ (i.e. there are no closed tableaux starting from Γ) there is a pointed QNGDM model (M, w_0) satisfying all the formulas in Γ . We do it by induction on the number of connectives and modalities in Γ . First, if Γ contains formulas with double negation, conjunction or negated conjunction on the top level, they can be decomposed according to the rules and the statement follows straightforwardly from the inductive hypotheses. Otherwise Γ has only (possibly negated) atoms, Δ -formulas and \Box -formulas. We start a model construction with one world w_0 which satisfy exactly atoms in $(\mathbb{P} \cap \Gamma)$ and with doxastic function $\mathcal{D}(i, w_0)(\alpha) = \max^* \{k' : \Delta_i^{k'} \alpha \in \Gamma\}$. It is easy to check that all formulas from $\mathcal{L}_0 \cap \Gamma$ will be satisfied in this world. To satisfy also all boxed formulas in Γ we use the inductive hypothesis for every negated box $\neg \Box_j^k \phi$ in Γ : the application of the rule ($\Box\text{-Elim}$) to that negated box should have at least one underivable denominator (with the corresponding partition δ) and by inductive hypothesis there is a pointed model (M', w'_0) , satisfying all formulas in that denominator. Incorporating M' into M and defining distance from w_0 to w'_0 on J and all its subgroups as the sum of the corresponding values of δ (and as ω for the non-subgroups) we ensure that $\Box_j^k \phi$ is falsified in w_0 while all the non-negated boxes in Γ are satisfied. \square

Thus, to check satisfiability of a formula φ in **LGDDA** we can perform an exhaustive search for the closed tableaux in **Tab_{LGDDA}** for $\{\varphi\}$, for which polynomial space w.r.t. size of φ is sufficient.¹

Theorem 3. *Satisfiability checking in LGDDA is PSPACE-complete.*

Proof. (Sketch) PSPACE-hardness follows from PSPACE-hardness of logic **LDA** [26], which is equivalent to a fragment of **LGDDA**. It can be solved in PSPACE by a proof search in **Tab_{LGDDA}**, starting from $\{\varphi\}$ and trying all possible rule applications. When trying the rule (\Box -Elim) we iterate through all possible $Y \subseteq X$ and for each of them iterate through all partitions from $\mathcal{P}art(k, J)$, which both can be stored using polynomial space w.r.t. $|\varphi|$, and the depth of the proof search is also bounded polynomially. \square

6 Conclusion

We have presented a proof-theoretic and complexity analysis of the notion of graded distributed belief, using a formal semantics based on graded belief bases. Following Spohn's ranking theory [34], we plan to study, in future work, a more general variant of the graded belief semantics based on ordinals instead of natural numbers. The notion of graded distributed belief we have defined is based on a counting view (Definition 4). In future work, we intend to investigate a qualitative version by replacing the counting view with a qualitative perspective based on set inclusion. Last but not least, we aim to move from a static to a dynamic setting by extending our framework with a notion of graded belief base change.

Acknowledgments

We thank the anonymous reviewers for their helpful comments and suggestions. This work is supported by the ANR project EpiRL (grant number ANR-22-CE23-0029) and European Union's Horizon 2020 research and innovation programme under grant agreement No 101034440.

References

- [1] T. Ågotnes & Y. N. Wáng (2017): *Resolving distributed knowledge*. *Artificial Intelligence* 252, pp. 1–21, doi:10.1016/J.ARTINT.2017.07.002.
- [2] P. Balbiani & H. van Ditmarsch (2024): *Towards Dynamic Distributed Knowledge*. In A. Ciabattoni, D. Gabelaia & I. Sedlár, editors: *Advances in Modal Logic, AiML 2024, Prague, Czech Republic, August 19-23, 2024*, College Publications, pp. 125–146.
- [3] P. Balbiani, D. Fernández-Duque, A. Herzig & E. Lorini (2019): *Stratified Evidence Logics*. In: *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence (IJCAI 2019)*, pp. 1523–1529, doi:10.24963/IJCAI.2019/211.
- [4] J. van Benthem, J. van Eijck, M. Gattinger & K. Su (2015): *Symbolic Model Checking for Dynamic Epistemic Logic*. In: *Proceedings of the 5th International Workshop on Logic, Rationality and Interaction (LORI 2015)*, LNCS 9394, Springer-Verlag, pp. 366–378, doi:10.1007/978-3-662-48561-3_30.

¹Notice, that during the proof search we only need to store the grades appearing in the formulas and iterate through all partitions in $\mathcal{P}art(k, J)$ when applying the rule (\Box -Elim), which consist of at most $|Agt|$ numbers not exceeding k . Therefore, the representation of the grades inside the formulas and how we measure their size does not matter, as long as it is the same for the numbers in the iterated partitions. For simplicity, we assume that any numbers occupies only constant memory and the size of the formula is measured as the number of nodes in its tree-representation, but the same reasoning can be applied to more refined measures.

- [5] K. Budzynska & M. Kacprzak (2008): *A Logic for Reasoning about Persuasion*. *Fundamenta Informaticae* 85, pp. 51–65, doi:10.3233/FUN-2008-851-405.
- [6] T. Charrier, A. Herzig, E. Lorini, F. Maffre & F. Schwarzentruher (2016): *Building Epistemic Logic from Observations and Public Announcements*. In: *Proceedings of the Fifteenth International Conference on Principles of Knowledge Representation and Reasoning (KR 2016)*, AAAI Press, pp. 268–277.
- [7] W. van Der Hoek, B. van Linder & J.-J. Meyer (1999): *Group knowledge is not always distributed (neither is it always implicit)*. *Mathematical social sciences* 38(2), pp. 215–240, doi:10.1016/S0165-4896(99)00013-X.
- [8] D. Dubois, J. Lang & H. Prade (1994): *Possibilistic Logic*. In D. M. Gabbay, C. J. Hogger & J. A. Robinson, editors: *Handbook of Logic in Artificial Intelligence and Logic Programming*, 3, Oxford University Press, Oxford, pp. 439–513, doi:10.1093/oso/9780198537472.003.0009.
- [9] R. Fagin & J. Y. Halpern (1987): *Belief, Awareness, and Limited Reasoning*. *Artificial Intelligence* 34(1), pp. 39–76, doi:10.1016/0004-3702(87)90003-8.
- [10] R. Fagin, J. Y. Halpern, Y. Moses & M. Vardi (1995): *Reasoning about Knowledge*. MIT Press, Cambridge, doi:10.7551/mitpress/5803.001.0001.
- [11] R. Galimullin & L. B. Kuijer (2024): *Varieties of Distributed Knowledge*. In Agata Ciabatonni, David Gabelaia & Igor Sedlár, editors: *Advances in Modal Logic, AiML 2024, Prague, Czech Republic, August 19-23, 2024*, College Publications, pp. 379–400.
- [12] J. Y. Halpern & Y. Moses (1992): *A Guide to Completeness and Complexity for Modal Logics of Knowledge and Belief*. *Artificial Intelligence* 54(2), pp. 319–379, doi:10.1016/0004-3702(92)90049-4.
- [13] S. O. Hansson (1993): *Theory contraction and base contraction unified*. *Journal of Symbolic Logic* 58(2), pp. 602–625, doi:10.2307/2275221.
- [14] A. Herzig, E. Lorini & F. Maffre (2015): *A Poor Man’s Epistemic Logic Based on Propositional Assignment and Higher-Order Observation*. In: *Proceedings of the 5th International Workshop on Logic, Rationality, and Interaction (LORI 2015)*, LNCS 9394, Springer, pp. 156–168, doi:10.1007/978-3-662-48561-3_13.
- [15] A. Herzig, E. Lorini, E. Perrotin, F. Romero & F. Schwarzentruher (2020): *A Logic of Explicit and Implicit Distributed Belief*. In: *Proceedings of the 24th European Conference on Artificial Intelligence (ECAI 2020)*, *Frontiers in Artificial Intelligence and Applications* 325, IOS Press, pp. 753–760, doi:10.3233/FAIA200163.
- [16] W. van der Hoek (1992): *Modalities for Reasoning about Knowledge and Quantities*. Ph.D. thesis, Free University of Amsterdam.
- [17] W. van der Hoek, P. Iliev & M. Wooldridge (2012): *A logic of revelation and concealment*. In: *Proceedings of the International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2012)*, IFAAMAS, pp. 1115–1122.
- [18] W. van der Hoek & J.-J. Ch. Meyer (1991): *Graded modalities in epistemic logic*. *Logique & Analyse* 133-134, pp. 251–270.
- [19] A. Hunter & S. Konieczny (2008): *Measuring Inconsistency through Minimal Inconsistent Sets*. In: *Proceedings of the Eleventh International Conference on Principles of Knowledge Representation and Reasoning (KR2008)*, AAAI Press, pp. 358–366.
- [20] D. de Jongh & F. Liu (2009): *Preference, Priorities and Belief*. In T. Gruene-Yanoff & S. O. Hansson, editors: *Preference Change*, Springer, pp. 85–108, doi:10.1007/978-90-481-2593-7_4.
- [21] K. Konolige (1986): *A deduction model of belief*. Morgan Kaufmann Publishers, Los Altos.
- [22] N. Laverny & J. Lang (2004): *From Knowledge-Based Programs to Graded Belief-Based Programs Part I: On-Line Reasoning*. In: *Proceedings of the 16th European Conference on Artificial Intelligence (ECAI 2004)*, IOS Press, pp. 368–372.
- [23] H. J. Levesque (1984): *A logic of implicit and explicit belief*. In: *Proceedings of the Fourth AAAI Conference on Artificial Intelligence (AAAI’84)*, AAAI Press, pp. 198–202.

- [24] J. Lindqvist, F. R. Velázquez-Quesada & T. Ågotnes (2022): *Cautious Distributed Belief*. In Carlos Areces & Diana Costa, editors: *Dynamic Logic. New Trends and Applications - 4th International Workshop, DaLi 2022, Haifa, Israel, July 31 - August 1, 2022, Revised Selected Papers, Lecture Notes in Computer Science* 13780, Springer, pp. 106–124, doi:10.1007/978-3-031-26622-5_7.
- [25] A. Lomuscio, H. Qu & F. Raimondi (2017): *MCMAS: an open-source model checker for the verification of multi-agent systems*. *International Journal on Software Tools for Technology Transfer* 19, pp. 9–30, doi:10.1007/s10009-015-0378-x.
- [26] E. Lorini (2018): *In Praise of Belief Bases: Doing Epistemic Logic Without Possible Worlds*. In S. A. McIlraith & K. Q. Weinberger, editors: *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, AAAI Press, pp. 1915–1922, doi:10.1609/aaai.v32i1.11560.
- [27] E. Lorini (2019): *Exploiting Belief Bases for Building Rich Epistemic Structures*. In L. S. Moss, editor: *Proceedings of the Seventeenth Conference on Theoretical Aspects of Rationality and Knowledge (TARK 2019), EPTCS* 297, pp. 332–353, doi:10.4204/EPTCS.297.21.
- [28] E. Lorini (2020): *Rethinking epistemic logic with belief bases*. *Artif. Intell.* 282, doi:10.1016/j.artint.2020.103233.
- [29] E. Lorini & E. Rapon (2022): *Logical Theories of Collective Attitudes and the Belief Base Perspective*. In: *Proceedings of the 21st International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2022)*, International Foundation for Autonomous Agents and Multiagent Systems (IFAAMAS), pp. 833–841.
- [30] E. Lorini & F. Schwarzentruher (2021): *A Computationally Grounded Logic of Graded Belief*. In: *Proceedings of the 17th European Conference on Logics in Artificial Intelligence (JELIA 2021)*, LNCS 12678, Springer, pp. 245–261, doi:10.1007/978-3-030-75775-5_17.
- [31] J. J. Meyer & W. van der Hoek (1995): *Epistemic logic for AI and computer science*. Cambridge University Press, doi:10.1017/CB09780511569852.
- [32] F. Roelofsen (2007): *Distributed knowledge*. *Journal of Applied Non-Classical Logics* 17(2), pp. 255–273, doi:10.3166/janc1.17.255-273.
- [33] Y. Shoham (2009): *Logical Theories of Intention and the Database Perspective*. *Journal of Philosophical Logic* 38(6), pp. 633–648, doi:10.1007/s10992-009-9116-8.
- [34] W. Spohn (1988): *Ordinal Conditional Functions: A Dynamic Theory of Epistemic States*. In W. L. Harper & B. Skyrms, editors: *Causation in Decision, Belief Change, and Statistics: Proceedings of the Irvine Conference on Probability and Causation*, Springer Netherlands, Dordrecht, pp. 105–134, doi:10.1007/978-94-009-2865-7_6.
- [35] R. Stalnaker (2002): *Common Ground*. *Linguistics and Philosophy* 25(5-6), pp. 701–721, doi:10.1023/A:1020867916902.
- [36] Y. N. Wáng & T. Ågotnes (2013): *Public announcement logic with distributed knowledge: expressivity, completeness and complexity*. *Synthese* 190(1), pp. 135–162, doi:10.1007/s11229-012-0243-3.