

# A List of Complexity Bounds for Property Testing by Quantum Sample-to-Query Lifting

Kean Chen \*

Qisheng Wang †

Zhicheng Zhang ‡

## Abstract

Quantum sample-to-query lifting, a relation between quantum sample complexity and quantum query complexity presented in Wang and Zhang (*SIAM J. Comput.* 2025), was significantly strengthened by Tang, Wright, and Zhandry (2025) to the case of state-preparation oracles. In this paper, we compile a list of quantum lower and upper bounds for property testing that are obtained by quantum sample-to-query lifting. The problems of interest include testing properties of probability distributions and quantum states, such as entropy and closeness. This collection contains new results, as well as new proofs of known bounds. In total, we present 49 complexity bounds, where 41 are new and 18 are (near-)optimal.

---

\*Kean Chen is with the Department of Computer and Information Science, University of Pennsylvania, Philadelphia, United States (e-mail: [keanchen.gan@gmail.com](mailto:keanchen.gan@gmail.com)).

†Qisheng Wang is with the School of Informatics, University of Edinburgh, Edinburgh, United Kingdom (e-mail: [QishengWang1994@gmail.com](mailto:QishengWang1994@gmail.com)).

‡Zhicheng Zhang is with the Centre for Quantum Software and Information, University of Technology Sydney, Sydney, Australia (e-mail: [iszc Zhang@gmail.com](mailto:iszc Zhang@gmail.com)).

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Spotlight	4
1.1.1	Quantum query lower bounds	5
1.1.2	Quantum sample upper bounds	8
1.2	Organization of this paper	8
<b>2</b>	<b>List of Quantum Query Lower Bounds</b>	<b>8</b>
2.1	For classical properties	8
2.1.1	Hypothesis testing	10
2.1.2	Closeness testing	10
2.1.3	Distance estimation	11
2.1.4	Entropy estimation	11
2.1.5	Support size	13
2.1.6	$k$ -wise uniformity testing	13
2.2	For quantum properties	14
2.2.1	Mixedness testing	14
2.2.2	Rank testing	14
2.2.3	Uniformity distinguishing	15
2.2.4	Entanglement spectrum testing	15
2.2.5	Quantum entropy estimation	16
2.2.6	Trace distance estimation	17
2.2.7	Fidelity estimation	17
2.3	Other quantum tasks	18
2.3.1	Amplitude estimation	19
2.3.2	Hamiltonian simulation	19
2.3.3	Quantum Gibbs sampling	20
2.3.4	The entanglement entropy problem	21
<b>3</b>	<b>List of Quantum Sample Upper Bounds</b>	<b>24</b>
3.1	Entropy estimation	24
3.1.1	Von Neumann entropy	24
3.1.2	Rényi entropy	24
3.2	Closeness estimation	24
3.2.1	Trace distance	24
3.2.2	Fidelity	25
3.2.3	Quantum $\ell_\alpha$ distance	25
3.2.4	Tsallis relative entropy	25
<b>4</b>	<b>Discussion</b>	<b>26</b>
	<b>References</b>	<b>27</b>

# 1 Introduction

Quantum sample-to-query lifting [WZ25a, WZ25b] reveals a novel connection between quantum query complexity and quantum sample complexity. This discovery turns out to be useful for establishing new complexity bounds in quantum property testing [MdW16]. The key observation is that multiple samples of a quantum state  $\rho$  (sample complexity) can simulate the quantum unitary transformation  $e^{-i\rho t}$  (query complexity) by density matrix exponentiation [LMR14, KLL<sup>+</sup>17, GKP<sup>+</sup>25].<sup>1</sup>

Recently, in [TWZ25], the quantum sample-to-query lifting has been thoroughly strengthened to apply to the very general case where the quantum oracle prepares a purification of the mixed quantum state. This input model is called *purified quantum query access* [GL20], originally considered in quantum computational complexity [Wat02], and now is the standard quantum query input model for the property testing of quantum states.

**Definition 1.1** (Purified quantum query access). *A purified quantum query access oracle for an unknown mixed quantum state  $\rho$  is described by a unitary operator  $U$  acting on two subsystems  $A$  and  $B$  such that*

$$\rho = \text{tr}_B \left( U_{AB} \cdot |0\rangle\langle 0|_{AB} \cdot U_{AB}^\dagger \right).$$

*In particular, a query to the oracle  $U$  means a query to (controlled-)  $U$  or (controlled-)  $U^\dagger$ .*

A promise problem for quantum state testing is described by a pair of disjoint sets of quantum states  $\mathcal{P} = (\mathcal{P}^{\text{yes}}, \mathcal{P}^{\text{no}})$ . The task is to determine with probability at least  $2/3$  whether an unknown quantum state  $\rho \in \mathcal{P}^{\text{yes}}$  or  $\rho \in \mathcal{P}^{\text{no}}$ , given the promise that it is in either case. The sample complexity of  $\mathcal{P}$ , denoted as  $S(\mathcal{P})$ , is the minimum number of samples of  $\rho$  for solving  $\mathcal{P}$ . The query complexity of  $\mathcal{P}$ , denoted as  $Q(\mathcal{P})$ , is the minimum number of queries to the purified quantum query access oracle for solving  $\mathcal{P}$ .

Using the above notations, [TWZ25, Theorem 1.5] can be rephrased as the following theorem.

**Theorem 1.1** (Quantum sample-to-query lifting for purified quantum query access [TWZ25]). *Let  $\mathcal{P}$  be a promise problem for quantum state testing. Then,*

$$Q(\mathcal{P}) = \Omega\left(\sqrt{S(\mathcal{P})}\right).$$

Prior to Theorem 1.1, similar results about the sample complexity in terms of mixed states and their purifications have appeared in the quantum property testing literature [SW22, Theorem 5.2] and [CWZ24]. The relation between quantum sample complexity and quantum query complexity revealed in Theorem 1.1 is somewhat surprising, since universal controllization [AFB14, GST24] and purification [LDCL25] are impossible and unitary inversion requires exponential resources [FK18, QDS<sup>+</sup>19b, QDS<sup>+</sup>19a, CSM23, GST24, CML<sup>+</sup>24, OYM24, YKS<sup>+</sup>24, SHH25, CYZ25].

As a corollary, Theorem 1.1 reproduces (and improves) the quantum sample-to-query lifting theorem in [WZ25a, Theorem 1.1] for the diamond quantum query complexity  $Q_\diamond^\alpha(\mathcal{P})$ , which states that  $Q_\diamond^\alpha(\mathcal{P}) \geq \tilde{\Omega}(\sqrt{S(\mathcal{P})})$  for any constant  $\alpha > 1$ .<sup>2</sup> Here,  $Q_\diamond^\alpha(\mathcal{P})$  is the minimum number of queries to a unitary oracle  $U$  with upper left corner block  $\rho/\alpha$ , where  $\rho$  is the quantum state to be tested and  $\alpha \geq 1$  is a parameter. In the language of block-encoding [GSLW19], the unitary oracle  $U$  is a block-encoding of  $\rho/\alpha$ . Theorem 1.1 gives the following stronger statement, which (i) allows  $\alpha$  to be 1, and (ii) removes the polylogarithmic factors.

<sup>1</sup>The idea of simulating unitary transformations by samples of quantum states appeared even earlier in quantum communication complexity [HL11]. The case of pure states was used in quantum cryptography [ARU14, JLS18, Qia24, GZ25] and the case of mixed states was used in quantum algorithms [GP22, WZ24a].

<sup>2</sup> $\tilde{O}(\cdot)$  and  $\tilde{\Omega}(\cdot)$  suppress the polylogarithmic factors.

**Corollary 1.2** (Improved quantum sample-to-query lifting for block-encoded access). *Let  $\mathcal{P}$  be a promise problem for quantum state testing. Then, for any  $\alpha \geq 1$ ,*

$$Q_{\diamond}^{\alpha}(\mathcal{P}) = \Omega\left(\sqrt{S(\mathcal{P})}\right).$$

*Proof.* Let  $\mathcal{O}$  be a unitary operator that prepares a purification of a quantum state  $\rho$ . Then, we can implement a unitary operator  $U$  with upper left corner block  $\rho$  using  $O(1)$  queries to  $\mathcal{O}$  by [LC19, Lemma 7] and [GSLW19, Lemma 25]. Therefore, Theorem 1.1 immediately yields the proof for the case of  $\alpha = 1$ . The case of  $\alpha > 1$  can be obtained by the fact [WZ25a, Theorem B.1] that  $Q_{\diamond}^{\alpha}(\mathcal{P}) \geq Q_{\diamond}^1(\mathcal{P})$  for any  $\alpha > 1$ .  $\square$

For the special case where the quantum state  $\rho$  is pure, we can obtain a quantum sample-to-query lifting in terms of the reflection operator. Let  $Q_{\diamond}^{\text{refl}}(\mathcal{P})$  be the diamond quantum query complexity of a pure-state quantum state testing problem  $\mathcal{P}$ , which is the minimum number of queries to the reflection operator  $R_{\psi} = I - 2|\psi\rangle\langle\psi|$  for the input pure state  $|\psi\rangle$  to be tested.

**Corollary 1.3** (Improved quantum sample-to-query lifting for reflection access). *Let  $\mathcal{P}$  be a promise problem for pure-state quantum state testing. Then,*

$$Q_{\diamond}^{\text{refl}}(\mathcal{P}) = \Omega\left(\sqrt{S(\mathcal{P})}\right).$$

*Proof.* This is immediate by Corollary 1.2 and noting that  $Q_{\diamond}^{\text{refl}}(\mathcal{P}) = \Theta(Q_{\diamond}^1(\mathcal{P}))$  for any pure-state quantum state testing problem  $\mathcal{P}$  (cf. [CWZ24, Lemma 5.6]).  $\square$

Theorem 1.1 can be restated below as a sampler of quantum query algorithms with purified quantum query access.

**Corollary 1.4** (Quantum sampler, Theorem 1.1 restated). *Let  $\mathcal{P}$  be a promise problem for quantum state testing. Then,*

$$S(\mathcal{P}) = O\left((Q(\mathcal{P}))^2\right).$$

Corollary 1.4 can be used to derive quantum sample upper bounds from quantum query upper bounds. Corollary 1.4 generalizes the sampler given in [WZ25b]. In comparison, the sampler in Corollary 1.4 applies to the purified quantum query access model, whereas the sampler in [WZ25b] applies to a weaker input model where the unitary oracle is a block-encoding of  $\rho$ . The time complexity (i.e., the number of elementary quantum gates) of the quantum algorithm obtained by Corollary 1.4 is  $\tilde{O}(n^4)$  due to the use of the Schur transform [Har05, BCH06, BCH07, KS18, Kro19, Ngu23, GBO23, BFG<sup>+</sup>25] in the approach of [TWZ25], where  $n$  is the sample complexity and the time complexity is obtained by the current best Schur transform [BFG<sup>+</sup>25]. In comparison, the time complexity of the quantum algorithm obtained by the sampler in [WZ25b] is  $\tilde{O}(n)$ .

It turns out that Theorem 1.1 and its variants (Corollaries 1.2 to 1.4) are able to derive new quantum complexity lower and upper bounds for a number of problems ranging from the classical world to the quantum world. In this paper, we compile a list of quantum lower and upper bounds that can be proved by quantum sample-to-query lifting.

## 1.1 Spotlight

In summary, this paper includes 48 quantum complexity bounds obtained by quantum sample-to-query lifting, where 40 are new and 19 are (near-)optimal. The statistics is given in Table 1.

Table 1: Statistics of quantum complexity bounds by quantum sample-to-query lifting.

Collection	#Bounds	#New	#Optimal	#New&Optimal
Testing Classical Properties (Table 2)	12	8	10	7
Testing Quantum Properties (Table 3)	19	18	2	1
Other Quantum Tasks (Table 4)	8	5	5	2
Sample Upper Bounds (Table 5)	10	10	1	1
Total	49	41	18	11

### 1.1.1 Quantum query lower bounds

We present a list of quantum query lower bounds obtained by quantum sample-to-query lifting. In particular, some lower bounds are tight. This shows that the quantum sample-to-query lifting method brings new methodologies into proving quantum query lower bounds, in addition to the quantum polynomial method [BBC<sup>+</sup>01], the quantum adversary method [Amb02], and the quantum compressed oracle method [Zha19].

**Testing classical properties.** In Table 2, 12 quantum query lower bounds for testing classical properties are listed, including hypothesis testing, uniformity testing, closeness testing, and entropy estimation of probability distributions, where 8 are new and 10 are near-optimal.

In particular, we present

1. A new proof (see Theorem 2.1) of the quantum query lower bound for hypothesis testing, which was originally proved in [Bel19] by the quantum adversary method.
2. Improved quantum query lower bounds for the estimation of total variation distance, Shannon entropy, and support size (see Theorems 2.5, 2.6 and 2.11), where the previous lower bounds are due to [BKT20] by the quantum polynomial method.
3. The *first* almost matching quantum query lower bound for Rényi entropy estimation (see Theorem 2.7), showing that the quantum algorithm given in [WZL24, Theorem 1] is near-optimal in the dimension  $d$  for  $0 < \alpha < 1$ .
4. The *first* non-trivial quantum query lower bound for 2-wise uniformity testing (see Theorem 2.12), showing that the quantum algorithm given in [LWL24, Theorem 5] is optimal in the precision parameter  $\varepsilon$ .

**Testing quantum properties.** In Table 3, 19 quantum query lower bounds for testing quantum properties are listed, including mixedness testing, rank testing, entropy estimation, and closeness estimation of quantum states, where 18 are new and 2 are near-optimal.

In particular, we present improved quantum query lower bounds for a series of property testing problems, including mixedness testing (Theorem 2.13), von Neumann entropy estimation (Theorem 2.23), trace distance estimation (Theorem 2.26), and fidelity estimation (Theorem 2.27), which are based on the quantum sample lower bound for mixedness testing and significantly improve the previous known lower bounds implied by or due to [CFMdW10, BKT20, Wan24, UNWT25].

Table 2: Quantum query lower bounds for testing classical properties.

Problem	Previous	This Paper	New?	Optimal?
Hypothesis Testing	$\Omega(1/d_H(P, Q))$ [Bel19]	$\Omega(1/d_H(P, Q))$ Theorem 2.1	Reproved	<b>Optimal</b>
$\ell_1$ Closeness Testing	$\Omega(d^{1/3} + \frac{1}{\varepsilon})$ [CFMdW10, LWL24]	$\Omega(\frac{d^{1/3}}{\varepsilon^{2/3}} + \frac{d^{1/4}}{\varepsilon})$ Theorem 2.2	<b>New</b>	<b>Optimal</b> in $d, \varepsilon$
Uniformity Testing	$\Omega(d^{1/3})$ [CFMdW10]	$\Omega(d^{1/3} + \frac{d^{1/4}}{\varepsilon})$ Theorem 2.3	<b>New</b>	<b>Optimal</b> in $d, \varepsilon$
$\ell_2$ Closeness Testing	$\Omega(\frac{1}{\varepsilon})$ [LWL24]	$\Omega(\frac{1}{\varepsilon})$ Theorem 2.4	Reproved	<b>Optimal</b>
Total Variation Distance Estimation	$\tilde{\Omega}(\sqrt{d})$ [BKT20]	$\Omega(\frac{\sqrt{d}}{\varepsilon \sqrt{\log(d/\varepsilon)}})$ Theorem 2.5	<b>New</b>	Near- <b>Optimal</b> in $d$
Shannon Entropy Estimation	$\tilde{\Omega}(\sqrt{d})$ [BKT20]	$\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon \log(d)}} + \frac{\log(d)}{\varepsilon})$ Theorem 2.6	<b>New</b>	Near- <b>Optimal</b> in $d, \varepsilon$
$\alpha$ -Rényi Entropy Estimation ( $0 < \alpha < 1$ )	$\Omega(\frac{d^{\frac{1}{2}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$ [LW19, WZL24]	$\Omega(d^{\frac{1}{2\alpha} - o(1)} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$ Theorem 2.7	<b>New</b>	Near- <b>Optimal</b> in $d$
$\alpha$ -Rényi Entropy Estimation ( $\alpha > 1$ )	$\Omega(\frac{d^{\frac{1}{2}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ [LW19]	$\Omega(d^{\frac{1}{2} - o(1)} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ Theorem 2.8	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation (Integer $\alpha$ )	$\Omega(\frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ [LW19]	$\Omega(\frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ Theorem 2.9	Reproved	Not Yet
$\alpha$ -Tsallis Entropy Estimation (Integer $\alpha$ )	$\Omega(\frac{1}{\sqrt{\alpha\varepsilon}})$ [Wan25]	$\Omega(\frac{1}{\sqrt{\alpha\varepsilon}})$ Theorem 2.10	Reproved	<b>Optimal</b> in $\alpha$ , Near- <b>Optimal</b> in $\varepsilon$
Support Size Estimation	$\tilde{\Omega}(\sqrt{d})$ [BKT20]	$\Omega(\frac{\sqrt{d}}{\sqrt{\log(d)}} \log(\frac{1}{\varepsilon}))$ Theorem 2.11	<b>New</b>	Near- <b>Optimal</b> in $d$
2-Wise Uniformity Testing	N/A	$\Omega(\frac{\sqrt{n}}{\varepsilon})$ Theorem 2.12	<b>New</b>	<b>Optimal</b> in $\varepsilon$

**Other quantum tasks.** In Table 4, 8 quantum query lower bounds for other quantum tasks are listed, including amplitude estimation, Hamiltonian simulation, quantum Gibbs sampling, and the entanglement entropy problem, where 5 are new and 5 are near-optimal.

In particular, we present

1. New proofs of a series of basic problems such as amplitude estimation (Theorem 2.30), Hamiltonian simulation (Theorem 2.31), and quantum Gibbs sampling (Theorem 2.32), whereas the previous matching lower bounds are based on the quantum polynomial method [NW99, BACS07] or unitary discrimination [CKBG23, Weg25].
2. The *first* almost matching quantum query lower bound for the entanglement entropy problem originally considered in [SY23] (see Theorem 2.34), significantly improving the previous lower bounds by [SY23, WZ25a, Weg25, CWZ24] and showing that the quantum algorithm given in [Weg25] is near-optimal in  $\Delta$ .

Table 3: Quantum query lower bounds for testing quantum properties.

Problem	Previous	This Paper	New?	Optimal?
Mixedness Testing	$\Omega(d^{1/3})$ [CFMdW10]	$\Omega(\frac{\sqrt{d}}{\varepsilon})$ Theorem 2.13	<b>New</b>	Not Yet
State Certification	N/A	$\Omega(\frac{\sqrt{d}}{\varepsilon})$ Corollary 2.14	<b>New</b>	Not Yet
Mixedness Testing for Block-Encoding	$\tilde{\Omega}(\frac{\sqrt{d}}{\varepsilon})$ [WZ25a]	$\Omega(\frac{\sqrt{d}}{\varepsilon})$ Corollary 2.15	<b>New</b>	Not Yet
Rank Testing	N/A	$\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}})$ Theorem 2.16	<b>New</b>	Not Yet
Rank Testing for Block-Encoding	$\tilde{\Omega}(\frac{\sqrt{r}}{\sqrt{\varepsilon}})$ [WZ25a]	$\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}})$ Corollary 2.17	<b>New</b>	Not Yet
Uniformity Distinguishing	N/A	$\Omega^*(\frac{r}{\sqrt{\Delta}})$ Theorem 2.18	<b>New</b>	Not Yet
Uniformity Distinguishing for Block-Encoding	$\tilde{\Omega}(\sqrt{r})$ [WZ25a]	$\Omega(\sqrt{r})$ Corollary 2.19	<b>New</b>	Not Yet
Maximal Entanglement Testing	N/A	$\Omega(\frac{\sqrt{d}}{\varepsilon})$ Theorem 2.20	<b>New</b>	Not Yet
Uniform Schmidt Testing	N/A	$\Omega(\frac{\sqrt{r}}{\varepsilon})$ Theorem 2.21	<b>New</b>	Not Yet
Uniform Schmidt Coefficient Testing	N/A	$\Omega^*(\frac{r}{\sqrt{\Delta}})$ Theorem 2.22	<b>New</b>	Not Yet
Von Neumann Entropy Estimation	$\tilde{\Omega}(\sqrt{d})$ [BKT20]	$\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon}} + \frac{\log(d)}{\varepsilon})$ Theorem 2.23	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation ( $0 < \alpha < 1$ )	$\Omega(\frac{d^{\frac{1}{3}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$ [LW19, WZL24]	$\Omega(d^{\frac{1}{2\alpha} - o(1)} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}} + \frac{\sqrt{d}}{\sqrt{\varepsilon}})$ Theorem 2.24	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation ( $\alpha > 1$ )	$\Omega(\frac{d^{\frac{1}{3}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon^{\frac{1}{2\alpha}}})$ [LW19]	$\Omega(\frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon^{\frac{1}{2\alpha}}} + \frac{\sqrt{d}}{\sqrt{\varepsilon}})$ Theorem 2.24	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation (Integer $\alpha$ )	$\Omega(\frac{d^{\frac{1}{3}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon^{\frac{1}{2\alpha}}})$ [LW19]	$\Omega(\frac{d^{1 - \frac{1}{\alpha}}}{\varepsilon^{\frac{1}{\alpha}}} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon^{\frac{1}{2\alpha}}})$ Theorem 2.24	<b>New</b>	Not Yet
$\alpha$ -Tsallis Entropy Estimation ( $1 < \alpha < \frac{3}{2}$ )	$\Omega(\frac{1}{\sqrt{\varepsilon}})$ [LW25b]	$\Omega(\frac{1}{\varepsilon^{2(\alpha-1)}})$ Theorem 2.25	<b>New</b>	Not Yet
$\alpha$ -Tsallis Entropy Estimation ( $\alpha \geq \frac{3}{2}$ )	$\Omega(\frac{1}{\sqrt{\varepsilon}})$ [LW25b]	$\Omega(\frac{1}{\varepsilon})$ Theorem 2.25	<b>New</b>	<b>Optimal</b> for integer $\alpha \geq 2$
Trace Distance Estimation	$\tilde{\Omega}(\sqrt{r} + \frac{1}{\varepsilon})$ [BKT20, Wan24]	$\Omega(\frac{\sqrt{r}}{\varepsilon})$ Theorem 2.26	<b>New</b>	Not Yet
Fidelity Estimation	$\Omega(r^{1/3} + \frac{1}{\varepsilon})$ [UNWT25]	$\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}} + \frac{1}{\varepsilon})$ Theorem 2.27	<b>New</b>	Not Yet
Well-Conditioned Fidelity Estimation	$\Omega(\frac{1}{\varepsilon})$ [LWWZ25]	$\Omega(\frac{1}{\varepsilon})$ Theorem 2.28	Reproved	Near- <b>Optimal</b>

Table 4: Quantum query lower bounds for other quantum tasks.

Problem	Previous	This Paper	New?	Optimal?
Amplitude Estimation	$\Omega(\frac{1}{\varepsilon})$ [NW99]	$\Omega(\frac{1}{\varepsilon})$ Theorem 2.30	Reproved	<b>Optimal</b>
Hamiltonian Simulation	$\Omega(t)$ [BACS07]	$\Omega(t)$ Theorem 2.31	Reproved	<b>Optimal</b>
Gibbs Sampling	$\Omega(\beta)$ [CKBG23, Weg25]	$\Omega(\beta)$ Theorem 2.32	Reproved	<b>Optimal</b>
Gibbs Sampling (Stronger Oracle)	$\tilde{\Omega}(\beta)$ [WZ25a]	$\Omega(\beta)$ Theorem 2.33	<b>New</b>	<b>Optimal</b>
Entanglement Entropy Problem ( $0 < \alpha < 1$ )	$\tilde{\Omega}(\frac{\sqrt{d}}{\sqrt{\Delta}} + \frac{d^{\frac{1}{2\alpha}-\frac{1}{2}}}{\Delta^{\frac{1}{2\alpha}}})$ [CWZ24]	$\Omega(d^{\frac{1}{2\alpha}-o(1)} + \frac{d^{\frac{1}{2\alpha}-\frac{1}{2}}}{\Delta^{\frac{1}{2\alpha}}} + \frac{\sqrt{d}}{\sqrt{\Delta}})$ Theorem 2.34	<b>New</b>	Not Yet
Entanglement Entropy Problem ( $\alpha = 1$ )	$\tilde{\Omega}(\frac{\sqrt{d}}{\sqrt{\Delta}})$ [CWZ24]	$\Omega(\frac{\sqrt{d}}{\sqrt{\Delta}} + \frac{\log(d)}{\Delta \sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})}})$ Theorem 2.34	<b>New</b>	Not Yet
Entanglement Entropy Problem ( $\alpha > 1$ )	$\tilde{\Omega}(\frac{\sqrt{d}}{\sqrt{\Delta}})$ [CWZ24]	$\Omega(\frac{\sqrt{d}}{\sqrt{\Delta}} + \frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\Delta \sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})}})$ Theorem 2.34	<b>New</b>	Not Yet
Entanglement Entropy Problem (Integer $\alpha$ )	$\tilde{\Omega}(\frac{\sqrt{d}}{\sqrt{\Delta}})$ [CWZ24]	$\Omega(\frac{d^{1-\frac{1}{\alpha}}}{\Delta^{\frac{1}{\alpha}}} + \frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\Delta})$ $\sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})}$ Theorem 2.34	<b>New</b>	Near- <b>Optimal</b> in $\Delta$

### 1.1.2 Quantum sample upper bounds

In Table 5, 10 quantum sample upper bounds are listed, including entropy estimation and closeness estimation of quantum states, where all upper bounds are new and 1 upper bound is known to be near-optimal.

In particular, we present

1. The state-of-the-art quantum algorithm for estimating the von Neumann entropy (Theorem 3.1), trace distance (Theorem 3.3) and fidelity (Theorem 3.4) of quantum states of rank  $r$  with sample complexity  $\tilde{O}(r^2)$ , which we conjecture are optimal in  $r$  (see Conjecture 1).
2. A quantum algorithm for well-conditioned fidelity estimation with sample complexity  $\tilde{O}(\frac{1}{\varepsilon^2})$  (see Theorem 3.5), matching the lower bound given in [LWWZ25, Lemma 40].

## 1.2 Organization of this paper

In the remainder of this paper, quantum query lower bounds obtained by quantum sample-to-query lifting are listed in Section 2 and quantum sample upper bounds obtained by quantum sample-to-query lifting are listed in Section 3. Open questions and conjectures are discussed in Section 4.

## 2 List of Quantum Query Lower Bounds

### 2.1 For classical properties

The study of quantum testing of classical properties was initiated in [BHH11]. For testing the properties of a  $d$ -dimensional classical distribution  $P = (p_1, p_2, \dots, p_d)$ , we assume a quantum

Table 5: Quantum sample upper bounds.

Problem	Previous	This Paper	New?	Optimal?
Von Neumann Entropy Estimation	$O(\frac{d^2}{\varepsilon} + \frac{\log^2(d)}{\varepsilon^2})$ [BMW16]	$\tilde{O}(\frac{r^2}{\varepsilon^4})$ Theorem 3.1	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation ( $0 < \alpha < 1$ )	$O(\frac{d^{\frac{2}{\alpha}}}{\varepsilon^{\frac{2}{\alpha}}})$ [AISW20]	$\tilde{O}(\frac{r^{\frac{2}{\alpha}}}{\varepsilon^{\frac{2}{\alpha}+2}})$ Theorem 3.2	<b>New</b>	Not Yet
$\alpha$ -Rényi Entropy Estimation ( $\alpha > 1$ )	$O(\frac{d^2}{\varepsilon^2})$ [AISW20]	$\tilde{O}(\frac{r^2}{\varepsilon^{2+\frac{2}{\alpha}}})$ Theorem 3.2	<b>New</b>	Not Yet
Trace Distance Estimation	$O(\frac{r^2}{\varepsilon^5} \log^2(\frac{r}{\varepsilon}) \log^2(\frac{1}{\varepsilon}))$ [WZ24a]	$O(\frac{r^2}{\varepsilon^4} \log^2(\frac{1}{\varepsilon}))$ Theorem 3.3	<b>New</b>	Not Yet
Fidelity Estimation	$\tilde{O}(\frac{r^{5.5}}{\varepsilon^{12}})$ [GP22]	$O(\frac{r^2}{\varepsilon^4} \log^2(\frac{1}{\varepsilon}))$ [UNWT25] Theorem 3.4	<b>New</b>	Not Yet
Well-Conditioned Fidelity Estimation	$\tilde{O}(\frac{\kappa^9}{\varepsilon^3})$ [LWWZ25]	$O(\frac{\kappa^2}{\varepsilon^2} \log^2(\frac{1}{\varepsilon}))$ [UNWT25] Theorem 3.5	<b>New</b>	Near- <b>Optimal</b> in $\varepsilon$
Quantum $\ell_\alpha$ Distance Estimation	$\tilde{O}(\frac{1}{\varepsilon^{3\alpha+2+\frac{2}{\alpha-1}}})$ [LW25a]	$O(\frac{1}{\varepsilon^{2\alpha+2+\frac{2}{\alpha-1}}})$ Theorem 3.6	<b>New</b>	Not Yet
$\alpha$ -Tsallis Relative Entropy Estimation ( $0 < \alpha < \frac{1}{2}$ )	$O(\frac{r^{2+3\alpha}}{\varepsilon^{\frac{2}{\alpha}+1-\alpha}} \log^2(\frac{r}{\varepsilon}))$ [BGW25]	$O(\frac{r^{2+2\alpha}}{\varepsilon^{\frac{2}{\alpha}+1-\alpha}})$ Theorem 3.7	<b>New</b>	Not Yet
$\alpha$ -Tsallis Relative Entropy Estimation ( $\frac{1}{2} < \alpha < 1$ )	$O(\frac{r^{5-3\alpha}}{\varepsilon^{\frac{2}{1-\alpha}+\frac{3}{\alpha}}} \log^2(\frac{r}{\varepsilon}))$ [BGW25]	$O(\frac{r^{4-2\alpha}}{\varepsilon^{\frac{2}{1-\alpha}+\frac{2}{\alpha}}})$ Theorem 3.7	<b>New</b>	Not Yet
Squared Hellinger Distance Estimation	$O(\frac{r^{3.5}}{\varepsilon^{10}} \log^4(\frac{r}{\varepsilon}))$ [BGW25]	$O(\frac{r^3}{\varepsilon^8} \log^2(\frac{r}{\varepsilon}))$ Theorem 3.7	<b>New</b>	Not Yet

query oracle  $U$  acting on two subsystems  $A$  and  $B$  such that

$$U_{AB}|0\rangle_A|0\rangle_B = \sum_{i=1}^d \sqrt{p_i}|i\rangle_A|\psi_i\rangle_B,$$

where  $\{|\psi_i\rangle\}_{i=1}^d$  is an orthonormal basis.<sup>3</sup> In other words,  $U$  is a purified quantum query access oracle for the diagonal quantum state

$$\rho = \sum_{i=1}^d p_i|i\rangle\langle i| = \text{diag}(p_1, p_2, \dots, p_d).$$

For any promise problem  $\mathcal{Q} = \{\mathcal{Q}^{\text{yes}}, \mathcal{Q}^{\text{no}}\}$  for classical distributions, one can define a promise problem  $\mathcal{P} = \{\mathcal{P}^{\text{yes}}, \mathcal{P}^{\text{no}}\}$  for quantum state testing such that

$$\mathcal{P}^X = \{ \rho = \text{diag}(p_1, p_2, \dots, p_d) : P = (p_1, p_2, \dots, p_d) \in \mathcal{Q}^X \} \text{ for } X \in \{\text{yes}, \text{no}\}.$$

<sup>3</sup>There have been several different quantum input models for testing classical properties. Here, we consider the purified quantum query access model, which is the weakest one (see [Bel19, GL20] for the discussions and comparison with other models).

It is clear that  $S(\mathcal{P}) = S(\mathcal{Q})$  and  $Q(\mathcal{P}) = Q(\mathcal{Q})$ . By Theorem 1.1, we immediately have

$$Q(\mathcal{Q}) = Q(\mathcal{P}) = \Omega\left(\sqrt{S(\mathcal{P})}\right) = \Omega\left(\sqrt{S(\mathcal{Q})}\right),$$

which allows us to establish a quantum query lower bound for  $\mathcal{Q}$  from its classical sample lower bound.

In the remaining part of this section, we list the quantum query lower bounds for testing properties of discrete distributions, where we will use  $d$  to denote the dimension of the distributions.

### 2.1.1 Hypothesis testing

**Problem 2.1** (Hypothesis testing). *Given an unknown distribution  $R$  that is either  $P$  or  $Q$ , determine whether  $R$  is  $P$  or  $Q$ .*

The quantum query complexity of Problem 2.1 has been shown to be  $\Theta(1/d_H(P, Q))$  in [Bel19]. The original proof of the lower bound  $\Omega(1/d_H(P, Q))$  given in [Bel19] uses the adversary bound in [BBH<sup>+</sup>18] (which is a generalization of the primal version of the general adversary bound [HLŠ07]).

By quantum sample-to-query lifting, we can simply reproduce this result.

**Theorem 2.1** ([Bel19, Theorem 4] reproduced). *The quantum query complexity of hypothesis testing for two distributions  $P$  and  $Q$  is  $\Omega(1/d_H(P, Q))$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for hypothesis testing is  $\Omega(1/d_H^2(P, Q))$  [BYKS01] (see also [BY02, Theorem 4.7]).  $\square$

### 2.1.2 Closeness testing

**Problem 2.2** ( $\ell_\alpha$  closeness testing). *Given an unknown distribution  $P$  and a known distribution  $Q$ , determine whether  $P = Q$  or  $\|P - Q\|_\alpha \geq \varepsilon$ , where the  $\ell_\alpha$  distance is induced by the  $\alpha$ -Schatten norm  $\|P\|_\alpha = (\sum_{i=1}^d p_i^\alpha)^{1/\alpha}$ . In particular, the  $\ell_1$  distance is called the total variation distance.*

**The case of  $\alpha = 1$ .** The  $\ell_1$  closeness testing was considered in [GL20] with a quantum algorithm with query complexity  $O(\frac{\sqrt{d}}{\varepsilon} \log^3(\frac{d}{\varepsilon}) \log \log(\frac{d}{\varepsilon}))$ . The current best quantum query upper bound for  $\ell_1$  closeness testing is  $O(\min\{\frac{d^{1/3}}{\varepsilon^{4/3}}, \frac{\sqrt{d}}{\varepsilon}\})$ , where  $O(\frac{d^{1/3}}{\varepsilon^{4/3}})$  is due to [CKO25] and  $O(\frac{\sqrt{d}}{\varepsilon})$  is due to [LWL24]. The prior best quantum query lower bound is  $\Omega(d^{1/3} + \frac{1}{\varepsilon})$ , where  $\Omega(d^{1/3})$  due to [CFMdW10] shows the optimality in  $d$  of [CKO25] and  $\Omega(\frac{1}{\varepsilon})$  due to [LWL24] shows the optimality in  $\varepsilon$  of [LWL24].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.2.** *The quantum query complexity of  $\ell_1$  closeness testing is  $\Omega(\frac{d^{1/3}}{\varepsilon^{2/3}} + \frac{d^{1/4}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have note that the sample lower bound for  $\ell_1$  closeness testing is  $\Omega(\frac{d^{2/3}}{\varepsilon^{4/3}} + \frac{d^{1/2}}{\varepsilon^2})$  [CDVV14].  $\square$

For the special case where  $Q$  is the uniform distribution, the problem is called *uniformity testing* and quantum algorithms for it were given in [BHH11] with query complexity  $O(d^{1/3})$  for  $\varepsilon = \Theta(1)$  and in [CFMdW10] with query complexity  $O(\frac{d^{1/3}}{\varepsilon^2})$ . However, the current best quantum query upper bound remains  $O(\min\{\frac{d^{1/3}}{\varepsilon^{4/3}}, \frac{\sqrt{d}}{\varepsilon}\})$  due to [CKO25, LWL24]; the prior best quantum query lower bound is  $\Omega(d^{1/3})$  due to [CFMdW10] for  $\varepsilon = \Theta(1)$ .

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.3.** *The quantum query complexity of uniformity testing is  $\Omega(d^{1/3} + \frac{d^{1/4}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1 to show a lower bound of  $\Omega(\frac{d^{1/4}}{\varepsilon})$ , we only have to note that the sample lower bound for uniformity testing is  $\Omega(\frac{\sqrt{d}}{\varepsilon^2})$  [Pan08, CDVV14].  $\square$

Theorem 2.3 shows that the current quantum query upper bound  $O(\min\{\frac{d^{1/3}}{\varepsilon^{4/3}}, \frac{\sqrt{d}}{\varepsilon}\})$  due to [CKO25, LWL24] is optimal in both  $d$  and  $\varepsilon$ .

**The case of  $\alpha = 2$ .** A quantum algorithm for  $\ell_2$  closeness testing was proposed in [GL20] with query complexity  $O(\frac{1}{\varepsilon} \log^3(\frac{1}{\varepsilon}) \log \log(\frac{1}{\varepsilon}))$ , which was later improved to  $O(\frac{1}{\varepsilon})$  in [LWL24] together with a matching lower bound of  $\Omega(\frac{1}{\varepsilon})$ . The lower bound in [LWL24] was obtained by applying the lower bound in [Bel19] for hypothesis testing.

By quantum sample-to-query lifting, we can simply reproduce this result.

**Theorem 2.4** ([LWL24, Theorem 13] reproduced). *The quantum query complexity of  $\ell_2$  closeness testing is  $\Omega(\frac{1}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for  $\ell_2$  closeness testing is  $\Omega(\frac{1}{\varepsilon^2})$  [CDVV14].  $\square$

### 2.1.3 Distance estimation

**Problem 2.3** (Total variation distance estimation). *Given two unknown distributions  $P$  and  $Q$ , estimate the  $\ell_1$  distance  $\|P - Q\|_1$  to within additive error  $\varepsilon$ .*

A quantum algorithm for the  $\ell_1$  distance estimation was proposed in [BHH11] with query complexity  $O(\frac{\sqrt{d}}{\varepsilon^8})$ . The current best quantum query upper bound is  $O(\frac{\sqrt{d}}{\varepsilon^2} \log(\frac{1}{\varepsilon}))$  due to [Mon15]. The prior best quantum query lower bound is  $\tilde{\Omega}(\sqrt{d})$  due to [BKT20, Theorem 1.5], where the polylogarithmic factor in  $d$  was omitted.

By quantum sample-to-query lifting, we can establish a quantum query lower bound with (1) an explicit (and possibly improved) polylogarithmic factor in  $d$  and (2) dependence on  $\varepsilon$ .

**Theorem 2.5.** *The quantum query complexity of  $\ell_1$  distance estimation is  $\Omega(\frac{\sqrt{d}}{\varepsilon \sqrt{\log(d/\varepsilon)}})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for  $\ell_1$  distance estimation is  $\Omega(\frac{d}{\varepsilon^2 \log(d/\varepsilon)})$  [JHW18, Theorem 3].  $\square$

### 2.1.4 Entropy estimation

**Problem 2.4** (Entropy estimation). *Given an unknown distribution  $P$ , estimate the entropy of  $P$  to within additive error  $\varepsilon$ .*

**Shannon entropy.** The Shannon entropy is defined by  $H(P) = -\sum_{i=1}^d p_i \ln(p_i)$ . A quantum algorithm for Shannon entropy estimation was proposed in [LW19, Theorem 6] with query complexity  $\tilde{O}(\frac{\sqrt{d}}{\varepsilon^2})$ , which was later improved to  $O(\frac{\sqrt{d}}{\varepsilon^{1.5}} (\frac{d}{\varepsilon}) \log \log(\frac{\log(d)}{\varepsilon}))$  in [GL20, Theorem 12]. The current best quantum query upper bound is  $\tilde{O}(\frac{\sqrt{d}}{\varepsilon})$  due to [SJ25] and the prior best quantum query lower bound is  $\tilde{\Omega}(\sqrt{d})$  due to [BKT20, Theorem 1.6], where the polylogarithmic factor in  $d$  was omitted.

By quantum sample-to-query lifting, we can establish a quantum query lower bound with (1) an explicit (and possibly improved) polylogarithmic factor in  $d$  and (2) optimal dependence on  $\varepsilon$ .

**Theorem 2.6.** *The quantum query complexity of Shannon entropy estimation is  $\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon \log(d)}} + \frac{\log(d)}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for Shannon entropy estimation is  $\Omega(\frac{d}{\varepsilon \log(d)} + \frac{\log^2(d)}{\varepsilon^2})$  [JVHW15, WY16].  $\square$

Theorem 2.6 shows that the quantum query upper bound given in [SJ25] is optimal in both  $d$  and  $\varepsilon$ .

**Rényi entropy.** The  $\alpha$ -Rényi entropy is defined by  $H_\alpha^{\text{Rén}}(P) = \frac{1}{1-\alpha} \ln(\sum_{i=1}^d p_i^\alpha)$ .

*The case of  $0 < \alpha < 1$ .* A quantum algorithm for estimating the  $\alpha$ -Rényi entropy was proposed in [LW19] with query complexity  $\tilde{O}(\frac{d^{\frac{1}{\alpha}-\frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}+1}})$  (this is the corrected one noted in [WZL24]). The current best quantum query upper bound is  $\tilde{O}(\frac{d^{\frac{1}{2\alpha}}}{\varepsilon^{\frac{1}{2\alpha}+1}})$  due to [WZL24] and the prior best quantum query lower bound is (1)  $\Omega(\frac{d^{\frac{1}{2\alpha}-\frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$  due to [WZL24, Theorem 9] and (2)  $\Omega(\frac{d^{\frac{1}{3}}}{\varepsilon^{\frac{1}{6}}})$  when  $\frac{1}{d} \leq \varepsilon \leq \frac{1}{2}$  due to [LW19, Theorem 14].

By quantum sample-to-query lifting, we can establish a matching quantum query lower bound below.

**Theorem 2.7.** *For  $0 < \alpha < 1$ , the quantum query complexity of  $\alpha$ -Rényi entropy estimation is  $\Omega(d^{\frac{1}{2\alpha}-o(1)} + \frac{d^{\frac{1}{2\alpha}-\frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$ .*

*Proof.* To apply Theorem 1.1 to show a lower bound of  $\Omega(d^{\frac{1}{2\alpha}-o(1)})$ , we only have to note that the sample lower bound for  $\alpha$ -Rényi entropy estimation is  $\Omega(d^{\frac{1}{\alpha}-o(1)})$  in [AOST17, Theorem 22].  $\square$

Theorem 2.7 shows that the quantum algorithm in [WZL24] for  $0 < \alpha < 1$  has near-optimal dependence on  $d$ .

*The case of non-integer  $\alpha > 1$ .* A quantum algorithm for estimating the  $\alpha$ -Rényi entropy was proposed in [LW19] with query complexity  $\tilde{O}(\frac{d^{1-\frac{1}{2\alpha}}}{\varepsilon^2})$ . The current best quantum query upper bound is  $\tilde{O}(\frac{d^{1-\frac{1}{2\alpha}}}{\varepsilon} + \frac{\sqrt{d}}{\varepsilon^{1+\frac{1}{2\alpha}}})$  due to [WZL24], and the prior best quantum query lower bound is  $\Omega(\frac{d^{\frac{1}{3}}}{\varepsilon^{\frac{1}{6}}} + \frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\varepsilon})$  due to [LW19].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.8.** *For non-integer  $\alpha > 1$ , the quantum query complexity of  $\alpha$ -Rényi entropy estimation is  $\Omega(\frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\varepsilon} + d^{\frac{1}{2}-o(1)})$ .*

*Proof.* To apply Theorem 1.1 to show a lower bound of  $\Omega(d^{\frac{1}{2}-o(1)})$ , we only have to note that the sample lower bound for  $\alpha$ -Rényi entropy estimation is  $\Omega(d^{1-o(1)})$  in [AOST17, Theorem 21].  $\square$

*The case of integer  $\alpha \geq 2$ .* A quantum algorithm for estimating the  $\alpha$ -Rényi entropy was proposed in [LW19] with query complexity  $\tilde{O}(\frac{d^{\nu(1-\frac{1}{\alpha})}}{\varepsilon^2})$ , where  $\nu = 1 - \frac{2\alpha-2}{2\alpha-1} < \frac{3}{4}$ . A matching quantum query lower bound  $\tilde{\Omega}(d^{1/3})$  is given in [LW19] for  $\alpha = 2$ . For integer  $\alpha \geq 3$ , the prior best quantum query lower bound is  $\Omega(\frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\varepsilon})$  due to [LW19].

By quantum sample-to-query lifting, we can simply reproduce this result.

**Theorem 2.9** ([LW19, Theorem 14] reproduced). *For integer  $\alpha \geq 3$ , the quantum query complexity of  $\alpha$ -Rényi entropy estimation is  $\Omega(\frac{d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for  $\alpha$ -Rényi entropy estimation for integer  $\alpha \geq 2$  is  $\Omega(\frac{d^{1-\frac{1}{\alpha}}}{\varepsilon^2})$  in [AOST17, Theorem 15].  $\square$

**Tsallis entropy.** The  $\alpha$ -Tsallis entropy is defined by  $H_\alpha^{\text{Tsa}}(P) = \frac{1}{1-\alpha}(\sum_{i=1}^d p_i^\alpha - 1)$ .

The case of integer  $\alpha \geq 2$ . A quantum algorithm for estimating the  $\alpha$ -Tsallis entropy with query complexity  $O(\frac{\sqrt{\log(1/\alpha\varepsilon)}}{\sqrt{\alpha\varepsilon}})$  was given in [Wan25] together with a lower bound of  $\Omega(\frac{1}{\sqrt{\alpha\varepsilon}})$ .

By quantum sample-to-query lifting, we can simply reproduce this result.

**Theorem 2.10** ([Wan25, Lemma 1.4] reproduced). *For integer  $\alpha \geq 2$ , the quantum query complexity of  $\alpha$ -Tsallis entropy estimation is  $\Omega(\frac{1}{\sqrt{\alpha\varepsilon}})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for  $\alpha$ -Tsallis entropy estimation for integer  $\alpha \geq 2$  is  $\Omega(\frac{1}{\alpha\varepsilon^2})$  in [CWY25, Theorem 4.3].  $\square$

### 2.1.5 Support size

**Problem 2.5** (Support size estimation). *Given an unknown distribution  $P$  with minimum nonzero mass at least  $\frac{1}{d}$ , estimate the support size of  $P$  to within additive error  $\varepsilon d$ .*

The problem of support size estimation is also known as the 0-Rényi entropy estimation, where the difference is that one has to assume the minimum nonzero mass of the unknown distribution. A quantum algorithm for support size estimation was given in [LW19] with query complexity  $\tilde{O}(\frac{\sqrt{d}}{\varepsilon^{1.5}})$ , which is also the current best one. The prior best quantum query lower bound is  $\tilde{\Omega}(\sqrt{d})$  due to [BKT20, Theorem 6.2].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.11.** *The quantum query complexity of support size estimation is  $\Omega(\frac{\sqrt{d}}{\sqrt{\log(d)}} \log(\frac{1}{\varepsilon}))$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for support size estimation is  $\Omega(\frac{d}{\log(d)} \log^2(\frac{1}{\varepsilon}))$  [WY19].  $\square$

### 2.1.6 $k$ -wise uniformity testing

**Problem 2.6** ( $k$ -wise uniformity testing). *Given an unknown distribution  $P$ , determine whether it is  $k$ -wise uniform or  $\varepsilon$ -far from any  $k$ -wise uniform distributions (in total variation distance). Here, a distribution  $P$  over  $\{0, 1\}^n$  is said to be  $k$ -wise uniform, if for every subset  $S \subseteq \{1, 2, \dots, n\}$  with  $|S| = k$ ,*

$$\Pr_{x \sim P}[x_S = v] = \frac{1}{2^k}$$

for any  $v \in \{0, 1\}^k$ , where  $x_S$  means the subsequence of  $x$  with index in  $S$ .

A quantum algorithm for  $k$ -wise uniformity testing was given in [LWL24] with query complexity  $O(\frac{n^{\frac{k}{2}}}{\varepsilon})$  for constant  $k \geq 2$ .

By quantum sample-to-query lifting, we can show a quantum query lower bound when  $k = 2$ .

**Theorem 2.12.** *The quantum query complexity of 2-wise uniformity testing is  $\Omega(\frac{\sqrt{n}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for 2-wise uniformity testing is  $\Omega(\frac{n}{\varepsilon^2})$  [OZ18, Theorem 5].  $\square$

Theorem 2.12 shows that the quantum query upper bound given in [LWL24] is optimal in  $\varepsilon$ .

## 2.2 For quantum properties

For the quantum query complexity of testing quantum properties, we assume purified quantum query access (Definition 1.1) to the input quantum states.

### 2.2.1 Mixedness testing

**Problem 2.7** (Mixedness testing). *Given an unknown  $d$ -dimensional state  $\rho$ , determine whether it is the maximally mixed (i.e.,  $\rho = \frac{I}{d}$ ) or  $\varepsilon$ -far from the maximally mixed state in trace distance (i.e.,  $\|\rho - \frac{I}{d}\|_1 \geq \varepsilon$ ).*

**Theorem 2.13.** *The quantum query complexity of mixedness testing is  $\Omega(\frac{\sqrt{d}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for mixedness testing is  $\Omega(\frac{d}{\varepsilon^2})$  [OW21, Theorem 1.10].  $\square$

The lower bound in Theorem 2.13 also applies to quantum state certification [BOW19], where the task is to determine whether an unknown quantum state  $\rho$  is identical to a given one  $\sigma$  or  $\rho$  is  $\varepsilon$ -far from  $\sigma$  in trace distance.

**Corollary 2.14.** *The quantum query complexity of quantum state certification is  $\Omega(\frac{\sqrt{d}}{\varepsilon})$ .*

Moreover, Theorem 2.13 also implies an improved quantum query lower bound given in [WZ25a, Corollary 4.19] for the mixedness testing of block-encoded matrices.

**Corollary 2.15.** *The quantum query complexity of determining whether an Hermitian matrix  $A$  block-encoded in a unitary oracle has spectrum  $(\frac{1}{d}, \dots, \frac{1}{d})$  or  $\varepsilon$ -far in trace norm is  $\Omega(\frac{\sqrt{d}}{\varepsilon})$ .*

### 2.2.2 Rank testing

**Problem 2.8** (Rank testing). *Given an unknown state  $\rho$ , determine whether it is of rank at most  $r$  or  $\varepsilon$ -far from any state that is of rank at most  $r$  in trace norm.*

**Theorem 2.16.** *The quantum query complexity of rank testing is  $\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for rank testing is  $\Omega(\frac{r}{\varepsilon})$  [OW21, Theorem 1.11].  $\square$

Theorem 2.16 also implies an improved quantum query lower bound given in [WZ25a, Corollary 4.8] for the rank testing of block-encoded matrices.

**Corollary 2.17.** *The quantum query complexity of determining whether an Hermitian matrix  $A$  block-encoded in a unitary oracle has rank  $\leq r$  or  $\varepsilon$ -far in trace norm from any matrices of rank  $\leq r$  is  $\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}})$ .*

### 2.2.3 Uniformity distinguishing

**Problem 2.9** (Uniformity distinguishing). *Given an unknown state  $\rho$ , determine whether  $\rho$ 's spectrum is uniform on either  $r$  or  $r + \Delta$  eigenvalues.*

**Theorem 2.18.** *For  $1 \leq \Delta < r$ , the quantum query complexity of uniformity distinguishing is  $\Omega^*(\frac{r}{\sqrt{\Delta}})$ .<sup>4</sup> For  $\Delta = r$ , a better lower bound of  $\Omega(\sqrt{r})$  can be obtained.*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for uniformity distinguishing is  $\Omega^*(\frac{r^2}{\Delta})$  [OW21, Theorem 1.12] for  $1 \leq \Delta < r$ . For  $\Delta = r$ , a better query lower bound of  $\Omega(\sqrt{r})$  can be obtained by noting the sample lower bound  $\Omega(r)$  for uniformity distinguishing in [CHW07, Theorem 3] (see also [OW21, Theorem 1.9]).  $\square$

Theorem 2.18 also implies an improved quantum query lower bound given in [WZ25a, Corollary 4.10] for the rank testing of block-encoded matrices when  $\Delta = r$ .

**Corollary 2.19.** *The quantum query complexity of determining whether an Hermitian matrix block-encoded in a unitary oracle has spectrum uniform on either  $r$  or  $2r$  eigenvalues is  $\Omega(\sqrt{r})$ .*

### 2.2.4 Entanglement spectrum testing

**Problem 2.10** (Maximal entanglement testing). *Given an unknown bipartite state  $|\psi\rangle \in \mathbb{C}^d \otimes \mathbb{C}^d$ , determine whether it is the maximally entangled or  $\varepsilon$ -far from any maximally entangled state in trace norm.*

**Theorem 2.20.** *The quantum query complexity of maximal entanglement testing is  $\Omega(\frac{\sqrt{d}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for maximal entanglement testing is  $\Omega(\frac{d}{\varepsilon^2})$  [CWZ24, Corollary 1.6].  $\square$

**Problem 2.11** (Schmidt rank testing). *Given an unknown bipartite state  $|\psi\rangle$ , determine whether it is of Schmidt rank at most  $r$  or  $\varepsilon$ -far from any state that is of Schmidt rank at most  $r$  in trace norm.*

**Theorem 2.21.** *The quantum query complexity of Schmidt rank testing is  $\Omega(\frac{\sqrt{r}}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for Schmidt rank testing is  $\Omega(\frac{r}{\varepsilon^2})$  [CWZ24, Corollary 1.4].  $\square$

**Problem 2.12** (Uniform Schmidt coefficient testing). *Given an unknown bipartite state  $|\psi\rangle$ , determine whether  $|\psi\rangle$ 's entanglement spectrum is uniform on either  $r$  or  $r + \Delta$  Schmidt coefficients.*

**Theorem 2.22.** *For  $1 \leq \Delta < r$ , the quantum query complexity of uniform Schmidt coefficient testing is  $\Omega^*(\frac{r}{\sqrt{\Delta}})$ . For  $\Delta = r$ , a better lower bound of  $\Omega(\sqrt{r})$  can be obtained.*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for uniform Schmidt coefficient testing is  $\Omega^*(\frac{r^2}{\Delta})$  [CWZ24, Corollary 1.8] for  $1 \leq \Delta < r$ . For  $\Delta = r$ , a better query lower bound of  $\Omega(\sqrt{r})$  can be obtained by noting the sample lower bound  $\Omega(r)$  for uniform Schmidt coefficient testing implied by [CWZ24, Corollary 1.3] and [CHW07, Theorem 3] (see also [OW21, Theorem 1.9]).  $\square$

---

<sup>4</sup> $\Omega^*(\cdot)$  suppresses quasi-polylogarithmic factors.

### 2.2.5 Quantum entropy estimation

**Problem 2.13** (Quantum entropy estimation). *Given an unknown quantum state  $\rho$ , estimate the entropy of  $\rho$  to within additive error  $\varepsilon$ .*

**Von Neumann entropy.** Given a  $d$ -dimensional quantum state  $\rho$ , the von Neumann entropy of  $\rho$  is defined by

$$S(\rho) = -\text{tr}(\rho \ln(\rho)).$$

Quantum algorithms were given in [GL20] with query complexity  $\tilde{O}(\frac{d}{\varepsilon^{1.5}})$  and in [WGL<sup>+</sup>24] with query complexity  $\tilde{O}(\frac{r}{\varepsilon^2})$  when  $\rho$  is of rank  $r$ . The prior best quantum query lower bound is  $\tilde{\Omega}(\sqrt{d})$  due to [BKT20, Theorem 1.6].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.23.** *The quantum query complexity of von Neumann entropy is  $\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon}} + \frac{\log(d)}{\varepsilon})$ .*

*Proof.* Note that a sample lower bound of  $\Omega(\frac{d}{\varepsilon})$  was shown in [WZ25b, Theorem 1.7]. On the other hand, a sample lower bound of  $\Omega(\frac{\log^2(d)}{\varepsilon^2})$  for estimating the Shannon entropy was shown in [JVHW15, WY16]. By simulating the measurement of von Neumann entropy estimator on the diagonal state, one can obtain a Shannon entropy estimator with the same sample complexity. Thus the lower bound  $\Omega(\frac{\log^2(d)}{\varepsilon^2})$  also applies to the von Neumann entropy. Therefore, we obtain a sample lower bound of  $\Omega(\frac{d}{\varepsilon} + \frac{\log^2(d)}{\varepsilon^2})$ . Then, by Theorem 1.1, we obtain the query lower bound  $\Omega(\sqrt{\frac{d}{\varepsilon} + \frac{\log^2(d)}{\varepsilon^2}}) = \Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon}} + \frac{\log(d)}{\varepsilon})$ .  $\square$

**Quantum Rényi entropy.** The quantum  $\alpha$ -Rényi entropy is defined by

$$S_\alpha^{\text{Rén}}(\rho) = \frac{1}{1-\alpha} \ln(\text{tr}(\rho^\alpha)).$$

The quantum query complexity of quantum Rényi entropy was studied in [SH21, WZW23, WZYW23, WGL<sup>+</sup>24]. The current best quantum query upper bound for quantum Rényi entropy estimation is  $\tilde{O}(\frac{d^{\frac{1}{2\alpha} + \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha} + 1}})$  for  $0 < \alpha < 1$  and  $\tilde{O}(\min\{\frac{d^{\frac{3}{2} - \frac{1}{2\alpha}}}{\varepsilon} + \frac{d}{\varepsilon^{1 + \frac{1}{2\alpha}}}, \frac{d}{\varepsilon^{1 + \frac{1}{\alpha}}}\})$  for  $\alpha > 1$  due to [WZL24]. The current best quantum query lower bounds are inherited from those for the estimation of classical entropy as mentioned in Section 2.1.4.

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.24.** *For  $0 < \alpha < 1$ , the query complexity of quantum  $\alpha$ -Rényi entropy is  $\Omega(d^{\frac{1}{2\alpha} - o(1)} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}} + \frac{\sqrt{d}}{\sqrt{\varepsilon}})$ . For non-integer  $\alpha > 1$ , the query complexity of quantum  $\alpha$ -Rényi entropy is  $\Omega(\frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon} + \frac{\sqrt{d}}{\sqrt{\varepsilon}})$ . For integer  $\alpha \geq 2$ , the query complexity of quantum  $\alpha$ -Rényi entropy is  $\Omega(\frac{d^{1 - \frac{1}{\alpha}}}{\varepsilon} + \frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ .*

*Proof.* For  $0 < \alpha < 1$ , Theorem 2.7 gives part of the query lower bound  $\Omega(d^{\frac{1}{2\alpha} - o(1)} + \frac{d^{\frac{1}{2\alpha} - \frac{1}{2}}}{\varepsilon^{\frac{1}{2\alpha}}})$ . Moreover, a query lower bound of  $\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon}})$  is obtained by Theorem 1.1 and noting the sample lower bound  $\Omega(\frac{d}{\varepsilon})$  for quantum  $\alpha$ -Rényi entropy estimation given in [WZ25b, Theorem VI.5].

For non-integer  $\alpha > 1$ , Theorem 2.8 gives part of the query lower bound  $\Omega(\frac{d^{\frac{1}{2} - \frac{1}{2\alpha}}}{\varepsilon})$ . Moreover, a query lower bound of  $\Omega(\frac{\sqrt{d}}{\sqrt{\varepsilon}})$  is obtained by Theorem 1.1 and noting the sample lower bound  $\Omega(\frac{d}{\varepsilon})$  for quantum  $\alpha$ -Rényi entropy estimation given in [WZ25b, Theorem VI.4].

For integer  $\alpha \geq 2$ , the query lower bound is obtained by Theorem 1.1 and noting the sample lower bound  $\Omega(\frac{d^{2-\frac{2}{\alpha}}}{\varepsilon^{\frac{2}{\alpha}}} + \frac{d^{1-\frac{1}{\alpha}}}{\varepsilon^2})$  given in [AISW20, Theorem 1].  $\square$

**Quantum Tsallis entropy.** The quantum  $\alpha$ -Tsallis entropy is defined by

$$S_{\alpha}^{\text{Tsa}}(\rho) = \frac{1}{1-\alpha}(\text{tr}(\rho^{\alpha}) - 1).$$

The current best quantum query complexity for quantum Tsallis entropy estimation is  $\tilde{O}(\frac{1}{\varepsilon^{1+\frac{1}{\alpha-1}}})$  for  $\alpha > 1$  due to [LW25b], where they provided a quantum query lower bound of  $\Omega(\frac{1}{\sqrt{\varepsilon}})$ .

**Theorem 2.25.** *For  $1 < \alpha < \frac{3}{2}$ , the quantum query complexity of quantum  $\alpha$ -Tsallis entropy estimation is  $\Omega(\frac{1}{\varepsilon^{2(\alpha-1)}})$ . For  $\alpha \geq \frac{3}{2}$ , the quantum query complexity is  $\Omega(\frac{1}{\varepsilon})$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for  $\alpha$ -Tsallis entropy estimation is  $\Omega(\frac{1}{\varepsilon^{\frac{1}{\alpha-1}}})$  for  $1 < \alpha < \frac{3}{2}$  and  $\Omega(\frac{1}{\varepsilon^2})$  for  $\alpha \geq \frac{3}{2}$  in [CW25, Theorem 20].  $\square$

### 2.2.6 Trace distance estimation

**Problem 2.14** (Trace distance estimation). *Given two unknown quantum states  $\rho$  and  $\sigma$  of rank  $r$ , estimate the trace distance*

$$T(\rho, \sigma) = \frac{1}{2} \text{tr}(|\rho - \sigma|)$$

*to within additive error  $\varepsilon$ .*

A quantum algorithm for trace distance estimation was proposed in [WGL<sup>+</sup>24, Theorem IV.1] with query complexity  $\tilde{O}(\frac{r^5}{\varepsilon^6})$ , which was later improved to  $O(\frac{r}{\varepsilon^2} \log(\frac{1}{\varepsilon}))$  in [WZ24a, Corollary III.2]. For the pure-state case where  $r = 1$ , optimal quantum algorithms for trace distance estimation were proposed in [Wan24] with query complexity  $\Theta(\frac{1}{\varepsilon})$ . The prior best quantum query lower bound is  $\tilde{\Omega}(\sqrt{r} + \frac{1}{\varepsilon})$ , where  $\tilde{\Omega}(\sqrt{r})$  is due to the quantum query lower bound for total variation distance estimation [BKT20, Theorem 1.5] with polylogarithmic factors in  $r$  omitted and  $\Omega(\frac{1}{\varepsilon})$  was mentioned in [Wan24, Theorem V.2].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.26.** *The quantum query complexity of trace distance estimation is  $\Omega(\frac{\sqrt{r}}{\varepsilon})$ .*

*Proof.* Given an  $r$ -dimensional state  $\rho$ , we can embed it into a  $d$ -dimensional Hilbert space using an isometry  $V : \mathbb{C}^r \rightarrow \mathbb{C}^d$ . Then, any trace estimation algorithm on  $V\rho V^{\dagger}$  and  $\frac{1}{r}V I_r V^{\dagger}$  ( $\frac{1}{r}I_r$  is the  $r$ -dimensional maximally mixed state) can be used to test whether  $\rho$  is the maximally mixed state or  $\varepsilon$ -far from the maximally mixed state in trace distance. Therefore, the sample lower bound  $\Omega(\frac{r}{\varepsilon^2})$  in [OW21, Theorem 1.10] applies also to the trace estimation task. By Theorem 1.1, we obtain a quantum query lower bound  $\Omega(\frac{\sqrt{r}}{\varepsilon})$  for trace distance estimation.  $\square$

### 2.2.7 Fidelity estimation

**Problem 2.15** (Fidelity estimation). *Given two unknown quantum states  $\rho$  and  $\sigma$  of rank  $r$ , estimate the fidelity*

$$F(\rho, \sigma) = \text{tr}\left(\sqrt{\sqrt{\sigma}\rho\sqrt{\sigma}}\right)$$

*to within additive error  $\varepsilon$ .*

A quantum algorithm for fidelity estimation was proposed in [WZC<sup>+</sup>23] with query complexity  $\tilde{O}(\frac{r^{12.5}}{\varepsilon^{13.5}})$ .<sup>5</sup> This was later improved to  $\tilde{O}(\frac{r^{6.5}}{\varepsilon^{7.5}})$  in [WGL<sup>+</sup>24, Theorem IV.5], to  $\tilde{O}(\frac{r^{2.5}}{\varepsilon^5})$  in [GP22, Corollary 28], and recently to  $\tilde{O}(\frac{r}{\varepsilon^2} \log(\frac{1}{\varepsilon}))$  in [UNWT25, Theorem 23]. For the pure-state case where  $r = 1$ , optimal quantum algorithms for fidelity estimation were proposed in [Wan24, FW25] with query complexity  $\Theta(\frac{1}{\varepsilon})$ . The prior best quantum query lower bound is  $\Omega(r^{1/3} + \frac{1}{\varepsilon})$  mentioned in [UNWT25, Proposition 31], where  $\Omega(r^{1/3})$  is due to the quantum query lower bound for uniformity testing of probability distributions [CFMdW10] and  $\Omega(1/\varepsilon)$  is due to the lower bound for quantum counting [BBC<sup>+</sup>01, NW99].

By quantum sample-to-query lifting, we can obtain an improved quantum query lower bound.

**Theorem 2.27.** *The quantum query complexity of fidelity estimation is  $\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}} + \frac{1}{\varepsilon})$ .*

*Proof.* Given an  $r$ -dimensional state  $\rho$ , we can embed it into a  $d$ -dimensional Hilbert space using an isometry  $V : \mathbb{C}^r \rightarrow \mathbb{C}^d$ . Then, any fidelity estimation algorithm on  $V\rho V^\dagger$  and  $\frac{1}{r}VI_rV^\dagger$  ( $\frac{1}{r}I_r$  is the  $r$ -dimensional maximally mixed state) can be used to test whether  $\rho$  is the maximally mixed state or  $\sqrt{\varepsilon}$ -far from the maximally mixed state in trace distance (due to the inequality  $T(\rho, \sigma) \leq \sqrt{1 - F(\rho, \sigma)^2}$  [NC10]). Therefore, the sample lower bound of  $\Omega(\frac{r}{\varepsilon^2})$  in [OW21, Theorem 1.10] gives a lower bound of  $\Omega(\frac{r}{\varepsilon})$  for the fidelity estimation task.

Moreover, [ALL22, Lemma 13] shows that estimating  $\text{tr}(\rho\sigma)$  for pure states  $\rho$  and  $\sigma$  to within error  $\varepsilon$  requires sample complexity  $\Omega(\frac{1}{\varepsilon^2})$ . Since  $\text{tr}(\rho\sigma) = F(\rho, \sigma)^2$  when  $\rho, \sigma$  are pure states, this lower bound also applies to the fidelity estimation task.

Therefore, we obtain a sample lower bound  $\Omega(\frac{r}{\varepsilon} + \frac{1}{\varepsilon^2})$  and by Theorem 1.1 we obtain a query lower bound  $\Omega(\frac{\sqrt{r}}{\sqrt{\varepsilon}} + \frac{1}{\varepsilon})$ .  $\square$

When the two quantum states are well-conditioned, i.e., the reciprocal of the minimum non-zero eigenvalue of  $\rho$  and  $\sigma$  is (upper bounded by)  $\kappa$ , a quantum algorithm for fidelity estimation was proposed in [LWWZ25, Theorem 16] with query complexity  $\tilde{O}(\frac{\kappa^4}{\varepsilon})$ , which was later improved to  $O(\frac{\kappa}{\varepsilon} \log(\frac{1}{\varepsilon}))$  in [UNWT25, Theorem 23]. A nearly matching lower bound of  $\Omega(\frac{1}{\varepsilon})$  was given in [LWWZ25, Lemma 17] when  $\kappa = \Theta(1)$ .

By quantum sample-to-query lifting, we can simply reproduce this result.

**Theorem 2.28** ([LWWZ25, Lemma 17] reproduced). *The quantum query complexity of well-conditioned fidelity estimation is  $\Omega(\frac{1}{\varepsilon})$  even if  $\kappa = \Theta(1)$ .*

*Proof.* To apply Theorem 1.1, we only have to note that the sample lower bound for well-conditioned fidelity estimation is  $\Omega(\frac{1}{\varepsilon^2})$  even if  $\kappa = \Theta(1)$ , which was given in [LWWZ25, Lemma 40].  $\square$

### 2.3 Other quantum tasks

There are a series of lower bounds that can be derived by reducing from quantum state discrimination and applying Theorem 1.1.

Let  $\text{Dis}_{\rho, \sigma}$  be a promise problem for quantum state discrimination; i.e., let  $\text{Dis}_{\rho, \sigma}^{\text{yes}} = \{\rho\}$  and  $\text{Dis}_{\rho, \sigma}^{\text{no}} = \{\sigma\}$ . We have the following lower bound for quantum state discrimination, which can be derived from the Helstrom-Holevo theorem [Hel69, Hol73].

**Lemma 2.29** (Lower bound for quantum state discrimination, cf. [WZ25a, Lemma 2.3]). *The quantum sample complexity for quantum state discrimination is lower bounded by  $S(\text{Dis}_{\rho, \sigma}) = \Omega(1/\gamma)$ , where  $\gamma = 1 - F(\rho, \sigma)$  is the infidelity.*

<sup>5</sup>An earlier version of [WZC<sup>+</sup>23] gave a quantum query complexity of  $\tilde{O}(\frac{r^{21.5}}{\varepsilon^{23.5}})$  for fidelity estimation.

### 2.3.1 Amplitude estimation

Amplitude estimation is a basic quantum subroutine to estimate the amplitude  $a$  of a quantum state  $a|0\rangle|\phi_0\rangle + \sqrt{1-a^2}|1\rangle|\phi_1\rangle$ , given its state preparation unitary  $U$ .

**Problem 2.16** (Amplitude estimation). *Given queries to a unitary  $U$  such that  $U|0\rangle = a|0\rangle|\phi_0\rangle + \sqrt{1-a^2}|1\rangle|\phi_1\rangle$  with  $a \in [0, 1]$ , the task is to estimate the amplitude  $a$  to within additive error  $\varepsilon$ ; i.e., output an  $\hat{a} \in [0, 1]$  such that  $|\hat{a} - a| \leq \varepsilon$  with probability  $\geq 2/3$ .*

Using Theorem 1.1 and the reduction in [WZ25a], we can reproduce the tight lower bound  $\Omega(1/\varepsilon)$  for amplitude estimation. Previously, this lower bound is obtained by reducing from quantum counting [NW99, Corollary 1.12], matching the upper bound  $O(1/\varepsilon)$  [BHMT02, Wan24]. It is worth noting that in Problem 2.16, if one is only given query to the time-forward  $U$  but not its time-reverse  $U^\dagger$ , the query lower bound will become  $\Omega(\min(d, 1/\varepsilon^2))$  [TW25].

**Theorem 2.30** (Lower bound for amplitude estimation [NW99, Corollary 1.12] reproduced). *The quantum query complexity of amplitude estimation is  $\Omega(1/\varepsilon)$ .*

*Proof.* We can reduce the quantum state discrimination problem  $\text{Dis}_{\rho_+, \rho_-}$  to the amplitude estimation problem as in [WZ25a], by considering the following two states

$$\rho_\pm = \left(\frac{1}{2} \mp \frac{5}{2}\varepsilon\right)|0\rangle\langle 0| + \left(\frac{1}{2} \pm \frac{5}{2}\varepsilon\right)|1\rangle\langle 1|,$$

with infidelity  $O(\varepsilon^2)$ . From Lemma 2.29, we have a sample lower bound  $S(\text{Dis}_{\rho_+, \rho_-}) = \Omega(1/\varepsilon^2)$ , which further implies a query lower bound  $Q(\text{Dis}_{\rho_+, \rho_-}) = \Omega(1/\varepsilon)$ , using Theorem 1.1. Suppose  $\mathcal{A}^U$  is a quantum algorithm that solves the amplitude estimation problem to within error  $\varepsilon$ , using  $Q$  queries to  $U$ . By taking  $U = U_{\rho_\pm}$  such that

$$U_{\rho_\pm}|0\rangle|0\rangle = \sqrt{\frac{1}{2} \mp \frac{5}{2}\varepsilon}|0\rangle|0\rangle + \sqrt{\frac{1}{2} \pm \frac{5}{2}\varepsilon}|1\rangle|1\rangle,$$

algorithm  $\mathcal{A}^U$  can solve  $\text{Dis}_{\rho_+, \rho_-}$ , because  $\sqrt{\frac{1}{2} + \frac{5}{2}\varepsilon} - \sqrt{\frac{1}{2} - \frac{5}{2}\varepsilon} > 3\varepsilon$ . Since  $U_{\rho_\pm}$  give purified query access to  $\rho_\pm$ , we obtain  $Q \geq Q(\text{Dis}_{\rho_+, \rho_-}) = \Omega(1/\varepsilon)$ .  $\square$

### 2.3.2 Hamiltonian simulation

Hamiltonian simulation [Fey82] is a task to simulate the dynamics of the Schrödinger equation governed by a Hamiltonian  $H$ . Specifically, we want to implement the unitary operator  $e^{-iHt}$  for a given Hamiltonian  $H$  and simulation time  $t$ .

**Problem 2.17** (Hamiltonian simulation). *Given a block-encoding  $U$  of a Hamiltonian  $H$ , the task is to approximately implement the evolution unitary  $e^{-iHt}$  for an evolution time  $t$  to a constant precision; i.e., to implement a quantum channel  $\mathcal{E}$  such that for any state  $\rho$ , the trace norm  $\|\mathcal{E}(\rho) - e^{-iHt}\rho e^{iHt}\|_1 \leq 0.01$ .*

Over the years, many efficient quantum algorithms for Hamiltonian simulation have been proposed, e.g., [Llo96, ATS03, BACS07, CW12, BCC<sup>+</sup>14, BCC<sup>+</sup>15, BCK15, LC17, LC19, ZWY24]. The optimal query complexity with respect to the simulation time  $t$  is  $\Theta(t)$  [LC17, LC19]. The lower bound part  $\Omega(t)$  is obtained by a reduction [BACS07, CK10, BCC<sup>+</sup>14, BCK15] from the parity problem, whose lower bound can be proved by the polynomial method [BBC<sup>+</sup>01, FGGS98].

Using Theorem 1.1 and the reduction in [WZ25a], we can reproduce this tight lower bound  $\Omega(t)$  for Hamiltonian simulation.

**Theorem 2.31** (Lower bound for Hamiltonian simulation, cf. [BACS07, GSLW19]). *For  $t \geq 2\pi$ , the quantum query complexity for Hamiltonian simulation is  $\Omega(t)$ .*

*Proof.* We can reduce from the quantum state discrimination problem  $\text{Dis}_{\rho,\sigma}$  as in [WZ25a], by considering the following two states

$$\rho = \frac{1}{2}|0\rangle\langle 0| + \frac{1}{2}|1\rangle\langle 1| \quad \text{and} \quad \sigma = \left(\frac{1}{2} + \frac{\pi}{t}\right)|0\rangle\langle 0| + \left(\frac{1}{2} - \frac{\pi}{t}\right)|1\rangle\langle 1|,$$

with infidelity  $O(1/t^2)$ . Similar to the proof of Theorem 2.30, by applying Lemma 2.29 and Theorem 1.1, we have query lower bound  $Q(\text{Dis}_{\rho,\sigma}) = \Omega(t)$ . Suppose  $\mathcal{A}^U$  is a quantum algorithm that simulates Hamiltonian for time  $t$  problem to within error 0.01, using  $Q$  queries to  $U$ . Let  $U_\rho$  and  $U_\sigma$  be purified query access to  $\rho$  and  $\sigma$ , respectively. Then, using [GSLW19, Lemma 25], one can obtain a query to a block-encoding of  $\rho$  (resp.  $\sigma$ ) using 2 queries to  $U_\rho$  (resp.  $U_\sigma$ ). Taking these block-encodings as  $U$  in  $\mathcal{A}^U$  leads to implementations, using  $Q$  queries, of  $e^{-i\frac{\pi}{2}t}$  and  $e^{-i\frac{\sigma}{2}t}$  to within error 0.01. This can solve  $\text{Dis}_{\rho,\sigma}$  by applying  $\mathcal{A}^U$  on state  $|+\rangle$  followed by a Hadamard basis measurement:

$$\left| \langle + | e^{-i\frac{\pi}{2}t} | + \rangle \right|^2 - 0.01 = 0.99 \geq \frac{2}{3} \quad \text{and} \quad \left| \langle - | e^{-i\frac{\sigma}{2}t} | + \rangle \right|^2 + 0.01 = 0.01 \leq \frac{1}{3}.$$

Thus,  $Q \geq Q(\text{Dis}_{\rho,\sigma}) = \Omega(t)$ . □

### 2.3.3 Quantum Gibbs sampling

Quantum Gibbs sampling is a task to prepare the Gibbs (thermal) state  $e^{-\beta H}/\mathcal{Z}$  of a given Hamiltonian  $H$  at inverse temperature  $\beta \geq 0$ . Here,  $\mathcal{Z} = \text{tr}(e^{-\beta H})$  is the normalization factor, also known as the partition function.

**Problem 2.18** (Quantum Gibbs sampling). *Given a block-encoding  $U$  of a Hamiltonian  $H$ , the task is to prepare the Gibbs state  $e^{-\beta H}/\mathcal{Z}$  to within constant error at inverse temperature  $\beta$ , where  $\mathcal{Z} = \text{tr}(e^{-\beta H})$  is the normalization factor; i.e., to prepare a quantum state  $\rho$  such that the trace norm  $\|\rho - e^{-\beta H}/\mathcal{Z}\|_1 \leq 0.01$ .*

Many quantum algorithms for Gibbs sampling have been proposed [PW09, TOV<sup>+</sup>11, YAG12, KB16, CS17, BK19, CKG23, ZBC23, RFA24, DLL25, RS25, CKBG25, HSDS25]. Gibbs sampling is found to be useful in solving semidefinite programs [BS17, vAGGdW20, BKL<sup>+</sup>19, vAG19]. Regarding Problem 2.18, a quantum algorithm with query complexity  $O(\beta)$  was presented in [GSLW19].

Using Theorem 1.1 and the reduction in [WZ25a], we can reproduce the tight lower bound  $\Omega(\beta)$  for quantum Gibbs sampling. Previously, this lower bound was obtained by reducing from Hamiltonian discrimination [CKBG23, Proposition G.5] or unitary discrimination [Weg25].

**Theorem 2.32** (Lower bound for Gibbs sampling). *For  $\beta \geq 4$ , the quantum query complexity for Gibbs sampling is  $\Omega(\beta)$ .*

*Proof.* We can reduce from the quantum state discrimination problem  $\text{Dis}_{\rho_+,\rho_-}$  as in [WZ25a], by considering the following two states

$$\rho_{\pm} = \left(\frac{1}{2} \mp \frac{2}{\beta}\right)|0\rangle\langle 0| + \left(\frac{1}{2} \pm \frac{2}{\beta}\right)|1\rangle\langle 1|,$$

with infidelity  $O(1/\beta^2)$ . Similar to the proof of Theorem 2.30, by applying Lemma 2.29 and Theorem 1.1, we have query lower bound  $Q(\text{Dis}_{\rho_+,\rho_-}) = \Omega(\beta)$ . Suppose  $\mathcal{A}^U$  is a quantum algorithm

that prepares the Gibbs state  $e^{-\beta H/\mathcal{Z}}$  at inverse temperature  $\beta$  to within trace norm error 0.01, using  $Q$  queries to  $U$ . Similar to the proof of Theorem 2.31, we can use 2 queries to  $U_\rho$  (resp.  $U_\sigma$ ) to obtain a query to a block-encoding of  $\rho$  (resp.  $\sigma$ ), where  $U_\rho$  (resp.  $U_\sigma$ ) provides purified query access to  $\rho$  (resp.  $\sigma$ ). Taking these block-encodings as  $U$  in  $\mathcal{A}^U$  leads to preparations, using  $Q$  queries, of mixed states  $\propto e^{-\beta \frac{\rho_\pm}{2}}$  to within error 0.01. This can solve  $\text{Dis}_{\rho_+, \rho_-}$  by applying  $\mathcal{A}^U$  followed by a computational basis measurement:

$$\begin{aligned} \text{tr} \left( |0\rangle\langle 0| \cdot \frac{e^{-\beta \frac{\rho_+}{2}}}{\text{tr}(e^{-\beta \frac{\rho_+}{2}})} \right) - 0.01 &= \frac{e}{e + e^{-1}} - 0.01 \geq \frac{2}{3} \\ \text{tr} \left( |0\rangle\langle 0| \cdot \frac{e^{-\beta \frac{\rho_-}{2}}}{\text{tr}(e^{-\beta \frac{\rho_-}{2}})} \right) + 0.01 &= \frac{e^{-1}}{e + e^{-1}} + 0.01 \leq \frac{1}{3}. \end{aligned}$$

Thus,  $Q \geq Q(\text{Dis}_{\rho_+, \rho_-}) = \Omega(\beta)$ .  $\square$

A variant of the standard Gibbs sampling in Problem 2.18 is to replace the given oracle by a block-encoding of  $\sqrt{H}$ , formalized below. In this setting, the query upper bound can achieve  $O(\sqrt{\beta})$  in some special cases [CS17], e.g., when  $H$  is a linear combination of Pauli operators.

**Problem 2.19** (Gibbs sampling with stronger oracles). *Given a block-encoding  $U$  of the square root  $\sqrt{H}$  of a Hamiltonian  $H$ , the task is to prepare the Gibbs state  $e^{-\beta H}/\mathcal{Z}$  to within constant error at inverse temperature  $\beta$ , as in Problem 2.18.*

Using Theorem 1.1 and the reduction in [WZ25a], we can show that the lower bound  $\Omega(\beta)$  for quantum Gibbs sampling still hold even with stronger oracles. This new lower bound improves the prior  $\tilde{\Omega}(\beta)$  [WZ25a].

**Theorem 2.33** (Impossibility of improving Gibbs sampling even with stronger oracles). *For  $\beta \geq 4$ , even with the stronger oracles in Problem 2.18, the quantum query complexity for Gibbs sampling is  $\Omega(\beta)$ .*

*Proof.* The proof is similar to that of Theorem 2.32 using the same construction. We only need to notice that

$$\begin{aligned} \text{tr} \left( |0\rangle\langle 0| \cdot \frac{e^{-\beta \frac{\rho_+}{2}}}{\text{tr}(e^{-\beta \frac{\rho_+}{2}})} \right) - 0.01 &= \frac{e^{0.5}}{e^{0.5} + e^{-0.5}} - 0.01 \geq \frac{2}{3} \\ \text{tr} \left( |0\rangle\langle 0| \cdot \frac{e^{-\beta \frac{\rho_-}{2}}}{\text{tr}(e^{-\beta \frac{\rho_-}{2}})} \right) + 0.01 &= \frac{e^{-0.5}}{e^{0.5} + e^{-0.5}} + 0.01 \leq \frac{1}{3}. \end{aligned}$$

$\square$

### 2.3.4 The entanglement entropy problem

The entanglement entropy problem [SY23] is a problem of unitary property testing that decides whether a bipartite state  $|\psi\rangle \in \mathcal{H}_A \otimes \mathcal{H}_B$  has low ( $\leq a$ ) or high ( $\geq b$ ) Rényi entanglement entropy.

**Problem 2.20** (The entanglement entropy problem [SY23, Definition 1.13]). *Given query access to the reflection operator  $U_\psi = I - 2|\psi\rangle\langle\psi|$  about a bipartite pure state  $|\psi\rangle \in \mathcal{H}_A \otimes \mathcal{H}_B$  with  $\mathcal{H}_A = \mathcal{H}_B = \mathbb{C}^d$ , the entanglement entropy problem  $\mathcal{P} = \text{QENTANGLEMENTENTROPY}_{\alpha,a,b}$  with  $0 < a < b \leq \ln(d)$  is a promise problem for testing whether a bipartite pure state has low ( $\leq a$ ) or high ( $\geq b$ ) entanglement entropy, with*

$$\begin{aligned}\mathcal{P}^{\text{yes}} &= \left\{ |\psi\rangle \in \mathcal{H}_A \otimes \mathcal{H}_B : S_\alpha^{\text{Rén}}(\text{tr}_B(|\psi\rangle\langle\psi|)) \leq a \right\}, \\ \mathcal{P}^{\text{no}} &= \left\{ |\psi\rangle \in \mathcal{H}_A \otimes \mathcal{H}_B : S_\alpha^{\text{Rén}}(\text{tr}_B(|\psi\rangle\langle\psi|)) \geq b \right\},\end{aligned}$$

where  $S_\alpha^{\text{Rén}}(\cdot)$  is the  $\alpha$ -Rényi entropy.

Previously, a query lower bound of  $\Omega(e^{a/4})$  was given in [SY23, Theorem 1.14] (when  $\alpha = 2$ ), which gives  $\Omega(d^{1/4})$  when  $a$  is close to  $\ln(d)$ . Later improvements focused on the dependence on  $\Delta = b - a$ . In [WZ25a, Theorem 4.3], a query lower bound of  $\tilde{\Omega}(\frac{1}{\sqrt{\Delta}})$  was given, which was improved to  $\Omega(\frac{1}{\sqrt{\Delta}})$  in [Weg25, Claim 2]. Later, a query lower bound of  $\tilde{\Omega}(\frac{\sqrt{d}}{\sqrt{\Delta}} + \frac{d^{\frac{1}{\alpha}-1}}{\Delta^{\frac{1}{\alpha}}})$  in terms of both  $d$  and  $\Delta$  was shown in [CWZ24, Theorem 5.1] for every  $\alpha > 0$ .

Using Theorem 1.1, we are able to prove new quantum query lower bounds for the entanglement entropy problem.

**Theorem 2.34.** *Let  $\mathcal{P}_{\alpha,a,b} = \text{QENTANGLEMENTENTROPY}_{\alpha,a,b}$  be the entanglement entropy problem. The quantum query complexity for  $\mathcal{P}$  has the following lower bounds, where  $\Delta = b - a$ :*

- For  $\alpha = 1$ :  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, \ln(d)-\Delta, \ln(d)}) = \Omega(\frac{\sqrt{d}}{\sqrt{\Delta}})$ . Moreover, there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, a, a+\Delta}) = \Omega(\frac{\frac{\sqrt{d}}{\sqrt{\Delta}} + \frac{\log(d)}{\Delta}}{\sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .
- For  $0 < \alpha < 1$ :  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, \ln(d)-\Delta, \ln(d)}) = \Omega(\frac{\sqrt{d}}{\sqrt{\Delta}})$  and  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, 0, \Delta}) = \Omega(d^{\frac{1}{2\alpha}-\frac{1}{2}})$ . Moreover, there exists a constant  $\Delta > 0$  and  $a \in [0, \ln(d) - \Delta]$  such that  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, a, a+\Delta}) = \Omega(d^{\frac{1}{2\alpha}-o(1)})$ .
- For  $\alpha > 1$ :
  - If  $\alpha$  is integer, then  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, \ln(d)-\Delta, \ln(d)}) = \Omega(d^{\frac{1}{\alpha}-\frac{1}{2\alpha}})$  for  $\Delta \geq \Omega(\frac{1}{\sqrt{d}})$ . Moreover, there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, a, a+\Delta}) = \Omega(\frac{d^{\frac{1}{\alpha}-\frac{1}{2\alpha}} + d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .
  - If  $\alpha$  is non-integer,  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, \ln(d)-\Delta, \ln(d)}) = \Omega(\frac{\sqrt{d}}{\sqrt{\Delta}})$ . Moreover, there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $Q_\diamond^{\text{refl}}(\mathcal{P}_{\alpha, a, a+\Delta}) = \Omega(\frac{\frac{\sqrt{d}}{\sqrt{\Delta}} + d^{\frac{1}{2}-\frac{1}{2\alpha}}}{\sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .

*Proof.* It is shown in [CWZ24] that  $\text{QENTANGLEMENTENTROPY}_{\alpha,a,b}$  can be reduced from  $\text{ENTROPY}_{\alpha,a,b}$ , a promise problem that tests whether the  $\alpha$ -Rényi entropy of a given mixed state is low ( $\leq a$ ) or high ( $\geq b$ ), defined similarly to Problem 2.20. Equivalently, we have  $S(\text{QENTANGLEMENTENTROPY}_{\alpha,a,b}) = S(\text{ENTROPY}_{\alpha,a,b})$ .

Let us consider the sample lower bound for  $S(\text{ENTROPY}_{\alpha,a,b})$  case by case:

- For  $\alpha = 1$ , we have  $S(\text{ENTROPY}_{\alpha, \ln(d) - \Delta, \ln(d)}) = \Omega(\frac{d}{\Delta})$  from the hard instance constructed in [WZ25b, Theorem VI.2]. For the second part, we can use a similar proof to that of Theorem 2.23 to obtain a sample lower bound for the estimating the von Neumann entropy. To achieve a sample lower bound for  $\text{ENTROPY}_{\alpha, a, a + \Delta}$ , we can use the following reduction from entropy estimation to entropy testing via a ternary search on the entropy value: each step we split the interval of possible entropy values into three intervals of equal lengths, and applying any algorithm for entropy testing enables us to shrink the interval length by  $1/3$ . We only need to take  $O(\log(\frac{1}{\Delta}))$  steps to obtain an algorithm for entropy estimation, where in each step we repeat the testing for  $O(\log \log(\frac{1}{\Delta}))$  times to boost the final success probability to be  $\geq 2/3$ . Consequently, the von Neumann entropy can be estimated to within additive error  $\Delta$  with sample complexity  $\sup_{a \in [0, \ln(d) - \Delta]} S(\text{ENTROPY}_{\alpha, a, a + \Delta}) \cdot O(\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta}))$ . Given the sample lower bound  $\Omega(\frac{d}{\varepsilon} + \frac{\log^2(d)}{\varepsilon^2})$  for von Neumann entropy estimation mentioned in Theorem 2.23, we have that there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $S(\text{ENTROPY}_{\alpha, a, a + \Delta}) = \Omega(\frac{\frac{d}{\Delta} + \frac{\log^2(d)}{\Delta^2}}{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .
- For  $0 < \alpha < 1$ , similarly, we have  $S(\text{ENTROPY}_{\alpha, \ln(d) - \Delta, \ln(d)}) = \Omega(\frac{d}{\Delta})$  and  $S(\text{ENTROPY}_{\alpha, 0, \Delta}) = \Omega(\frac{d^{\frac{1}{\alpha} - 1}}{\Delta^{\frac{1}{\alpha}}})$  from [WZ25b, Theorem VI.5]. For the second part, using a similar proof to that of Theorem 2.7 and the previous reduction for the case of  $\alpha = 1$ , there exists a constant  $\Delta > 0$  and  $a \in [0, \ln(d) - \Delta]$  such that  $S(\text{ENTROPY}_{\alpha, a, a + \Delta}) = \Omega(d^{\frac{1}{\alpha} - o(1)})$ .
- For  $\alpha > 1$ :
  - If  $\alpha$  is an integer, then  $S(\text{ENTROPY}_{\alpha, \ln(d) - \Delta, \ln(d)}) = \Omega(\frac{d^{2 - \frac{2}{\alpha}}}{\Delta^{\frac{2}{\alpha}}})$  for  $\Delta \geq \Omega(\frac{1}{\sqrt{d}})$  from the hard instance in [AISW20, Lemma 9]. For the second part, using a similar proof to that of Theorem 2.24 and the previous reduction for the case of  $\alpha = 1$ , there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $S(\text{ENTROPY}_{\alpha, a, a + \Delta}) = \Omega(\frac{\frac{d^{2 - \frac{2}{\alpha}}}{\Delta^{\frac{2}{\alpha}}} + \frac{d^{1 - \frac{1}{\alpha}}}{\Delta^2}}{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .
  - Similarly, if  $\alpha$  is a non-integer, then  $S(\text{ENTROPY}_{\alpha, \ln(d) - \Delta, \ln(d)}) = \Omega(\frac{d}{\Delta})$  from the hard instance in [WZ25b, Theorem VI.4]. For the second part, using a similar proof to that of Theorem 2.24 and the previous reduction for the case of  $\alpha = 1$ , there exists an  $a \in [0, \ln(d) - \Delta]$  such that  $S(\text{ENTROPY}_{\alpha, a, a + \Delta}) = \Omega(\frac{\frac{d}{\Delta} + \frac{d^{1 - \frac{1}{\alpha}}}{\Delta^2}}{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})})$ .

Finally, using Corollary 1.3, the conclusion immediately follows.  $\square$

A quantum algorithm was presented in [Weg25, Proposition 1] with query complexity  $O(\frac{d}{\Delta})$  for the case of  $\alpha = 2$ . For the same case, Theorem 2.34 gives a lower bound of  $\Omega(\frac{1}{\Delta \sqrt{\log(\frac{1}{\Delta}) \log \log(\frac{1}{\Delta})}}) = \tilde{\Omega}(\frac{1}{\Delta})$  in  $\Delta$ , which shows that the quantum algorithm in [Weg25] for the entanglement entropy problem is near-optimal in  $\Delta$ .

## 3 List of Quantum Sample Upper Bounds

### 3.1 Entropy estimation

#### 3.1.1 Von Neumann entropy

The current best quantum sample upper bound for von Neumann entropy estimation is  $O(\frac{d^2}{\varepsilon^2})$  due to [AISW20] and  $O(\frac{d^2}{\varepsilon} + \frac{\log^2(d)}{\varepsilon^2})$  due to [BMW16].

By the quantum sampler, we can obtain a quantum sample upper bound for von Neumann entropy estimation in the low-rank case.

**Theorem 3.1.** *The sample complexity of von Neumann entropy estimation is  $\tilde{O}(\frac{r^2}{\varepsilon^4})$  when the rank of the quantum state is  $r$ .*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $\tilde{O}(\frac{r}{\varepsilon^2})$  for von Neumann entropy estimation given in [WGL<sup>+</sup>24].  $\square$

#### 3.1.2 Rényi entropy

The current best quantum sample upper bound for  $\alpha$ -Rényi entropy estimation is  $O(\frac{d^{\frac{2}{\alpha}}}{\varepsilon^{\frac{2}{\alpha}}})$  for  $0 < \alpha < 1$  and  $O(\frac{d^2}{\varepsilon^2})$  for non-integer  $\alpha > 1$  due to [AISW20].

By the quantum sampler, we can obtain a quantum sample upper bound for  $\alpha$ -Rényi entropy estimation in the low-rank case.

**Theorem 3.2.** *The sample complexity of  $\alpha$ -Rényi entropy estimation is  $\tilde{O}(\frac{r^{\frac{2}{\alpha}}}{\varepsilon^{\frac{2}{\alpha}+2}})$  for  $0 < \alpha < 1$  and  $\tilde{O}(\frac{r^2}{\varepsilon^{2+\frac{2}{\alpha}}})$  for  $\alpha > 1$ , when the rank of the quantum state is  $r$ .*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $\tilde{O}(\frac{r^{\frac{1}{\alpha}}}{\varepsilon^{\frac{1}{\alpha}+1}})$  for  $0 < \alpha < 1$  and  $\tilde{O}(\frac{r}{\varepsilon^{1+\frac{1}{\alpha}}})$  for non-integer  $\alpha > 1$  for  $\alpha$ -Rényi entropy estimation given in [WZL24].  $\square$

### 3.2 Closeness estimation

#### 3.2.1 Trace distance

The current best quantum sample upper bound for trace distance estimation is  $O(\frac{r^2}{\varepsilon^5} \log^2(\frac{r}{\varepsilon}) \log^2(\frac{1}{\varepsilon}))$  due to [WZ24a], where  $r$  is the rank of quantum states. For the pure-state case where  $r = 1$ , an optimal quantum algorithm for trace distance estimation was proposed in [WZ24b] with sample complexity  $\Theta(\frac{1}{\varepsilon^2})$ .

By the quantum sampler, we can obtain an improved quantum sample upper bound.

**Theorem 3.3.** *The sample complexity of trace distance estimation is  $O(\frac{r^2}{\varepsilon^4} \log^2(\frac{1}{\varepsilon}))$ , where  $r$  is the rank of quantum states.*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $O(\frac{r}{\varepsilon^2} \log(\frac{1}{\varepsilon}))$  for trace distance estimation given in [WZ24a].  $\square$

### 3.2.2 Fidelity

The quantum sample upper bound for fidelity estimation is known to be  $\tilde{O}(\frac{r^{5.5}}{\varepsilon^{12}})$  due to [GP22] and  $\tilde{O}(\frac{\kappa^9}{\varepsilon^3})$  due to [LWWZ25], where  $r$  is the rank of quantum states and  $\kappa$  is the “condition number” such that  $\rho, \sigma \geq \frac{I}{\kappa}$ . For the pure-state case where  $r = 1$ , an optimal quantum algorithm for fidelity estimation was proposed in [WZ24b] with sample complexity  $\Theta(\frac{1}{\varepsilon^2})$ .

By the quantum sampler, we can reproduce the quantum sample upper bounds in [UNWT25, Theorem 25].

**Theorem 3.4** ([UNWT25, Theorem 25] reproduced). *The sample complexity of fidelity estimation is  $O(\frac{r^2}{\varepsilon^4} \log^2(\frac{1}{\varepsilon}))$ , where  $r$  is the rank of quantum states.*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $O(\frac{r}{\varepsilon^2} \log(\frac{1}{\varepsilon}))$  for fidelity estimation given in [UNWT25, Theorem 23].  $\square$

**Theorem 3.5** ([UNWT25, Theorem 25] reproduced). *The sample complexity of well-conditioned fidelity estimation is  $O(\frac{\kappa^2}{\varepsilon^2} \log^2(\frac{1}{\varepsilon}))$ .*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $O(\frac{\kappa}{\varepsilon} \log(\frac{1}{\varepsilon}))$  for fidelity estimation given in [UNWT25, Theorem 23].  $\square$

Theorem 3.5 achieves an optimal dependence on  $\varepsilon$  up to polylogarithmic factors, which matches the lower bound  $\Omega(\frac{1}{\varepsilon^2})$  given in [LWWZ25, Lemma 40] when  $\kappa = \Theta(1)$ .

### 3.2.3 Quantum $\ell_\alpha$ distance

**Problem 3.1** (Quantum  $\ell_\alpha$  distance estimation). *Given two unknown quantum states  $\rho$  and  $\sigma$ , estimate the  $\ell_\alpha$  distance*

$$T_\alpha(\rho, \sigma) = \frac{1}{2}(\text{tr}(|\rho - \sigma|^\alpha))^{1/\alpha}$$

*to within additive error  $\varepsilon$ .*

It was noted in [WGL<sup>+</sup>24] that quantum  $\ell_\alpha$  distance can be estimated with sample complexity  $\text{poly}(r, \frac{1}{\varepsilon})$ , where the two unknown quantum states have rank  $r$ . The current best quantum sample upper bound for quantum  $\ell_\alpha$  distance estimation is  $\tilde{O}(\frac{1}{\varepsilon^{3\alpha+2+\frac{2}{\alpha-1}}})$  for constant  $\alpha > 1$  due to [LW25a], removing the previous  $r$ -dependence. Moreover, a lower bound of  $\Omega(\frac{1}{\varepsilon^2})$  was also given in [LW25a].

By the sampler, we can obtain an improved quantum sample upper bound.

**Theorem 3.6.** *For  $\alpha > 1$ , the sample complexity of quantum  $\ell_\alpha$  distance estimation is  $O(\frac{1}{\varepsilon^{2\alpha+2+\frac{2}{\alpha-1}}})$ .*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound  $O(\frac{1}{\varepsilon^{\alpha+1+\frac{1}{\alpha-1}}})$  for quantum  $\ell_\alpha$  distance estimation given in [LW25a, Theorem 14].  $\square$

### 3.2.4 Tsallis relative entropy

The  $\alpha$ -Tsallis relative entropy of a quantum state  $\rho$  with respect to another quantum state  $\sigma$  is defined by

$$D_\alpha^{\text{Tsa}}(\rho \parallel \sigma) = \frac{1}{1-\alpha} (1 - \text{tr}(\rho^\alpha \sigma^{1-\alpha})), \quad 0 < \alpha < 1.$$

In particular, the case of  $\alpha = \frac{1}{2}$  refers to the squared Hellinger distance [LZ04], defined by

$$d_H^2(\rho, \sigma) = \frac{1}{2} D_{\frac{1}{2}}^{\text{Tsa}}(\rho \parallel \sigma) = 1 - \text{tr}(\sqrt{\rho} \sqrt{\sigma}).$$

**Problem 3.2** (Quantum Tsallis relative entropy estimation). *Given two unknown quantum states  $\rho$  and  $\sigma$  of rank  $r$ , estimate the  $D_\alpha^{\text{Tsallis}}(\rho||\sigma)$  to within additive error  $\varepsilon$ .*

The current best quantum sample upper bound for  $\alpha$ -Tsallis relative entropy estimation is given by [BGW25], which is  $O(\frac{r^{2+3\alpha}}{\varepsilon^{\frac{2}{\alpha}+1-\alpha}} \log^2(\frac{r}{\varepsilon}))$  for  $0 < \alpha < \frac{1}{2}$ ,  $O(\frac{r^{5-3\alpha}}{\varepsilon^{\frac{2}{1-\alpha}+\frac{3}{\alpha}}} \log^2(\frac{r}{\varepsilon}))$  for  $\frac{1}{2} < \alpha < 1$ , and  $O(\frac{r^{3.5}}{\varepsilon^{10}} \log^4(\frac{r}{\varepsilon}))$  for  $\alpha = \frac{1}{2}$ .

By the quantum sampler, we can obtain a quantum sample upper bound for quantum  $\alpha$ -Tsallis relative entropy estimation.

**Theorem 3.7.** *The sample complexity of quantum  $\alpha$ -Tsallis relative entropy estimation is  $O(\frac{r^{2+2\alpha}}{\varepsilon^{\frac{2}{\alpha}+1-\alpha}})$  for  $0 < \alpha < \frac{1}{2}$ ,  $O(\frac{r^{4-2\alpha}}{\varepsilon^{\frac{2}{1-\alpha}+\frac{2}{\alpha}}})$  for  $\frac{1}{2} < \alpha < 1$ , and  $O(\frac{r^3}{\varepsilon^8} \log^2(\frac{r}{\varepsilon}))$  for  $\alpha = \frac{1}{2}$ , when the rank of the quantum state is  $r$ .*

*Proof.* To apply Corollary 1.4, we only have to note the quantum query upper bound given by [BGW25], which is  $O(\frac{r^{1+\alpha}}{\varepsilon^{\frac{1}{\alpha}+1-\alpha}})$  for  $0 < \alpha < \frac{1}{2}$ ,  $O(\frac{r^{2-\alpha}}{\varepsilon^{\frac{1}{1-\alpha}+\frac{1}{\alpha}}})$  for  $\frac{1}{2} < \alpha < 1$ , and  $O(\frac{r^{1.5}}{\varepsilon^4} \log(\frac{r}{\varepsilon}))$  for  $\alpha = \frac{1}{2}$ .  $\square$

## 4 Discussion

In this paper, we compile a list of quantum complexity bounds for property testing problems, thus exhibiting the power of quantum sample-to-query lifting. Using this powerful tool, we think that it is also possible to improve the quantum singular value transformation for quantum channels recently proposed by [NRTM25]. In addition, the techniques of [TWZ25] were recently shown to be useful in quantum state tomography [PSTW25].

To conclude this paper, we ask several open questions for future research.

1. Can we prove lower bounds for the small-error case by the lifting method?

In this paper, all quantum query lower bounds assume that the error probability is a small constant, e.g.,  $\leq \frac{1}{3}$ . However, it is not clear how to use the lifting method to derive quantum query lower bounds when the error probability is extremely small. By contrast, the quantum polynomial method [BBC<sup>+</sup>01] has been shown to be useful for the small-error case, e.g., [BCdWZ99, MdW23].

2. Can we prove a matching quantum query lower bound for solving systems of linear equations by the lifting method?

For a (sparse) matrix  $A$  with  $I/\kappa \leq A \leq I$  for some  $\kappa > 0$ , preparing the pure state  $|x\rangle \propto A^{-1}|0\rangle$  is known to require quantum query complexity  $\Omega(\kappa)$  [HHL09, OD21, HK21, WZ24c]. For example, the approach in [OD21] uses the lower bound for computing partial Boolean functions in [NW99], which traces back to the quantum polynomial method [BBC<sup>+</sup>01]. In comparison, a proof using the lifting method will provide an information-theoretic understanding of solving systems of linear equations.

3. Can we show prove a matching sample lower bound of  $\Omega(d^2)$  for von Neumann entropy estimation, trace distance estimation, and fidelity estimation?

The sample complexity of the uniformity testing of probability distributions is known to be  $\Theta(\sqrt{d})$  [Pan08, CDVV14], whereas its closeness estimation counterparts were shown to have

a near-quadratic blowup. For example, the sample complexities of Shannon entropy estimation [VV11, JVHW15, WY16] and total variation distance estimation [VV17] are known to be  $\Theta(\frac{d}{\log(d)})$ . Here, for convenience, we assume the precision parameter  $\varepsilon = \Theta(1)$  is a small enough constant. In the quantum case, the sample complexity of the mixedness testing of quantum states (the quantum counterpart of the uniformity testing of probability distributions) is known to be  $\Theta(d)$  [OW21]. As also suggested in [Wri23], we therefore conjecture that a similar quadratic blowup also appears in the quantum case.

**Conjecture 1.** *The quantum sample complexities of von Neumann entropy estimation, trace distance estimation, and fidelity estimation are  $\Omega(d^2)$ .*

Conjecture 1 means that the current best sample upper bounds for von Neumann entropy estimation [AISW20, BMW16, WZ25b], trace distance estimation [WZ24a], and fidelity estimation [UNWT25] are optimal. Moreover, if Conjecture 1 is true, then by quantum sample-to-query lifting, we can further prove matching query lower bounds for these problems.

**Proposition 4.1.** *If Conjecture 1 is true, then the quantum query complexities of von Neumann entropy estimation, trace distance estimation, and fidelity estimation are  $\Omega(d)$ .*

Notably, Proposition 4.1 means that if Conjecture 1 is true, then the current best query upper bounds for von Neumann entropy estimation [GL20, WGL<sup>+</sup>24], trace distance estimation [WZ24a], and fidelity estimation [UNWT25] are also optimal.

## References

- [AFCB14] Mateus Araújo, Adrien Feix, Fabio Costa, and Časlav Brukner. Quantum circuits cannot control unknown operations. *New Journal of Physics*, 16(9):093026, 2014. [doi:10.1088/1367-2630/16/9/093026](#). 3
- [AISW20] Jayadev Acharya, Ibrahim Issa, Nirmal V. Shende, and Aaron B. Wagner. Estimating quantum entropy. *IEEE Journal on Selected Areas in Information Theory*, 1(2):454–468, 2020. [doi:10.1109/JSAIT.2020.3015235](#). 9, 17, 23, 24, 27
- [ALL22] Anurag Anshu, Zeph Landau, and Yunchao Liu. Distributed quantum inner product estimation. In *Proceedings of the 54th Annual ACM SIGACT Symposium on Theory of Computing*, pages 44–51, 2022. [doi:10.1145/3519935.3519974](#). 18
- [Amb02] Andris Ambainis. Quantum lower bounds by quantum arguments. *Journal of Computer and System Sciences*, 64(4):750–767, 2002. [doi:10.1006/jcss.2002.1826](#). 5
- [AOST17] Jayadev Acharya, Alon Orlitsky, Ananda Theertha Suresh, and Himanshu Tyagi. Estimating Renyi entropy of discrete distributions. *IEEE Transactions on Information Theory*, 63(1):38–56, 2017. [doi:10.1109/TIT.2016.2620435](#). 12, 13
- [ARU14] Andris Ambainis, Ansis Rosmanis, and Dominique Unruh. Quantum attacks on classical proof systems: the hardness of quantum rewinding. In *Proceedings of the 55th IEEE Annual Symposium on Foundations of Computer Science*, pages 474–483, 2014. [doi:10.1109/FOCS.2014.57](#). 3

- [ATS03] Dorit Aharonov and Amnon Ta-Shma. Adiabatic quantum state generation and statistical zero knowledge. In *Proceedings of the 35th Annual ACM Symposium on Theory of Computing*, pages 20–29, 2003. doi:10.1145/780542.780546. 19
- [BACS07] Dominic W. Berry, Graeme Ahokas, Richard Cleve, and Barry C. Sanders. Efficient quantum algorithms for simulating sparse Hamiltonians. *Communications in Mathematical Physics*, 270(2):359–371, 2007. doi:10.1007/s00220-006-0150-x. 6, 8, 19, 20
- [BBC<sup>+</sup>01] Robert Beals, Harry Buhrman, Richard Cleve, Michele Mosca, and Ronald de Wolf. Quantum lower bounds by polynomials. *Journal of the ACM*, 48(4):778–797, 2001. doi:10.1145/502090.502097. 5, 18, 19, 26
- [BBH<sup>+</sup>18] Aleksandrs Belovs, Gilles Brassard, Peter Høyer, Marc Kaplan, Sophie Laplante, and Louis Salvail. Provably secure key establishment against quantum adversaries. In *Proceedings of the 12th Conference on the Theory of Quantum Computation, Communication and Cryptography*, pages 3:1–3:17, 2018. doi:10.4230/LIPIcs.TQC.2017.3. 10
- [BCC<sup>+</sup>14] Dominic W. Berry, Andrew M. Childs, Richard Cleve, Robin Kothari, and Rolando D. Somma. Exponential improvement in precision for simulating sparse Hamiltonians. In *Proceedings of the 46th Annual ACM Symposium on Theory of Computing*, pages 283–292, 2014. doi:10.1145/2591796.2591854. 19
- [BCC<sup>+</sup>15] Dominic W. Berry, Andrew M. Childs, Richard Cleve, Robin Kothari, and Rolando D. Somma. Simulating Hamiltonian dynamics with a truncated Taylor series. *Physical Review Letters*, 114(9):090502, 2015. doi:10.1103/PhysRevLett.114.090502. 19
- [BCdWZ99] Harry Buhrman, Richard Cleve, Ronald de Wolf, and Christof Zalka. Bounds for small-error and zero-error quantum algorithms. In *Proceedings of the 40th Annual Symposium on Foundations of Computer Science*, pages 358–368, 1999. doi:10.1109/SFFCS.1999.814607. 26
- [BCH06] Dave Bacon, Isaac L. Chuang, and Aram W. Harrow. Efficient quantum circuits for Schur and Clebsch-Gordan transforms. *Physical Review Letters*, 97(17):170502, 2006. doi:10.1103/PhysRevLett.97.170502. 4
- [BCH07] Dave Bacon, Isaac L. Chuang, and Aram W. Harrow. The quantum Schur and Clebsch-Gordan transforms: I. efficient qudit circuits. In *Proceedings of the 18th Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1235–1244, 2007. 4
- [BCK15] Dominic W. Berry, Andrew M. Childs, and Robin Kothari. Hamiltonian simulation with nearly optimal dependence on all parameters. In *Proceedings of the 56th IEEE Annual Symposium on Foundations of Computer Science*, pages 792–809, 2015. doi:10.1109/FOCS.2015.54. 19
- [Bel19] Aleksandrs Belovs. Quantum algorithms for classical probability distributions. In *Proceedings of the 27th Annual European Symposium on Algorithms*, pages 16:1–16:11, 2019. doi:10.4230/LIPIcs.ESA.2019.16. 5, 6, 9, 10, 11

- [BFG<sup>+</sup>25] Adam Burchardt, Jiani Fei, Dmitry Grinko, Martin Larocca, Maris Ozols, Sydney Timmerman, and Vladyslav Visnevskiy. High-dimensional quantum Schur transforms. ArXiv preprints, 2025. [arXiv:2509.22640](#). 4
- [BGW25] Jinge Bao, Minbo Gao, and Qisheng Wang. On estimating the quantum Tsallis relative entropy. ArXiv preprints, 2025. [arXiv:2510.00752](#). 9, 26
- [BHH11] Sergey Bravyi, Aram W. Harrow, and Avinatan Hassidim. Quantum algorithms for testing properties of distributions. *IEEE Transactions on Information Theory*, 57(6):3971–3981, 2011. [doi:10.1109/TIT.2011.2134250](#). 8, 10, 11
- [BHMT02] Gilles Brassard, Peter Høyer, Michele Mosca, and Alain Tapp. Quantum amplitude amplification and estimation. In Samuel J. Lomonaco, Jr. and Howard E. Brandt, editors, *Quantum Computation and Information*, volume 305 of *Contemporary Mathematics*, pages 53–74. AMS, 2002. [doi:10.1090/comm/305/05215](#). 19
- [BK19] Fernando G. S. L. Brandão and Michael J. Kastoryano. Finite correlation length implies efficient preparation of quantum thermal states. *Communications in Mathematical Physics*, 365:1–16, 2019. [doi:10.1007/s00220-018-3150-8](#). 20
- [BKL<sup>+</sup>19] Fernando G. S. L. Brandão, Amir Kalev, Tongyang Li, Cedric Yen-Yu Lin, Krysta M. Svore, and Xiaodi Wu. Quantum SDP solvers: large speed-ups, optimality, and applications to quantum learning. In *Proceedings of the 46th International Colloquium on Automata, Languages, and Programming*, pages 27:1–27:14, 2019. [doi:10.4230/LIPIcs.ICALP.2019.27](#). 20
- [BKT20] Mark Bun, Robin Kothari, and Justin Thaler. The polynomial method strikes back: tight quantum query bounds via dual polynomials. *Theory of Computing*, 16(10):1–71, 2020. [doi:10.4086/toc.2020.v016a010](#). 5, 6, 7, 11, 13, 16, 17
- [BMW16] Mohammad Bavarian, Saeed Mehraban, and John Wright. Learning entropy. A manuscript on von Neumann entropy estimation, private communication, 2016. 9, 24, 27
- [BOW19] Costin Bădescu, Ryan O’Donnell, and John Wright. Quantum state certification. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 503–514, 2019. [doi:10.1145/3313276.3316344](#). 14
- [BS17] Fernando G. S. L. Brandão and Krysta M. Svore. Quantum speed-ups for solving semidefinite programs. In *Proceedings of the 58th IEEE Annual Symposium on Foundations of Computer Science*, pages 415–426, 2017. [doi:10.1109/FOCS.2017.45](#). 20
- [BY02] Ziv Bar-Yossef. *The Complexity of Massive Data Set Computations*. Phd thesis, University of California, Berkeley, 2002. URL: <https://www.proquest.com/docview/304791145>. 10
- [BYKS01] Ziv Bar-Yossef, Ravi Kumar, and D. Sivakumar. Sampling algorithms: lower bounds and applications. In *Proceedings of the 33rd Annual ACM Symposium on Theory of Computing*, pages 266–275, 2001. [doi:10.1145/380752.380810](#). 10

- [CDVV14] Siu-On Chan, Ilias Diakonikolas, Gregory Valiant, and Paul Valiant. Optimal algorithms for testing closeness of discrete distributions. In *Proceedings of the 25th Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1193–1203, 2014. doi:[10.1137/1.9781611973402.88](https://doi.org/10.1137/1.9781611973402.88). 10, 11, 26
- [CFMdW10] Sourav Chakraborty, Eldar Fischer, Arie Matsliah, and Ronald de Wolf. New results on quantum property testing. In *Proceedings of the 30th IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science*, pages 145–156, 2010. doi:[10.4230/LIPIcs.FSTTCS.2010.145](https://doi.org/10.4230/LIPIcs.FSTTCS.2010.145). 5, 6, 7, 10, 18
- [CHW07] Andrew M. Childs, Aram W. Harrow, and Paweł Wocjan. Weak Fourier-Schur sampling, the hidden subgroup problem, and the quantum collision problem. In *Proceedings of the 24th Annual Symposium on Theoretical Aspects of Computer Science*, pages 598–609, 2007. doi:[10.1007/978-3-540-70918-3\\_51](https://doi.org/10.1007/978-3-540-70918-3_51). 15
- [CK10] Andrew M. Childs and Robin Kothari. Limitations on the simulation of non-sparse Hamiltonians. *Quantum Information and Computation*, 10(7):669–684, 2010. doi:[10.26421/QIC10.7-8-7](https://doi.org/10.26421/QIC10.7-8-7). 19
- [CKBG23] Chi-Fang Chen, Michael J. Kastoryano, Fernando G. S. L. Brandão, and András Gilyén. Quantum thermal state preparation. ArXiv preprints, 2023. arXiv:[2303.18224](https://arxiv.org/abs/2303.18224). 6, 8, 20
- [CKBG25] Chi-Fang Chen, Michael Kastoryano, Fernando G. S. L. Brandão, and András Gilyén. Efficient quantum thermal simulation. *Nature*, 646(8085):561–566, 2025. doi:[10.1038/s41586-025-09583-x](https://doi.org/10.1038/s41586-025-09583-x). 20
- [CKG23] Chi-Fang Chen, Michael J. Kastoryano, and András Gilyén. An efficient and exact noncommutative quantum Gibbs sampler. ArXiv preprints, 2023. arXiv:[2311.09207](https://arxiv.org/abs/2311.09207). 20
- [CKO25] Clément L. Canonne, Robin Kothari, and Ryan O’Donnell. Uniformity testing when you have the source code. In *Proceedings of the 20th Conference on the Theory of Quantum Computation, Communication and Cryptography*, pages 7:1–7:20, 2025. doi:[10.4230/LIPIcs.TQC.2025.7](https://doi.org/10.4230/LIPIcs.TQC.2025.7). 10, 11
- [CML<sup>+</sup>24] Yu-Ao Chen, Yin Mo, Yingjian Liu, Lei Zhang, and Xin Wang. Quantum algorithm for reversing unknown unitary evolutions. ArXiv preprints, 2024. arXiv:[2403.04704](https://arxiv.org/abs/2403.04704). 3
- [CS17] Anirban Narayan Chowdhury and Rolando D. Somma. Quantum algorithms for Gibbs sampling and hitting-time estimation. *Quantum Information and Computation*, 17(1–2):41–64, 2017. doi:[10.26421/QIC17.1-2-3](https://doi.org/10.26421/QIC17.1-2-3). 20, 21
- [CSM23] Jordan Cotler, Thomas Schuster, and Masoud Mohseni. Information-theoretic hardness of out-of-time-order correlators. *Physical Review A*, 108(6):062608, 2023. doi:[10.1103/PhysRevA.108.062608](https://doi.org/10.1103/PhysRevA.108.062608). 3
- [CW12] Andrew M. Childs and Nathan Wiebe. Hamiltonian simulation using linear combinations of unitary operations. *Quantum Information and Computation*, 12(11–12):901–924, 2012. doi:[10.26421/QIC12.11-12-1](https://doi.org/10.26421/QIC12.11-12-1). 19

- [CW25] Kean Chen and Qisheng Wang. Improved sample upper and lower bounds for trace estimation of quantum state powers. In *Proceedings of the 38th Annual Conference on Learning Theory*, pages 1008–1028, 2025. URL: <https://proceedings.mlr.press/v291/chen25d.html>. 17
- [CWYZ25] Kean Chen, Qisheng Wang, Zhan Yu, and Zhicheng Zhang. Simultaneous estimation of nonlinear functionals of a quantum state. ArXiv preprints, 2025. [arXiv:2505.16715](#). 13
- [CWZ24] Kean Chen, Qisheng Wang, and Zhicheng Zhang. Local test for unitarily invariant properties of bipartite quantum states. ArXiv preprints, 2024. [arXiv:2404.04599](#). 3, 4, 6, 8, 15, 22
- [CYZ25] Kean Chen, Nengkun Yu, and Zhicheng Zhang. Tight bound for quantum unitary time-reversal. ArXiv preprints, 2025. [arXiv:2507.05736](#). 3
- [DLL25] Zhiyan Ding, Bowen Li, and Lin Lin. Efficient quantum Gibbs samplers with Kubo–Martin–Schwinger detailed balance condition. *Communications in Mathematical Physics*, 406(3), 2025. [doi:10.1007/s00220-025-05235-3](#). 20
- [Fey82] Richard P. Feynman. Simulating physics with computers. *International Journal of Theoretical Physics*, 21(6):467–488, 1982. [doi:10.1007/BF02650179](#). 19
- [FGGS98] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, and Michael Sipser. Limit on the speed of quantum computation in determining parity. *Physical Review Letters*, 81(24):5442, 1998. [doi:10.1103/PhysRevLett.81.5442](#). 19
- [FK18] Bill Fefferman and Shelby Kimmel. Quantum vs. classical proofs and subset verification. In *Proceedings of the 43rd International Symposium on Mathematical Foundations of Computer Science*, pages 22:1–22:23, 2018. [doi:10.4230/LIPIcs.MFCS.2018.22](#). 3
- [FW25] Wang Fang and Qisheng Wang. Optimal quantum algorithm for estimating fidelity to a pure state. In *Proceedings of the 32nd Annual European Symposium on Algorithms*, pages 4:1–4:12, 2025. [doi:10.4230/LIPIcs.ESA.2025.4](#). 18
- [GBO23] Dmitry Grinko, Adam Burchardt, and Maris Ozols. Gelfand-Tsetlin basis for partially transposed permutations, with applications to quantum information. ArXiv preprints, 2023. [arXiv:2310.02252](#). 4
- [GKP<sup>+</sup>25] Byeongseon Go, Hyukjoon Kwon, Siheon Park, Dhruvil Patel, and Mark M. Wilde. Sample-based Hamiltonian and Lindbladian simulation: Non-asymptotic analysis of sample complexity. *Quantum Science and Technology*, 2025. [doi:10.1088/2058-9565/ae075b](#). 3
- [GL20] András Gilyén and Tongyang Li. Distributional property testing in a quantum world. In *Proceedings of the 11th Innovations in Theoretical Computer Science Conference*, pages 25:1–25:19, 2020. [doi:10.4230/LIPIcs.ITCS.2020.25](#). 3, 9, 10, 11, 16, 27
- [GP22] András Gilyén and Alexander Poremba. Improved quantum algorithms for fidelity estimation. ArXiv preprints, 2022. [arXiv:2203.15993](#). 3, 9, 18, 25

- [GSLW19] András Gilyén, Yuan Su, Guang Hao Low, and Nathan Wiebe. Quantum singular value transformation and beyond: exponential improvements for quantum matrix arithmetics. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 193–204, 2019. doi:[10.1145/3313276.3316366](https://doi.org/10.1145/3313276.3316366). 3, 4, 20
- [GST24] Zuzana Gavorová, Matan Seidel, and Yonathan Touati. Topological obstructions to quantum computation with unitary oracles. *Physical Review A*, 109(3):032625, 2024. doi:[10.1103/PhysRevA.109.032625](https://doi.org/10.1103/PhysRevA.109.032625). 3
- [GZ25] Eli Goldin and Mark Zhandry. Translating between the common Haar random state model and the unitary model. In *Proceedings of the 45th Annual International Cryptology Conference*, pages 269–300, 2025. doi:[10.1007/978-3-032-01878-6\\_9](https://doi.org/10.1007/978-3-032-01878-6_9). 3
- [Har05] Aram W. Harrow. *Applications of Coherent Classical Communication and the Schur Transform to Quantum Information Theory*. Phd thesis, Massachusetts Institute of Technology, 2005. URL: <http://hdl.handle.net/1721.1/34973>. 4
- [Hel69] Carl W. Helstrom. Quantum detection and estimation theory. *Journal of Statistical Physics*, 1(2):231–252, 1969. doi:[10.1007/BF01007479](https://doi.org/10.1007/BF01007479). 18
- [HHL09] Aram W. Harrow, Avinatan Hassidim, and Seth Lloyd. Quantum algorithm for linear systems of equations. *Physical Review Letters*, 103(15):150502, 2009. doi:[10.1103/PhysRevLett.103.150502](https://doi.org/10.1103/PhysRevLett.103.150502). 26
- [HK21] Aram W. Harrow and Robin Kothari. In preparation, 2021. 26
- [HL11] Aram W. Harrow and Debbie W. Leung. A communication-efficient nonlocal measurement with application to communication complexity and bipartite gate capacities. *IEEE Transactions on Information Theory*, 57(8):5504–5508, 2011. doi:[10.1109/TIT.2011.2158468](https://doi.org/10.1109/TIT.2011.2158468). 3
- [HLS07] Peter Høyer, Troy Lee, and Robert Špalek. Negative weights make adversaries stronger. In *Proceedings of the 39th Annual ACM Symposium on Theory of Computing*, pages 526–535, 2007. doi:[10.1145/1250790.1250867](https://doi.org/10.1145/1250790.1250867). 10
- [Hol73] Alexander S. Holevo. Statistical decision theory for quantum systems. *Journal of Multivariate Analysis*, 3(4):337–394, 1973. doi:[10.1016/0047-259X\(73\)90028-6](https://doi.org/10.1016/0047-259X(73)90028-6). 18
- [HSDS25] Dominik Hahn, Ryan Sweke, Abhinav Deshpande, and Oles Shtanko. Efficient quantum Gibbs sampling with local circuits. ArXiv preprints, 2025. arXiv:[2506.04321](https://arxiv.org/abs/2506.04321). 20
- [JHW18] Jiantao Jiao, Yanjun Han, and Tsachy Weissman. Minimax estimation of the  $l_1$  distance. *IEEE Transactions on Information Theory*, 64(10):6672–6706, 2018. doi:[10.1109/TIT.2018.2846245](https://doi.org/10.1109/TIT.2018.2846245). 11
- [JLS18] Zhengfeng Ji, Yi-Kai Liu, and Fang Song. Pseudorandom quantum states. In *Proceedings of the 38th Annual International Cryptology Conference*, pages 126–152, 2018. doi:[10.1007/978-3-319-96878-0\\_5](https://doi.org/10.1007/978-3-319-96878-0_5). 3

- [JVHW15] Jiantao Jiao, Kartik Venkat, Yanjun Han, and Tsachy Weissman. Minimax estimation of functionals of discrete distributions. *IEEE Transactions on Information Theory*, 61(5):2835–2885, 2015. doi:10.1109/TIT.2015.2412945. 12, 16, 27
- [KB16] Michael J. Kastoryano and Fernando G. S. L. Brandão. Quantum Gibbs samplers: the commuting case. *Communications in Mathematical Physics*, 344:915–957, 2016. doi:10.1007/s00220-016-2641-8. 20
- [KLL<sup>+</sup>17] Shelby Kimmel, Cedric Yen-Yu Lin, Guang Hao Low, Maris Ozols, and Theodore J. Yoder. Hamiltonian simulation with optimal sample complexity. *npj Quantum Information*, 3(1):1–7, 2017. doi:10.1038/s41534-017-0013-7. 3
- [Kro19] Hari Krovi. An efficient high dimensional quantum Schur transform. *Quantum*, 3:122, 2019. doi:10.22331/q-2019-02-14-122. 4
- [KS18] William M. Kirby and Frederick W. Strauch. A practical quantum algorithm for the Schur transform. *Quantum Information and Computation*, 18(9–10):721–742, 2018. doi:10.26421/QIC18.9-10-1. 4
- [LC17] Guang Hao Low and Isaac L. Chuang. Optimal Hamiltonian simulation by quantum signal processing. *Physical Review Letters*, 118(1):010501, 2017. doi:10.1103/PhysRevLett.118.010501. 19
- [LC19] Guang Hao Low and Isaac L. Chuang. Hamiltonian simulation by qubitization. *Quantum*, 3:163, 2019. doi:10.22331/q-2019-07-12-163. 4, 19
- [LDCL25] Zhenhuan Liu, Zhenyu Du, Zhenyu Cai, and Zi-Wen Liu. No universal purification in quantum mechanics. ArXiv preprints, 2025. arXiv:2509.21111. 3
- [Llo96] Seth Lloyd. Universal quantum simulators. *Science*, 273(5278):1073–1078, 1996. doi:10.1126/science.273.5278.1073. 19
- [LMR14] Seth Lloyd, Masoud Mohseni, and Patrick Rebentrost. Quantum principal component analysis. *Nature Physics*, 10(9):631–633, 2014. doi:10.1038/nphys3029. 3
- [LW19] Tongyang Li and Xiaodi Wu. Quantum query complexity of entropy estimation. *IEEE Transactions on Information Theory*, 65(5):2899–2921, 2019. doi:10.1109/TIT.2018.2883306. 6, 7, 11, 12, 13
- [LW25a] Yupan Liu and Qisheng Wang. On estimating the quantum  $\ell_\alpha$  distance. In *Proceedings of the 33rd Annual European Symposium on Algorithms*, pages 106:1–106:19, 2025. doi:10.4230/LIPIcs.ESA.2025.106. 9, 25
- [LW25b] Yupan Liu and Qisheng Wang. On estimating the trace of quantum state powers. In *Proceedings of the 2025 Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 947–993, 2025. doi:10.1137/1.9781611978322.28. 7, 17
- [LWL24] Jingquan Luo, Qisheng Wang, and Lvzhou Li. Succinct quantum testers for closeness and  $k$ -wise uniformity of probability distributions. *IEEE Transactions on Information Theory*, 70(7):5092–5103, 2024. doi:10.1109/TIT.2024.3393756. 5, 6, 10, 11, 13, 14

- [LWWZ25] Nana Liu, Qisheng Wang, Mark M. Wilde, and Zhicheng Zhang. Quantum algorithms for matrix geometric means. *npj Quantum Information*, 11:101, 2025. doi:10.1038/s41534-025-00973-7. 7, 8, 9, 18, 25
- [LZ04] Shunlong Luo and Qiang Zhang. Informational distance on quantum-state space. *Physical Review A*, 69(3):032106, 2004. doi:10.1103/PhysRevA.69.032106. 25
- [MdW16] Ashley Montanaro and Ronald de Wolf. A survey of quantum property testing. In *Theory of Computing Library*, number 7 in Graduate Surveys, pages 1–81. University of Chicago, 2016. doi:10.4086/toc.gs.2016.007. 3
- [MdW23] Nikhil S. Mande and Ronald de Wolf. Tight bounds for quantum phase estimation and related problems. In *Proceedings of the 31st Annual European Symposium on Algorithms*, pages 81:1–81:16, 2023. doi:10.4230/LIPIcs.ESA.2023.81. 26
- [Mon15] Ashley Montanaro. Quantum speedup of Monte Carlo methods. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 471(2181):20150301, 2015. doi:10.1098/rspa.2015.0301. 11
- [NC10] Michael A Nielsen and Isaac L Chuang. *Quantum computation and quantum information*. Cambridge university press, 2010. 18
- [Ngu23] Quynh T. Nguyen. The mixed Schur transform: efficient quantum circuit and applications. ArXiv preprints, 2023. arXiv:2310.01613. 4
- [NRTM25] Ryotaro Niwa, Zane Marius Rossi, Philip Taranto, and Mio Murao. Singular value transformation for unknown quantum channels. ArXiv preprints, 2025. arXiv:2506.24112. 26
- [NW99] Ashwin Nayak and Felix Wu. The quantum query complexity of approximating the median and related statistics. In *Proceedings of the 31st Annual ACM Symposium on Theory of Computing*, pages 384–393, 1999. doi:10.1145/301250.301349. 6, 8, 18, 19, 26
- [OD21] Davide Orsucci and Vedran Dunjko. On solving classes of positive-definite quantum linear systems with quadratically improved runtime in the condition number. *Quantum*, 5:573, 2021. doi:10.22331/q-2021-11-08-573. 26
- [OW21] Ryan O’Donnell and John Wright. Quantum spectrum testing. *Communications in Mathematical Physics*, 387(1):1–75, 2021. doi:10.1007/s00220-021-04180-1. 14, 15, 17, 18, 27
- [OYM24] Tatsuki Odake, Satoshi Yoshida, and Mio Murao. Analytical lower bound on query complexity for transformations of unknown unitary operations. ArXiv preprints, 2024. arXiv:2405.07625. 3
- [OZ18] Ryan O’Donnell and Yu Zhao. On closeness to  $k$ -wise uniformity. In *Proceedings of Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques (APPROX/RANDOM 2018)*, pages 54:1–54:19, 2018. doi:10.4230/LIPIcs.APPROX-RANDOM.2018.54. 14

- [Pan08] Liam Paninski. A coincidence-based test for uniformity given very sparsely sampled discrete data. *IEEE Transactions on Information Theory*, 54(10):4750–4755, 2008. doi:10.1109/TIT.2008.928987. 11, 26
- [PSTW25] Angelos Pelecanos, Jack Spilecki, Ewin Tang, and John Wright. Mixed state tomography reduces to pure state tomography. ArXiv preprints, 2025. arXiv:2511.15806. 26
- [PW09] David Poulin and Pawel Wocjan. Sampling from the thermal quantum Gibbs state and evaluating partition functions with a quantum computer. *Physical Review Letters*, 103(22):220502, 2009. doi:10.1103/PhysRevLett.103.220502. 20
- [QDS<sup>+</sup>19a] Marco Túlio Quintino, Qingxiuxiong Dong, Atsushi Shimbo, Akihito Soeda, and Mio Murao. Probabilistic exact universal quantum circuits for transforming unitary operations. *Physical Review A*, 100(6):062339, 2019. doi:10.1103/PhysRevA.100.062339. 3
- [QDS<sup>+</sup>19b] Marco Túlio Quintino, Qingxiuxiong Dong, Atsushi Shimbo, Akihito Soeda, and Mio Murao. Reversing unknown quantum transformations: Universal quantum circuit for inverting general unitary operations. *Physical Review Letters*, 123(21):210502, 2019. doi:10.1103/PhysRevLett.123.210502. 3
- [Qia24] Luowen Qian. Unconditionally secure quantum commitments with preprocessing. In *Proceedings of the 44th Annual International Cryptology Conference*, pages 38–58, 2024. doi:10.1007/978-3-031-68394-7\_2. 3
- [RFA24] Cambyse Rouzé, Daniel Stilck França, and Álvaro M. Alhambra. Optimal quantum algorithm for Gibbs state preparation. ArXiv preprints, 2024. arXiv:2411.04885. 20
- [RS25] Akshar Ramkumar and Mehdi Soleimanifar. Mixing time of quantum Gibbs sampling for random sparse Hamiltonians. In *Proceedings of the 20th Conference on the Theory of Quantum Computation, Communication and Cryptography*, pages 3:1–3:23, 2025. doi:10.4230/LIPIcs.TQC.2025.3. 20
- [SH21] Sathyawageeswar Subramanian and Min-Hsiu Hsieh. Quantum algorithm for estimating  $\alpha$ -renyi entropies of quantum states. *Physical Review A*, 104(2):022428, 2021. doi:10.1103/PhysRevA.104.022428. 16
- [SHH25] Thomas Schuster, Jonas Haferkamp, and Hsin-Yuan Huang. Random unitaries in extremely low depth. *Science*, 389(6755):92–96, 2025. doi:10.1126/science.adv8590. 3
- [SJ25] Myeongjin Shin and Kabgyun Jeong. Near optimal quantum algorithm for estimating Shannon entropy. ArXiv preprints, 2025. arXiv:2509.07452. 11, 12
- [SW22] Mehdi Soleimanifar and John Wright. Testing matrix product states. In *Proceedings of the 2022 Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1679–1701, 2022. doi:10.1137/1.9781611977073.68. 3
- [SY23] Adrian She and Henry Yuen. Unitary property testing lower bounds by polynomials. In *Proceedings of the 14th Innovations in Theoretical Computer Science Conference*, pages 96:1–96:17, 2023. doi:10.4230/LIPIcs.ITCS.2023.96. 6, 21, 22

- [TOV<sup>+</sup>11] K. Temme, T. J. Osborne, K. G. Vollbrecht, D. Poulin, and F. Verstraete. Quantum Metropolis sampling. *Nature*, 471(7336):87–90, 2011. doi:[10.1038/nature09770](https://doi.org/10.1038/nature09770). 20
- [TW25] Ewin Tang and John Wright. Amplitude amplification and estimation require inverses. ArXiv preprints, 2025. arXiv:[2507.23787](https://arxiv.org/abs/2507.23787). 19
- [TWZ25] Ewin Tang, John Wright, and Mark Zhandry. Conjugate queries can help. ArXiv preprints, 2025. arXiv:[2510.07622](https://arxiv.org/abs/2510.07622). 3, 4, 26
- [UNWT25] Takeru Utsumi, Yoshifumi Nakata, Qisheng Wang, and Ryuji Takagi. Quantum algorithms for Uhlmann transformation. ArXiv preprints, 2025. arXiv:[2509.03619](https://arxiv.org/abs/2509.03619). 5, 7, 9, 18, 25, 27
- [vAG19] Joran van Apeldoorn and András Gilyén. Improvements in quantum SDP-solving with applications. In *Proceedings of the 46th International Colloquium on Automata, Languages, and Programming*, pages 99:1–99:15, 2019. doi:[10.4230/LIPIcs.ICALP.2019.99](https://doi.org/10.4230/LIPIcs.ICALP.2019.99). 20
- [vAGGdW20] Joran van Apeldoorn, András Gilyén, Sander Gribling, and Ronald de Wolf. Quantum SDP-solvers: better upper and lower bounds. *Quantum*, 4:230, 2020. doi:[10.22331/q-2020-02-14-230](https://doi.org/10.22331/q-2020-02-14-230). 20
- [VV11] Gregory Valiant and Paul Valiant. Estimating the unseen: an  $n/\log(n)$ -sample estimator for entropy and support size, shown optimal via new CLTs. In *Proceedings of the 43rd Annual ACM Symposium on Theory of Computing*, pages 685–694, 2011. doi:[10.1145/1993636.1993727](https://doi.org/10.1145/1993636.1993727). 27
- [VV17] Gregory Valiant and Paul Valiant. Estimating the unseen: improved estimators for entropy and other properties. *Journal of the ACM*, 64(6):37:1–37:41, 2017. doi:[10.1145/3125643](https://doi.org/10.1145/3125643). 27
- [Wan24] Qisheng Wang. Optimal trace distance and fidelity estimations for pure quantum states. *IEEE Transactions on Information Theory*, 70(12):8791–8805, 2024. doi:[10.1109/TIT.2024.3447915](https://doi.org/10.1109/TIT.2024.3447915). 5, 7, 17, 18, 19
- [Wan25] Qisheng Wang. Information-theoretic lower bounds for approximating monomials via optimal quantum Tsallis entropy estimation. ArXiv preprint, 2025. arXiv:[2509.03496](https://arxiv.org/abs/2509.03496). 6, 13
- [Wat02] John Watrous. Limits on the power of quantum statistical zero-knowledge. In *Proceedings of the 43rd Annual IEEE Symposium on Foundations of Computer Science*, pages 459–468, 2002. doi:[10.1109/SFCS.2002.1181970](https://doi.org/10.1109/SFCS.2002.1181970). 3
- [Weg25] Jordi Weggemans. Lower bounds for unitary property testing with proofs and advice. *Quantum*, 9:1717, 2025. doi:[10.22331/q-2025-04-18-1717](https://doi.org/10.22331/q-2025-04-18-1717). 6, 8, 20, 22, 23
- [WGL<sup>+</sup>24] Qisheng Wang, Ji Guan, Junyi Liu, Zhicheng Zhang, and Mingsheng Ying. New quantum algorithms for computing quantum entropies and distances. *IEEE Transactions on Information Theory*, 70(8):5653–5680, 2024. doi:[10.1109/TIT.2024.3399014](https://doi.org/10.1109/TIT.2024.3399014). 16, 17, 18, 24, 25, 27
- [Wri23] John Wright. Private communication, 2023. 27

- [WY16] Yihong Wu and Pengkun Yang. Minimax rates of entropy estimation on large alphabets via best polynomial approximation. *IEEE Transactions on Information Theory*, 62(6):3702–3720, 2016. doi:[10.1109/TIT.2016.2548468](https://doi.org/10.1109/TIT.2016.2548468). 12, 16, 27
- [WY19] Yihong Wu and Pengkun Yang. Chebyshev polynomials, moment matching, and optimal estimation of the unseen. *Annals of Statistics*, 47(2):857–883, 2019. doi:[10.1214/17-AOS1665](https://doi.org/10.1214/17-AOS1665). 13
- [WZ24a] Qisheng Wang and Zhicheng Zhang. Fast quantum algorithms for trace distance estimation. *IEEE Transactions on Information Theory*, 70(4):2720–2733, 2024. doi:[10.1109/TIT.2023.3321121](https://doi.org/10.1109/TIT.2023.3321121). 3, 9, 17, 24, 27
- [WZ24b] Qisheng Wang and Zhicheng Zhang. Sample-optimal quantum estimators for pure-state trace distance and fidelity via sampler. ArXiv preprints, 2024. arXiv:[2410.21201](https://arxiv.org/abs/2410.21201). 24, 25
- [WZ24c] Qisheng Wang and Zhicheng Zhang. Tight quantum depth lower bound for solving systems of linear equations. *Physical Review A*, 110(1):012422, 2024. doi:[10.1103/PhysRevA.110.012422](https://doi.org/10.1103/PhysRevA.110.012422). 26
- [WZ25a] Qisheng Wang and Zhicheng Zhang. Quantum lower bounds by sample-to-query lifting. *SIAM Journal on Computing*, 54(5):1294–1334, 2025. doi:[10.1137/24M1638616](https://doi.org/10.1137/24M1638616). 3, 4, 6, 7, 8, 14, 15, 18, 19, 20, 21, 22
- [WZ25b] Qisheng Wang and Zhicheng Zhang. Time-efficient quantum entropy estimator via sampler. *IEEE Transactions on Information Theory*, 71(12):9569–9599, 2025. doi:[10.1109/TIT.2025.3576137](https://doi.org/10.1109/TIT.2025.3576137). 3, 4, 16, 23, 27
- [WZC<sup>+</sup>23] Qisheng Wang, Zhicheng Zhang, Kean Chen, Ji Guan, Wang Fang, Junyi Liu, and Mingsheng Ying. Quantum algorithm for fidelity estimation. *IEEE Transactions on Information Theory*, 69(1):273–282, 2023. doi:[10.1109/TIT.2022.3203985](https://doi.org/10.1109/TIT.2022.3203985). 18
- [WZL24] Xinzhao Wang, Shengyu Zhang, and Tongyang Li. A quantum algorithm framework for discrete probability distributions with applications to Rényi entropy estimation. *IEEE Transactions on Information Theory*, 70(5):3399–3426, 2024. doi:[10.1109/TIT.2024.3382037](https://doi.org/10.1109/TIT.2024.3382037). 5, 6, 7, 12, 16, 24
- [WZW23] Youle Wang, Benchu Zhao, and Xin Wang. Quantum algorithms for estimating quantum entropies. *Physical Review Applied*, 19(4):044041, 2023. doi:[10.1103/PhysRevApplied.19.044041](https://doi.org/10.1103/PhysRevApplied.19.044041). 16
- [WZYW23] Youle Wang, Lei Zhang, Zhan Yu, and Xin Wang. Quantum phase processing and its applications in estimating phase and entropies. *Physical Review A*, 108(6):062413, 2023. doi:[10.1103/PhysRevA.108.062413](https://doi.org/10.1103/PhysRevA.108.062413). 16
- [YAG12] Man-Hong Yung and Alán Aspuru-Guzik. A quantum-quantum Metropolis algorithm. *Proceedings of the National Academy of Sciences*, 109(3):754–759, 2012. doi:[10.1073/pnas.1111758109](https://doi.org/10.1073/pnas.1111758109). 20
- [YKS<sup>+</sup>24] Satoshi Yoshida, Yuki Koizumi, Michał Studziński, Marco Túlio Quintino, and Mio Murao. One-to-one correspondence between deterministic port-based teleportation and unitary estimation. ArXiv preprints, 2024. arXiv:[2408.11902](https://arxiv.org/abs/2408.11902). 3

- [ZBC23] Daniel Zhang, Jan Lukas Bosse, and Toby Cubitt. Dissipative quantum Gibbs sampling. ArXiv preprints, 2023. [arXiv:2304.04526](#). 20
- [Zha19] Mark Zhandry. How to record quantum queries, and applications to quantum indistinguishability. In *Proceedings of the 39th Annual International Cryptology Conference*, pages 239–268, 2019. [doi:10.1007/978-3-030-26951-7\\_9](#). 5
- [ZWY24] Zhicheng Zhang, Qisheng Wang, and Mingsheng Ying. Parallel quantum algorithm for Hamiltonian simulation. *Quantum*, 8:1228, 2024. [doi:10.22331/q-2024-01-15-1228](#). 19