

# UniLight: A Unified Representation for Lighting

Zitian Zhang<sup>1,2</sup> Iliyan Georgiev<sup>2</sup> Michael Fischer<sup>2</sup>  
 Yannick Hold-Geoffroy<sup>2</sup> Jean-François Lalonde<sup>1</sup> Valentin Deschaintre<sup>2</sup>  
<sup>1</sup>Université Laval, <sup>2</sup>Adobe Research

<https://lvsn.github.io/UniLight>




Figure 1. We propose UNILIGHT: A *joint* latent space to unify previously incompatible lighting representations. Our joint lighting embedding enables applications such as retrieval, example-based light control during image generation, and environment map generation from various modalities.

## Abstract

*Lighting has a strong influence on visual appearance, yet understanding and representing lighting in images remains notoriously difficult. Various lighting representations exist, such as environment maps, irradiance, spherical harmonics, or text, but they are incompatible, which limits cross-modal transfer. We thus propose UNILIGHT, a joint latent space as lighting representation, that unifies multiple modalities within a shared embedding. Modality-specific encoders for text, images, irradiance, and environment maps are trained contrastively to align their representations, with an auxiliary spherical-harmonics prediction task reinforcing directional understanding. Our multi-modal data pipeline enables large-scale training and evaluation across three tasks: lighting-based retrieval, environment-map generation, and lighting control in diffusion-based image synthesis. Experiments show that our representation captures consistent and transferable lighting features, enabling flexible manipulation across modalities.*

## 1. Introduction

Lighting plays a central role in determining the visual appearance of images. Consequently, lighting representation and control are fundamental for image understanding, gen-

eration, and editing. However, lighting is notoriously difficult to represent and can take many forms, including environment maps [35], textual descriptions [68], irradiance maps [65], or simply reference images depicting example illumination [60]. Each representation has distinct, and often complementary, advantages and limitations, which makes them largely incompatible with one another. As a result, most lighting estimation or control methods are designed around a single representation and cannot easily adapt to others, limiting their flexibility [35, 65].

Several works attempt to mitigate the limitations of the traditional lighting representations. For example, Li et al. [32] extend spherical Gaussians by estimating them locally over each pixel in the image, thus making them spatially-varying. More recently, inspired by Neural Radiance Fields (NeRFs) [42], researchers have begun encoding lighting implicitly using a neural network [3, 33, 61]. While these implicit representations can capture complex illumination effects, they are typically task-specific and are not compatible with other lighting representations.

In this work, we propose a joint latent space that unifies multiple lighting modalities, as shown in Fig. 1. We train modality-specific encoders for text, environment maps, irradiance maps, and images to extract lighting information into a common high-dimensional space. Our encoders build on vision transformers (ViTs) [44] and text encoders [57],

and are jointly trained with a contrastive learning objective across all modalities. To further improve light direction understanding, we introduce an auxiliary task that predicts degree-3 spherical harmonics coefficients from the joint embedding.

We devise a multi-modal data pipeline, from environment maps only, to support training and to evaluate the learned representation on three downstream tasks: (a) lighting-based retrieval, which retrieves modalities with similar illumination; (b) environment map generation, conditioned on any supported modality; and (c) flexible lighting control for diffusion-based image synthesis [65]. We further ablate our design decisions and demonstrate that both the contrastive and auxiliary training objectives are critical to learn a latent space that captures accurate lighting structure and orientation.

In summary, we make the following contributions:

- A multi-modal data pipeline for unified lighting representation learning.
- A contrastive framework aligning the representation of lighting across text, image, irradiance, and environment map modalities.
- An auxiliary spherical harmonics prediction loss enhancing directional encoding.
- Extensive experiments demonstrating versatility across lighting-related applications.

## 2. Related work

**Lighting modeling and estimation** have been long-standing challenges in computer vision and graphics. Early approaches often relied on simplified illumination models such as point or directional light sources to infer scene geometry from shading cues [24, 58]. In his seminal work, Debevec [10] introduced the use of environment maps to capture real-world illumination, enabling realistic image-based lighting. Subsequent work extended this idea by estimating environment lighting from images using cues such as reflections, shadows, and geometry [28, 29, 53].

Recent work has demonstrated strong performance in estimating lighting using learning-based methods, targeting indoor scenes [17, 18, 34, 55, 66], outdoor environments [23, 67, 72], or both [9, 30, 45]. Contemporary approaches further leverage NeRFs [26, 52, 61] or 3D Gaussian Splats [2] to model high-frequency, spatially-varying illumination. We refer the reader to the comprehensive survey of light representations used in the literature in Einabadi et al. [13] for more details.

Recent approaches attempt implicit latent-space disentanglement, for instance using PCA [21] or optimization [8, 31]. While these methods yield promising interpretable directions, they still require manual annotations. In this work, we propose to extract an implicit joint latent space that can serve as unified representation for disentangled

lighting control in image generation.

**Relighting** aims to modify the illumination conditions of an image while preserving the intrinsic identity of its elements. Traditional methods leverage inverse rendering techniques to estimate normals, materials, and lighting properties [36, 53], enabling re-illumination. These approaches, however, are typically sensitive to reconstruction accuracy: minor errors in geometry or material estimation can lead to implausible results, substantially reducing robustness.

Portrait relighting has received particular attention [5, 25, 40, 41, 43, 47, 50, 56, 68, 71] and attracted interest for digital avatars, virtual presence, and entertainment. In recent years, the relighting of generic scenes has gained traction [7, 19, 27, 38, 60, 64]. In this context, the generation of shadows and coherent indirect illumination has emerged as a key challenge, with dedicated methods tackling shadow generation [4, 54] and removal [20, 62].

In parallel with the rise of generative modeling, newer methods have begun to incorporate generative priors to achieve greater semantic consistency in relighting. For instance, latent-space editing in StyleGAN has been used for relighting [1]. More recent works apply diffusion-based models [15, 51] to relight by editing intrinsic image properties [37, 65, 70] or by guiding lighting changes via user-specified cues such as shadows [16]. For video and dynamic scenes, approaches leveraging diffusion models have even tackled video inverse-rendering, enabling relighting in the temporal domain [22, 35]. A related line of work estimates geometry first, then conditions a diffusion model on radiance hints to produce relit imagery [14].

These methods are typically designed for a single type of lighting control, limiting users’ ability to use their preferred lighting representation. We show that our joint lighting representation facilitates the design of multi-modal lighting applications for illumination control in both indoor and outdoor scenarios but also for environment map generation or light-driven retrieval.

## 3. Dataset

We aim to develop a joint embedding space that represents illumination across several modalities: 360° environment maps, regular images, irradiance maps, and text descriptions. In this section, we describe how we construct our dataset that encompasses and aligns these modalities.

Specifically, we construct a new dataset to train and evaluate our multi-modal encoders derived from a set of 8,020 high-dynamic-range (HDR) environment maps combining both outdoor (ULaval Outdoor [23], Polyhaven [46], Domeble [12]) and indoor sources (ULaval Indoor [17], Polyhaven [46], and pictures we acquired ourselves using a Theta Z1 camera). We take 9 crops per environment map






Figure 2. Dataset creation. Starting from an environment map, we extract 9 images and use Prism [11] to estimate their intrinsics. The images further serve as input to DiffusionLight-Turbo [6] for environment-map estimation and to a vision-language model (VLM) [57] to produce a text description (see Sec. 3 for details).

to generate a total of 72,180 multi-modal samples, each consisting of: (1) the environment map itself, (2) an image extracted from it, (3) an irradiance representation of the image, and (4) a text description for the image. Figure 2 shows an overview of our data generation pipeline; next we describe how we derive each aforementioned modality.

**Image.** We extract perspective images from an environment map by randomly rotating the map about the vertical axis and projecting it onto an image plane. Each extracted image has a resolution of  $512 \times 512$  pixels and a  $90^\circ$  field of view. We auto-expose the extracted image with Reinhard’s luminance mapping [49] with a scale  $F_d = 0.35$ , and tone-map the result using  $\gamma = 2.2$ .

**Irradiance.** For each image, we compute the corresponding irradiance map using Prism [11], a recent intrinsic decomposition method that can estimate spatially varying illumination. We include this representation as it is common in generative rendering pipelines [11, 65].

**Text.** We generate natural language descriptions of the lighting in each image using InternVL3-38B [57], a VLM capable of captioning images. As in Fig. 2, the bright light sources in the corresponding HDR environment map are identified using a method akin to [18], which detects large connected components above an intensity threshold. To this end, the threshold is initialized at a high value ( $\tau_0 = 4$ ) and lowered by one stop ( $\tau_{i+1} = \tau_i / \sqrt{2}$ ) until pixels above that value are found. The brightest point in each region above  $\tau$  is kept as the dominant light source. Second, the positions of the dominant light sources are integrated into a struc-

tured prompt for the VLM to describe the illumination of the images extracted from the environment map, emphasizing directional cues. The VLM is then queried with this prompt, the Reinhard [49] tone-mapped environment map, and the extracted image. This procedure yields text descriptions that accurately capture key lighting directions, as illustrated in Fig. 2. The full prompt, our algorithm for brightest-region identification, and examples of text descriptions are detailed in the supplementary material.

**Spherical harmonics.** To better capture the main directional lighting information, our model also estimates spherical harmonics (SH) coefficients, as described in Sec. 4.2. For this purpose, we fit SH coefficients up to degree  $l = 3$  to each environment map, to obtain a compact representation of the scene illumination.

**Estimated environment map.** To complement the high-quality environment maps in our dataset, we also estimate an environment map for each extracted image using DiffusionLight-Turbo [6]. These estimated maps are included during training to ensure encoders compatibility with them, as they can be easily generated from an image.

## 4. Multi-modal embedding

We propose a multi-modal embedding model that maps diverse lighting-related modalities -environment maps, irradiance maps, images, and text descriptions - into a shared latent space. Separate encoders are fine-tuned for image-based modalities and text, and their outputs are aligned using a lightweight transformer-based fusion module trained with a contrastive objective. The resulting latent space should place aligned lighting modalities, *e.g.* corresponding environment maps and text descriptions, close to each other. We show an overview of our method in Fig. 3.

### 4.1. Encoders

**Image-based encoders.** We employ a separate DINOv2-B [44] backbone for each image modality: environment map, image, and irradiance map.

To represent HDR information from an environment map  $I_{\text{hdr}}$ , we convert it into both a low-dynamic-range (LDR) image  $I_{\text{ldr}}$  using Reinhard [49] tone-mapping, and a logarithmic encoding  $I_{\text{log}} = \log(I_{\text{hdr}} + 1) / \log(I_{\text{max}})$  following prior work [26, 35]. We set  $I_{\text{max}} = 1000$  as a normalization constant defining the upper bound of HDR values above which values are clipped. In addition, we provide a per-pixel x,y,z coordinate encoding  $I_{\text{dir}}$  that corresponds to the latitude-longitude projection of the environment map, supplying explicit directional information. The complete encoder input for environment maps is thus  $\{I_{\text{ldr}}, I_{\text{log}}, I_{\text{dir}}\}$




Figure 3. Overview of our embedding approach. Image- and text-based lighting modalities (see Sec. 4.1) are first embedded using DINOv2 and Qwen3, respectively. All modalities are then processed by lightweight fusion modules which are trained contrastively to output into our joint latent space, UNILIGHT. To improve latent-space coherence, a linear-probing head estimates spherical-harmonics (SH) coefficients from the latents, and a dedicated loss aligns these coefficients to ground-truth coefficients extracted from the environment map.

combining LDR, HDR, and directional cues. During training, environment maps are randomly sampled from either ground-truth data or DiffusionLight-Turbo [6] estimates to improve robustness to different input formats. We also apply random dropout to the  $I_{\log}$  channels to ensure compatibility with purely LDR inputs.

For the image and irradiance-map input modalities, the DINOv2-B encoders are simply given their respective image as input with no further change.

**Text encoder.** We encode textual lighting descriptions using the 0.6B-parameter variant of Qwen3 Embedding [69], a large language model that produces general-purpose semantic embeddings from natural language. More specifically, we prompt the model with the lighting description and add additional instructions to encode the scene lighting, dominant light positions and overall brightness and color temperature. We include the exact prompt formatting in the supplemental material. We fine-tune this encoder within our multi-modal framework to better capture lighting-related semantics.

## 4.2. Architecture

The modality-specific backbones (DINOv2 and Qwen3) produce features with varying sequence lengths  $T_{\text{backbone}}$  and dimensions  $D_{\text{backbone}}$ . To unify these outputs, we introduce a summary module comprising  $T$  learnable query tokens per modality that attend to the backbone features through a multi-head attention layer followed by layer normalization. A linear projection then maps the resulting token features to a shared latent embedding  $E \in \mathbb{R}^{T \times D}$ ,

where we set  $T = 8$  and  $D = 512$  unless otherwise stated. We ablate the impact of the number of tokens Sec. 5.1.

To encourage the latent space to capture directional lighting cues, we add a spherical-harmonics (SH) prediction head which takes our embedding tokens as input. The head estimates SH coefficients up to degree  $l = 3$ , providing explicit supervision on lighting directionality during training.

**Loss function.** To force UNILIGHT to closely align the latent codes for different modalities describing the same lighting condition, we employ a contrastive objective across all lighting modalities. Given a batch of samples, each containing an image, irradiance map, environment map, and lighting description, each modality is passed through its corresponding encoder (DINOv2 or Qwen3). We then compute pairwise cosine similarities between all modality embeddings and apply a cross-entropy contrastive loss  $\mathcal{L}_{\text{contrastive}}$  to maximize agreement between matching pairs. To enforce directional consistency, we add an SH supervision term based on the mean squared error between the predicted and ground-truth coefficients:  $\mathcal{L}_{\text{SH}} = \|\text{SH}_{\text{pred}} - \text{SH}_{\text{GT}}\|_2^2$ . The total loss combines both objectives:

$$\mathcal{L} = \mathcal{L}_{\text{contrastive}} + \mathcal{L}_{\text{SH}}. \quad (1)$$

## 5. Experiments

We evaluate our model and demonstrate our joint latent embedding on three applications: cross-modal retrieval, environment map generation, and image relighting. We show that our UNILIGHT representation enables both light understanding and editing by leveraging diffusion models [15].




Figure 4. Analysis of light direction encoding in our unified representation. The environment map is rotated about the vertical axis (x-axis), and the resulting cosine similarity against the original orientation is shown. Similarity decreases with increasing rotation, indicating that the latent features explicitly encode light direction.




Figure 5. Cosine similarity (top, higher is better), inverse rank (bottom left, higher is better), and rank (bottom right, lower is better) between different modalities.

## 5.1. Model evaluation

Our approach encodes multiple lighting modalities into a joint latent space. We evaluate the sensitivity of our latent embeddings to lighting direction and analyze our design choices through ablation studies.

**Light direction.** We rotate environment maps from our test set horizontally from  $-180^\circ$  to  $+180^\circ$  in  $30^\circ$  increments and compute cosine similarity between transformed and initial (i.e.,  $0^\circ$ ) embeddings. Figure 4 shows that similarity decreases with larger rotations, indicating our embeddings successfully capture directional lighting information.

**SH reconstruction.** We further evaluate the light-encoding capabilities of our representation using our model’s SH-prediction head. For a sample in our test dataset, we obtain embeddings for all modalities and render environment maps from the SH representations predicted from each embedding. In Fig. 6 we compare these maps to a ground truth rendered from the SH representation ex-

Table 1. Ablation study. Retrieval metrics for varying numbers of tokens or SH-degree supervision, computed over 603 test-data points. We include averaged retrieval statistics for Image $\rightarrow$ Text and Text $\rightarrow$ Image on CLIP embeddings for comparison.

Variant	R@1	R@5	R@10	MRR	Median rank	Mean rank
CLIP ViT-B/32	2.6	10.8	16.9	0.077	72.0	107.3
1 tokens, SH3	23.8	47.4	58.9	0.355	10.7	22.2
2 tokens, SH3	24.3	48.7	60.1	0.362	9.9	21.2
4 tokens, SH3	25.1	49.0	60.5	0.369	10.1	21.5
8 tokens, SH3	24.9	49.0	60.6	0.367	9.8	21.2
16 tokens, SH3	<b>26.5</b>	<b>50.7</b>	<b>61.4</b>	<b>0.382</b>	<b>9.6</b>	<b>21.2</b>
8 tokens, NOSH	10.2	31.9	45.0	0.215	15.5	29.7
8 tokens, SH1	20.7	43.3	54.4	0.320	14.2	25.9
8 tokens, SH3	<b>24.9</b>	<b>49.0</b>	<b>60.6</b>	<b>0.367</b>	<b>9.8</b>	<b>21.2</b>
8 tokens, SH5	24.1	47.7	59.5	0.358	10.2	21.5

tracted directly from the environment map in the dataset sample. We additionally mark the location of the dominant light direction in each map (given by the order-1 SH coefficients) with a red cross. We observe close alignment between all modalities and the ground truth, indicating that our embeddings accurately encode structural lighting information. Even though the text description carries much less information than other modalities, its SH representation exhibits good alignment.

**Ablation study.** We ablate our UNILIGHT encoders on the number of tokens used by our embedding (1, 4, 8, and 16), and spherical harmonics degree supervision by comparing retrieval statistics in Tab. 1. The retrieval is performed on our test set, containing 603 data points, across all modality pairs bidirectionally (e.g., environment map  $\rightarrow$  text and text  $\rightarrow$  environment map), and averaged. We can see that increasing the number of tokens offers small improvements in retrieval accuracy at the cost of dimensionality/memory. We chose 8 tokens, but different methods may prefer a tighter or larger representation to satisfy memory or precision constraints. In which case, 1 or 16 token(s) respectively may be preferred. We also show that spherical harmonics of degree 3 (SH3) yield the greatest improvement in retrieval, while removing the spherical harmonics direction supervision (NOSH) significantly degrades retrieval accuracy.

## 5.2. Retrieval

We evaluate our shared latent space through cross-modal retrieval. Given a query embedding obtained from an input lighting modality, we aim to retrieve other modalities with similar lighting. We first extract embeddings from all modalities in our test set, consisting of 603 entries. We then compute pairwise cosine similarities between the query embedding and all other embeddings.

Qualitative results of this retrieval task are shown in Fig. 8. From the query in the leftmost column, we retrieve



Figure 6. We visualize the SH coefficients extracted by our SH head (see Fig. 3) from the UNILIGHT embeddings of the input modalities (rows 1 and 3). We render the predicted SH to an environment map (rows 2 and 4) and visualize the dominant light direction as a red cross. Note how both the reconstructed environment maps and the dominant light directions align across modalities as well as with the reference, indicating that they indeed have similar latent embeddings.

the elements from another modality and show the top-3 and bottom-3 matching illumination. We observe that the lighting direction and color are very similar across the top retrieved results, regardless of scene content, highlighting the focus of our representation on lighting.

We report standard retrieval metrics in Fig. 5, including Retrieval@K (R@K, whether the correct match appears among the top K results), Mean Reciprocal Rank (MRR), and the median ranks of the ground truth match. Evaluation is performed bidirectionally for each modality pair. The “Est. Envmap” modality corresponds to an environment map estimated from the image using DiffusionLight-Turbo [6]; as an estimation, it naturally yields lower similarity scores. Text accuracy is also lower than for other modalities, likely due to the inherent ambiguity of text descriptions. Despite these differences, similarity scores and ranks across modalities indicate strong cross-modal alignment, effectively translating lighting concepts between environment maps, images, irradiance, and text. As shown in Tab. 1, our lighting-specific embedding achieves markedly higher performance than CLIP [48] on image↔text retrieval across all tested token counts and SH degrees, demonstrating its effectiveness for lighting-related tasks.

### 5.3. Environment-map generation

We fine-tune Stable Diffusion 3.5 Medium [15] to output an LDR environment map and repurpose its text-conditioning branch to accept our lighting embedding. We show results of this application in Fig. 9 and include a pipeline diagram in the supplemental material. We observe that our method can produce structurally coherent 360° environment maps that are consistent with the conditioning, across input modalities.




Figure 7. Image relighting pipeline using our X→RGB model. We first decompose the input image into intrinsics (discarding lighting information) and then resynthesize it by feeding a UNILIGHT embedding that encodes the desired lighting.



Image → Env. maps							
Text → Env. maps	<i>“indoor, natural light from the left, warm glow, two table lamps with warm yellow light, balanced illumination, cozy ambiance.”</i>						
Irradiance → Env. maps							
Text → Image	<i>“outdoor, bright sun from the upper right, warm golden hue, clear blue sky, reflections on water, no artificial lights.”</i>						
Image → Text		<i>“outdoor, diffused sunlight, overcast sky, soft lighting, muted colors.”</i> 0.998	<i>“outdoor, soft diffused light, cool hue, overcast sky, muted colors, grays and earth tones.”</i> 0.997	<i>“outdoor, soft diffused light, cool muted hue, overcast sky, uniform illumination, subdued grayish tones.”</i> 0.993	<i>“indoor, natural light from tall windows on the right, warm yellow hue, soft illumination, serene atmosphere.”</i> -0.589	<i>“indoor, natural light from large windows, soft shadows, recessed strip lights, warm inviting tone.”</i> -0.513	<i>“outdoor, bright sun from the upper right, warm golden hue, direct illumination, natural ambiance, warm tones dominate.”</i> -0.512
	<b>Query</b>	<b>Top 1</b>	<b>Top 2</b>	<b>Top 3</b>	<b>Worst 1</b>	<b>Worst 2</b>	<b>Worst 3</b>

Figure 8. Top-three retrieval comparisons across different modalities in the rows. For example, the first row embeds an image and retrieves environment maps, using the image’s UNILIGHT embedding as a query. Columns show the three best and worst matches. The inset values are the cosine similarities between query and result embeddings.

Image					
Env. map					N/A
Text	<i>“The primary natural light source is the sun, positioned to the upper right, casting a soft and diffused light with a cool blue hue. There are no visible artificial lights.”</i>				N/A
Irradiance					N/A
	<b>Input modality</b>	<b>Reference</b>	<b>Ours (seed 1)</b>	<b>Ours (seed 2)</b>	<b>DL-Turbo [6]</b>

Figure 9. Environment-map generation using our UNILIGHT-conditioned diffusion model with four control modalities, for two different seeds. We compare to DiffusionLight-Turbo [6] which supports only image conditioning.

#### 5.4. Light control for image generation

To assess the utility of our lighting representation for re-lighting, we integrate it into the X→RGB framework [65]. Similar to the original model, our model (based on Stable Diffusion 3.5) takes intrinsic channels as input (albedo, normal, roughness, and metallicity), but we replace the irradiance input intrinsic with our UNILIGHT embedding. As illustrated in Fig. 7, this modification enables multi-modal control, allowing lighting conditions to be specified via text, image, irradiance, or an environment map. This provides a consistent and flexible approach to re-lighting, including transferring illumination from arbitrary reference images or descriptions to new scenes. To relight outdoor images, we apply a sky masking model [59] to replace the sky with the associated environment map, which facilitates evaluating lighting coherence. Figure 10 shows results of our approach, with much improved quality over baselines.



Figure 10. Image relighting using our UNILIGHT-conditioned  $X \rightarrow \text{RGB}$  model (see Fig. 7) with different lighting modalities. We apply four lighting conditions on two images (rows) and compare against three baselines (columns): LumiNet [60] (image modality), DiffusionRenderer [35] (environment map), and original  $X \rightarrow \text{RGB}$  [65] (text). We also show irradiance-conditioned generation with our model; comparing to original  $X \rightarrow \text{RGB}$  [65] here is moot as that model requires the irradiance to be aligned with (the intrinsics of) the input image.

## 6. Discussion

Our work represents a step toward a unified representation of lighting, demonstrating a shared latent space that bridges different modalities. Despite this advance, some limitations remain. First, although our current representation encodes light direction effectively, it does not represent the light spatial variation, which can be important for complex indoor scenes. This could be improved by attempting to merge more spatial modalities (e.g., [39]) for local control and our supported high-level representations (e.g., environment map, text) for global control. More generally, while we take a step towards unifying lighting representation, including additional representations (e.g., shading based [16]) to further facilitate user interaction is an interesting avenue for future work. Finally, aligning our embeddings to existing popular encoders [63] may further simplify the fine-tuning of the diffusion model using our lighting embeddings or enable zero-shot use.

## 7. Conclusion

We presented UNILIGHT, a unified latent lighting representation that operates across multiple modalities, including text, images, environment maps, and irradiance. Our latent

space is learned through a contrastive framework grounded with a spherical harmonics loss. We demonstrated the accuracy of our representation through multi-modal light retrieval and showcased its effectiveness in downstream tasks such as light generation and relighting. We believe our contributions lay the groundwork for flexible physically grounded control of generative models, opening new possibilities for lighting-aware synthesis and editing.

## References

- [1] Anand Bhattad, James Soole, and David A Forsyth. StyLitGAN: Image-based relighting via latent control. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [2] Christophe Bolduc, Yannick Hold-Geoffroy, Zhixian Shu, and Jean-François Lalonde. GaSLight: Gaussian splats for spatially-varying lighting in hdr. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2025. 2
- [3] Mark Boss, Varun Jampani, Raphael Braun, Ce Liu, Jonathan Barron, and Hendrik Lensch. Neural-pil: Neural pre-integrated lighting for reflectance decomposition. In *Adv. Neural Inform. Process. Syst.*, 2021. 1
- [4] Clément Chadebec, Onur Tasar, Sanjeev Sreetharan, and Benjamin Aubin. LBM: Latent bridge matching for fast image-to-image translation. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2025. 2



- [5] Sumit Chaturvedi, Mengwei Ren, Yannick Hold-Geoffroy, Jingyuan Liu, Julie Dorsey, and Zhixin Shu. SynthLight: Portrait relighting with diffusion model by learning to re-render synthetic faces. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2025. 2
- [6] Worameth Chinchuthakun, Pakkapon Phongthawee, Amit Raj, Varun Jampani, Pramook Khungurn, and Supasorn Suwajanakorn. DiffusionLight-Turbo: Accelerated light probes for free via single-pass chrome ball inpainting. In *ArXiv*, 2025. 3, 4, 6, 7
- [7] Jun Myeong Choi, Annie Wang, Pieter Peers, Anand Bhattad, and Roni Sengupta. ScribbleLight: Single Image Indoor Relighting with Scribbles. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2025. 2
- [8] Yusuf Dalva and Pinar Yanardag. NoiseCLR: A contrastive learning approach for unsupervised discovery of interpretable directions in diffusion models. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [9] Mohammad Reza Karimi Dastjerdi, Jonathan Eisenmann, Yannick Hold-Geoffroy, and Jean-François Lalonde. EverLight: Indoor-outdoor editable HDR lighting estimation. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2023. 2
- [10] Paul Debevec. Rendering synthetic objects into real scenes: Bridging traditional and image-based graphics with global illumination and high dynamic range photography. In *ACM SIGGRAPH Conf.*, 1998. 2
- [11] Alara Dirik, Tuanfeng Wang, Duygu Ceylan, Stefanos Zafeiriou, and Anna Frühstück. Prism: A unified framework for photorealistic reconstruction and intrinsic scene modeling, 2025. 3
- [12] Domeble. The domeble hdri dataset. <https://www.domeble.com/tag/hdri/>, 2025. 2
- [13] Farshad Einabadi, Jean-Yves Guillemaut, and Adrian Hilton. Deep neural models for illumination estimation and relighting: A survey. *Comput. Graph. Forum*, 40(6):315–331, 2021. 2
- [14] Yotam Erel, Rishabh Dabral, Vladislav Golyanik, Amit H Bermano, and Christian Theobalt. PractiLight: Practical light control using foundational diffusion models. *arXiv preprint arXiv:2509.01837*, 2025. 2
- [15] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, Dustin Podell, Tim Dockhorn, Zion English, and Robin Rombach. Scaling rectified flow transformers for high-resolution image synthesis. In *Int. Conf. Mach. Learn.*, 2024. 2, 4, 6
- [16] Frédéric Fortier-Chouinard, Zitian Zhang, Louis-Etienne Messier, Mathieu Garon, Anand Bhattad, and Jean-François Lalonde. Spotlight: Shadow-guided object relighting via diffusion. In *Int. Conf. 3D Vis.*, 2026. 2, 8
- [17] Marc-André Gardner, Kalyan Sunkavalli, Ersin Yumer, Xiaohui Shen, Emiliano Gambaretto, Christian Gagné, and Jean-François Lalonde. Learning to predict indoor illumination from a single image. *ACM Trans. Graph.*, 36(6), 2017. 2
- [18] Marc-Andre Gardner, Yannick Hold-Geoffroy, Kalyan Sunkavalli, Christian Gagne, and Jean-Francois Lalonde. Deep parametric indoor lighting estimation. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2019. 2, 3
- [19] David Griffiths, Tobias Ritschel, and Julien Philip. OutCast: Single image relighting with cast shadows. *Comput. Graph. Forum*, 43, 2022. 2
- [20] Lanqing Guo, Siyu Huang, Ding Liu, Hao Cheng, and Bihan Wen. Shadowformer: Global context helps shadow removal. In *Assoc. Adv. of Art. Int.*, 2023. 2
- [21] René Haas, Inbar Huberman-Spiegelglas, Rotem Mulayoff, Stella Graßhof, Sami S Brandt, and Tomer Michaeli. Discovering interpretable directions in the semantic latent space of diffusion models. In *Int. Conf. Aut. Face Gest. Recog.*, 2024. 2
- [22] Kai He, Ruofan Liang, Jacob Munkberg, Jon Hasselgren, Nandita Vijaykumar, Alexander Keller, Sanja Fidler, Igor Gilitschenski, Zan Gojcic, and Zian Wang. UniRelight: Learning joint decomposition and synthesis for video relighting. *arXiv preprint arXiv:2506.15673*, 2025. 2
- [23] Yannick Hold-Geoffroy, Akshaya Athawale, and Jean-François Lalonde. Deep sky modeling for single image outdoor lighting estimation. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2019. 2
- [24] Berthold KP Horn. Shape from shading: A method for obtaining the shape of a smooth opaque object from one view. 1970. 2
- [25] Andrew Hou, Zhixin Shu, Xuaner Zhang, He Zhang, Yannick Hold-Geoffroy, Jae Shin Yoon, and Xiaoming Liu. COMPOSE: Comprehensive portrait shadow editing. In *Eur. Conf. Comput. Vis.*, 2024. 2
- [26] Haian Jin, Yuan Li, Fujun Luan, Yuanbo Xiangli, Sai Bi, Kai Zhang, Zexiang Xu, Jin Sun, and Noah Snively. Neural gaffer: Relighting any object via diffusion. In *Adv. Neural Inform. Process. Syst.*, 2024. 2, 3
- [27] Peter Kocsis, Julien Philip, Kalyan Sunkavalli, Matthias Nießner, and Yannick Hold-Geoffroy. LightIt: Illumination modeling and control for diffusion models. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [28] Jean-François Lalonde and Iain Matthews. Lighting estimation in outdoor image collections. In *Int. Conf. 3D Vis.*, 2014. 2
- [29] Jean-François Lalonde, Alexei A Efros, and Srinivasa G Narasimhan. Estimating the natural illumination conditions from a single outdoor image. *Int. J. Comput. Vis.*, 98(2): 123–145, 2012. 2
- [30] Chloe LeGendre, Wan-Chun Ma, Graham Fyffe, John Flynn, Laurent Charbonnel, Jay Busch, and Paul Debevec. DeepLight: Learning illumination for unconstrained mobile mixed reality. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2019. 2
- [31] Hang Li, Chengzhi Shen, Philip Torr, Volker Tresp, and Jindong Gu. Self-discovering interpretable diffusion latent directions for responsible text-to-image generation. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [32] Zhengqin Li, Mohammad Shafiei, Ravi Ramamoorthi, Kalyan Sunkavalli, and Manmohan Chandraker. Inverse rendering for complex indoor scenes: Shape, spatially-varying lighting and svbrdf from a single image. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2020. 1

- [33] Zhong Li, Liangchen Song, Celong Liu, Junsong Yuan, and Yi Xu. Neulf: Efficient novel view synthesis with neural 4d light field. *arXiv preprint arXiv:2105.07112*, 2021. 1
- [34] Zhengqin Li, Li Yu, Mikhail Okunev, Manmohan Chandraker, and Zhao Dong. Spatiotemporally consistent hdr indoor lighting estimation. *ACM Trans. Graph.*, 42(3):1–15, 2023. 2
- [35] Ruofan Liang, Zan Gojcic, Huan Ling, Jacob Munkberg, Jon Hasselgren, Zhi-Hao Lin, Jun Gao, Alexander Keller, Nandita Vijaykumar, Sanja Fidler, and Zian Wang. Diffusion-Renderer: Neural inverse and forward rendering with video diffusion models. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2025. 1, 2, 3, 8
- [36] Stephen Lombardi and Ko Nishino. Reflectance and illumination recovery in the wild. *IEEE Trans. Pattern Anal. Mach. Intell.*, 38(1):129–141, 2015. 2
- [37] Linjie Lyu, Valentin Deschaintre, Yannick Hold-Geoffroy, Miloš Hašan, Jae Shin Yoon, Thomas Leimkuehler, Christian Theobalt, and Iliyan Georgiev. IntrinsicEdit: Precise generative image manipulation in intrinsic space. *ACM Trans. Graph.*, 44(4), 2025. 2
- [38] Nadav Magar, Amir Hertz, Eric Tabellion, Yael Pritch, Alex Rav-Acha, Ariel Shamir, and Yedid Hoshen. LightLab: Controlling light sources in images with diffusion models. In *ACM SIGGRAPH Conf.*, 2025. 2
- [39] Nadav Magar, Amir Hertz, Eric Tabellion, Yael Pritch, Alex Rav-Acha, Ariel Shamir, and Yedid Hoshen. Lightlab: Controlling light sources in images with diffusion models. In *ACM SIGGRAPH Conf.*, 2025. 8
- [40] Yiqun Mei, Yu Zeng, He Zhang, Zhixin Shu, Xuaner Zhang, Sai Bi, Jianming Zhang, HyunJoon Jung, and Vishal M Patel. Holo-relighting: Controllable volumetric portrait relighting from a single image. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [41] Yiqun Mei, Mingming He, Li Ma, Julien Philip, Wenqi Xian, David M George, Xueming Yu, Gabriel Dedic, Ahmet Levent Taşel, Ning Yu, et al. Lux post facto: Learning portrait performance relighting with conditional video diffusion and a hybrid dataset. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2025. 2
- [42] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *Comm. ACM*, 65(1):99–106, 2021. 1
- [43] Thomas Nestmeyer, Jean-François Lalonde, Iain Matthews, and Andreas Lehrmann. Learning physics-guided face relighting under directional light. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2020. 2
- [44] Maxime Oquab, Timothée Darcet, Theo Moutakanni, Huy V. Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Russell Howes, Po-Yao Huang, Hu Xu, Vasu Sharma, Shang-Wen Li, Wojciech Galuba, Mike Rabbat, Mido Assran, Nicolas Ballas, Gabriel Synnaeve, Ishan Misra, Herve Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. Dinov2: Learning robust visual features without supervision, 2023. 1, 3
- [45] Pakkapon Phongthawee, Worameth Chinchuthakun, Nontaphat Sinsunthithet, Amit Raj, Varun Jampani, Pramook Khungurn, and Supasorn Suwajanakorn. DiffusionLight: Light probes for free by painting a chrome ball. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [46] A PolyHaven. Poly haven: The public 3D asset library. <https://polyhaven.com/hdris>, 2025. 2
- [47] Puntawat Ponglertnapakorn, Nontawat Tritrong, and Supasorn Suwajanakorn. DiFaReli: Diffusion face relighting. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2023. 2
- [48] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *Int. Conf. Mach. Learn.*, pages 8748–8763, 2021. 6
- [49] Erik Reinhard, Michael Stark, Peter Shirley, and James Ferwerda. Photographic tone reproduction for digital images. In *Seminal Graphics Papers: Pushing the Boundaries, Volume 2*, pages 661–670. 2023. 3
- [50] Mengwei Ren, Wei Xiong, Jae Shin Yoon, Zhixin Shu, Jianming Zhang, HyunJoon Jung, Guido Gerig, and He Zhang. Relightful harmonization: Lighting-aware portrait background replacement. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2024. 2
- [51] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2022. 2
- [52] Viktor Rudnev, Mohamed Elgharib, William Smith, Lingjie Liu, Vladislav Golyanik, and Christian Theobalt. Nerf for outdoor scene relighting. In *Eur. Conf. Comput. Vis.*, 2022. 2
- [53] Imari Sato, Yoichi Sato, and Katsushi Ikeuchi. Illumination from shadows. *IEEE Trans. Pattern Anal. Mach. Intell.*, 25(3):290–300, 2003. 2
- [54] Yichen Sheng, Yifan Liu, Jianming Zhang, Wei Yin, A Cengiz Oztireli, He Zhang, Zhe Lin, Eli Shechtman, and Bedrich Benes. Controllable shadow generation using pixel height maps. In *Eur. Conf. Comput. Vis.*, 2022. 2
- [55] Shuran Song and Thomas Funkhouser. Neural illumination: Lighting prediction for indoor environments. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2019. 2
- [56] Tiancheng Sun, Jonathan T Barron, Yun-Ta Tsai, Zexiang Xu, Xueming Yu, Graham Fyffe, Christoph Rhemann, Jay Busch, Paul E Debevec, and Ravi Ramamoorthi. Single image portrait relighting. *ACM Trans. Graph.*, 38(4):79–1, 2019. 2
- [57] Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, et al. InternVL3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025. 1, 3
- [58] Robert J Woodham. Photometric method for determining surface orientation from multiple images. *Opt. eng.*, 19(1): 139–144, 1980. 2



- [59] Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. In *Adv. Neural Inform. Process. Syst.*, 2021. [7](#)
- [60] Xiaoyan Xing, Konrad Groh, Sezer Karaoglu, Theo Gevers, and Anand Bhattad. LumiNet: Latent intrinsics meets diffusion models for indoor scene relighting. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2025. [1](#), [2](#), [8](#)
- [61] Yao Yao, Jingyang Zhang, Jingbo Liu, Yihang Qu, Tian Fang, David McKinnon, Yanghai Tsin, and Long Quan. NeiLF: Neural incident light field for physically-based material estimation. In *Eur. Conf. Comput. Vis.*, 2022. [1](#), [2](#)
- [62] Jae Shin Yoon, Zhixin Shu, Mengwei Ren, Cecilia Zhang, Yannick Hold-Geoffroy, Krishna Kumar Singh, and He Zhang. Generative portrait shadow removal. *ACM Trans. Graph.*, 43(6):1–13, 2024. [2](#)
- [63] Sihyun Yu, Sangkyung Kwak, Huiwon Jang, Jongheon Jeong, Jonathan Huang, Jinwoo Shin, and Saining Xie. Representation alignment for generation: Training diffusion transformers is easier than you think. *arXiv preprint arXiv:2410.06940*, 2024. [8](#)
- [64] Chong Zeng, Yue Dong, Pieter Peers, Youkang Kong, Hongzhi Wu, and Xin Tong. Dilightnet: Fine-grained lighting control for diffusion-based image generation. In *ACM SIGGRAPH Conf.*, 2024. [2](#)
- [65] Zheng Zeng, Valentin Deschaintre, Iliyan Georgiev, Yannick Hold-Geoffroy, Yiwei Hu, Fujun Luan, Ling-Qi Yan, and Miloš Hašan. RGB $\leftrightarrow$ X: Image decomposition and synthesis using material- and lighting-aware diffusion models. In *ACM SIGGRAPH Conf.*, 2024. [1](#), [2](#), [3](#), [7](#), [8](#)
- [66] Fangneng Zhan, Changgong Zhang, Yingchen Yu, Yuan Chang, Shijian Lu, Feiying Ma, and Xuansong Xie. EM-Light: Lighting estimation via spherical distribution approximation. In *Assoc. Adv. of Art. Int.*, 2021. [2](#)
- [67] Jinsong Zhang, Kalyan Sunkavalli, Yannick Hold-Geoffroy, Sunil Hadap, Jonathan Eisenman, and Jean-François Lalonde. All-weather deep outdoor lighting estimation. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2019. [2](#)
- [68] Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Scaling in-the-wild training for diffusion-based illumination harmonization and editing by imposing consistent light transport. In *Int. Conf. Learn. Represent.*, 2025. [1](#), [2](#)
- [69] Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025. [4](#)
- [70] Zitian Zhang, Frédéric Fortier-Chouinard, Mathieu Garon, Anand Bhattad, and Jean-François Lalonde. ZeroComp: Zero-shot object compositing from image intrinsics via diffusion. In *IEEE/CVF Winter Conf. App. Comput. Vis.*, 2025. [2](#)
- [71] Hao Zhou, Sunil Hadap, Kalyan Sunkavalli, and David W Jacobs. Deep single-image portrait relighting. In *IEEE/CVF Int. Conf. Comput. Vis.*, 2019. [2](#)
- [72] Yongjie Zhu, Yinda Zhang, Si Li, and Boxin Shi. Spatially-varying outdoor lighting estimation from intrinsics. In *IEEE/CVF Conf. Comput. Vis. Pattern Recog.*, 2021. [2](#)