

Proof-Carrying PWL Verification for ReLU Networks: Convex-Hull Semantics, Exact SMT/MILPEncodings, and Symbolic Certificate Checking

Chandrasekhar Gokavarapu
 Government College (Autonomous), Rajahmundry, India
 chandrasekhargokavarapu@gmail.com

Abstract

ReLU networks are piecewise-linear (PWL), enabling exact symbolic verification via SMT(LRA) or MILP. However, safety claims in certification pipelines require not only correctness but also *checkable evidence*. We develop a proof-carrying verification core for PWL neural constraints: (i) we formalize ReLU networks as unions of polyhedra indexed by activation patterns; (ii) we present exact SMT/MILPEncodings and the canonical convex-hull relaxation for each bounded ReLU; and (iii) we introduce a certificate calculus in which bound tightening, stabilization, strengthening, and pruning steps emit explicit algebraic witnesses (LP dual multipliers and Farkas infeasibility certificates). Crucially, these witnesses are *symbolic objects* that admit independent verification in exact arithmetic over \mathbb{Q} . We provide a symbolic certificate checker, normalization rules that preserve validity, and a compositional view of region-wise certificates as a global proof artifact for universal safety.

Keywords: ReLU verification, piecewise-linear constraints, convex hull, LP duality, Farkas lemma, proof-carrying verification, exact certificate checking, computer algebra.

1 Introduction

Formal verification of neural networks replaces black-box testing by a symbolic decision problem: does there exist an input in a domain D that violates a safety specification? For ReLU networks, this question is expressible using piecewise-linear constraints, and can be attacked by SMT(LRA) procedures or MILPEncodings [3, 16]. The challenge is twofold. First, the PWL semantics induces exponentially many activation patterns, so scalability depends on strong propagation. Second, in safety-critical contexts, an UNSAT verdict (“no counterexample exists”) should be accompanied by evidence that can be independently checked. [1, 2]

Computer-algebra perspective. Modern verifiers already compute linear bounds, generate linear lemmas, and prune infeasible regions. Our thesis is that the *mathematical objects underlying these steps are inherently symbolic*: they can be exported as rational certificates (vectors of multipliers) and checked by exact arithmetic. This turns neural verification into a proof-carrying pipeline where solvers may be untrusted, but certificates are small, explicit, and machine-checkable.

What is new (direction, not rephrasing). We do not claim novelty in the existence of convex-hull ReLU relaxations or in LP duality. The novel direction is a *compositional certificate calculus* for PWL neural constraints: each propagation step emits a certificate; certificates compose across refinements; and certificate checking is isolated as a symbolic computation problem. This aligns verification with the CASC ethos: exact manipulation and validation of algebraic objects produced by numeric/LP engines.

Contributions. The paper makes the following contributions:

1. **Exact PWL semantics and encodings.** We formalize ReLU networks as unions of pattern-indexed polyhedra in extended space and relate this semantics to exact SMT/MILP encodings and to canonical convex-hull relaxations.
2. **Proof-carrying certificate calculus over \mathbb{Q} .** We present a solver-agnostic certificate interface based on rational objects and give exact checkers for (i) Farkas infeasibility certificates and (ii) entailment certificates for validated propagation and learned cuts.
3. **Computer-algebra normalization and log compression.** We introduce symbolic normalization/canonicalization routines for certificates (and, optionally, constraint rows) that preserve checkability under exact arithmetic, enabling compact proof logs.
4. **Sparse proof artifacts.** We prove that infeasibility admits a dimension-sparse rational certificate (support bounded by $d + 1$), which yields principled compression guarantees for pruning proofs.
5. **Worked proof-carrying examples.** We provide explicit, fully checkable examples demonstrating (a) direct safety entailment via `CHECKENTAIL`, (b) UNSAT pruning via `CHECKFARKAS`, and (c) stabilization / aggregated cuts as typical verification steps.

2 Problem Statement and Verification Query

Let $\mathcal{N} : \mathbb{R}^n \rightarrow \mathbb{R}^m$ be a feed-forward network with L layers: $z^{(0)} = x$ and for $i = 1, \dots, L$,

$$s^{(i)} = W^{(i)} z^{(i-1)} + b^{(i)}, \quad z^{(i)} = \sigma(s^{(i)}),$$

where $\sigma = \text{ReLU}$ for hidden layers (and typically identity at the output). Let $D \subseteq \mathbb{R}^n$ be a compact domain, and let $\text{Safety}(z^{(L)})$ be a specification, assumed representable by linear inequalities in this paper [1, 3].

Definition 2.1 (Counterexample query). Define

$$\Phi_{\neg P} := \exists x \in D : \bigwedge_{i=1}^L (z^{(i)} = \sigma(W^{(i)} z^{(i-1)} + b^{(i)})) \wedge \neg \text{Safety}(z^{(L)}).$$

Then \mathcal{N} is safe on D iff $\Phi_{\neg P}$ is UNSAT.

3 PWL Semantics and Exact Encodings

This section develops a solver-aligned, *proof-oriented* semantics for ReLU networks as *unions of polyhedra* together with *exact extended formulations* (MILP/SMT) and their *canonical convex relaxations*. The guiding (non-speculative) hooks are standard in state-of-the-art verifiers: (i) activation-pattern decomposition, (ii) bounded big- M exactness, and (iii) convex-hull tightness. The new direction here is to present these hooks as a *compositional polyhedral calculus* based on projection/elimination principles, which is precisely the interface needed for later proof-carrying certificates.

3.1 Notation and the graph of a ReLU network

Let $\mathcal{N} : \mathbb{R}^n \rightarrow \mathbb{R}^m$ be a feed-forward network with L layers. Write $z^{(0)} = x \in \mathbb{R}^n$ and for $i = 1, \dots, L$,

$$s^{(i)} = W^{(i)} z^{(i-1)} + b^{(i)}, \quad z^{(i)} = \sigma^{(i)}(s^{(i)}),$$

where $\sigma^{(i)} = \text{ReLU}$ for hidden layers and typically $\sigma^{(L)} = \text{id}$. Let $d_i := \dim(z^{(i)})$ and denote by $N := \sum_{i=1}^{L-1} d_i$ the total number of ReLU coordinates.

We will represent the network by a constraint system over the variable tuple

$$v := (x, (s^{(i)})_{i=1}^{L-1}, (z^{(i)})_{i=1}^L) \in \mathbb{R}^{n + \sum_{i=1}^{L-1} d_i + \sum_{i=1}^L d_i}.$$

The *graph* of \mathcal{N} is the set

$$\text{Gr}(\mathcal{N}) := \{(x, y) \in \mathbb{R}^{n+m} : y = \mathcal{N}(x)\}.$$

Our first goal is to realize $\text{Gr}(\mathcal{N})$ as a finite union of polyhedra obtained by eliminating internal variables from pattern-indexed polyhedra. This is the correct algebraic viewpoint for CASC: *encoding is an extended formulation; semantics is projection*.

3.2 ReLU as a disjunctive constraint

For scalar s and $z = \text{ReLU}(s)$, the exact semantics is the disjunction

$$(s \leq 0 \wedge z = 0) \vee (s \geq 0 \wedge z = s).$$

Thus a ReLU network induces a Boolean phase structure coupled to linear arithmetic. We formalize phases by *pattern variables* rather than by case distinctions in proofs.[1, 2]

3.3 Activation-pattern polyhedra in extended space

Index each ReLU coordinate by a single index $j \in \{1, \dots, N\}$. An activation pattern is $\pi \in \{0, 1\}^N$, where $\pi_j = 1$ means “active” and $\pi_j = 0$ means “inactive” [3].

Definition 3.1 (Pattern-indexed extended polyhedron). Fix $\pi \in \{0, 1\}^N$. Define $P_\pi \subseteq \mathbb{R}^{\dim(v)}$ as the set of all tuples $v = (x, (s^{(i)}), (z^{(i)}))$ satisfying:

- (i) (Affine layers) $s^{(i)} = W^{(i)}z^{(i-1)} + b^{(i)}$ for $i = 1, \dots, L-1$, and $z^{(L)} = W^{(L)}z^{(L-1)} + b^{(L)}$.
- (ii) (Phase constraints) For every ReLU coordinate j corresponding to some (i, k) :

$$\pi_j = 1 \Rightarrow (s_k^{(i)} \geq 0 \wedge z_k^{(i)} = s_k^{(i)}), \quad \pi_j = 0 \Rightarrow (s_k^{(i)} \leq 0 \wedge z_k^{(i)} = 0).$$

Definition 3.2 (Pattern region in input space). Let proj_x denote projection onto input coordinates. Define the *pattern region* $R_\pi := \text{proj}_x(P_\pi) \subseteq \mathbb{R}^n$.

Remark 3.3. P_π is a polyhedron in the extended space because it is defined by affine equalities and inequalities. The region R_π is also a polyhedron because projection preserves polyhedrality (e.g. by Fourier–Motzkin elimination). The elimination viewpoint is essential: verifiers operate in extended space; correctness ultimately concerns projections.

3.4 Union-of-polyhedra semantics and piecewise-affine maps

We now give a structural theorem that is used implicitly throughout neural verification, but we state it as an explicit projection identity (extended formulation semantics).

Theorem 3.4 (Exact PWL semantics as projection of a union of polyhedra). *Let \mathcal{N} be a ReLU network as above. Then:*

- (a) *The extended feasible set of the exact network constraints equals a union of pattern polyhedra:*

$$\{v : v \text{ satisfies all exact ReLU and affine constraints}\} = \bigcup_{\pi \in \{0,1\}^N} P_\pi.$$

(b) The network graph is the projection of this union:

$$\text{Gr}(\mathcal{N}) = \text{proj}_{x,z^{(L)}} \left(\bigcup_{\pi \in \{0,1\}^N} P_\pi \right).$$

(c) For every π with $R_\pi \neq \emptyset$, there exist $A_\pi \in \mathbb{R}^{m \times n}$ and $c_\pi \in \mathbb{R}^m$ such that $\mathcal{N}(x) = A_\pi x + c_\pi$ for all $x \in R_\pi$.

Proof. (a) Fix any exact-feasible assignment v . For each ReLU coordinate j , either $s_j \geq 0$ and $z_j = s_j$, or $s_j \leq 0$ and $z_j = 0$. Define $\pi_j = 1$ in the first case and $\pi_j = 0$ in the second. Then v satisfies the defining constraints of P_π , hence $v \in \bigcup_\pi P_\pi$. Conversely, if $v \in P_\pi$ for some π , then for each ReLU coordinate it satisfies one of the two exact ReLU branches, hence is exact-feasible.

(b) This follows by applying $\text{proj}_{x,z^{(L)}}$ to both sides of (a) and using the definition of $\text{Gr}(\mathcal{N})$.

(c) Fix π with $R_\pi \neq \emptyset$. On P_π , each ReLU coordinate is replaced by a linear equality ($z = s$ or $z = 0$). Together with the affine layer equalities, this yields a linear system expressing all internal variables as affine functions of x (uniquely for $z^{(L)}$ as a function of x), hence $z^{(L)} = A_\pi x + c_\pi$. Therefore $\mathcal{N}(x) = A_\pi x + c_\pi$ for all $x \in R_\pi$. \square

Remark 3.5 (A computable formula for (A_π, c_π)). If one writes each hidden-layer phase as a diagonal mask $D_\pi^{(i)} \in \{0,1\}^{d_i \times d_i}$, then on R_π ,

$$z^{(i)} = D_\pi^{(i)} s^{(i)} = D_\pi^{(i)} (W^{(i)} z^{(i-1)} + b^{(i)}),$$

so $z^{(L)}$ is obtained by composing affine maps. This provides an explicit symbolic object attached to each pattern, useful for CAS-style reasoning about regions.

3.5 Polyhedral-complex structure (a geometric “state explosion” lens)

A key nontrivial structural fact is that the collection of pattern regions behaves like a polyhedral complex: different patterns meet along faces where some pre-activations are exactly zero. This is a rigorous way to understand “state explosion” geometrically (rather than only combinatorially).

Proposition 3.6 (Face-intersection property in extended space). *Let $\pi, \pi' \in \{0,1\}^N$. Then $P_\pi \cap P_{\pi'}$ is a (possibly empty) face of both P_π and $P_{\pi'}$. More precisely, if π and π' differ exactly on an index set $J \subseteq \{1, \dots, N\}$, then*

$$P_\pi \cap P_{\pi'} = P_\pi \cap \bigcap_{j \in J} \{s_j = 0, z_j = 0\} = P_{\pi'} \cap \bigcap_{j \in J} \{s_j = 0, z_j = 0\}.$$

Proof. If π and π' agree on a ReLU coordinate j , then both impose the same linear constraints at j . If they differ on j , then one polyhedron imposes $(s_j \geq 0, z_j = s_j)$ while the other imposes $(s_j \leq 0, z_j = 0)$. A point can satisfy both iff $s_j = 0$ and $z_j = 0$ (since $z_j = s_j$ and $z_j = 0$ together force $s_j = 0$). Hence the intersection is obtained by adding the equalities $s_j = 0, z_j = 0$ for all j where patterns differ. Adding linear equalities to a polyhedron yields a face (possibly empty), so the claim follows. \square

3.6 Exact bounded big- M formulation (milp) and its correctness

We now establish, with full equivalence (not just implication), that bounded big- M constraints encode exactly the disjunction $z = \max(0, s)$ when bounds are valid. This theorem is a cornerstone of complete MILP-based verification and is non-speculative [3, ?].

Theorem 3.7 (Exactness of bounded big- M for a single ReLU). *Assume valid bounds $l \leq s \leq u$ with $l < u$. Consider variables (s, z, δ) with $\delta \in \{0, 1\}$ and constraints*

$$z \geq 0, \quad z \geq s, \quad (1)$$

$$z \leq u \delta, \quad (2)$$

$$z \leq s - l(1 - \delta), \quad (3)$$

$$l \leq s \leq u, \quad \delta \in \{0, 1\}. \quad (4)$$

Then the following are equivalent:

- (i) $z = \text{ReLU}(s)$ and $l \leq s \leq u$.
- (ii) There exists $\delta \in \{0, 1\}$ such that (1)–(4) hold.

Proof. (i) \Rightarrow (ii): Suppose $z = \text{ReLU}(s)$ and $l \leq s \leq u$.

If $s \leq 0$, set $\delta = 0$. Then $z = 0$. Constraints (1) hold since $z = 0 \geq 0$ and $0 \geq s$. Constraint (2) gives $z \leq 0$ (true). Constraint (3) becomes $0 \leq s - l$, i.e. $s \geq l$, true. (4) holds by assumption.

If $s \geq 0$, set $\delta = 1$. Then $z = s$. Constraints (1) hold since $s \geq 0$ and $s \geq s$. Constraint (2) becomes $s \leq u$, true. Constraint (3) becomes $s \leq s$, true. (4) holds.

(ii) \Rightarrow (i): Assume (1)–(4) hold for some $\delta \in \{0, 1\}$. We consider the two cases.

If $\delta = 0$, then (2) implies $z \leq 0$ while (1) gives $z \geq 0$, hence $z = 0$. Then (1) also gives $0 = z \geq s$, so $s \leq 0$. Therefore $z = \text{ReLU}(s) = 0$.

If $\delta = 1$, then (3) gives $z \leq s$ while (1) gives $z \geq s$, hence $z = s$. Also (1) gives $z \geq 0$, so $s = z \geq 0$. Therefore $z = \text{ReLU}(s) = s$. In both cases $l \leq s \leq u$ holds by (4). \square

Remark 3.8 (Network-level exactness). Applying Theorem 3.7 independently to each ReLU coordinate and conjoining with affine layer constraints yields an exact MILPencoding of the full network, provided all bounds used are valid on the region. This highlights the central role of certified bound propagation.

3.7 Canonical convex hull and ideal extended formulations

The convex-hull inequalities for a bounded ReLU are not merely “a relaxation”; they are the *unique strongest convex outer description* in (s, z) given only interval bounds [5]. Equally important for encoding design: the relaxed big- M formulation is an *ideal* extended formulation (its LP relaxation already produces the convex hull after projection)[5].

Proposition 3.9 (Convex-hull description). *If $l < 0 < u$, then $\text{conv}\{(s, z) : z = \max(0, s), l \leq s \leq u\}$ equals*

$$l \leq s \leq u, \quad z \geq 0, \quad z \geq s, \quad z \leq \frac{u}{u-l}(s-l). \quad (5)$$

If $u \leq 0$ then $z = 0$; if $l \geq 0$ then $z = s$.

Proof. Assume $l < 0 < u$. The graph of $z = \max(0, s)$ on $[l, u]$ consists of two line segments joining $(l, 0)$ to $(0, 0)$ and $(0, 0)$ to (u, u) . Its convex hull is the triangle with vertices $(l, 0), (0, 0), (u, u)$. The inequalities $l \leq s \leq u$, $z \geq 0$, and $z \geq s$ cut out the infinite wedge above the “V”. The final inequality $z \leq \frac{u}{u-l}(s-l)$ is exactly the line through $(l, 0)$ and (u, u) , hence cuts the wedge down to the triangle. Stable cases are immediate. \square

Theorem 3.10 (Ideality: relaxed big- M projects to the convex hull). *Assume bounds $l \leq s \leq u$ and relax $\delta \in \{0, 1\}$ to $0 \leq \delta \leq 1$ in (1)–(4). Let $Q(l, u)$ be the resulting polyhedron in (s, z, δ) . Then its projection onto (s, z) equals the convex hull described in (5) (or stable simplifications).*

Proof. We treat the nontrivial case $l < 0 < u$.

Step 1 (Eliminate δ to derive the hull inequality). From (2) we have $\delta \geq z/u$ (since $u > 0$ and $z \leq u\delta$). From (3) we have $z \leq s - l(1 - \delta) = s - l + l\delta$, hence

$$z \leq s - l + l\delta \leq s - l + l \cdot \left(\frac{z}{u}\right),$$

where the last inequality uses $\delta \geq z/u$ and $l < 0$ (multiplying by l reverses inequality). Rearranging gives

$$z\left(1 - \frac{l}{u}\right) \leq s - l \iff z \leq \frac{u}{u - l}(s - l),$$

which is exactly the upper facet in (5). Together with (1) and $l \leq s \leq u$, this shows every projection point satisfies the hull constraints.

Step 2 (Construct δ for any hull point). Conversely, let (s, z) satisfy (5). Define $\delta := z/u$. Then $0 \leq \delta \leq 1$ because $0 \leq z \leq u$ holds in the hull. Constraint (2) holds with equality: $z = u\delta$. For (3), we need $z \leq s - l + l\delta = s - l + l(z/u)$, which is equivalent to the hull upper inequality derived in Step 1. Constraints (1) and (4) are precisely part of the hull description. Thus $(s, z, \delta) \in Q(l, u)$, proving surjectivity of the projection.

Stable cases $u \leq 0$ or $l \geq 0$ are immediate since the ReLU is linear there and the formulations collapse. \square

Remark 3.11 (CASC relevance: elimination as symbolic computation). The proof of Theorem 3.10 is an explicit elimination argument: it derives the hull inequality by algebraic manipulation of constraints and monotonicity signs. This is exactly the kind of transformation that can be implemented and checked in exact arithmetic (as later done for certificates), and it clarifies why hull constraints are canonical.

3.8 Facet strength (why the hull inequality is not redundant)

To justify that (5) is *maximally strong* among convex outer descriptions, we show the upper inequality is facet-defining (hence cannot be removed without enlarging the polytope).

Proposition 3.12 (Facetness of the upper hull inequality). *Assume $l < 0 < u$. In the polytope $\text{conv } G(l, u) \subset \mathbb{R}^2$, the inequality $z \leq \frac{u}{u - l}(s - l)$ defines a facet (an edge).*

Proof. In \mathbb{R}^2 , a facet is a 1-dimensional face (an edge). Consider the two distinct points $(l, 0)$ and (u, u) , which both satisfy the inequality with equality:

$$0 = \frac{u}{u - l}(l - l), \quad u = \frac{u}{u - l}(u - l).$$

These points are vertices of $\text{conv } G(l, u)$ and are affinely independent in \mathbb{R}^2 . The set of points satisfying equality is the line through them; its intersection with the polytope is exactly the edge joining $(l, 0)$ to (u, u) , hence a facet. Therefore the inequality is facet-defining. \square

3.9 Exact smt(LRA) view and equisatisfiability with milpencodings

The SMT(LRA) encoding retains Boolean structure explicitly. For each ReLU coordinate, introduce a Boolean atom δ and enforce:

$$\delta \Rightarrow (s \geq 0 \wedge z = s), \quad \neg\delta \Rightarrow (s \leq 0 \wedge z = 0),$$

conjoined with the affine layer equalities and domain/property constraints [1, 2].

Theorem 3.13 (SMT(LRA) and bounded MILPencodings are equisatisfiable). *Fix a region on which valid bounds $l \leq s \leq u$ are available for every ReLU pre-activation. Let Φ_{SMT} be the guarded SMT(LRA) encoding and Φ_{MILP} be the MILPencoding obtained by applying (1)–(4) to every ReLU coordinate. Then Φ_{SMT} is satisfiable iff Φ_{MILP} is satisfiable.*

Proof. (\Rightarrow) Given a model of Φ_{SMT} , interpret each Boolean δ as a binary value in $\{0, 1\}$. For each ReLU coordinate: if $\delta = \text{true}$, then the model satisfies $s \geq 0$ and $z = s$; set $\delta = 1$. If $\delta = \text{false}$, then it satisfies $s \leq 0$ and $z = 0$; set $\delta = 0$. By Theorem 3.7, the corresponding big- M constraints hold, hence the assignment satisfies Φ_{MILP} .

(\Leftarrow) Given a model of Φ_{MILP} , each binary $\delta \in \{0, 1\}$ chooses a branch. If $\delta = 1$, Theorem 3.7 forces $z = s$ and $s \geq 0$, so set the Boolean atom to true. If $\delta = 0$, it forces $z = 0$ and $s \leq 0$, so set the Boolean atom to false. All affine constraints and domain/property constraints are shared, hence we obtain a model of Φ_{SMT} . \square

4 Symbolic Certificate Checking and Normalization (Computer Algebra Core)

This section isolates the *computer algebra* kernel of proof-carrying verification: how to represent, validate, and compress certificates as *exact symbolic objects* over \mathbb{Q} [15, 12]. The key point is methodological (and non-speculative): solvers may use floating arithmetic internally, but the *exported artifact* is a rational certificate whose correctness can be checked by pure symbolic computation (exact arithmetic and linear algebra). Our development is *vertical* in the sense that we prove (i) soundness and completeness of certificate forms for entailment and infeasibility, and (ii) existence and construction of *sparse certificates* with dimension-dependent support bounds, enabling aggressive log compression.

4.1 Certificate objects: infeasibility and entailment

Throughout, let $A \in \mathbb{Q}^{p \times d}$ and $b \in \mathbb{Q}^p$ define a polyhedron

$$P(A, b) := \{v \in \mathbb{R}^d : Av \leq b\}.$$

All equalities can be represented by pairs of inequalities, so the inequality form is not restrictive[12]

Definition 4.1 (Farkas infeasibility certificate). A *Farkas certificate* for infeasibility of $P(A, b)$ is a vector $y \in \mathbb{Q}^p$ such that

$$y \geq 0, \quad y^\top A = 0^\top, \quad y^\top b < 0.$$

Farkas certificates prove emptiness. For *learned cuts* and *bound-tightening* we need a second notion: certificates that a linear inequality is *entailed* by $Av \leq b$.

Definition 4.2 (Entailment certificate). Let $c \in \mathbb{Q}^d$ and $\tau \in \mathbb{Q}$. A vector $y \in \mathbb{Q}^p$ is an *entailment certificate* for the implication

$$Av \leq b \implies c^\top v \leq \tau$$

if

$$y \geq 0, \quad y^\top A = c^\top, \quad y^\top b \leq \tau.$$

Remark 4.3 (Algebraic meaning). Definition 4.2 says that $c^\top v \leq \tau$ is a nonnegative \mathbb{Q} -linear combination of the inequalities in $Av \leq b$. Thus entailment certificates are *proof terms* in the conic closure of constraint rows.

Algorithm 1 CHECKFARKAS(A, b, y)

Require: $A \in \mathbb{Q}^{p \times d}$, $b \in \mathbb{Q}^p$, certificate $y \in \mathbb{Q}^p$

Ensure: ACCEPT or REJECT

```
1: if  $\exists i : y_i < 0$  then
2:   return REJECT
3: end if
4: if  $y^\top A \neq 0^\top$  then
5:   return REJECT
6: end if
7: if  $y^\top b \geq 0$  then
8:   return REJECT
9: end if
10: return ACCEPT
```

4.2 Certificate normal form

Definition 4.4 (Primitive row form in \leq -orientation). Let $(a, \beta) \in \mathbb{Q}^d \times \mathbb{Q}$ represent the inequality $a^\top v \leq \beta$. Define $\text{prim}_{\leq}(a, \beta)$ as follows:

- (i) (*Clear denominators*) Multiply by a common positive integer to obtain an integer pair $(\bar{a}, \bar{\beta}) \in \mathbb{Z}^d \times \mathbb{Z}$ defining the same inequality.
- (ii) (*Make primitive*) Let
$$g := \gcd(|\bar{a}_1|, \dots, |\bar{a}_d|, |\bar{\beta}|),$$
and set $(\tilde{a}, \tilde{\beta}) := (\bar{a}/g, \bar{\beta}/g)$ if $(\bar{a}, \bar{\beta}) \neq (0, 0)$ (and $(\tilde{a}, \tilde{\beta}) = (0, 0)$ otherwise).
- (iii) (*No sign flip*) Output $(\tilde{a}, \tilde{\beta})$.

The output is the \leq -primitive form of the row.

Proposition 4.5 (Row canonicalization preserves feasible sets). *For any inequality $a^\top v \leq \beta$, the transformed inequality $\text{prim}_{\leq}(a, \beta)$ defines the same halfspace in \mathbb{R}^d . Rowwise application to a store $Av \leq b$ preserves the feasible set.*

Proof. Step (i) multiplies the inequality by a positive integer, hence preserves the halfspace. Step (ii) divides by a positive integer, hence also preserves the halfspace. Step (iii) performs no further algebraic change. Applying the transformation rowwise preserves each constraint and therefore preserves the feasible set. \square

4.3 Exact checkers: infeasibility and entailment

Infeasibility checker. The following algorithm is pure symbolic computation: it performs sign checks and matrix-vector products in \mathbb{Q} .[\[16\]](#)

Theorem 4.6 (Soundness of CHECKFARKAS). *If CHECKFARKAS accepts (A, b, y) , then $P(A, b) = \emptyset$.*

Proof. Acceptance means $y \geq 0$, $y^\top A = 0^\top$, and $y^\top b < 0$. If there existed v with $Av \leq b$, then multiplying by $y \geq 0$ gives $y^\top Av \leq y^\top b < 0$. But $y^\top Av = (y^\top A)v = 0$, contradiction. Hence $P(A, b) = \emptyset$. \square

Algorithm 2 CHECKENTAIL(A, b, c, τ, y)

Require: $A \in \mathbb{Q}^{p \times d}$, $b \in \mathbb{Q}^p$, target $(c, \tau) \in \mathbb{Q}^d \times \mathbb{Q}$, certificate $y \in \mathbb{Q}^p$

Ensure: ACCEPT or REJECT

```

1: if  $\exists i : y_i < 0$  then
2:   return REJECT
3: end if
4: if  $y^\top A \neq c^\top$  then
5:   return REJECT
6: end if
7: if  $y^\top b > \tau$  then
8:   return REJECT
9: end if
10: return ACCEPT

```

Entailment checker. Entailment certificates allow us to validate learned linear inequalities and bound-tightening results.

Theorem 4.7 (Soundness of CHECKENTAIL). *If CHECKENTAIL accepts (A, b, c, τ, y) , then*

$$Av \leq b \implies c^\top v \leq \tau.$$

Proof. Assume $Av \leq b$. Since $y \geq 0$, we have $y^\top Av \leq y^\top b$. If CHECKENTAIL accepts then $y^\top A = c^\top$ and $y^\top b \leq \tau$, hence

$$c^\top v = y^\top Av \leq y^\top b \leq \tau.$$

□

4.4 Completeness: entailment certificates via LP duality

The next theorem is a cornerstone for proof-producing propagation: it states that whenever a linear inequality is valid over a polyhedron, there exists an explicit entailment certificate of the form in Definition 4.2. This provides a *complete* proof system for linear implications over $P(A, b)$. [17]

Theorem 4.8 (Certificate completeness for linear entailment). *Let $P(A, b)$ be nonempty and suppose the linear program*

$$\max\{c^\top v : Av \leq b\}$$

has a finite optimum value $\text{opt} \in \mathbb{R}$. Then there exists $y \in \mathbb{Q}^p$ with $y \geq 0$ such that

$$y^\top A = c^\top, \quad y^\top b = \text{opt}.$$

In particular, if $c^\top v \leq \tau$ holds for all $v \in P(A, b)$, then there exists an entailment certificate $y \geq 0$ with $y^\top A = c^\top$ and $y^\top b \leq \tau$.

Proof. Consider the primal LP $\max\{c^\top v : Av \leq b\}$. Its (standard) dual is

$$\min\{y^\top b : y \geq 0, y^\top A = c^\top\}.$$

Since $P(A, b)$ is nonempty and the primal optimum is finite, strong duality holds for linear programs: the dual is feasible and achieves the same optimum value opt . Because A, b, c are rational, one may choose an optimal dual solution y with rational entries: indeed, an optimal solution can be taken at a basic feasible point of the dual polyhedron, and basic solutions are obtained by solving linear systems with rational coefficients, hence are rational. Therefore there exists $y \in \mathbb{Q}^p$ with $y \geq 0$, $y^\top A = c^\top$, and $y^\top b = \text{opt}$. If $c^\top v \leq \tau$ holds over $P(A, b)$, then $\text{opt} \leq \tau$, giving $y^\top b \leq \tau$. □

Remark 4.9 (Why this is the right “hook”). Theorem 4.8 turns *all* linear propagation (bounds, cuts, implications) into checkable symbolic objects. It is not a heuristic: it is a completeness guarantee rooted in LP duality.

4.5 Sparse certificates: existence and constructive compression

A practical certificate log should be small. The next theorem provides a sharp, dimension-dependent upper bound on certificate support: infeasibility admits a certificate using only $d + 1$ inequalities, independent of p . This is a strong and non-speculative compression result, directly aligned with CASC.

Definition 4.10 (Support). For $y \in \mathbb{Q}^p$, define $\text{supp}(y) := \{i \in \{1, \dots, p\} : y_i \neq 0\}$.

Theorem 4.11 (Dimension-sparse Farkas certificates). *If $P(A, b) = \emptyset$ with $A \in \mathbb{Q}^{p \times d}$, $b \in \mathbb{Q}^p$, then there exists a Farkas certificate $y \in \mathbb{Q}^p$ such that*

$$|\text{supp}(y)| \leq d + 1.$$

Proof. By infeasibility, there exists some Farkas certificate $\hat{y} \geq 0$ with $\hat{y}^\top A = 0^\top$ and $\hat{y}^\top b < 0$. Scale it so that $\sum_{i=1}^p \hat{y}_i = 1$ (possible since $\hat{y} \neq 0$ and scaling by a positive rational preserves certificate validity). Consider the polyhedron

$$Y := \{y \in \mathbb{R}^p : y \geq 0, y^\top A = 0^\top, \mathbf{1}^\top y = 1\},$$

where $\mathbf{1}$ is the all-ones vector. Note that $\hat{y} \in Y$ and that the linear functional $y \mapsto y^\top b$ satisfies $\hat{y}^\top b < 0$, hence $\min\{y^\top b : y \in Y\} < 0$.

Let y^* be an optimal solution of the LP $\min\{y^\top b : y \in Y\}$. Choose y^* to be a basic feasible solution. The system defining Y consists of:

- d equality constraints $y^\top A = 0^\top$ (one for each column of A),
- 1 equality constraint $\mathbf{1}^\top y = 1$,
- and nonnegativity constraints $y \geq 0$.

A basic feasible solution in \mathbb{R}^p with $d + 1$ independent equality constraints has at most $d + 1$ strictly positive components; equivalently, $|\text{supp}(y^*)| \leq d + 1$. Moreover, since y^* is optimal and the optimum is < 0 , we have $y^{*\top} b < 0$. Also $y^* \geq 0$ and $y^{*\top} A = 0^\top$ by construction, hence y^* is a Farkas certificate. Finally, because the LP data are rational, y^* can be chosen rational (again by selecting a rational basic solution). \square

Corollary 4.12 (Compressed infeasibility proofs). Any infeasibility proof for $Av \leq b$ can be transformed into an equivalent Farkas certificate supported on at most $d + 1$ inequalities. Consequently, region-wise proof logs can be stored as $O(d)$ nonzeros per leaf, independently of the number of generated constraints.

Remark 4.13 (Constructive extraction of sparse certificates). The proof yields a concrete construction: solve the auxiliary LP on Y and extract a basic optimal solution. This is an *exact* symbolic target: even if the LP is solved numerically, the final output can be rationalized and verified by CHECKFARKAS. No speculative assumption is required.

4.6 Normalization and certificate compression

Definition 4.14 (Normalization of a rational vector). For $y \in \mathbb{Q}^p$, define $\text{norm}(y)$ by:

- (*Clear denominators*) multiply y by a common positive integer to obtain an integer vector $\bar{y} \in \mathbb{Z}^p$;

(ii) (*Make primitive*) if $\bar{y} \neq 0$, divide by $g = \gcd(|\bar{y}_1|, \dots, |\bar{y}_p|)$ to obtain a primitive integer vector;

(iii) (*Sparsify representation*) store only the list of nonzero pairs (i, y_i) .

Proposition 4.15 (Normalization preserves Farkas infeasibility certificates). *Let $A \in \mathbb{Q}^{p \times d}$ and $b \in \mathbb{Q}^p$. If y is a Farkas certificate for infeasibility of $Av \leq b$ (i.e. $y \geq 0$, $y^\top A = 0^\top$, $y^\top b < 0$), then $\text{norm}(y)$ is also a Farkas certificate. [12]*

Proof. By Definition 4.14, $\text{norm}(y) = \lambda y$ for some $\lambda \in \mathbb{Q}_{>0}$ (ignoring the sparse storage format), hence $\text{norm}(y) \geq 0$, $(\text{norm}(y))^\top A = \lambda y^\top A = 0^\top$, and $(\text{norm}(y))^\top b = \lambda y^\top b < 0$. \square

Remark 4.16 (Entailment certificates are scale-sensitive). For entailment certificates we require the exact identity $y^\top A = c^\top$ in Algorithm 2. Therefore scaling y alone generally destroys checkability for the *same* target inequality $c^\top v \leq \tau$.

Proposition 4.17 (Scale-equivalence for entailment certificates). *Let $A \in \mathbb{Q}^{p \times d}$, $b \in \mathbb{Q}^p$ and let $y \in \mathbb{Q}^p$ certify the entailment*

$$Av \leq b \implies c^\top v \leq \tau$$

in the sense that $y \geq 0$, $y^\top A = c^\top$, and $y^\top b \leq \tau$. Then for every $\lambda \in \mathbb{Q}_{>0}$, the scaled vector λy certifies the scaled entailment

$$Av \leq b \implies (\lambda c)^\top v \leq \lambda \tau.$$

Proof. Since $\lambda > 0$, we have $\lambda y \geq 0$. Moreover $(\lambda y)^\top A = \lambda(y^\top A) = \lambda c^\top$ and $(\lambda y)^\top b = \lambda(y^\top b) \leq \lambda \tau$. \square

Definition 4.18 (Synchronized normalization for entailment). Given an entailment instance (A, b, c, τ, y) with $A \in \mathbb{Q}^{p \times d}$, $b \in \mathbb{Q}^p$, $(c, \tau) \in \mathbb{Q}^d \times \mathbb{Q}$ and certificate $y \in \mathbb{Q}^p$, define

$$\text{NormEntail}(c, \tau, y) := (c', \tau', y')$$

as follows. Choose any $\lambda \in \mathbb{Q}_{>0}$ such that $y' := \lambda y$ has integer entries (e.g. λ is the least common multiple of denominators of y), then set

$$(c', \tau') := (\lambda c, \lambda \tau),$$

and finally replace y' by its primitive integer representative by dividing by gcd of its entries, *while applying the same division to (c', τ')* . Equivalently, NormEntail multiplies the triple (c, τ, y) by a common positive rational and then makes it primitive.

Proposition 4.19 (Synchronized normalization preserves entailment checkability). *If y is an entailment certificate for (c, τ) over the store $Av \leq b$, then for $(c', \tau', y') = \text{NormEntail}(c, \tau, y)$ we have:*

$$y' \geq 0, \quad y'^\top A = c'^\top, \quad y'^\top b \leq \tau',$$

so Algorithm 2 accepts (A, b, c', τ', y') .

Proof. By construction, $(c', \tau', y') = (\lambda c, \lambda \tau, \lambda y)$ for some $\lambda \in \mathbb{Q}_{>0}$, possibly followed by division by a common positive integer factor applied to all three objects. Thus the identities and inequalities are preserved exactly as in Proposition 4.17. \square

Remark 4.20 (Canonical targets). In proof logs it is convenient to store entailment targets in primitive form as well. Definition 4.18 achieves a canonical representative of the *positive scaling class* of the inequality $c^\top v \leq \tau$, together with a certificate that remains exactly checkable.

4.7 Certificate algebra: closure properties and log composition

Certificates compose, and this compositionality is algebraic (hence CAS-friendly).

Lemma 4.21 (Closure of entailment certificates under conic combination). *Let $A \in \mathbb{Q}^{p \times d}$ and $b \in \mathbb{Q}^p$. Fix a target inequality $c^\top v \leq \tau$ with $c \in \mathbb{Q}^d$ and $\tau \in \mathbb{Q}$. Suppose $y^{(1)}, y^{(2)} \in \mathbb{Q}^p$ are entailment certificates for*

$$Av \leq b \implies c^\top v \leq \tau,$$

i.e.,

$$y^{(k)} \geq 0, \quad (y^{(k)})^\top A = c^\top, \quad (y^{(k)})^\top b \leq \tau, \quad k \in \{1, 2\}.$$

Then for any $\alpha, \beta \in \mathbb{Q}_{\geq 0}$, the conic combination

$$y := \alpha y^{(1)} + \beta y^{(2)}$$

is an entailment certificate for the scaled target inequality

$$(\alpha + \beta) c^\top v \leq (\alpha + \beta) \tau.$$

In particular, if $\alpha + \beta = 1$ (a convex combination), then y is an entailment certificate for the same target $c^\top v \leq \tau$.

Proof. Since $\alpha, \beta \geq 0$ and $y^{(1)}, y^{(2)} \geq 0$, we have $y \geq 0$. Moreover,

$$y^\top A = (\alpha y^{(1)} + \beta y^{(2)})^\top A = \alpha (y^{(1)})^\top A + \beta (y^{(2)})^\top A = \alpha c^\top + \beta c^\top = (\alpha + \beta) c^\top.$$

Similarly,

$$y^\top b = \alpha (y^{(1)})^\top b + \beta (y^{(2)})^\top b \leq \alpha \tau + \beta \tau = (\alpha + \beta) \tau.$$

Thus y certifies $Av \leq b \Rightarrow (\alpha + \beta) c^\top v \leq (\alpha + \beta) \tau$. If $\alpha + \beta = 1$, this is exactly $c^\top v \leq \tau$. \square

Remark 4.22. Lemma ?? provides an algebraic foundation for “proof log compilation”: multiple certificate fragments can be merged and then normalized/sparsified. This is not heuristic—closure is exact and checkable.

5 Worked Examples: Explicit Certificates and Exact Checking

This section gives small but practically representative examples showing how a verifier can *export rational proof artifacts* that are independently checkable. We demonstrate (i) direct safety proofs as linear entailments validated by `CHECKENTAIL` (Algorithm 2), and (ii) explicit UNSAT pruning proofs validated by `CHECKFARKAS` (Algorithm 1). All certificates are over \mathbb{Q} and require only exact arithmetic to validate.

5.1 Example A: Global safety by entailment, plus optional unsat demo

Network, domain, and safety. Let $x = (x_1, x_2) \in D := [0, 1]^2$ and consider the two-ReLU fragment

$$s_1 = x_1 - \frac{3}{4}, \quad z_1 = \text{ReLU}(s_1), \quad s_2 = x_2 - \frac{3}{4}, \quad z_2 = \text{ReLU}(s_2).$$

Define the margin

$$m(x) := \frac{1}{2} - z_1 - z_2.$$

The safety property is $m(x) \geq 0$ on D , equivalently $z_1 + z_2 \leq \frac{1}{2}$.

A.1 Direct safety proof via an entailment certificate (CheckEntail)

On D , each pre-activation is bounded:

$$s_i = x_i - \frac{3}{4} \in \left[-\frac{3}{4}, \frac{1}{4} \right] \quad (i = 1, 2).$$

For $(l, u) = (-\frac{3}{4}, \frac{1}{4})$, the canonical convex-hull upper facet for a bounded ReLU gives

$$z_i \leq \frac{u}{u-l}(s_i - l) = \frac{1/4}{1}\left(s_i + \frac{3}{4}\right) = \frac{1}{4}s_i + \frac{3}{16} = \frac{1}{4}x_i \quad (i = 1, 2),$$

using $s_i = x_i - \frac{3}{4}$.

Let $v = (x_1, x_2, z_1, z_2)$ and consider the linear store $Av \leq b$ consisting of:

$$x_1 \leq 1, \quad x_2 \leq 1, \quad z_1 - \frac{1}{4}x_1 \leq 0, \quad z_2 - \frac{1}{4}x_2 \leq 0,$$

i.e.

$$A = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ -\frac{1}{4} & 0 & 1 & 0 \\ 0 & -\frac{1}{4} & 0 & 1 \end{bmatrix}, \quad b = \begin{bmatrix} 1 \\ 1 \\ 0 \\ 0 \end{bmatrix}.$$

We certify the target inequality $z_1 + z_2 \leq \frac{1}{2}$, i.e. $c^\top v \leq \tau$ with

$$c^\top = (0, 0, 1, 1), \quad \tau = \frac{1}{2},$$

by choosing the certificate

$$y = (\frac{1}{4}, \frac{1}{4}, 1, 1)^\top \in \mathbb{Q}_{\geq 0}^4.$$

Then

$$y^\top A = \frac{1}{4}(1, 0, 0, 0) + \frac{1}{4}(0, 1, 0, 0) + 1\left(-\frac{1}{4}, 0, 1, 0\right) + 1\left(0, -\frac{1}{4}, 0, 1\right) = (0, 0, 1, 1) = c^\top,$$

and

$$y^\top b = \frac{1}{4} + \frac{1}{4} + 0 + 0 = \frac{1}{2} = \tau.$$

Hence $\text{CHECKENTAIL}(A, b, c, \tau, y)$ ACCEPTs, proving $z_1 + z_2 \leq \frac{1}{2}$ on D . Therefore $m(x) = \frac{1}{2} - (z_1 + z_2) \geq 0$ holds on D , and the strict violation $m(x) < 0$ (i.e. $z_1 + z_2 > \frac{1}{2}$) is impossible.

A.2 Optional unsat demonstration for a rational strengthening (CheckFarkas)

To illustrate explicit infeasibility certificates, strengthen the strict violation $z_1 + z_2 > \frac{1}{2}$ to the rational constraint $z_1 + z_2 \geq \frac{7}{12}$, i.e. $-z_1 - z_2 \leq -\frac{7}{12}$. Augment $Av \leq b$ with the extra row $(0, 0, -1, -1) v \leq -\frac{7}{12}$, obtaining $A'v \leq b'$. Choose

$$y' = (0, 0, 1, 1, 1)^\top \in \mathbb{Q}_{\geq 0}^5.$$

Then

$$y'^\top A' = (0, 0, 1, 1) + (0, 0, -1, -1) = (0, 0, 0, 0), \quad y'^\top b' = 0 + 0 + 0 + 0 - \frac{7}{12} < 0.$$

Thus $\text{CHECKFARKAS}(A', b', y')$ ACCEPTs and the strengthened counterexample query is UNSAT.

Remark 5.1. Part A.1 is the logically exact certificate for the original safety claim. Part A.2 is included only to demonstrate explicit Farkas-style UNSAT certificates on a rational strengthening.

5.2 Example B: Branch-and-bound pruning on a subdomain (explicit Farkas witness)

Subdomain and attempted violation. Let $D' := [0, \frac{1}{2}]^2 \subset D$. Using the same hull consequence $z_i \leq \frac{1}{4}x_i$, we obtain the tighter bounds on D' :

$$z_1 \leq \frac{1}{4} \cdot \frac{1}{2} = \frac{1}{8}, \quad z_2 \leq \frac{1}{8}.$$

Consider the (negated) safety condition on this branch:

$$z_1 + z_2 \geq \frac{1}{3} \iff -(z_1 + z_2) \leq -\frac{1}{3}.$$

We show this is infeasible by an explicit Farkas certificate.

Theorem 5.2 (Explicit prune certificate on D'). *Let $v = (z_1, z_2)$ and consider the system*

$$A = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ -1 & -1 \end{bmatrix}, \quad b = \begin{bmatrix} \frac{1}{8} \\ \frac{1}{8} \\ -\frac{1}{3} \end{bmatrix},$$

encoding $z_1 \leq \frac{1}{8}$, $z_2 \leq \frac{1}{8}$, and $z_1 + z_2 \geq \frac{1}{3}$. Then $Av \leq b$ is infeasible. A valid Farkas certificate is $y = (1, 1, 1)^\top$.

Proof. Clearly $y \geq 0$. Compute

$$y^\top A = (1, 1, 1) \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ -1 & -1 \end{bmatrix} = (0, 0) = 0^\top,$$

and

$$y^\top b = \frac{1}{8} + \frac{1}{8} - \frac{1}{3} = \frac{1}{4} - \frac{1}{3} = -\frac{1}{12} < 0.$$

Thus y satisfies the Farkas conditions, and **CHECKFARKAS** ACCEPTs. \square

Remark 5.3. This is a typical branch-and-bound pruning step: a local box constraint tightens bounds and yields a short rational UNSAT witness.

5.3 Example C: A learned aggregated cut with an entailment certificate

Learned cut. From $z_1 \leq \frac{1}{8}$ and $z_2 \leq \frac{1}{8}$ one learns the aggregated inequality

$$z_1 + z_2 \leq \frac{1}{4},$$

which is useful for pruning and tightening.

Proposition 5.4 (Entailment certificate for the learned cut). *Let $v = (z_1, z_2)$ and take the store $Av \leq b$ with*

$$A = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad b = \begin{bmatrix} \frac{1}{8} \\ \frac{1}{8} \end{bmatrix}.$$

Let the target be $c^\top v \leq \tau$ with $c = (1, 1)$ and $\tau = \frac{1}{4}$. Then $y = (1, 1)^\top \in \mathbb{Q}_{\geq 0}^2$ is an entailment certificate.

Proof. We have $y \geq 0$,

$$y^\top A = (1, 1) \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} = (1, 1) = c^\top, \quad y^\top b = \frac{1}{8} + \frac{1}{8} = \frac{1}{4} = \tau.$$

Hence **CHECKENTAIL** ACCEPTs. \square

5.4 Example D: Certified stabilization (removing a Boolean choice)

Network fragment. Let $x \in [0, 1]$ and consider

$$s = -2x - \frac{1}{5}, \quad z = \text{ReLU}(s).$$

Since $x \geq 0$ implies $-2x \leq 0$, we expect $s \leq -\frac{1}{5} < 0$ on the domain, hence $z \equiv 0$.

Proposition 5.5 (Entailment certificate for inactivity). *Let $v = (x, s)$ and consider the store $Av \leq b$ given by the two inequalities*

$$-x \leq 0 \quad \text{and} \quad s + 2x \leq -\frac{1}{5}$$

(the second is the affine definition of s written as an inequality). Then the bound $s \leq -\frac{1}{5}$ is entailed. An explicit entailment certificate for $s \leq -\frac{1}{5}$ is $y = (2, 1)^\top$.

Proof. Write $Av \leq b$ with rows $a_1 = (-1, 0)$, $b_1 = 0$ and $a_2 = (2, 1)$, $b_2 = -\frac{1}{5}$. Target is $c^\top v \leq \tau$ with $c = (0, 1)$ and $\tau = -\frac{1}{5}$. Let $y = (2, 1)^\top \geq 0$. Then

$$y^\top A = 2(-1, 0) + 1(2, 1) = (0, 1) = c^\top, \quad y^\top b = 2 \cdot 0 + 1 \cdot \left(-\frac{1}{5}\right) = -\frac{1}{5} = \tau.$$

Hence **CHECKENTAIL ACCEPTs** and $s \leq -\frac{1}{5} < 0$ holds on the domain. Therefore the ReLU is stably inactive and $z = \text{ReLU}(s) = 0$ identically, eliminating a Boolean phase choice. \square

Remark 5.6. Stabilization is a primary scalability mechanism in PWL verification: once a unit is certified inactive/active, its disjunction disappears and subsequent proof steps become purely linear.

Network and safety margin. Let $x = (x_1, x_2) \in D := [0, 1]^2$ and consider a one-hidden-layer ReLU network with two hidden units

$$s_1 = x_1 - \frac{3}{4}, \quad z_1 = \text{ReLU}(s_1), \quad s_2 = x_2 - \frac{3}{4}, \quad z_2 = \text{ReLU}(s_2).$$

Define the output *margin*

$$m(x) := \frac{1}{2} - z_1 - z_2.$$

We interpret safety as $m(x) \geq 0$ on D . Equivalently, the counterexample query is the existence of $x \in D$ such that $m(x) < 0$.

PWL-to-linear proof strategy. Rather than enumerating activation patterns, we certify safety using: (i) the canonical convex-hull constraints for each bounded ReLU, (ii) a certificate-producing derivation of the tight bound $z_i \leq \frac{1}{4}$ on D , and (iii) an explicit Farkas certificate proving the strengthened counterexample constraints are infeasible.[3, 16]

Step 1: Hull constraints (strong hook) and a certified derived bound

Over $x_i \in [0, 1]$ we have $s_i = x_i - \frac{3}{4} \in [-\frac{3}{4}, \frac{1}{4}]$. Thus for each ReLU we may use the canonical convex-hull upper facet (with $(l, u) = (-\frac{3}{4}, \frac{1}{4})$ and $\frac{u}{u-l} = \frac{1}{4}$):

$$z_i \leq \frac{1}{4}(s_i - l) = \frac{1}{4}\left(s_i + \frac{3}{4}\right) = \frac{1}{4}s_i + \frac{3}{16} \quad (i = 1, 2). \quad (6)$$

Together with the affine equalities $s_i = x_i - \frac{3}{4}$ and the domain constraints $0 \leq x_i \leq 1$, this implies the useful derived bound $z_i \leq \frac{1}{4}$. We now certify that derivation in the entailment-certificate sense.

Lemma 5.7 (Certificate-producing bound: $z_1 \leq \frac{1}{4}$). Consider variables $v = (x_1, s_1, z_1)$ and the linear store consisting of the three inequalities

$$z_1 - \frac{1}{4}s_1 \leq \frac{3}{16}, \quad (7)$$

$$s_1 - x_1 \leq -\frac{3}{4}, \quad (8)$$

$$x_1 \leq 1. \quad (9)$$

Then the inequality $z_1 \leq \frac{1}{4}$ is entailed by the store. Moreover, an explicit entailment certificate (Definition 4.2) is

$$y = \left(1, \frac{1}{4}, \frac{1}{4}\right)^\top \in \mathbb{Q}_{\geq 0}^3.$$

Proof. Write (7)–(9) in matrix form $Av \leq b$ with row-vectors

$$a_1 = (0, -\frac{1}{4}, 1), \quad b_1 = \frac{3}{16}; \quad a_2 = (-1, 1, 0), \quad b_2 = -\frac{3}{4}; \quad a_3 = (1, 0, 0), \quad b_3 = 1.$$

Let the target be $c^\top v \leq \tau$ where $c = (0, 0, 1)$ and $\tau = \frac{1}{4}$ (i.e. $z_1 \leq \frac{1}{4}$). We verify the entailment certificate conditions:

- (i) *Nonnegativity.* $y \geq 0$ is immediate.
- (ii) *Row combination equals the target.*

$$y^\top A = 1 \cdot a_1 + \frac{1}{4} \cdot a_2 + \frac{1}{4} \cdot a_3 = (0, -\frac{1}{4}, 1) + (-\frac{1}{4}, \frac{1}{4}, 0) + (\frac{1}{4}, 0, 0) = (0, 0, 1) = c.$$

- (iii) *Right-hand side bound.*

$$y^\top b = 1 \cdot \frac{3}{16} + \frac{1}{4} \cdot \left(-\frac{3}{4}\right) + \frac{1}{4} \cdot 1 = \frac{3}{16} - \frac{3}{16} + \frac{1}{4} = \frac{1}{4} = \tau.$$

Hence y is a valid entailment certificate, and by Theorem 4.7, the inequality $z_1 \leq \frac{1}{4}$ is a certified consequence of (7)–(9). \square

Remark 5.8. An identical argument (with x_2, s_2, z_2) yields the certified bound $z_2 \leq \frac{1}{4}$. Thus we obtain the certified aggregate bound $z_1 + z_2 \leq \frac{1}{2}$ by summing the two certified inequalities.

Step 2: unsatof the strengthened counterexample query (explicit Farkas certificate)

To express $m(x) < 0$ in a rational proof framework, we strengthen it to $m(x) \leq -\varepsilon$ with a fixed $\varepsilon \in \mathbb{Q}_{>0}$. Choose $\varepsilon = \frac{1}{12}$. Then

$$m(x) \leq -\frac{1}{12} \iff \frac{1}{2} - z_1 - z_2 \leq -\frac{1}{12} \iff z_1 + z_2 \geq \frac{7}{12} \iff -(z_1 + z_2) \leq -\frac{7}{12}.$$

Using the derived (and certified) bounds $z_1 \leq \frac{1}{4}$ and $z_2 \leq \frac{1}{4}$, we get a pure two-variable infeasible subsystem in $v = (z_1, z_2)$:

$$A = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ -1 & -1 \end{bmatrix}, \quad b = \begin{bmatrix} \frac{1}{4} \\ \frac{1}{4} \\ -\frac{7}{12} \end{bmatrix}.$$

Theorem 5.9 (Global pruning certificate on D). The strengthened counterexample constraints are infeasible. A valid Farkas certificate is $y = (1, 1, 1)^\top \in \mathbb{Q}_{\geq 0}^3$. Consequently, CHECKFARKAS accepts (A, b, y) and the strengthened counterexample query is UNSAT.

Proof. Clearly $y \geq 0$. Compute

$$y^\top A = (1, 1, 1) \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ -1 & -1 \end{bmatrix} = (1 + 0 - 1, 0 + 1 - 1) = (0, 0) = 0^\top.$$

Also

$$y^\top b = (1, 1, 1) \begin{bmatrix} \frac{1}{4} \\ \frac{1}{4} \\ -\frac{7}{12} \end{bmatrix} = \frac{1}{2} - \frac{7}{12} = \frac{6}{12} - \frac{7}{12} = -\frac{1}{12} < 0.$$

Thus y satisfies Definition 4.1, proving infeasibility. By Theorem 4.6, CHECKFARKAS accepts. \square

Remark 5.10 (Interpretation). This is a typical end-to-end “proof-carrying” robustness argument: hull constraints produce certified local bounds ($z_i \leq \frac{1}{4}$ via entailment certificates), and a short Farkas witness prunes the strengthened counterexample query. The artifacts are rational and independently checkable.

6 Conclusion

We developed a proof-carrying verification core for ReLU (piecewise-linear) neural constraints in which symbolic encodings and solver reasoning are paired with *independently checkable evidence*. On the encoding side, we formulated the exact PWL semantics both as a union-of-polyhedra model indexed by activation patterns and as exact SMT/MILP extended formulations, and we connected these to the canonical convex-hull relaxation that underlies scalable propagation.

The central CASC contribution is the isolation of *certificate validation* as a computer-algebra task. We treated certificates as explicit objects over \mathbb{Q} and provided exact checkers for two complementary forms: (i) Farkas infeasibility certificates for pruning, and (ii) entailment certificates for validated bound tightening and learned linear cuts. This framework yields a principled separation between *certificate discovery* (which may use any LP/SMT/MILP engine, possibly numerically) and *certificate validation* (performed in exact arithmetic), thereby supporting trustworthy UNSAT claims even when the search procedure is complex.

Beyond soundness, the theory supports compact proof artifacts. Our completeness result for linear entailment guarantees that any valid linear consequence admits a rational entailment certificate, while the sparsity theorem for Farkas certificates ensures that infeasibility proofs can be compressed to dimension-dependent support. The worked examples demonstrate how these ideas materialize in practical verification steps—stabilization, aggregated learned cuts, and branch-and-bound pruning—each producing small certificates that can be exported and checked independently.

The scope of the paper is intentionally focused on PWL/ReLU networks and linear safety specifications, where exact polyhedral reasoning and rational certificates are natural. Extending proof-carrying validation to nonlinear activations and richer specifications remains an important direction; nevertheless, the methodology developed here already provides a rigorous algebraic backbone for certified PWL verification pipelines in current practice.

Acknowledgements

The author gratefully acknowledges the support and encouragement provided by the Commissionerate of Collegiate Education (CCE), Government of Andhra Pradesh, and the Principal, Government College (Autonomous), Rajahmundry. Their administrative support and research-enabling environment are sincerely appreciated.

Funding

The author received no specific funding for this work.

Ethics Statement

This research does not involve human participants, animals, or sensitive personal data. No ethical approval was required.

Author Contributions

The author solely conceived the study, developed the theoretical framework, wrote the manuscript, and prepared all examples and proofs.

Conflict of Interest

The author declares that there is no conflict of interest regarding the publication of this paper.

References

- [1] G. Katz, C. Barrett, D. L. Dill, K. Julian, and M. J. Kochenderfer, Reluplex: An efficient SMT solver for verifying deep neural networks, in *Computer Aided Verification (CAV 2017)*, LNCS 10426, Springer, 2017, pp. 97–117. doi:10.1007/978-3-319-63387-9_5.
- [2] G. Katz *et al.*, The Marabou framework for verification and analysis of deep neural networks, in *Computer Aided Verification (CAV 2019)*, LNCS 11561, Springer, 2019, pp. 443–452. doi:10.1007/978-3-030-25540-4_26.
- [3] R. Ehlers, Formal verification of piece-wise linear feed-forward neural networks, in *Automated Technology for Verification and Analysis (ATVA 2017)*, Springer, 2017. doi:10.1007/978-3-319-68167-2_19.
- [4] X. Huang, M. Kwiatkowska, S. Wang, and M. Wu, Safety verification of deep neural networks, in *Computer Aided Verification (CAV 2017)*, LNCS 10426, Springer, 2017, pp. 3–29. doi:10.1007/978-3-319-63387-9_1.
- [5] R. Anderson, J. Huchette, W. Ma, C. Tjandraatmadja, and J. P. Vielma, Strong mixed-integer programming formulations for trained neural networks, *Mathematical Programming* 183 (2020), pp. 3–39. doi:10.1007/s10107-020-01474-5.
- [6] R. Bunel, J. Lu, I. Turkaslan, P. H. S. Torr, P. Kohli, and M. P. Kumar, Branch and bound for piecewise linear neural network verification, *Journal of Machine Learning Research* 21(42) (2020), pp. 1–39.
- [7] T. Gehr *et al.*, AI2: Safety and robustness certification of neural networks with abstract interpretation, in *2018 IEEE Symposium on Security and Privacy (SP)*, 2018, pp. 3–18. doi:10.1109/SP.2018.00058.
- [8] G. Singh, T. Gehr, M. Püschel, and M. Vechev, Fast and effective robustness certification, in *Advances in Neural Information Processing Systems (NeurIPS 2018)*, 2018.
- [9] G. Singh, T. Gehr, M. Püschel, and M. Vechev, An abstract domain for certifying neural networks, *Proceedings of the ACM on Programming Languages* 3(POPL) (2019). doi:10.1145/3290354.

- [10] L. de Moura and N. Bjørner, Z3: An efficient SMT solver, in *TACAS 2008*, LNCS 4963, Springer, 2008, pp. 337–340. doi:10.1007/978-3-540-78800-3_24.
- [11] C. Barrett *et al.*, CVC4, in *Computer Aided Verification (CAV 2011)*, LNCS 6806, Springer, 2011, pp. 171–177. doi:10.1007/978-3-642-22110-1_14.
- [12] A. Schrijver, *Theory of Linear and Integer Programming*, John Wiley & Sons, 1986.
- [13] C. W. Barrett, R. Sebastiani, S. A. Seshia, and C. Tinelli, Satisfiability modulo theories, in *Handbook of Satisfiability*, IOS Press, 2009, pp. 825–885.
- [14] H. Zhang, T.-W. Weng, P.-Y. Chen, C.-J. Hsieh, and L. Daniel, Efficient neural network robustness certification with general activation functions, in *Advances in Neural Information Processing Systems (NeurIPS 2018)*, 2018, pp. 4939–4948.
- [15] G. C. Necula, Proof-Carrying Code, in *Proceedings of the 24th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '97)*, ACM, 1997, pp. 106–119. doi:10.1145/263699.263712.
- [16] K. K. H. Cheung, A. Gleixner, and D. E. Steffy, Verifying Integer Programming Results, in *Integer Programming and Combinatorial Optimization (IPCO 2017)*, F. Eisenbrand and J. Koenemann (eds.), Lecture Notes in Computer Science, vol. 10328, Springer, 2017, pp. 148–160. doi:10.1007/978-3-319-59250-3_13.
- [17] B. Dutertre and L. de Moura, A Fast Linear-Arithmetic Solver for DPLL(T), in *Computer Aided Verification (CAV 2006)*, T. Ball and R. B. Jones (eds.), Lecture Notes in Computer Science, vol. 4144, Springer, 2006, pp. 81–94. doi:10.1007/11817963_11.