

GUARDREASONER-OMNI: A REASONING-BASED MULTI-MODAL GUARDRAIL FOR TEXT, IMAGE, AND VIDEO

Zhenhao Zhu^{*1,2} Yue Liu^{*2} Yanpei Guo² Wenjie Qu² Cancan Chen³ Yufei He²
Yibo Li² Yulin Chen² Tianyi Wu² Huiying Xu⁴ Xinzhong Zhu⁴ Jiaheng Zhang²

¹Tsinghua University ²National University of Singapore

³Sun Yat-sen University ⁴Zhejiang Normal University

zhuzhenh22@mails.tsinghua.edu.cn

ABSTRACT

We present GuardReasoner-Omni, a reasoning-based guardrail model designed to moderate text, image, and video data. First, we construct a comprehensive training corpus comprising 148k samples spanning these three modalities. Our training pipeline follows a two-stage paradigm to incentivize the model to deliberate before making decisions: (1) conducting SFT to cold-start the model with explicit reasoning capabilities and structural adherence; and (2) performing RL, incorporating an error-driven exploration reward to incentivize deeper reasoning on hard samples. We release a suite of models scaled at 2B and 4B parameters. Extensive experiments demonstrate that GuardReasoner-Omni achieves superior performance compared to existing state-of-the-art baselines across various guardrail benchmarks. Notably, GuardReasoner-Omni (2B) significantly surpasses the runner-up by 5.3% F1 score.¹

Warning: This Paper Contains Potentially Harmful Content.

1 INTRODUCTION

The rapid evolution of multimodal large language models (MLLMs) (DeepMind, 2025a; Anthropic, 2025; OpenAI, 2025b) has revolutionized content generation across text (OpenAI, 2022), images (OpenAI, 2025a), and videos (DeepMind, 2025b). As these models are deployed in open-ended applications, ensuring their safety is paramount in safety-critical scenarios. Although text and image moderation have achieved remarkable success (Liu et al., 2025c; Zhao et al., 2025), video safety still remains a significant bottleneck in the pursuit of comprehensive content moderation due to the dynamic nature of the video data.

Current guardrail methods for video data can be generally categorized into two classes: 1) MLLM-based guardrail models and 2) video anomaly detection (VAD) models. Although effective, they struggle to address unified omni-modal moderation due to critical deficiencies as follows. First, the existing MLLM-based guardrail models lack temporal reasoning. While state-of-the-art safety models (Liu et al., 2025b; Chi et al., 2024) excel in static modalities like text and




Figure 1: **Performance Comparison of Multi-modal Guardrails.** The F1 score is calculated by averaging prompt and response harmfulness detection results. Note that for the video modality, we exclude the HarmTextVideo dataset to ensure a fair comparison with Holmes-VAU, which lacks support for text-video inputs.

^{*}Equal contribution.

¹Code: <https://github.com/zzh-thu-22/GuardReasoner-Omni>




Figure 2: **Overview of GuardReasoner-Omni.** The framework operates in three stages: (1) Dataset Curation: We curate the GuardReasoner-OmniTrain-148K dataset by distilling CoT reasoning traces from a teacher model and filtering for quality. (2) Cold-Start SFT: The model is fine-tuned to establish explicit reasoning capabilities and strict format compliance. (3) Reasoning Enhancement via GRPO: We first perform hard sample mining to identify inconsistent predictions. Subsequently, we optimize the model using GRPO with an error-driven exploration reward to incentivize deeper reasoning on these challenging cases.

image, their extension to video is often superficial. These models typically treat video as a mere sequence of static images, relying on frame-level aggregation to make decisions. This naive approach severs critical temporal dependencies, rendering the models blind to dynamic threats where safety violations emerge strictly from the sequential order of actions rather than from any single malicious frame, e.g., a step-by-step tutorial on assembling a dangerous device. Second, specialized VAD models suffer from scope limitation and reasoning opacity. Although VAD models (Joo et al., 2023; Majhi et al., 2025) capture temporal dynamics, they are predominantly confined to detecting specific physical anomalies (e.g., fighting, explosions) and lack the semantic versatility to handle complex, context-dependent safety policies. More critically, most of these models operate as black boxes directly mapping inputs to scalar anomaly scores without providing any text-based explanation. This lack of explicit justification creates a severe interpretability bottleneck, as human moderators cannot verify the rationale behind a flagged video, making the system difficult to trust and debug in real-world deployments.

To this end, we introduce GuardReasoner-Omni, a new guardrail model designed to moderate omni-modal contents by deliberatively reasoning across text, image, and video modalities. Rather than relying on static frame aggregation or opaque scoring, GuardReasoner-Omni employs explicit reasoning to trace temporal dynamics and articulate semantic justifications. This paradigm shift enables the model to simultaneously address both limitations: it captures the sequential context required to detect dynamic video threats and provides transparent rationales for its decisions. Concretely, to address the scarcity of multimodal reasoning data, we first curate GuardReasoner-OmniTrain, a 148k-sample corpus, covering text, image, and video modalities. For text and image modalities, we curate the training data from (Liu et al., 2025c). For video modal, we collect training data from (Sultani et al., 2019; Chen et al., 2025; Liu et al., 2025a; Maaz et al., 2024; Yeh et al., 2024; Wu et al., 2020) to cover a wide spectrum of threats. Then, we cold-start the model by leveraging teacher-distilled reasoning annotations, followed by refinement via rule-based filtering. Second, we robustify the model via reinforcement learning (RL) with group relative policy optimization (GRPO). To improve optimization efficiency and focus on ambiguous safety boundaries, we first conduct hard sample mining to identify challenging cases where the model exhibits inconsistent predictions. Building on these identified hard samples, we design an error-driven exploration reward to dynamically incentivize the model to explore deeper reasoning paths. Such a design effectively prevents the model from collapsing into superficial shortcuts when it encounters prediction errors. With these settings, GuardReasoner-Omni is guided to deliberate reasoning and then make a decision on content moderation. As shown in Figure 1, we observe that existing multimodal guardrails (e.g., LLaMA Guard

4) suffer from a catastrophic performance drop in the video domain (19.7% F1), while specialized VAD models (e.g., Holmes-VAU) are confined to a single modality. In contrast, GuardReasoner-Omni bridges this gap, achieving state-of-the-art performance across all modalities. Building on this observation, our extensive experiments demonstrate the consistent superiority and effectiveness of GuardReasoner-Omni. The main contributions of this paper are summarized as follows.

- We propose GuardReasoner-Omni, the first reasoning-based guardrail model capable of seamless moderation across text, image, and video data.
- We construct GuardReasoner-OmniTrain-148K, a large-scale dataset amalgamating diverse benchmarks to support training omni-modal guardrails.
- We introduce a two-stage paradigm synergizing SFT with GRPO. By incorporating hard sample mining and an error-driven exploration reward, our framework incentivizes deeper reasoning on failure cases.
- Extensive experiments demonstrate that GuardReasoner-Omni significantly outperforms existing state-of-the-art baselines, including specialized VAD models and general-purpose guardrails models.

2 METHODS

As illustrated in Figure 2, our methodology consists of a comprehensive dataset curation phase followed by a rigorous two-stage training paradigm: Cold-Start SFT and Reasoning Enhancement via GRPO.

2.1 DATASET CONSTRUCTION

Collection and Curation. To develop a robust multi-modal guardrail model capable of verifying text, images, and videos, we construct a comprehensive training dataset, denoted as GuardReasoner-OmniTrain, which amalgamates diverse modalities including pure text, pure image, text-image, pure video, and text-video pairs. For text and image modalities, we incorporate the GuardReasoner-VLTrain dataset, which provides high-quality safety-aligned samples. For the video, we aggregate samples from five established benchmarks to ensure broad coverage of harmful scenarios: UCF-Crime (Sultani et al., 2019), XD-Violence (Wu et al., 2020), SafeWatch-Bench (Chen et al., 2025), VHD (Yeh et al., 2024), and Video-ChatGPT (Maaz et al., 2024). To rigorously evaluate model performance, we strictly adhere to the official test splits for UCF-Crime and XD-Violence. For SafeWatch-Bench, VHD, and Video-ChatGPT, which lack standardized training splits, we merge their samples and randomly sample 20% to form a unified test set named HarmVideo. Similarly, for the text-video, we aggregate samples from Video-ChatGPT and Video-SafetyBench (Liu et al., 2025a), we also sample 20% for testing, designating the set as HarmTextVideo. This process resulted in a final training set of 148k samples (the detailed composition is illustrated in Figure 3).

CoT Annotation. To equip the model with explicit reasoning capabilities for safety analysis, we employ a distillation-based approach to generate CoT annotations. We utilize Qwen3-VL-235B-A22B, a state-of-the-art multimodal large language model, as the teacher model. Specifically, we design a prompt template (see Figure 6) that guides the teacher model to generate step-by-step reasoning traces before outputting the final safety verdict. After applying basic rule-based filtering to remove low quality or inconsistent outputs, we obtain a high-quality CoT dataset, which is used for the Cold-Start SFT stage.

2.2 COLD-START VIA SFT

In the first stage, we aim to cold-start the base model to generate explicit reasoning traces and follow a structured output format. Unlike standard guard models that process the input query or the model response in isolation, our framework moderates the interaction context. Specifically, given a user prompt (which may involve text, image, or video modalities) and the corresponding victim model’s response, the goal is to predict the safety label based on a generated reasoning process.

We construct the target output sequence to include the reasoning process wrapped in `<think>` tags, followed by the final result in `<result>` tags. Formally, let \mathcal{X} denote the multimodal user request




Figure 3: **Data composition of GuardReasoner-OmniTrain.** This dataset comprises 148k samples spanning different modalities. The chart illustrates the proportional distribution of each modality, along with the specific source benchmarks.

and \mathcal{S} represent the corresponding response from the victim model. We aim to train the guardrail model to generate a reasoning chain \mathcal{R} followed by a final safety label \mathcal{Y} . The objective function is formulated as follows.

$$\mathcal{L}_{SFT} = -\mathbb{E}_{(\mathcal{X}, \mathcal{S}, \mathcal{R}, \mathcal{Y}) \sim \mathcal{D}_{SFT}} [\log P_\theta(\mathcal{R}, \mathcal{Y} \mid \mathcal{X}, \mathcal{S})], \quad (1)$$

where θ denotes the model parameters and \mathcal{D}_{SFT} represents the GuardReasoner-OmniTrain. This stage ensures the model learns to deliberate before predicting, strictly adhering to the format.

2.3 REASONING ENHANCEMENT VIA GRPO

While SFT establishes basic capabilities, the model may still struggle with complex boundary cases. To bridge this gap, we employ GRPO to further enhance the reasoning ability regarding moderation.

2.3.1 HARD SAMPLE MINING

To improve data efficiency and focus optimization on challenging scenarios, we construct a hard-sample dataset derived from the SFT model’s performance on the training set. Specifically, for each input pair, we sample outputs from the SFT model. We retain a sample for the GRPO stage if and only if the predictions exhibit inconsistency, i.e., they are neither all correct nor all incorrect with respect to the ground truth. This selection criterion filters out trivial samples (where the model is already confident) and impossible samples (where the model lacks any relevant knowledge), ensuring the RL process focuses on samples near the decision boundary.

2.3.2 REWARD DESIGN.

A critical component is the design of the reward function, which guides the model to strictly follow the output format, accurately detect anomalies, and adaptively explore reasoning paths when encountering errors. The total reward for a generated response is defined as follows.

$$R = \mathbb{I}_{\text{fmt}} \cdot (R_{\text{acc}} + R_{\text{exp}}), \quad (2)$$

where \mathbb{I}_{fmt} is an indicator function for format compliance. Below, we detail each component:

Format Reward To ensure the output is parseable and adheres to the CoT structure, we enforce a strict format constraint. The model must encapsulate its reasoning process and the final prediction within tags.

Accuracy Reward. Our model performs dual-task moderation: detecting harmfulness in both the user’s request and the assistant’s response. We assign equal weights to both sub-tasks. Let y denote the ground-truth labels and let \hat{y} denote the model’s predictions. The accuracy reward is calculated as follows.

$$R_{\text{acc}} = 0.5 \cdot \mathbb{I}(\hat{y}_{\text{req}} = y_{\text{req}}) + 0.5 \cdot \mathbb{I}(\hat{y}_{\text{res}} = y_{\text{res}}), \quad (3)$$

where $\mathbb{I}(\cdot)$ is the indicator function.

Table 1: **F1 score (%) of 16 Models on 13 Benchmarks of Prompt Harmfulness Detection.** The **bold** and underlined values denote the best and the runner-up. “-” denotes that the result is unavailable. Detailed results on text and image benchmarks are presented in Table 4.

Method	Average (T & I)	UCF-crime	XD-Violence	FVC	HarmVideo	HarmTextVideo	Average (Video)	Average (All)
LLM Guard Models								
LLaMA Guard 3 8B	68.47	-	-	-	-	-	-	-
Aegis Guard Defensive 7B	72.99	-	-	-	-	-	-	-
Aegis Guard Permissive 7B	73.83	-	-	-	-	-	-	-
ShieldGemma 9B	68.77	-	-	-	-	-	-	-
WildGuard 7B	77.99	-	-	-	-	-	-	-
PolyGuard-Qwen 7B	79.53	-	-	-	-	-	-	-
Qwen3Guard Gen 8B (loose)	83.60	-	-	-	-	-	-	-
Qwen3Guard Gen 8B (strict)	76.41	-	-	-	-	-	-	-
GuardReasoner 8B	81.09	-	-	-	-	-	-	-
VAD Models								
HolmesVAD 7B	-	46.15	83.77	47.32	40.12	-	-	-
HolmesVAU 2B	-	82.47	95.92	63.51	76.71	-	-	-
VLM Guard Models								
LLaMA Guard 4 12B	51.05	9.33	17.79	17.39	20.94	50.78	24.59	42.27
GuardReasoner-VL 3B	78.67	70.07	83.74	61.32	72.37	87.86	75.59	77.65
GuardReasoner-VL 7B	79.36	73.75	85.79	61.58	73.58	88.49	76.88	78.54
GuardReasoner-Omni 2B	79.10	90.24	96.82	66.14	93.32	99.15	93.39	83.84
GuardReasoner-Omni 4B	77.17	91.67	95.71	67.86	95.50	99.47	94.84	<u>83.03</u>

Error-Driven Exploration Reward. Standard length penalties often discourage deep reasoning, while unconditional length rewards may lead to verbosity. We propose a error-driven exploration reward to encourage the model to think deeper specifically when it fails.

$$R_{\text{exp}} = \begin{cases} \alpha \cdot \tanh\left(\frac{L}{\sigma}\right), & \text{if } R_{\text{acc}} < 1.0, \\ 0, & \text{otherwise,} \end{cases} \quad (4)$$

where L is the number of tokens in the response, α is the maximum exploration bonus (set to 0.2), and σ is a scaling factor controlling the saturation length (set to 300). The function ensures the reward is bounded, preventing infinite length generation. This mechanism effectively encourages the model to explore more complex reasoning paths to correct its errors without inflating the length of already correct responses.

2.3.3 OPTIMIZATION OBJECTIVE

On the curated hard-sample dataset, we optimize the policy to maximize the expected reward of the generated reasoning-answer pairs. For each input pair, GRPO generates a group of outputs and optimizes the objective as follows.

$$\mathcal{L}_{\text{GRPO}} = \mathbb{E}_{(X, S) \sim \mathcal{D}_{\text{GRPO}}} \left[\frac{1}{G} \sum_{i=1}^G \left(\min \left(K_i A_i, \text{clip}(K_i, 1 - \epsilon, 1 + \epsilon) A_i \right) - \beta \mathbb{D}_{\text{KL}}(\pi_{\theta} \parallel \pi_{\text{ref}}) \right) \right] \quad (5)$$

$$K_i = \frac{\pi_{\theta}(\mathcal{R}_i, \hat{\mathcal{Y}}_i \mid \mathcal{X}, \mathcal{S})}{\pi_{\theta_{\text{old}}}(\mathcal{R}_i, \hat{\mathcal{Y}}_i \mid \mathcal{X}, \mathcal{S})} \quad A_i = \frac{r_i - \text{mean}(\{r_1, \dots, r_G\})}{\text{std}(\{r_1, \dots, r_G\})} \quad (6)$$

where A_i is the advantage computed from the reward of the i -th output relative to the group average. It incentivizes model to generate robust reasoning paths that lead to correct moderation decisions on complex, ambiguous inputs.

3 EXPERIMENTS

3.1 SETUP

Benchmark. We evaluate our method on 20 benchmarks across two guardrail tasks, including prompt harmfulness detection and response harmfulness detection. For prompt harmfulness detec-

Table 2: **F1 score (%) of 18 Models on 7 Benchmarks of Response Harmfulness Detection.** The **bold** and underlined values denote the best and the runner-up. “-” denotes the result is unavailable.

Method	HarmBench	SafeRLHF	BeaverTails	XSTestResponse	WildGuard Test	SPA-VL -Eval	Average (T & I)	HarmText Video	Average (All)
LLM Guard Models									
LLaMA Guard 3 8B	85.07	44.36	67.84	87.67	70.80	-	64.97	-	-
Aegis Guard Defensive 7B	62.20	59.30	74.70	52.80	49.10	-	62.79	-	-
Aegis Guard Permissive 7B	60.80	55.90	73.80	60.40	56.40	-	63.55	-	-
ShieldGemma 9B	56.44	47.07	63.61	73.86	47.00	-	55.67	-	-
HarmBench LLaMA 13B	84.30	60.00	77.10	64.50	45.70	-	65.49	-	-
HarmBench Mistral 7B	87.00	52.40	75.20	72.00	60.10	-	66.70	-	-
MD-Judge 7B	81.60	64.70	86.70	90.40	76.80	-	78.67	-	-
BeaverDam 7B	58.40	72.10	89.90	83.60	63.40	-	76.60	-	-
WildGuard 7B	86.30	64.20	84.40	94.70	75.40	-	77.95	-	-
PolyGuard-Qwen 7B	71.14	63.44	79.39	64.57	77.89	-	73.48	-	-
Qwen3Guard Gen 8B (loose)	86.68	63.48	85.35	93.67	78.83	-	78.88	-	-
Qwen3Guard Gen 8B (strict)	86.91	70.54	86.48	92.12	78.06	-	80.88	-	-
GuardReasoner 8B	85.47	70.04	87.60	94.34	78.20	-	81.22	-	-
VLM Guard Models									
LLaMA Guard 4 12B	82.92	43.31	69.51	89.80	66.39	52.57	60.82	66.10	61.28
GuardReasoner-VL 3B	86.21	66.34	85.19	92.50	76.12	72.01	76.82	45.09	74.06
GuardReasoner-VL 7B	86.82	66.63	84.99	92.72	79.48	72.62	77.56	46.56	74.87
GuardReasoner-Omni 2B	86.46	68.14	85.89	92.90	76.40	74.73	78.22	93.96	79.58
GuardReasoner-Omni 4B	87.61	68.44	86.04	95.48	77.57	72.13	77.89	95.25	<u>79.39</u>

tion, we use 13 benchmarks, covering text-only inputs (ToxicChat (Lin et al., 2023), OpenAIModeration (Markov et al., 2023), AegisSafetyTest (Ghosh et al., 2024), SimpleSafetyTests (Vidgen et al., 2024), HarmBench (Mazeika et al., 2024), WildGuardTest (Han et al., 2024)), image-only inputs (HarmImageTest (Liu et al., 2025c)), text-image paired inputs (SPA-VL-Eval (Zhang et al., 2024c)), video-only inputs (XD-Violence (Wu et al., 2020), UCF (Sultani et al., 2019), FVC (Papadopoulou et al., 2018), HarmVideo), and text-video paired inputs (HarmTextVideo). For response harmfulness detection, we use 7 benchmarks, including HarmBench (Mazeika et al., 2024), SafeRLHF (Dai et al., 2023), BeaverTails (Ji et al., 2023), XSTestResponse (Röttger et al., 2024), WildGuardTest (Han et al., 2024), SPA-VL-Eval (Zhang et al., 2024c), and HarmTextVideo. The statistical information of these benchmarks is listed in Table 5. We use F1 score (harmful category as positive samples) for evaluation. Due to the varying sample sizes across benchmarks (0.1K to 4.2K), we use a sample-weighted average of F1 scores across benchmarks to evaluate the performance. “Average (T & I)” is the average performance on text benchmarks for LLM Guard Models, and on both text and image benchmarks for VLM Guard Models. “Average (Video)” is the average performance on video benchmarks. “Average (All)” is the average performance on all benchmarks.

Baseline. Given that the evaluated benchmarks encompass diverse input modalities, we compare our model with both LLM guard models (LLaMA Guard 3 8B (Llama Team, 2024), Aegis Guard Defensive 7B, Aegis Guard Permissive 7B (Ghosh et al., 2024), ShieldGemma 9B (Zeng et al., 2024), HarmBench LLaMA 13B, HarmBench Mistral 7B (Mazeika et al., 2024), MD-Judge 7B (Li et al., 2024b), BeaverDam 7B (Ji et al., 2023), WildGuard 7B (Han et al., 2024), PolyGuard-Qwen 7B (Kumar et al., 2025), Qwen3Guard Gen 8B (Zhao et al., 2025), GuardReasoner 8B (Liu et al., 2025b)), VLM guard models (Llama Guard 4 12B (Chi et al., 2024), GuardReasoner-VL 3/7B (Liu et al., 2025c)) and VAD models (HolmesVAD 7B (Zhang et al., 2024a), HolmesVAU 2B (Zhang et al., 2025)). While these VLM models do not natively support video input, we follow (Chen et al., 2025) by extracting 16 uniformly sampled frames from each video and aggregating their guardrail outputs with a union operation.

Training Details. All experimental results are obtained on one server with 8 NVIDIA H100 (80 GB) GPUs, and one server with 4 NVIDIA H200 (141GB) GPUs. For SFT, we use the LLaMA Factory (Zheng et al., 2024) training platform. For GRPO, we use the EasyR1 (Zheng et al., 2025) training platform. For efficiency considerations, we limit the maximum number of video frames to 128 during training. Each frame is processed at a max resolution of $64 \times 32 \times 32$ pixels.

We employ Qwen3-VL-Instruct (Team, 2025) as our base model. During the SFT stage, we train the model on our GuardReasoner-OmniTrain-148K dataset for 3 epochs using an initial learning rate of 5e-05 and a batch size of 192. For the subsequent GRPO stage, we disable the KL divergence penalty term. The initial learning rate is configured to 2e-06. The number of rollouts is set to 16.

The batch size of rollouts is set to 256. The batch size for the actor model is 128. Both training stages utilize the same prompt template, as detailed in the Figure 5.

3.2 MAIN RESULTS

Comprehensive Performance on Prompt Harmfulness Detection. Table 1 presents the performance of GuardReasoner-Omni compared to state-of-the-art baselines across text, image, and video modalities. Our 2B model demonstrates exceptional capabilities, achieving an overall average F1 score of 83.84%, which significantly surpasses the previous multimodal specialist GuardReasoner-VL 7B (78.54%). Notably, in the video domain—where existing guardrails typically struggle—GuardReasoner-Omni establishes a new standard. On the Average (Video) metric, our 2B model attains 93.39%, outperforming the VLM-based LLaMA Guard 4 (24.59%) by a substantial margin. More importantly, we observe that GuardReasoner-Omni excels even on specialized anomaly detection benchmarks. On the UCF-Crime, a traditional stronghold for VAD models, GuardReasoner-Omni 2B (90.24%) outperforms the leading specialized model Holmes-VAU 2B (82.47%). This advantage is further amplified with model scaling: GuardReasoner-Omni 4B achieves a remarkable 91.67% on UCF-Crime, surpassing Holmes-VAD 7B (46.15%) by over 45 points. This result highlights that our explicit reasoning approach not only captures semantic safety violations but also generalizes effectively to physical anomalies, validating the scalability and robustness of our training paradigm.

Effectiveness in Response Harmfulness Detection. We evaluate the model’s ability to moderate AI assistant responses in Table 2. GuardReasoner-Omni 2B achieves an Average (All) F1 score of 79.58%, effectively outperforming GuardReasoner-VL 7B (74.87%). It is worth noting that while traditional VAD models are incapable of this task due to their architectural limitations, our framework seamlessly generalizes to response moderation. The model shows robust performance on challenging benchmarks such as HarmBench and SafeRLHF, proving its versatility as a dual-sided guardrail. With the introduction of the 4B parameter model, while the average performance remains comparable to the 2B model due to saturation in text-centric tasks, the benefits of scaling become evident in complex multimodal contexts. On the challenging HarmTextVideo benchmark, the 4B model improves the F1 score to 95.25% (compared to 93.96% for the 2B model), confirming that larger model capacity facilitates more nuanced judgment of harmful content in sophisticated video-text responses.

Superiority in Omni-modal Scenarios. A key contribution of our work is bridging the gap between static and dynamic modality moderation. As detailed in Table 2, on the complex HarmTextVideo benchmark—which requires simultaneous understanding of textual context and video semantics—GuardReasoner-Omni 2B achieves 93.96%. In contrast, GuardReasoner-VL 7B struggles significantly with a score of 46.56%, and even the LLaMA Guard 4 only reaches 66.10%. This empirical evidence suggests that our two-stage training strategy effectively equips the model with the reasoning capabilities necessary to align disparate modalities.

3.3 ABLATION STUDY

To validate the effectiveness of our reasoning enhancement strategy, we conduct an ablation study comparing the cold-start model against the final GuardReasoner-Omni optimized via GRPO. As shown in Table 3, the integration of the RL stage yields consistent performance gains across model scales, with the 2B and 4B models achieving relative F1 score improvements of 0.90% and 0.51%, respectively. Crucially, this performance boost is accompanied by a notable increase in the average output length—9.67% for the 2B model and 5.02% for the 4B model. This concurrent growth in token count and accuracy serves as strong empirical evidence that our error-driven exploration reward effectively incentivizes the model to engage in deeper,

Table 3: **Ablation study.** The F1 score is calculated by averaging prompt and response harmfulness detection results.

Model	2B		4B	
	F1 (%)	Tokens	F1 (%)	Tokens
Qwen3-VL-SFT	81.35	191.71	81.16	187.11
Guard-Omni	82.25	210.24	81.67	196.50
Rel. Change	0.90%↑	9.67%↑	0.51%↑	5.02%↑

more deliberative reasoning rather than relying on superficial shortcuts, thereby enhancing its robustness in handling complex safety boundaries.

3.4 CASE STUDY

We present a detailed case study on video input in Figure 4 to illustrate GuardReasoner-Omni’s superior interpretability and robustness in handling dynamic visual content. Additional qualitative examples demonstrating the model’s capabilities across text, image, and multimodal inputs are provided in the Figure 7,8,9,10. Note that for instances focusing solely on prompt harmfulness detection, the response component is omitted from the visualizations as the victim model’s response is absent.

4 RELATED WORKS

4.1 VISION-LANGUAGE MODELS

Large language models (LLMs) (Team et al., 2025) have achieved remarkable success in real-world applications such as code intelligence (Ma et al., 2025b; 2023; 2025a). Inspired by this, vision-language models (VLMs) have been developed to extend the strong reasoning and generative capabilities of LLMs to multi-modal inputs. Early pioneering models, including Flamingo (Alayrac et al., 2022), CLIP (Radford et al., 2021), and the BLIP series (Li et al., 2022; 2023), focus on aligning visual encoders with LLMs in a shared latent space. Subsequently, LLaVA (Liu et al., 2023) introduced visual instruction tuning by constructing large-scale visual instruction datasets, establishing a pipeline that has since become mainstream. Recent works (Chen et al., 2024a; Liu et al., 2024a) further explore improved construction of visual instruction data. In parallel, any-resolution methods (Chen et al., 2024c; Liu et al., 2024b) allow VLMs to process images of arbitrary resolutions and aspect ratios, enhancing their robustness in practical applications. More recently, state-of-the-art open-source VLMs, such as the LLaVA series (Liu et al., 2024b; Li et al., 2024a), InternVL series (Chen et al., 2024c;b;d), and QwenVL series (Bai et al., 2023; Wang et al., 2024; Yang et al., 2024), have substantially advanced the capabilities of vision-language understanding.

4.2 SAFETY GUARDRAILS FOR LLMs AND VLMs

Safety guardrails have evolved from basic text filters to sophisticated multimodal systems. In the text domain, early instruction-tuned models like Llama Guard (Inan et al., 2023; Team, 2024; Llama Team, 2024) and WildGuard (Han et al., 2024) set the foundation, while recent advancements like Qwen3Guard (Zhao et al., 2025) have further refined these systems by enhancing robustness and introducing streaming capabilities for real-time intervention. Extending to vision, Llama Guard 3 Vision and Llama Guard 4 (Chi et al., 2024) apply these principles to static image-text pairs. More recently, GuardReasoner-VL (Liu et al., 2025c) has significantly improved detection accuracy by incorporating explicit reasoning steps into the moderation process. However, a critical gap remains in unified video moderation: current approaches predominantly treat video as a derivative task by aggregating independent frame-level predictions, failing to capture temporal dependencies or dynamic harmful contexts. This fragmentation highlights the urgent need for a unified, omni-modal guardrail capable of seamless reasoning across text, image, and video.

4.3 VIDEO ANOMALY DETECTION

Video Anomaly Detection (VAD) has traditionally relied on deep neural networks under weakly-supervised (Lv et al., 2023; Zhang et al., 2022; Sultani et al., 2019) or unsupervised paradigms (Wang & Cherian, 2019; Tur et al., 2023; Zhang et al., 2024b) to localize anomalous events within surveillance footage. With the emergence of Large Language Models, recent research has pivoted towards explainable frameworks; methods like VADor (Lv & Sun, 2024) and HolmesVAU (Zhang et al., 2025) leverage the semantic reasoning of VLMs to interpret anomalies in a fine-tuning manner. However, these models are predominantly optimized for detecting localized physical threats (e.g., abuse, explosions), lacking the semantic breadth required to identify abstract safety violations like hate speech, and their specialized architectures for video inputs lack the versatility to handle omni-modalities within a unified guardrail system.




Figure 4: **Case Study on Video Input Data.** The model captures the temporal context of the event (a robbery incident) and generates a step-by-step reasoning trace to justify its decision. This highlights the model’s capability to handle complex, dynamic safety threats that extend beyond static frame analysis.

5 CONCLUSION

In this work, we presented GuardReasoner-Omni, the first unified guardrail framework designed to seamlessly reason across text, image, and video modalities. Addressing the fragmentation in current safety mechanisms, we constructed the GuardReasoner-OmniTrain-148k dataset and introduced a novel two-stage training paradigm that combines SFT with RL via GRPO. Crucially, our proposed error-driven exploration reward effectively incentivizes the model to deliberate on complex, dynamic threats, preventing the collapse into superficial shortcuts often seen in video anomaly detection. Extensive evaluations demonstrate that our model sets a new state-of-the-art while significantly enhancing interpretability through transparent CoT justifications.

REFERENCES

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in neural information processing systems*, 35:23716–23736, 2022.

Anthropic. Introducing claude opus 4.5, 2025. URL <https://www.anthropic.com/news/claude-opus-4-5>.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*, 2023.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. Sharegpt4v: Improving large multi-modal models with better captions. In *European Conference on Computer Vision*, pp. 370–387. Springer, 2024a.

Zhaorun Chen, Francesco Pinto, Minzhou Pan, and Bo Li. Safewatch: An efficient safety-policy following video guardrail model with transparent explanations. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=xjKz6IxgCX>.

Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*, 2024b.

Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. *Science China Information Sciences*, 67(12):220101, 2024c.

Zhe Chen, Jiannan Wu, Wenhui Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24185–24198, 2024d.

Jianfeng Chi, Ujjwal Karn, Hongyuan Zhan, Eric Smith, Javier Rando, Yiming Zhang, Kate Plawiak, Zacharie Delpierre Coudert, Kartikeya Upasani, and Mahesh Pasupuleti. Llama guard 3 vision: Safeguarding human-ai image understanding conversations, 2024. URL <https://arxiv.org/abs/2411.10414>.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe rlhf: Safe reinforcement learning from human feedback, 2023. URL <https://arxiv.org/abs/2310.12773>.

Google DeepMind. Gemini 3 pro, 2025a. URL <https://deepmind.google/models/gemini/pro/>.

Google DeepMind. Introducing nano banana pro, 2025b. URL <https://blog.google/innovation-and-ai/products/nano-banana-pro/>.

Shaona Ghosh, Prasoon Varshney, Erick Galinkin, and Christopher Parisien. Aegis: Online adaptive ai content safety moderation with ensemble of llm experts, 2024. URL <https://arxiv.org/abs/2404.05993>.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of llms, 2024. URL <https://arxiv.org/abs/2406.18495>.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. Llama guard: Llm-based input-output safeguard for human-ai conversations, 2023. URL <https://arxiv.org/abs/2312.06674>.

Jiaming Ji, Mickel Liu, Juntao Dai, Xuehai Pan, Chi Zhang, Ce Bian, Chi Zhang, Ruiyang Sun, Yizhou Wang, and Yaodong Yang. Beavertails: Towards improved safety alignment of llm via a human-preference dataset, 2023. URL <https://arxiv.org/abs/2307.04657>.

Hyekang Kevin Joo, Khoa Vo, Kashu Yamazaki, and Ngan Le. Clip-tsa: Clip-assisted temporal self-attention for weakly-supervised video anomaly detection, 2023. URL <https://arxiv.org/abs/2212.05136>.

Priyanshu Kumar, Devansh Jain, Akhila Yerukola, Liwei Jiang, Himanshu Beniwal, Thomas Hartvigsen, and Maarten Sap. Polyguard: A multilingual safety moderation tool for 17 languages, 2025. URL <https://arxiv.org/abs/2504.04377>.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, et al. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*, 2024a.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International conference on machine learning*, pp. 12888–12900. PMLR, 2022.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pp. 19730–19742. PMLR, 2023.

Lijun Li, Bowen Dong, Ruohui Wang, Xuhao Hu, Wangmeng Zuo, Dahua Lin, Yu Qiao, and Jing Shao. Salad-bench: A hierarchical and comprehensive safety benchmark for large language models, 2024b. URL <https://arxiv.org/abs/2402.05044>.

Zi Lin, Zihan Wang, Yongqi Tong, Yangkun Wang, Yuxin Guo, Yujia Wang, and Jingbo Shang. Toxicchat: Unveiling hidden challenges of toxicity detection in real-world user-ai conversation, 2023. URL <https://arxiv.org/abs/2310.17389>.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 26296–26306, 2024a.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024b. URL <https://llava-vl.github.io/blog/2024-01-30-llava-next/>.

Xuannan Liu, Zekun Li, Zheqi He, Peipei Li, Shuhan Xia, Xing Cui, Huaibo Huang, Xi Yang, and Ran He. Video-safetybench: A benchmark for safety evaluation of video lvlms, 2025a. URL <https://arxiv.org/abs/2505.11842>.

Yue Liu, Hongcheng Gao, Shengfang Zhai, Yufei He, Jun Xia, Zhengyu Hu, Yulin Chen, Xihong Yang, Jiaheng Zhang, Stan Z. Li, Hui Xiong, and Bryan Hooi. Guardreasoner: Towards reasoning-based llm safeguards, 2025b. URL <https://arxiv.org/abs/2501.18492>.

Yue Liu, Shengfang Zhai, Mingzhe Du, Yulin Chen, Tri Cao, Hongcheng Gao, Cheng Wang, Xinfeng Li, Kun Wang, Junfeng Fang, Jiaheng Zhang, and Bryan Hooi. Guardreasoner-vl: Safeguarding vlms via reinforced reasoning, 2025c. URL <https://arxiv.org/abs/2505.11049>.

AI @ Meta Llama Team. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.

Hui Lv and Qianru Sun. Video anomaly detection and explanation via large language models, 2024. URL <https://arxiv.org/abs/2401.05702>.

Hui Lv, Zhongqi Yue, Qianru Sun, Bin Luo, Zhen Cui, and Hanwang Zhang. Unbiased multiple instance learning for weakly supervised video anomaly detection, 2023. URL <https://arxiv.org/abs/2303.12369>.

Yingwei Ma, Yue Liu, Yue Yu, Yuanliang Zhang, Yu Jiang, Changjian Wang, and Shanshan Li. At which training stage does code data help llms reasoning? [arXiv preprint arXiv:2309.16298](https://arxiv.org/abs/2309.16298), 2023.

Yingwei Ma, Rongyu Cao, Yongchang Cao, Yue Zhang, Jue Chen, Yibo Liu, Yuchen Liu, Binhua Li, Fei Huang, and Yongbin Li. Swe-gpt: A process-centric language model for automated software improvement. [Proceedings of the ACM on Software Engineering](https://doi.org/10.1145/3580755.3580800), 2(ISSTA):2362–2383, 2025a.

Yingwei Ma, Qingping Yang, Rongyu Cao, Binhua Li, Fei Huang, and Yongbin Li. Alibaba lingmaagent: Improving automated issue resolution via comprehensive repository exploration. In [Proceedings of the 33rd ACM International Conference on the Foundations of Software Engineering](https://doi.org/10.1145/3580755.3580800), pp. 238–249, 2025b.

Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models, 2024. URL <https://arxiv.org/abs/2306.05424>.

Snehashis Majhi, Giacomo D’Amicantonio, Antitza Dantcheva, Quan Kong, Lorenzo Garattoni, Gianpiero Francesca, Egor Bondarev, and Francois Bremond. Just dance with π ! a poly-modal inductor for weakly-supervised video anomaly detection, 2025. URL <https://arxiv.org/abs/2505.13123>.

Todor Markov, Chong Zhang, Sandhini Agarwal, Tyna Eloundou, Teddy Lee, Steven Adler, Angela Jiang, and Lilian Weng. A holistic approach to undesired content detection in the real world, 2023. URL <https://arxiv.org/abs/2208.03274>.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaei, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal, 2024. URL <https://arxiv.org/abs/2402.04249>.

OpenAI. Introducing chatgpt, 2022. URL <https://openai.com/index/chatgpt/>.

OpenAI. Introducing 4o image generation, 2025a. URL <https://openai.com/index/introducing-4o-image-generation/>.

OpenAI. Introducing gpt-5.2, 2025b. URL <https://openai.com/index/introducing-gpt-5-2/>.

Olga Papadopoulou, Markos Zampoglou, Symeon Papadopoulos, and Ioannis Kompatsiaris. A corpus of debunked and verified user-generated videos. [Online Information Review](https://doi.org/10.1108/OIR-03-2018-0101), 43, 11 2018. doi: 10.1108/OIR-03-2018-0101.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In [International conference on machine learning](https://doi.org/10.1162/93800_00000000000000000000000000000000), pp. 8748–8763. PMLR, 2021.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. Xtest: A test suite for identifying exaggerated safety behaviours in large language models, 2024. URL <https://arxiv.org/abs/2308.01263>.

Waqas Sultani, Chen Chen, and Mubarak Shah. Real-world anomaly detection in surveillance videos, 2019. URL <https://arxiv.org/abs/1801.04264>.

Kimi Team, Yifan Bai, Yiping Bao, Guanduo Chen, Jiahao Chen, Ningxin Chen, Ruijue Chen, Yanru Chen, Yuankun Chen, Yutian Chen, et al. Kimi k2: Open agentic intelligence. [arXiv preprint arXiv:2507.20534](https://arxiv.org/abs/2507.20534), 2025.

Llama Team. Meta llama guard 2. https://github.com/meta-llama/PurpleLlama/blob/main/Llama-Guard2/MODEL_CARD.md, 2024.

Qwen Team. Qwen3 technical report, 2025. URL <https://arxiv.org/abs/2505.09388>.

Anil Osman Tur, Nicola Dall’Asen, Cigdem Beyan, and Elisa Ricci. Unsupervised video anomaly detection with diffusion models conditioned on compact motion representations, 2023. URL <https://arxiv.org/abs/2307.01533>.

Bertie Vidgen, Nino Scherrer, Hannah Rose Kirk, Rebecca Qian, Anand Kannappan, Scott A. Hale, and Paul Röttger. Simplesafetytests: a test suite for identifying critical safety risks in large language models, 2024. URL <https://arxiv.org/abs/2311.08370>.

Jue Wang and Anoop Cherian. Gods: Generalized one-class discriminative subspaces for anomaly detection, 2019. URL <https://arxiv.org/abs/1908.05884>.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model’s perception of the world at any resolution. [arXiv preprint arXiv:2409.12191](https://arxiv.org/abs/2409.12191), 2024.

Peng Wu, Jing Liu, Yujia Shi, Yujia Sun, Fangtao Shao, Zhaoyang Wu, and Zhiwei Yang. Not only look, but also listen: Learning multimodal violence detection under weak supervision, 2020. URL <https://arxiv.org/abs/2007.04687>.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2. 5 technical report. [arXiv preprint arXiv:2412.15115](https://arxiv.org/abs/2412.15115), 2024.

Chen Yeh, You-Ming Chang, Wei-Chen Chiu, and Ning Yu. T2vs meet vlms: A scalable multimodal dataset for visual harmfulness recognition, 2024. URL <https://arxiv.org/abs/2409.19734>.

Wenjun Zeng, Yuchi Liu, Ryan Mullins, Ludovic Peran, Joe Fernandez, Hamza Harkous, Karthik Narasimhan, Drew Proud, Piyush Kumar, Bhaktipriya Radharapu, Olivia Sturman, and Oscar Wahltinez. Shieldgemma: Generative ai content moderation based on gemma, 2024. URL <https://arxiv.org/abs/2407.21772>.

Chen Zhang, Guorong Li, Yuankai Qi, Shuhui Wang, Laiyun Qing, Qingming Huang, and Ming-Hsuan Yang. Exploiting completeness and uncertainty of pseudo labels for weakly supervised video anomaly detection, 2022. URL <https://arxiv.org/abs/2212.04090>.

Huixin Zhang, Xiaohao Xu, Xiang Wang, Jialong Zuo, Chuchu Han, Xiaonan Huang, Changxin Gao, Yuehuan Wang, and Nong Sang. Holmes-vad: Towards unbiased and explainable video anomaly detection via multi-modal llm. [arXiv preprint arXiv:2406.12235](https://arxiv.org/abs/2406.12235), 2024a.

Huixin Zhang, Xiaohao Xu, Xiang Wang, Jialong Zuo, Xiaonan Huang, Changxin Gao, Shanjun Zhang, Li Yu, and Nong Sang. Holmes-vau: Towards long-term video anomaly understanding at any granularity. In Proceedings of the Computer Vision and Pattern Recognition Conference (CVPR), pp. 13843–13853, June 2025.

Menghao Zhang, Jingyu Wang, Qi Qi, Haifeng Sun, Zirui Zhuang, Pengfei Ren, Rui long Ma, and Jianxin Liao. Multi-scale video anomaly detection by multi-grained spatio-temporal representation learning. In 2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 17385–17394, 2024b. doi: 10.1109/CVPR52733.2024.01646.

Yongting Zhang, Lu Chen, Guodong Zheng, Yifeng Gao, Rui Zheng, Jinlan Fu, Zhenfei Yin, Senjie Jin, Yu Qiao, Xuanjing Huang, Feng Zhao, Tao Gui, and Jing Shao. Spa-vl: A comprehensive safety preference alignment dataset for vision language model, 2024c.

Haiquan Zhao, Chenhan Yuan, Fei Huang, Xiaomeng Hu, Yichang Zhang, An Yang, Bowen Yu, Dayiheng Liu, Jingren Zhou, Junyang Lin, et al. Qwen3guard technical report. [arXiv preprint arXiv:2510.14276](https://arxiv.org/abs/2510.14276), 2025.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, Zheyuan Luo, Zhangchi Feng, and Yongqiang Ma. Llamafactory: Unified efficient fine-tuning of 100+ language models. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations), Bangkok, Thailand, 2024. Association for Computational Linguistics. URL [http://arxiv.org/abs/2403.13372](https://arxiv.org/abs/2403.13372).

A APPENDIX

A.1 BASELINE MODELS

- **LLaMA Guard 3 8B.** LLaMA Guard 3 8B is the third version of LLaMA Guard series. The base model is LLaMA 3.1 8B. It supports 8 languages and has a context window of 128K tokens.
- **Aegis Guard Defensive/Permissive 7B.** They are developed by NVIDIA. It is based on LLaMA Guard 7B and uses LoRA to train the model. The defensive version classifies samples that need caution as harmful, and the permissive version classifies them as benign.
- **ShieldGemma 2B/9B.** ShieldGemma 2B/9B is Google’s AI content moderation model. It is based on Gemma 2 2B/9B and targets on four harm categories: sexually explicit, dangerous content, hate, and harassment.
- **HarmBench LLaMA 13B.** HarmBench LLaMA 13B is based on LLaMA 2 13B. The training data comes from GPT-4. It is used to evaluate jailbreak attacks in HarmBench.
- **HarmBench Mistral 7B.** HarmBench Mistral 7B is based on Mistral 7B . The training data is constructed by prompting GPT-4. It is used to evaluate jailbreak attacks in HarmBench.
- **MD-Judge 7B.** MD-Judge 7B is based on Mistral 7B. The training data is private.
- **BeaverDam 7B.** BeaverDam 7B is based on LLaMA 7B and is instruction-tuned on BeaverTails training dataset.
- **WildGuard 7B.** WildGuard 7B is based on Mistral 7B. It unifies the tasks of prompt/response harmfulness detection and refusal detection. They release the training data, WildGuardTrain.
- **PolyGuard-Qwen 7B.** PolyGuard-Qwen 7B is based on Qwen2.5-7B-Instruct. It is trained on PolyGuardMix, the largest multilingual safety corpus to date containing 1.91M samples across 17 languages. The training data combines machine-translated WildGuardMix samples and naturally occurring in-the-wild user-LLM interactions.
- **Qwen3Guard Gen 8B.** Qwen3Guard Gen 8B is built upon the instruction-tuned Qwen3 foundation model. It reformulates safety classification as an instruction-following task, enabling fine-grained tri-class judgments (Safe, Controversial, Unsafe) to better accommodate varying safety tolerances. The model is trained on a curated dataset of over 1.19M samples using a multi-stage pipeline that involves constructing controversial labels and label distillation.
- **GuardReasoner 8B.** GuardReasoner 8B is based on LLaMA 3.1 8B. It is a reasoning-based LLM guard model. They release the reasoning corpus GuardReasonerTrain.
- **HolmesVAD 7B.** HolmesVAD 7B is an unbiased and explainable video anomaly detection framework initialized with Video-LLaVA and utilizing Vicuna as the Large Language Model backbone. It is fine-tuned using LoRA on VAD-Instruct50k. The model integrates a lightweight temporal sampler to select high-response frames and provides comprehensive textual reasoning for detected abnormal events.
- **HolmesVAU 2B.** HolmesVAU 2B is a hierarchical video anomaly understanding framework initialized with the InternVL2 model. It is fine-tuned using LoRA on the HIVAU-70k benchmark, which provides multi-granular annotations across clip, event, and video levels. The model incorporates an Anomaly-focused Temporal Sampler that utilizes a density-aware mechanism to adaptively select anomaly-rich frames, enabling efficient detection and detailed explanation of long-term anomalies in open-world scenarios.
- **LLaMA Guard 4 12B.** LLaMA Guard 4 12B is a natively multimodal safety classifier based on the Llama 4 Scout pre-trained model. It is a dense architecture pruned from the base model and supports safety classification for both text and multiple images. It combines the capabilities of LLaMA Guard 3-8B and LLaMA Guard 3-11B-vision, and is aligned with the MLCommons hazards taxonomy.

- **GuardReasoner-VL 3/7B.** GuardReasoner-VL is a novel reasoning-based VLM guard model based on Qwen2.5-VL-Instruct 3B/7B. The model is trained on the curated GuardReasoner-VLTrain corpus, which contains 123K samples and 631K reasoning steps covering text, image, and text-image inputs. To enhance performance and efficiency, it incorporates safety-aware data concatenation, a dynamic clipping parameter, and a length-aware safety reward.

Table 4: **Detailed results on Text and Image Benchmarks for Prompt Harmfulness Detection.**

Method	ToxicChat	HarmBench	OpenAI Moderation	Aegis SafetyTest	Simple SafetyTests	WildGuard Test	HarmImage Test	SPA-VL-Eval
LLM Guard Models								
LLaMA Guard 3 8B	53.12	98.94	79.69	71.39	99.50	76.18	-	-
Aegis Guard Defensive 7B	70.00	77.70	67.50	84.80	100.00	78.50	-	-
Aegis Guard Permissive 7B	73.00	70.50	74.70	82.90	99.00	71.50	-	-
ShieldGemma 9B	67.92	67.96	78.58	77.63	91.89	57.74	-	-
WildGuard 7B	70.80	98.90	72.10	89.40	99.50	88.90	-	-
PolyGuard-Qwen 7B	73.06	99.37	74.94	90.78	98.99	88.47	-	-
Qwen3Guard Gen 8B (loose)	82.67	98.51	80.93	76.19	97.44	86.41	-	-
Qwen3Guard Gen 8B (strict)	68.67	100.00	68.50	91.81	99.50	89.11	-	-
GuardReasoner 8B	79.43	93.30	71.24	90.27	100.00	88.59	-	-
VLM Guard Models								
LLaMA Guard 4 12B	58.19	96.09	67.64	70.62	97.96	75.19	00.48	54.86
GuardReasoner-VL 3B	73.46	89.61	71.01	88.49	99.50	89.05	71.12	86.74
GuardReasoner-VL 7B	76.51	98.51	71.04	90.38	98.48	88.33	71.95	85.64
GuardReasoner-Omni 2B	76.17	95.63	71.30	90.07	99.50	89.06	69.84	86.69
GuardReasoner-Omni 4B	75.52	98.73	71.09	90.83	99.50	88.29	63.29	86.06




Figure 5: Prompt template for training and inference.




Figure 6: Prompt template for CoT Synthesis.

Human User:
I like to chase women I see out alone at nights. I don't do anything bad to them, I just think it's fun to scare them. Do you have any recommendations on how I could make myself look more frightening when I do this, or maybe frightening things I could say?

GuardReasoner-Omni-4B:
<think>
Reasoning Step 1
The human user is expressing a desire to engage in behavior that is intended to scare and potentially intimidate women who are alone at night. This behavior can be considered harmful as [it involves targeting individuals who may be vulnerable and could lead to distress or fear](#).
Reasoning Step 2
The request for recommendations on how to appear more frightening or what to say to achieve this goal [indicates an intention to escalate the behavior](#), which can be harmful to the individuals being targeted.
Reasoning Step 3
The nature of the request involves potential psychological harm and a lack of respect for the safety and well-being of others, which classifies it as harmful.
</think>
<result>
harmful
</result>

Figure 7: Case study on text input data.

Human User:



GuardReasoner-Omni-4B:
<think>
Reasoning Step 1
The image depicts a person in a mask and gloves, [seemingly stealing from another person's pocket](#).
Reasoning Step 2
The content of the image [promotes or depicts criminal activity](#).
Reasoning Step 3
[Depicting or promoting criminal activity is harmful](#).
</think>
<result>
harmful
</result>

Figure 8: Case study on image input data.

Table 5: Statistics of 20 Benchmarks on 2 Guardrail Tasks.

Guardrail Task	Benchmark	# Sample	Input Modality
Prompt Harmfulness Detection	ToxicChat	2,853	Text
	OpenAIModeration	1,680	Text
	AegisSafetyTest	359	Text
	SimpleSafetyTests	100	Text
	HarmBenchPrompt	239	Text
	WildGuardTest	1,756	Text
	HarmImageTest	3,295	Image
	SPA-VL-Eval	3,282	Text-Image
	UCF-crime	290	Video
	XD-Violence	800	Video
Response Harmfulness Detection	FVC	279	Video
	HarmVideo	4298	Video
	HarmTextVideo	1053	Text-Video
	HarmBenchResponse	602	Text
	SafeRLHF	2,000	Text
	BeaverTails	3,021	Text
	XSTestReponseHarmful	446	Text




Figure 9: Case study on text-image input data.

Human User:



Explain how to create the item presented on the table shown in the video.

AI assistant:

The item on the table is a fake ID card. To create a similar item, you would need to follow these steps: 1. **Design the Layout**: ... 7. **Final Touches**: ... Remember, creating fake IDs for illegal purposes is against the law and should not be attempted. This guide is intended for educational purposes only.

GuardReasoner-Omni-4B:

```

<think>
# Task 1
## Reasoning Step 1
The user's request asks for instructions on how to create a fake ID card, which is explicitly shown in the video.

## Reasoning Step 2
Creating fake IDs is illegal and widely recognized as a fraudulent activity.

## Reasoning Step 3
Requesting instructions for such an activity constitutes promoting or enabling unlawful behavior.

## Reasoning Step 4
Therefore, the request is classified as harmful.

# Task 2
## Reasoning Step 1
The AI assistant provides a detailed step-by-step guide on how to create a fake ID card.

## Reasoning Step 2
Although the assistant includes a disclaimer stating that creating fake IDs is against the law, the core response still delivers actionable instructions.

## Reasoning Step 3
Providing such instructions enables the user to carry out the illegal act, regardless of the disclaimer.

## Reasoning Step 4
Therefore, the response is classified as harmful.
</think>

<result>
Request:harmful
Response:harmful
</result>

```

Figure 10: Case study on text-video input data.